The Parma Polyhedra Library C Language Interface Developer's Manual* (version 0.11.2)

Roberto Bagnara†
Patricia M. Hill‡
Enea Zaffanella§

February 27, 2011

*This work has been partly supported by: University of Parma's FIL scientific research project (ex 60%) "Pure and Applied Mathematics"; MURST project "Automatic Program Certification by Abstract Interpretation"; MURST project "Abstract Interpretation, Type Systems and Control-Flow Analysis"; MURST project "Automatic Aggregate- and Number-Reasoning for Computing: from Decision Algorithms to Constraint Programming with Multisets, Sets, and Maps"; MURST project "Constraint Based Verification of Reactive Systems"; MURST project "Abstract Interpretation: Design and Applications"; EPSRC project "Numerical Domains for Software Analysis"; EPSRC project "Geometric Abstractions for Scalable Program Analyzers".

†bagnara@cs.unipr.it, Department of Mathematics, University of Parma, Italy.
‡hill@comp.leeds.ac.uk, School of Computing, University of Leeds, U.K.
§zaffanella@cs.unipr.it, Department of Mathematics, University of Parma, Italy.

Copyright © 2001–2010 Roberto Bagnara (bagnara@cs.unipr.it).

This document describes the Parma Polyhedra Library (PPL).

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

The PPL is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. A copy of the license is included in the section entitled "GNU GENERAL PUBLIC LICENSE".

The PPL is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

For the most up-to-date information see the Parma Polyhedra Library site:

http://www.cs.unipr.it/ppl/

Contents

1 Main Page **1**

2 GNU General Public License **2**

3 GNU Free Documentation License **12**

4 Module Index **17**

4.1 Modules 17

5 Namespace Index **17**

5.1 Namespace List 17

6 Class Index **18**

6.1 Class List 18

7 File Index **19**

7.1 File List 19

8 Module Documentation **19**

8.1 C Language Interface 19

8.2 Library Initialization and Finalization 19

8.3 Version Checking 21

8.4 Error Handling 24

8.5 Handling 25

8.6 Library Datatypes 27

9 Namespace Documentation **36**

9.1 Parma_Polyhedra_Library Namespace Reference 36

9.2 Parma_Polyhedra_Library::Interfaces Namespace Reference 36

9.3 Parma_Polyhedra_Library::Interfaces::C Namespace Reference 37

10 Class Documentation **58**

10.1 Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_Wrapper Class Reference 58

10.2 Parma_Polyhedra_Library::Interfaces::C::deterministic_timeout_exception Class Reference 61

10.3 ppl_Artificial_Parameter_Sequence_const_iterator_tag Interface Reference 61

10.4 ppl_Artificial_Parameter_tag Interface Reference 64

10.5 ppl_Coefficient_tag Interface Reference 65

10.6 ppl_Congruence_System_const_iterator_tag Interface Reference 68

10.7 ppl_Congruence_System_tag Interface Reference 70

10.8 ppl_Congruence_tag Interface Reference 74

10.9 ppl_Constraint_System_const_iterator_tag Interface Reference 77

10.10 ppl_Constraint_System_tag Interface Reference 79

10.11 ppl_Constraint_tag Interface Reference 83

10.12 ppl_Generator_System_const_iterator_tag Interface Reference 86

10.13 ppl_Generator_System_tag Interface Reference 88

10.14 ppl_Generator_tag Interface Reference 92

10.15 ppl_Grid_Generator_System_const_iterator_tag Interface Reference 95

10.16 ppl_Grid_Generator_System_tag Interface Reference 97

10.17 ppl_Grid_Generator_tag Interface Reference 100

10.18 ppl_Linear_Expression_tag Interface Reference 103

10.19 ppl_MIP_Problem_tag Interface Reference 109

10.20 ppl_PIP_Decision_Node_tag Interface Reference 119

10.21 ppl_PIP_Problem_tag Interface Reference 120

10.22 ppl_PIP_Solution_Node_tag Interface Reference 129

10.23 ppl_PIP_Tree_Node_tag Interface Reference 130

10.24 ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag Interface Reference 132

10.25 ppl_Pointset_Powerset_C_Polyhedron_iterator_tag Interface Reference 134

10.26 ppl_Pointset_Powerset_C_Polyhedron_tag Interface Reference 137

10.27 ppl_Polyhedron_tag Interface Reference 140

10.28 Parma_Polyhedra_Library::Interfaces::C::timeout_exception Class Reference 170

11 File Documentation **171**

11.1 C_interface.dox File Reference 171
11.2 fdl.dox File Reference 172
11.3 gpl.dox File Reference 172
11.4 ppl_c_header.h File Reference 172
11.5 ppl_c_implementation_common.cc File Reference 177
11.6 ppl_c_implementation_common.defs.hh File Reference 231
11.7 ppl_c_implementation_common.inlines.hh File Reference 233
11.8 ppl_c_version.h File Reference 237

1 Main Page

All the declarations needed for using the PPL's C interface (preprocessor symbols, data types, variables and functions) are collected in the header file `ppl_c.h`. This file, which is designed to work with pre-ANSI and ANSI C compilers as well as C99 and C++ compilers, should be included, either directly or via some other header file, with the directive

```
#include <ppl_c.h>
```

If this directive does not work, then your compiler is unable to find the file `ppl_c.h`. So check that the library is installed (if it is not installed, you may want to `make install`, perhaps with root privileges) in the right place (if not you may want to reconfigure the library using the appropriate pathname for the `--prefix` option); and that your compiler knows where it is installed (if not you should add the path to the directory where `ppl_c.h` is located to the compiler's include file search path; this is usually done with the `-I` option).

The name space of the PPL's C interface is `PPL_*` for preprocessor symbols, enumeration values and variables; and `ppl_*` for data types and function names. The interface systematically uses *opaque data types* (generic pointers that completely hide the internal representations from the client code) and provides all required access functions. By using just the interface, the client code can exploit all the functionalities of the library yet avoid directly manipulating the library's data structures. The advantages are that (1) applications do not depend on the internals of the library (these may change from release to release), and (2) the interface invariants can be thoroughly checked (by the access functions).

Note

> All functions taking as input argument an opaque pointer datatype assume that such an argument is actually *referring to a valid PPL object*. For instance, a function with an argument having type `ppl_MIP_Problem_t` will expect a valid MIP_Problem object, previously initialized by calling, e.g., `ppl_new_MIP_Problem`. If that is not the case (e.g., if a null pointer is passed in), the behavior is undefined.

The PPL's C interface is initialized by means of the `ppl_initialize` function. This function must be called *before using any other interface of the library*. The application can release the resources allocated by the library by calling the `ppl_finalize` function. After this function is called *no other interface of the library may be used* until the interface is re-initialized using `ppl_initialize`.

Any application using the PPL should make sure that only the intended version(s) of the library are ever used. The version used can be checked at compile-time thanks to the macros PPL_VERSION_MAJOR, PPL_VERSION_MINOR, PPL_VERSION_REVISION and PPL_VERSION_BETA, which give, respectively major, minor, revision and beta numbers of the PPL version. This is an example of their use:

```
#if PPL_VERSION_MAJOR == 0 && PPL_VERSION_MINOR < 6
```

```
# error "PPL version 0.6 or following is required"
#endif
```

Compile-time checking, however, is not normally enough, particularly in an environment where there is dynamic linking. Run-time checking can be performed by means of the functions `ppl_version_major`, `ppl_version_minor`, `ppl_version_revision`, and `ppl_version_beta`. The PPL's C interface also provides functions `ppl_version`, returning character string containing the full version number, and `ppl_banner`, returning a string that, in addition, provides (pointers to) other useful information for the library user.

All programs using the PPL's C interface must link with the following libraries: `libppl_c` (PPL's C interface), `libppl` (PPL's core), `libgmpxx` (GMP's C++ interface), and `libgmp` (GMP's library core). On most Unix-like systems, this is done by adding `-lppl_c`, `-lppl`, `-lgmpxx`, and `-lgmp` to the compiler's or linker's command line. For example:

```
gcc myprogram.o -lppl_c -lppl -lgmpxx -lgmp
```

If this does not work, it means that your compiler/linker is not finding the libraries where it expects. Again, this could be because you forgot to install the library or you installed it in a non-standard location. In the latter case you will need to use the appropriate options (usually `-L`) and, if you use shared libraries, some sort of run-time path selection mechanisms. Consult your compiler's documentation for details. Notice that the PPL is built using `Libtool` and an application can exploit this fact to significantly simplify the linking phase. See Libtool's documentation for details. Those working under Linux can find a lot of useful information on how to use program libraries (including static, shared, and dynamically loaded libraries) in the `Program Library HOWTO`.

For examples on how to use the functions provided by the C interface, you are referred to the directory `demos/ppl_lpsol/` in the source distribution. It contains a *Mixed Integer (Linear) Programming* solver written in C. In order to use this solver you will need to install `GLPK` (the GNU Linear Programming Kit): this is used to read linear programs in MPS format.

2 GNU General Public License

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. http://fsf.org/

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may

convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction

is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms

that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),

EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
 one line to give the program's name and a brief idea of what it does.
Copyright (C)  year   name of author

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program.  If not, see  http://www.gnu.org/licenses/.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
 program  Copyright (C)  year   name of author
This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.
```

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see http://www.gnu.org/licenses/.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read http://www.gnu.org/philosophy/why-not-lgpl.html.

3 GNU Free Documentation License

Version 1.2, November 2002


```
Copyright (C) 2000,2001,2002  Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA  02110-1301,  USA.
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
```


0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a worldwide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- **A.** Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- **B.** List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- **C.** State on the Title page the name of the publisher of the Modified Version, as the publisher.
- **D.** Preserve all the copyright notices of the Document.
- **E.** Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- **F.** Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- **G.** Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- **H.** Include an unaltered copy of this License.
- **I.** Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- **J.** Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

- **K.** For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- **L.** Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- **M.** Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- **N.** Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- **O.** Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements."

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See http://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (c)  YEAR  YOUR NAME.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled
```

```
"GNU Free Documentation License".
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with...Texts." line with this:

```
with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

4 Module Index

4.1 Modules

Here is a list of all modules:

C Language Interface 19

Library Initialization and Finalization 19

Version Checking 21

Error Handling 24

Handling 25

Library Datatypes 27

5 Namespace Index

5.1 Namespace List

Here is a list of all namespaces with brief descriptions:

Parma_Polyhedra_Library 36

Parma_Polyhedra_Library::Interfaces 36

Parma_Polyhedra_Library::Interfaces::C 37

6 Class Index

6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_Wrapper (A class to wrap an array of fixed length into a partial function interface suitable for the map_space_-dimension() methods) 58

Parma_Polyhedra_Library::Interfaces::C::deterministic_timeout_exception 61

ppl_Artificial_Parameter_Sequence_const_iterator_tag (Types and functions for iterating on PIP artificial parameters) 61

ppl_Artificial_Parameter_tag (Types and functions for PIP artificial parameters) 64

ppl_Coefficient_tag (Types and functions for coefficients) 65

ppl_Congruence_System_const_iterator_tag (Types and functions for iterating on congruence systems) 68

ppl_Congruence_System_tag (Types and functions for congruence systems) 70

ppl_Congruence_tag (Types and functions for congruences) 74

ppl_Constraint_System_const_iterator_tag (Types and functions for iterating on constraint systems) 77

ppl_Constraint_System_tag (Types and functions for constraint systems) 79

ppl_Constraint_tag (Types and functions for constraints) 83

ppl_Generator_System_const_iterator_tag (Types and functions for iterating on generator systems) 86

ppl_Generator_System_tag (Types and functions for generator systems) 88

ppl_Generator_tag (Types and functions for generators) 92

ppl_Grid_Generator_System_const_iterator_tag (Types and functions for iterating on grid generator systems) 95

ppl_Grid_Generator_System_tag (Types and functions for grid generator systems) 97

ppl_Grid_Generator_tag (Types and functions for grid generators) 100

ppl_Linear_Expression_tag (Types and functions for linear expressions) 103

ppl_MIP_Problem_tag (Types and functions for MIP problems) 109

ppl_PIP_Decision_Node_tag (Types and functions for PIP decision nodes) 119

ppl_PIP_Problem_tag (Types and functions for PIP problems) 120

ppl_PIP_Solution_Node_tag (Types and functions for PIP solution nodes) 129

ppl_PIP_Tree_Node_tag (Types and functions for generic PIP tree nodes) 130

ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag (Types and functions for iterating on the disjuncts of a const ppl_Pointset_Powerset_C_Polyhedron_tag) 132

ppl_Pointset_Powerset_C_Polyhedron_iterator_tag (Types and functions for iterating on the disjuncts of a ppl_Pointset_Powerset_C_Polyhedron_tag) 134

ppl_Pointset_Powerset_C_Polyhedron_tag (Types and functions for the Pointset_Powerset of C_Polyhedron objects) 137

ppl_Polyhedron_tag (Types and functions for the domains of C and NNC convex polyhedra) 140

Parma_Polyhedra_Library::Interfaces::C::timeout_exception 170

7 File Index

7.1 File List

Here is a list of all files with brief descriptions:

ppl_c_header.h 172

ppl_c_implementation_common.cc 177

ppl_c_implementation_common.defs.hh 231

ppl_c_implementation_common.inlines.hh 233

ppl_c_version.h 237

8 Module Documentation

8.1 C Language Interface

The Parma Polyhedra Library comes equipped with an interface for the C language.

8.2 Library Initialization and Finalization

Functions

- int ppl_initialize (void)

  Initializes the Parma Polyhedra Library. This function must be called before any other function.

- int ppl_finalize (void)

  Finalizes the Parma Polyhedra Library. This function must be called after any other function.

- int ppl_set_rounding_for_PPL (void)

  Sets the FPU rounding mode so that the PPL abstractions based on floating point numbers work correctly.

- int ppl_restore_pre_PPL_rounding (void)

  Sets the FPU rounding mode as it was before initialization of the PPL.

- int ppl_irrational_precision (unsigned *p)

  Writes to `p` *the precision parameter used for irrational calculations.*

- int ppl_set_irrational_precision (unsigned p)

Sets the precision parameter used for irrational calculations.

8.2.1 Detailed Description

Functions for initialization/finalization of the library, as well as setting/resetting of floating-point rounding mode.

8.2.2 Function Documentation

8.2.2.1 int ppl_finalize (void)

Finalizes the Parma Polyhedra Library. This function must be called after any other function.

Returns

`PPL_ERROR_INVALID_ARGUMENT` if the library was already finalized.

Definition at line 243 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::saved_cxx_Variable_output_function.

8.2.2.2 int ppl_initialize (void)

Initializes the Parma Polyhedra Library. This function must be called before any other function.

Returns

`PPL_ERROR_INVALID_ARGUMENT` if the library was already initialized.

Definition at line 181 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::c_variable_default_output_function(), Parma_Polyhedra_Library::Interfaces::C::c_variable_output_function, Parma_Polyhedra_Library::Interfaces::C::cxx_Variable_output_function(), and Parma_Polyhedra_Library::Interfaces::C::saved_cxx_Variable_output_function.

8.2.2.3 int ppl_irrational_precision (unsigned $*$ *p*)

Writes to `p` the precision parameter used for irrational calculations.

Definition at line 328 of file ppl_c_implementation_common.cc.

8.2.2.4 int ppl_restore_pre_PPL_rounding (void)

Sets the FPU rounding mode as it was before initialization of the PPL.

After calling this function it is absolutely necessary to call set_rounding_for_PPL() before using any PPL abstractions based on floating point numbers. This is performed automatically at finalization-time.

Definition at line 321 of file ppl_c_implementation_common.cc.

8.2.2.5 int ppl_set_irrational_precision (unsigned *p*)

Sets the precision parameter used for irrational calculations.

If `p` is less than or equal to `INT_MAX`, sets the precision parameter used for irrational calculations to `p`. Then, in the irrational calculations returning an unbounded rational, (e.g., when computing a square root), the lesser between numerator and denominator will be limited to `2**p`.

Definition at line 335 of file ppl_c_implementation_common.cc.

8.2.2.6 int ppl_set_rounding_for_PPL (void)

Sets the FPU rounding mode so that the PPL abstractions based on floating point numbers work correctly.

This is performed automatically at initialization-time. Calling this function is needed only if restore_pre_-PPL_rounding() has been previously called.

Definition at line 314 of file ppl_c_implementation_common.cc.

8.3 Version Checking

Defines

- #define PPL_VERSION "0.11.2"

  A string containing the PPL version.

- #define PPL_VERSION_MAJOR 0

  The major number of the PPL version.

- #define PPL_VERSION_MINOR 11

  The minor number of the PPL version.

- #define PPL_VERSION_REVISION 2

  The revision number of the PPL version.

- #define PPL_VERSION_BETA 0

  The beta number of the PPL version. This is zero for official releases and nonzero for development snapshots.

Functions

- int ppl_version_major (void)

  Returns the major number of the PPL version.

- int ppl_version_minor (void)

  Returns the minor number of the PPL version.

- int ppl_version_revision (void)

  Returns the revision number of the PPL version.

- int ppl_version_beta (void)

  Returns the beta number of the PPL version.

- int ppl_version (const char **p)

  Writes to `*p` a pointer to a character string containing the PPL version.

- int ppl_banner (const char **p)

  Writes to `*p` a pointer to a character string containing the PPL banner.

8.3.1 Detailed Description

Symbolic constants and functions related to library version checking.

8.3.2 Define Documentation

8.3.2.1 #define PPL_VERSION "0.11.2"

A string containing the PPL version.

Let `M` and `m` denote the numbers associated to PPL_VERSION_MAJOR and PPL_VERSION_MINOR, respectively. The format of PPL_VERSION is `M "." m` if both PPL_VERSION_REVISION (`r`) and PPL_VERSION_BETA (`b`)are zero, `M "." m "pre" b` if PPL_VERSION_REVISION is zero and PPL_VERSION_BETA is not zero, `M "." m "." r` if PPL_VERSION_REVISION is not zero and PPL_VERSION_BETA is zero, `M "." m "." r "pre" b` if neither PPL_VERSION_REVISION nor PPL_VERSION_BETA are zero.

Definition at line 38 of file ppl_c_version.h.

8.3.2.2 #define PPL_VERSION_BETA 0

The beta number of the PPL version. This is zero for official releases and nonzero for development snapshots.

Definition at line 63 of file ppl_c_version.h.

8.3.2.3 #define PPL_VERSION_MAJOR 0

The major number of the PPL version.

Definition at line 44 of file ppl_c_version.h.

8.3.2.4 #define PPL_VERSION_MINOR 11

The minor number of the PPL version.

Definition at line 50 of file ppl_c_version.h.

8.3.2.5 #define PPL_VERSION_REVISION 2

The revision number of the PPL version.

Definition at line 56 of file ppl_c_version.h.

8.3.3 Function Documentation

8.3.3.1 int ppl_banner (const char ** *p*)

Writes to *p a pointer to a character string containing the PPL banner.

The banner provides information about the PPL version, the licensing, the lack of any warranty whatsoever, the C++ compiler used to build the library, where to report bugs and where to look for further information.

Definition at line 376 of file ppl_c_implementation_common.cc.

8.3.3.2 int ppl_version (const char ** *p*)

Writes to *p a pointer to a character string containing the PPL version.

Definition at line 366 of file ppl_c_implementation_common.cc.

8.3.3.3 int ppl_version_beta (void)

Returns the beta number of the PPL version.

Definition at line 360 of file ppl_c_implementation_common.cc.

8.3.3.4 int ppl_version_major (void)

Returns the major number of the PPL version.

Definition at line 342 of file ppl_c_implementation_common.cc.

8.3.3.5 int ppl_version_minor (void)

Returns the minor number of the PPL version.

Definition at line 348 of file ppl_c_implementation_common.cc.

8.3.3.6 int ppl_version_revision (void)

Returns the revision number of the PPL version.

Definition at line 354 of file ppl_c_implementation_common.cc.

8.4 Error Handling

Enumerations

- enum ppl_enum_error_code {

  PPL_ERROR_OUT_OF_MEMORY, PPL_ERROR_INVALID_ARGUMENT, PPL_ERROR_-DOMAIN_ERROR, PPL_ERROR_LENGTH_ERROR,

  PPL_ARITHMETIC_OVERFLOW, PPL_STDIO_ERROR, PPL_ERROR_INTERNAL_ERROR, PPL_ERROR_UNKNOWN_STANDARD_EXCEPTION,

  PPL_ERROR_UNEXPECTED_ERROR, PPL_TIMEOUT_EXCEPTION, PPL_ERROR_LOGIC_-ERROR }

  Defines the error codes that any function may return.

Functions

- int ppl_set_error_handler (void(∗h)(enum ppl_enum_error_code code, const char ∗description))

  Installs the user-defined error handler pointed at by `h`.

8.4.1 Detailed Description

Symbolic constants and functions related to error reporting/handling.

8.4.2 Enumeration Type Documentation

8.4.2.1 enum ppl_enum_error_code

Defines the error codes that any function may return.

Enumerator:

PPL_ERROR_OUT_OF_MEMORY The virtual memory available to the process has been exhausted.

PPL_ERROR_INVALID_ARGUMENT A function has been invoked with an invalid argument.

PPL_ERROR_DOMAIN_ERROR A function has been invoked outside its domain of definition.

PPL_ERROR_LENGTH_ERROR The construction of an object that would exceed its maximum permitted size was attempted.

PPL_ARITHMETIC_OVERFLOW An arithmetic overflow occurred and the computation was consequently interrupted. This can *only* happen in library's incarnations using bounded integers as coefficients.

PPL_STDIO_ERROR An error occurred during a C input/output operation. A more precise indication of what went wrong is available via `errno`.

PPL_ERROR_INTERNAL_ERROR An internal error that was diagnosed by the PPL itself. This indicates a bug in the PPL.

PPL_ERROR_UNKNOWN_STANDARD_EXCEPTION A standard exception has been raised by the C++ run-time environment. This indicates a bug in the PPL.

PPL_ERROR_UNEXPECTED_ERROR A totally unknown, totally unexpected error happened. This indicates a bug in the PPL.

PPL_TIMEOUT_EXCEPTION An exception has been raised by the PPL as a timeout previously set by the user has expired.

PPL_ERROR_LOGIC_ERROR The client program attempted to use the PPL in a way that violates its internal logic. This happens, for instance, when the client attempts to use the timeout facilities on a system that does not support them.

Definition at line 298 of file ppl_c_header.h.

8.4.3 Function Documentation

8.4.3.1 int ppl_set_error_handler (void(∗)(enum ppl_enum_error_code code, const char ∗description) *h*)

Installs the user-defined error handler pointed at by `h`.

The error handler takes an error code and a textual description that gives further information about the actual error. The C string containing the textual description is read-only and its existence is not guaranteed after the handler has returned.

8.5 Handling

Functions

- int ppl_set_timeout (unsigned time)

  Sets the timeout for computations whose completion could require an exponential amount of time.

- int ppl_reset_timeout (void)

  Resets the timeout time so that the computation is not interrupted.

- int ppl_set_deterministic_timeout (unsigned weight)

  Sets a threshold for computations whose completion could require an exponential amount of time.

- int ppl_reset_deterministic_timeout (void)

  Resets the deterministic timeout so that the computation is not interrupted.

8.5.1 Detailed Description

Functions for setting and resetting timeouts.

8.5.2 Function Documentation

8.5.2.1 int ppl_reset_deterministic_timeout (void)

Resets the deterministic timeout so that the computation is not interrupted.

Definition at line 301 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reset_deterministic_timeout().

8.5.2.2 int ppl_reset_timeout (void)

Resets the timeout time so that the computation is not interrupted.

Definition at line 270 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reset_timeout().

8.5.2.3 int ppl_set_deterministic_timeout (unsigned *weight*)

Sets a threshold for computations whose completion could require an exponential amount of time.

Parameters

weight The maximum computational weight allowed. It must be strictly greater than zero.

Computations taking exponential time will be interrupted some time after reaching the `weight` complexity threshold. If the computation is interrupted that way, the interrupted function will return error code `PPL_TIMEOUT_EXCEPTION`. Otherwise, if the computation completes without being interrupted, then the deterministic timeout should be reset by calling `ppl_reset_deterministic_timeout()`.

Note

This "timeout" checking functionality is said to be *deterministic* because it is not based on actual elapsed time. Its behavior will only depend on (some of the) computations performed in the PPL library and it will be otherwise independent from the computation environment (CPU, operating system, compiler, etc.).

Warning

The weight mechanism is under alpha testing. In particular, there is still no clear relation between the weight threshold and the actual computational complexity. As a consequence, client applications should be ready to reconsider the tuning of these weight thresholds when upgrading to newer version of the PPL.

Definition at line 283 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reset_deterministic_timeout().

8.5.2.4 int ppl_set_timeout (unsigned *time*)

Sets the timeout for computations whose completion could require an exponential amount of time.

Parameters

time The number of hundreths of seconds. It must be strictly greater than zero.

Computations taking exponential time will be interrupted some time after `time` hundreths of seconds have elapsed since the call to the timeout setting function. If the computation is interrupted that way, the interrupted function will return error code `PPL_TIMEOUT_EXCEPTION`. Otherwise, if the computation completes without being interrupted, then the timeout should be reset by calling `ppl_reset_timeout()`.

Definition at line 252 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reset_timeout().

8.6 Library Datatypes

Typedefs for the library datatypes and related symbolic constants.

Typedefs

- typedef size_t ppl_dimension_type

  An unsigned integral type for representing space dimensions.

- typedef const char * ppl_io_variable_output_function_type (ppl_dimension_type var)

  The type of output functions used for printing variables.

- typedef struct ppl_Polyhedron_tag * ppl_Polyhedron_t

  Opaque pointer.

- typedef struct ppl_Polyhedron_tag const * ppl_const_Polyhedron_t

  Opaque pointer to const object.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_tag * ppl_Pointset_Powerset_C_Polyhedron_-t

  Opaque pointer.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_tag const * ppl_const_Pointset_Powerset_C_-Polyhedron_t

  Opaque pointer to const object.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_iterator_tag * ppl_Pointset_Powerset_C_-Polyhedron_iterator_t

  Opaque pointer.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_iterator_tag const * ppl_const_Pointset_-Powerset_C_Polyhedron_iterator_t

  Opaque pointer to const object.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag * ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t

  Opaque pointer.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag const * ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t

  Opaque pointer to const object.

Enumerations

- enum ppl_enum_Constraint_Type {

  PPL_CONSTRAINT_TYPE_LESS_THAN, PPL_CONSTRAINT_TYPE_LESS_OR_EQUAL, PPL_CONSTRAINT_TYPE_EQUAL, PPL_CONSTRAINT_TYPE_GREATER_OR_EQUAL,

  PPL_CONSTRAINT_TYPE_GREATER_THAN }

  Describes the relations represented by a constraint.

- enum ppl_enum_Generator_Type { PPL_GENERATOR_TYPE_LINE, PPL_GENERATOR_TYPE_RAY, PPL_GENERATOR_TYPE_POINT, PPL_GENERATOR_TYPE_CLOSURE_POINT }

  Describes the different kinds of generators.

- enum ppl_enum_Grid_Generator_Type { PPL_GRID_GENERATOR_TYPE_LINE, PPL_GRID_GENERATOR_TYPE_PARAMETER, PPL_GRID_GENERATOR_TYPE_POINT }

  Describes the different kinds of grid generators.

- enum ppl_enum_Bounded_Integer_Type_Width {

  PPL_BITS_8, PPL_BITS_16, PPL_BITS_32, PPL_BITS_64,

  PPL_BITS_128 }

  Widths of bounded integer types.

- enum ppl_enum_Bounded_Integer_Type_Representation { PPL_UNSIGNED, PPL_SIGNED_2_COMPLEMENT }

  Representation of bounded integer types.

- enum ppl_enum_Bounded_Integer_Type_Overflow { PPL_OVERFLOW_WRAPS, PPL_OVERFLOW_UNDEFINED, PPL_OVERFLOW_IMPOSSIBLE }

  Overflow behavior of bounded integer types.

Functions

- int ppl_max_space_dimension (ppl_dimension_type *m)

  Writes to `m` *the maximum space dimension this library can handle.*

- int ppl_not_a_dimension (ppl_dimension_type *m)

  Writes to `m` *a value that does not designate a valid dimension.*

- int ppl_io_print_variable (ppl_dimension_type var)

  Pretty-prints `var` *to* `stdout`.

- int ppl_io_fprint_variable (FILE ∗stream, ppl_dimension_type var)

  Pretty-prints `var` *to the given output* `stream`.

- int ppl_io_asprint_variable (char ∗∗strp, ppl_dimension_type var)

  Pretty-prints `var` *to a malloc-allocated string, a pointer to which is returned via* `strp`.

- int ppl_io_set_variable_output_function (ppl_io_variable_output_function_type ∗p)

  Sets the output function to be used for printing variables to `p`.

- int ppl_io_get_variable_output_function (ppl_io_variable_output_function_type ∗∗pp)

  Writes a pointer to the current variable output function to `pp`.

- char ∗ ppl_io_wrap_string (const char ∗src, unsigned indent_depth, unsigned preferred_first_line_-length, unsigned preferred_line_length)

  Utility function for the wrapping of lines of text.

Variables

- unsigned int PPL_COMPLEXITY_CLASS_POLYNOMIAL

  Code of the worst-case polynomial complexity class.

- unsigned int PPL_COMPLEXITY_CLASS_SIMPLEX

  Code of the worst-case exponential but typically polynomial complexity class.

- unsigned int PPL_COMPLEXITY_CLASS_ANY

  Code of the universal complexity class.

- unsigned int PPL_POLY_CON_RELATION_IS_DISJOINT

  Individual bit saying that the polyhedron and the set of points satisfying the constraint are disjoint.

- unsigned int PPL_POLY_CON_RELATION_STRICTLY_INTERSECTS

  Individual bit saying that the polyhedron intersects the set of points satisfying the constraint, but it is not included in it.

- unsigned int PPL_POLY_CON_RELATION_IS_INCLUDED

  Individual bit saying that the polyhedron is included in the set of points satisfying the constraint.

- unsigned int PPL_POLY_CON_RELATION_SATURATES

  Individual bit saying that the polyhedron is included in the set of points saturating the constraint.

- unsigned int PPL_POLY_GEN_RELATION_SUBSUMES

  Individual bit saying that adding the generator would not change the polyhedron.

8.6.1 Detailed Description

Typedefs for the library datatypes and related symbolic constants. The datatypes provided by the library should be manipulated by means of the corresponding opaque pointer types and the functions working on them.

Note

To simplify the detection of common programming mistakes, we provide both pointer-to-const and pointer-to-nonconst opaque pointers, with implicit conversions mapping each pointer-to-nonconst to the corresponding pointer-to-const when needed. The user of the C interface is therefore recommended to adopt the pointer-to-const type whenever read-only access is meant.

8.6.2 Typedef Documentation

8.6.2.1 typedef struct ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag const* ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t

Opaque pointer to const object.

Definition at line 1498 of file C_interface.dox.

8.6.2.2 typedef struct ppl_Pointset_Powerset_C_Polyhedron_iterator_tag const* ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t

Opaque pointer to const object.

Definition at line 1484 of file C_interface.dox.

8.6.2.3 typedef struct ppl_Pointset_Powerset_C_Polyhedron_tag const* ppl_const_Pointset_Powerset_C_Polyhedron_t

Opaque pointer to const object.

Definition at line 1470 of file C_interface.dox.

8.6.2.4 typedef struct ppl_Polyhedron_tag const* ppl_const_Polyhedron_t

Opaque pointer to const object.

Definition at line 48 of file C_interface.dox.

8.6.2.5 typedef size_t ppl_dimension_type

An unsigned integral type for representing space dimensions.

Definition at line 454 of file ppl_c_header.h.

8.6.2.6 typedef const char* ppl_io_variable_output_function_type(ppl_dimension_type var)

The type of output functions used for printing variables.

An output function for variables must write a textual representation for `var` to a character buffer, null-terminate it, and return a pointer to the beginning of the buffer. In case the operation fails, 0 should be returned and perhaps `errno` should be set in a meaningful way. The library does nothing with the buffer, besides printing its contents.

Definition at line 498 of file ppl_c_header.h.

8.6.2.7 typedef struct ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag* ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t

Opaque pointer.

Definition at line 1494 of file C_interface.dox.

8.6.2.8 typedef struct ppl_Pointset_Powerset_C_Polyhedron_iterator_tag* ppl_Pointset_Powerset_C_Polyhedron_iterator_t

Opaque pointer.

Definition at line 1480 of file C_interface.dox.

8.6.2.9 typedef struct ppl_Pointset_Powerset_C_Polyhedron_tag* ppl_Pointset_Powerset_C_-Polyhedron_t

Opaque pointer.

Definition at line 1466 of file C_interface.dox.

8.6.2.10 typedef struct ppl_Polyhedron_tag* ppl_Polyhedron_t

Opaque pointer.

Definition at line 45 of file C_interface.dox.

8.6.3 Enumeration Type Documentation

8.6.3.1 enum ppl_enum_Bounded_Integer_Type_Overflow

Overflow behavior of bounded integer types.

Enumerator:

PPL_OVERFLOW_WRAPS On overflow, wrapping takes place. This means that, for a w-bit bounded integer, the computation happens modulo 2^w.

PPL_OVERFLOW_UNDEFINED On overflow, the result is undefined. This simply means that the result of the operation resulting in an overflow can take any value.

Note

Even though something more serious can happen in the system being analyzed ---due to, e.g., C's undefined behavior---, here we are only concerned with the results of arithmetic operations. It is the responsibility of the analyzer to ensure that other manifestations of undefined behavior are conservatively approximated.

PPL_OVERFLOW_IMPOSSIBLE Overflow is impossible. This is for the analysis of languages where overflow is trapped before it affects the state, for which, thus, any indication that an overflow may have affected the state is necessarily due to the imprecision of the analysis.

Definition at line 2362 of file ppl_c_header.h.

8.6.3.2 enum ppl_enum_Bounded_Integer_Type_Representation

Representation of bounded integer types.

Enumerator:

PPL_UNSIGNED Unsigned binary.

PPL_SIGNED_2_COMPLEMENT Signed binary where negative values are represented by the two's complement of the absolute value.

Definition at line 2349 of file ppl_c_header.h.

8.6.3.3 enum ppl_enum_Bounded_Integer_Type_Width

Widths of bounded integer types.

Enumerator:

PPL_BITS_8 8 bits.

PPL_BITS_16 16 bits.

PPL_BITS_32 32 bits.

PPL_BITS_64 64 bits.

PPL_BITS_128 128 bits.

Definition at line 2333 of file ppl_c_header.h.

8.6.3.4 enum ppl_enum_Constraint_Type

Describes the relations represented by a constraint.

Enumerator:

PPL_CONSTRAINT_TYPE_LESS_THAN The constraint is of the form $e < 0$.

PPL_CONSTRAINT_TYPE_LESS_OR_EQUAL The constraint is of the form $e \leq 0$.

PPL_CONSTRAINT_TYPE_EQUAL The constraint is of the form $e = 0$.

PPL_CONSTRAINT_TYPE_GREATER_OR_EQUAL The constraint is of the form $e \geq 0$.

PPL_CONSTRAINT_TYPE_GREATER_THAN The constraint is of the form $e > 0$.

Definition at line 1082 of file ppl_c_header.h.

8.6.3.5 enum ppl_enum_Generator_Type

Describes the different kinds of generators.

Enumerator:

PPL_GENERATOR_TYPE_LINE The generator is a line.

PPL_GENERATOR_TYPE_RAY The generator is a ray.

PPL_GENERATOR_TYPE_POINT The generator is a point.

PPL_GENERATOR_TYPE_CLOSURE_POINT The generator is a closure point.

Definition at line 1392 of file ppl_c_header.h.

8.6.3.6 enum ppl_enum_Grid_Generator_Type

Describes the different kinds of grid generators.

Enumerator:

PPL_GRID_GENERATOR_TYPE_LINE The grid generator is a line.

PPL_GRID_GENERATOR_TYPE_PARAMETER The grid generator is a parameter.

PPL_GRID_GENERATOR_TYPE_POINT The grid generator is a point.

Definition at line 1984 of file ppl_c_header.h.

8.6.4 Function Documentation

8.6.4.1 int ppl_io_asprint_variable (char ** *strp*, ppl_dimension_type *var*)

Pretty-prints `var` to a malloc-allocated string, a pointer to which is returned via `strp`.

Definition at line 2608 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::c_variable_output_function, PPL_ERROR_OUT_-OF_MEMORY, and PPL_STDIO_ERROR.

8.6.4.2 int ppl_io_fprint_variable (FILE * *stream*, ppl_dimension_type *var*)

Pretty-prints `var` to the given output `stream`.

Definition at line 2599 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::c_variable_output_function, and PPL_STDIO_-ERROR.

8.6.4.3 int ppl_io_get_variable_output_function (ppl_io_variable_output_function_type ** *pp*)

Writes a pointer to the current variable output function to `pp`.

Definition at line 2672 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::c_variable_output_function.

8.6.4.4 int ppl_io_print_variable (ppl_dimension_type *var*)

Pretty-prints `var` to `stdout`.

Definition at line 2590 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::c_variable_output_function, and PPL_STDIO_-ERROR.

8.6.4.5 int ppl_io_set_variable_output_function (ppl_io_variable_output_function_type * *p*)

Sets the output function to be used for printing variables to `p`.

Definition at line 2664 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::c_variable_output_function.

8.6.4.6 char* ppl_io_wrap_string (const char * *src*, unsigned *indent_depth*, unsigned *preferred_first_line_length*, unsigned *preferred_line_length*)

Utility function for the wrapping of lines of text.

Parameters

src The source string holding the text to wrap.

indent_depth The indentation depth.

preferred_first_line_length The preferred length for the first line of text.

preferred_line_length The preferred length for all the lines but the first one.

Returns

The wrapped string in a malloc-allocated buffer.

Definition at line 2653 of file ppl_c_implementation_common.cc.

8.6.4.7 int ppl_max_space_dimension (ppl_dimension_type * *m*)

Writes to `m` the maximum space dimension this library can handle.

Definition at line 383 of file ppl_c_implementation_common.cc.

8.6.4.8 int ppl_not_a_dimension (ppl_dimension_type * *m*)

Writes to `m` a value that does not designate a valid dimension.

Definition at line 390 of file ppl_c_implementation_common.cc.

8.6.5 Variable Documentation

8.6.5.1 unsigned int PPL_COMPLEXITY_CLASS_ANY

Code of the universal complexity class.

Definition at line 149 of file ppl_c_implementation_common.cc.

8.6.5.2 unsigned int PPL_COMPLEXITY_CLASS_POLYNOMIAL

Code of the worst-case polynomial complexity class.

Definition at line 147 of file ppl_c_implementation_common.cc.

8.6.5.3 unsigned int PPL_COMPLEXITY_CLASS_SIMPLEX

Code of the worst-case exponential but typically polynomial complexity class.

Definition at line 148 of file ppl_c_implementation_common.cc.

8.6.5.4 unsigned int PPL_POLY_CON_RELATION_IS_DISJOINT

Individual bit saying that the polyhedron and the set of points satisfying the constraint are disjoint.

Definition at line 140 of file ppl_c_implementation_common.cc.

8.6.5.5 unsigned int PPL_POLY_CON_RELATION_IS_INCLUDED

Individual bit saying that the polyhedron is included in the set of points satisfying the constraint.

Definition at line 142 of file ppl_c_implementation_common.cc.

8.6.5.6 unsigned int PPL_POLY_CON_RELATION_SATURATES

Individual bit saying that the polyhedron is included in the set of points saturating the constraint.

Definition at line 143 of file ppl_c_implementation_common.cc.

8.6.5.7 unsigned int PPL_POLY_CON_RELATION_STRICTLY_INTERSECTS

Individual bit saying that the polyhedron intersects the set of points satisfying the constraint, but it is not included in it.

Definition at line 141 of file ppl_c_implementation_common.cc.

8.6.5.8 unsigned int PPL_POLY_GEN_RELATION_SUBSUMES

Individual bit saying that adding the generator would not change the polyhedron.

Definition at line 145 of file ppl_c_implementation_common.cc.

9 Namespace Documentation

9.1 Parma_Polyhedra_Library Namespace Reference

Namespaces

- namespace Interfaces

9.2 Parma_Polyhedra_Library::Interfaces Namespace Reference

Namespaces

- namespace C

9.3 Parma_Polyhedra_Library::Interfaces::C Namespace Reference

Classes

- class Array_Partial_Function_Wrapper

  A class to wrap an array of fixed length into a partial function interface suitable for the map_space_-dimension() methods.

- class timeout_exception
- class deterministic_timeout_exception

Typedefs

- typedef const char ∗ c_variable_output_function_type (ppl_dimension_type var)
- typedef void(∗ error_handler_type)(enum ppl_enum_error_code code, const char ∗description)
- typedef Constraint_System::const_iterator Constraint_System_const_iterator
- typedef Generator_System::const_iterator Generator_System_const_iterator
- typedef Congruence_System::const_iterator Congruence_System_const_iterator
- typedef Grid_Generator_System::const_iterator Grid_Generator_System_const_iterator
- typedef PIP_Tree_Node::Artificial_Parameter Artificial_Parameter
- typedef PIP_Tree_Node::Artificial_Parameter_Sequence Artificial_Parameter_Sequence
- typedef PIP_Tree_Node::Artificial_Parameter_Sequence::const_iterator Artificial_Parameter_-Sequence_const_iterator

Functions

- const char ∗ c_variable_default_output_function (ppl_dimension_type var)
- void cxx_Variable_output_function (std::ostream &s, const Variable &v)
- void notify_error (enum ppl_enum_error_code code, const char ∗description)
- void reset_timeout ()
- void reset_deterministic_timeout ()
- Relation_Symbol relation_symbol (enum ppl_enum_Constraint_Type t)
- Bounded_Integer_Type_Width bounded_integer_type_width (enum ppl_enum_Bounded_Integer_-Type_Width w)
- Bounded_Integer_Type_Representation bounded_integer_type_representation (enum ppl_enum_-Bounded_Integer_Type_Representation r)
- mpz_class & reinterpret_mpz_class (mpz_t n)

  Reinterpret an mpz_t as mpz_class.

- const Coefficient ∗ to_const (ppl_const_Coefficient_t x)
- Coefficient ∗ to_nonconst (ppl_Coefficient_t x)
- ppl_const_Coefficient_t to_const (const Coefficient ∗x)
- ppl_Coefficient_t to_nonconst (Coefficient ∗x)
- const Linear_Expression ∗ to_const (ppl_const_Linear_Expression_t x)
- Linear_Expression ∗ to_nonconst (ppl_Linear_Expression_t x)
- ppl_const_Linear_Expression_t to_const (const Linear_Expression ∗x)
- ppl_Linear_Expression_t to_nonconst (Linear_Expression ∗x)
- const Constraint ∗ to_const (ppl_const_Constraint_t x)
- Constraint ∗ to_nonconst (ppl_Constraint_t x)
- ppl_const_Constraint_t to_const (const Constraint ∗x)

- ppl_Constraint_t to_nonconst (Constraint ∗x)
- const Constraint_System ∗ to_const (ppl_const_Constraint_System_t x)
- Constraint_System ∗ to_nonconst (ppl_Constraint_System_t x)
- ppl_const_Constraint_System_t to_const (const Constraint_System ∗x)
- ppl_Constraint_System_t to_nonconst (Constraint_System ∗x)
- const Constraint_System_const_iterator ∗ to_const (ppl_const_Constraint_System_const_iterator_t x)
- Constraint_System_const_iterator ∗ to_nonconst (ppl_Constraint_System_const_iterator_t x)
- ppl_const_Constraint_System_const_iterator_t to_const (const Constraint_System_const_iterator ∗x)
- ppl_Constraint_System_const_iterator_t to_nonconst (Constraint_System_const_iterator ∗x)
- const Generator ∗ to_const (ppl_const_Generator_t x)
- Generator ∗ to_nonconst (ppl_Generator_t x)
- ppl_const_Generator_t to_const (const Generator ∗x)
- ppl_Generator_t to_nonconst (Generator ∗x)
- const Generator_System ∗ to_const (ppl_const_Generator_System_t x)
- Generator_System ∗ to_nonconst (ppl_Generator_System_t x)
- ppl_const_Generator_System_t to_const (const Generator_System ∗x)
- ppl_Generator_System_t to_nonconst (Generator_System ∗x)
- const Generator_System_const_iterator ∗ to_const (ppl_const_Generator_System_const_iterator_t x)
- Generator_System_const_iterator ∗ to_nonconst (ppl_Generator_System_const_iterator_t x)
- ppl_const_Generator_System_const_iterator_t to_const (const Generator_System_const_iterator ∗x)
- ppl_Generator_System_const_iterator_t to_nonconst (Generator_System_const_iterator ∗x)
- const Congruence ∗ to_const (ppl_const_Congruence_t x)
- Congruence ∗ to_nonconst (ppl_Congruence_t x)
- ppl_const_Congruence_t to_const (const Congruence ∗x)
- ppl_Congruence_t to_nonconst (Congruence ∗x)
- const Congruence_System ∗ to_const (ppl_const_Congruence_System_t x)
- Congruence_System ∗ to_nonconst (ppl_Congruence_System_t x)
- ppl_const_Congruence_System_t to_const (const Congruence_System ∗x)
- ppl_Congruence_System_t to_nonconst (Congruence_System ∗x)
- const Congruence_System_const_iterator ∗ to_const (ppl_const_Congruence_System_const_-iterator_t x)
- Congruence_System_const_iterator ∗ to_nonconst (ppl_Congruence_System_const_iterator_t x)
- ppl_const_Congruence_System_const_iterator_t to_const (const Congruence_System_const_-iterator ∗x)
- ppl_Congruence_System_const_iterator_t to_nonconst (Congruence_System_const_iterator ∗x)
- const Grid_Generator ∗ to_const (ppl_const_Grid_Generator_t x)
- Grid_Generator ∗ to_nonconst (ppl_Grid_Generator_t x)
- ppl_const_Grid_Generator_t to_const (const Grid_Generator ∗x)
- ppl_Grid_Generator_t to_nonconst (Grid_Generator ∗x)
- const Grid_Generator_System ∗ to_const (ppl_const_Grid_Generator_System_t x)
- Grid_Generator_System ∗ to_nonconst (ppl_Grid_Generator_System_t x)
- ppl_const_Grid_Generator_System_t to_const (const Grid_Generator_System ∗x)
- ppl_Grid_Generator_System_t to_nonconst (Grid_Generator_System ∗x)
- const Grid_Generator_System_const_iterator ∗ to_const (ppl_const_Grid_Generator_System_-const_iterator_t x)
- Grid_Generator_System_const_iterator ∗ to_nonconst (ppl_Grid_Generator_System_const_-iterator_t x)

- ppl_const_Grid_Generator_System_const_iterator_t to_const (const Grid_Generator_System_-const_iterator ∗x)
- ppl_Grid_Generator_System_const_iterator_t to_nonconst (Grid_Generator_System_const_iterator ∗x)
- const Artificial_Parameter ∗ to_const (ppl_const_Artificial_Parameter_t x)
- Artificial_Parameter ∗ to_nonconst (ppl_Artificial_Parameter_t x)
- ppl_const_Artificial_Parameter_t to_const (const Artificial_Parameter ∗x)
- ppl_Artificial_Parameter_t to_nonconst (Artificial_Parameter ∗x)
- const Artificial_Parameter_Sequence ∗ to_const (ppl_const_Artificial_Parameter_Sequence_t x)
- Artificial_Parameter_Sequence ∗ to_nonconst (ppl_Artificial_Parameter_Sequence_t x)
- ppl_const_Artificial_Parameter_Sequence_t to_const (const Artificial_Parameter_Sequence ∗x)
- ppl_Artificial_Parameter_Sequence_t to_nonconst (Artificial_Parameter_Sequence ∗x)
- const Artificial_Parameter_Sequence_const_iterator ∗ to_const (ppl_const_Artificial_Parameter_-Sequence_const_iterator_t x)
- Artificial_Parameter_Sequence_const_iterator ∗ to_nonconst (ppl_Artificial_Parameter_Sequence_-const_iterator_t x)
- ppl_const_Artificial_Parameter_Sequence_const_iterator_t to_const (const Artificial_Parameter_-Sequence_const_iterator ∗x)
- ppl_Artificial_Parameter_Sequence_const_iterator_t to_nonconst (Artificial_Parameter_Sequence_-const_iterator ∗x)
- const MIP_Problem ∗ to_const (ppl_const_MIP_Problem_t x)
- MIP_Problem ∗ to_nonconst (ppl_MIP_Problem_t x)
- ppl_const_MIP_Problem_t to_const (const MIP_Problem ∗x)
- ppl_MIP_Problem_t to_nonconst (MIP_Problem ∗x)
- const PIP_Problem ∗ to_const (ppl_const_PIP_Problem_t x)
- PIP_Problem ∗ to_nonconst (ppl_PIP_Problem_t x)
- ppl_const_PIP_Problem_t to_const (const PIP_Problem ∗x)
- ppl_PIP_Problem_t to_nonconst (PIP_Problem ∗x)
- const PIP_Tree_Node ∗ to_const (ppl_const_PIP_Tree_Node_t x)
- PIP_Tree_Node ∗ to_nonconst (ppl_PIP_Tree_Node_t x)
- ppl_const_PIP_Tree_Node_t to_const (const PIP_Tree_Node ∗x)
- ppl_PIP_Tree_Node_t to_nonconst (PIP_Tree_Node ∗x)
- const PIP_Decision_Node ∗ to_const (ppl_const_PIP_Decision_Node_t x)
- PIP_Decision_Node ∗ to_nonconst (ppl_PIP_Decision_Node_t x)
- ppl_const_PIP_Decision_Node_t to_const (const PIP_Decision_Node ∗x)
- ppl_PIP_Decision_Node_t to_nonconst (PIP_Decision_Node ∗x)
- const PIP_Solution_Node ∗ to_const (ppl_const_PIP_Solution_Node_t x)
- PIP_Solution_Node ∗ to_nonconst (ppl_PIP_Solution_Node_t x)
- ppl_const_PIP_Solution_Node_t to_const (const PIP_Solution_Node ∗x)
- ppl_PIP_Solution_Node_t to_nonconst (PIP_Solution_Node ∗x)
- Bounded_Integer_Type_Overflow bounded_integer_type_overflow (enum ppl_enum_Bounded_-Integer_Type_Overflow o)

Variables

- error_handler_type user_error_handler = 0
- ppl_io_variable_output_function_type ∗ c_variable_output_function
- Variable::output_function_type ∗ saved_cxx_Variable_output_function

9.3.1 Typedef Documentation

9.3.1.1 typedef PIP_Tree_Node::Artificial_Parameter Parma_Polyhedra_-Library::Interfaces::C::Artificial_Parameter

Definition at line 80 of file ppl_c_implementation_common.inlines.hh.

9.3.1.2 typedef PIP_Tree_Node::Artificial_Parameter_Sequence Parma_Polyhedra_-Library::Interfaces::C::Artificial_Parameter_Sequence

Definition at line 84 of file ppl_c_implementation_common.inlines.hh.

9.3.1.3 typedef PIP_Tree_Node::Artificial_Parameter_Sequence::const_iterator Parma_Polyhedra_Library::Interfaces::C::Artificial_Parameter_Sequence_const_iterator

Definition at line 89 of file ppl_c_implementation_common.inlines.hh.

9.3.1.4 typedef const char∗ Parma_Polyhedra_Library::Interfaces::C::c_variable_output_-function_type(ppl_dimension_type var)

Definition at line 81 of file ppl_c_implementation_common.cc.

9.3.1.5 typedef Congruence_System::const_iterator Parma_Polyhedra_-Library::Interfaces::C::Congruence_System_const_iterator

Definition at line 66 of file ppl_c_implementation_common.inlines.hh.

9.3.1.6 typedef Constraint_System::const_iterator Parma_Polyhedra_-Library::Interfaces::C::Constraint_System_const_iterator

Definition at line 50 of file ppl_c_implementation_common.inlines.hh.

9.3.1.7 typedef void(∗ Parma_Polyhedra_Library::Interfaces::C::error_handler_type)(enum ppl_enum_error_code code, const char ∗description)

Definition at line 42 of file ppl_c_implementation_common.defs.hh.

9.3.1.8 typedef Generator_System::const_iterator Parma_Polyhedra_-Library::Interfaces::C::Generator_System_const_iterator

Definition at line 58 of file ppl_c_implementation_common.inlines.hh.

9.3.1.9 typedef Grid_Generator_System::const_iterator Parma_Polyhedra_-Library::Interfaces::C::Grid_Generator_System_const_iterator

Definition at line 75 of file ppl_c_implementation_common.inlines.hh.

9.3.2 Function Documentation

9.3.2.1 Bounded_Integer_Type_Overflow Parma_Polyhedra_Library::Interfaces::C::bounded_-integer_type_overflow (enum ppl_enum_Bounded_Integer_Type_Overflow *o*) `[inline]`

Definition at line 152 of file ppl_c_implementation_common.inlines.hh.

References PPL_OVERFLOW_IMPOSSIBLE, PPL_OVERFLOW_UNDEFINED, and PPL_-OVERFLOW_WRAPS.

9.3.2.2 Bounded_Integer_Type_Representation Parma_Polyhedra_-Library::Interfaces::C::bounded_integer_type_representation (enum ppl_enum_Bounded_Integer_Type_Representation *r*) `[inline]`

Definition at line 140 of file ppl_c_implementation_common.inlines.hh.

References PPL_SIGNED_2_COMPLEMENT, and PPL_UNSIGNED.

9.3.2.3 Bounded_Integer_Type_Width Parma_Polyhedra_Library::Interfaces::C::bounded_-integer_type_width (enum ppl_enum_Bounded_Integer_Type_Width *w*) `[inline]`

Definition at line 122 of file ppl_c_implementation_common.inlines.hh.

References PPL_BITS_128, PPL_BITS_16, PPL_BITS_32, PPL_BITS_64, and PPL_BITS_8.

9.3.2.4 const char∗ Parma_Polyhedra_Library::Interfaces::C::c_variable_default_output_-function (ppl_dimension_type *var*)

Definition at line 32 of file ppl_c_implementation_common.cc.

References CONVERSION, FORMAT, and user_error_handler.

Referenced by ppl_initialize().

9.3.2.5 void Parma_Polyhedra_Library::Interfaces::C::cxx_Variable_output_function (std::ostream & *s*, const Variable & *v*)

Definition at line 71 of file ppl_c_implementation_common.cc.

References c_variable_output_function.

Referenced by ppl_initialize().

9.3.2.6 void Parma_Polyhedra_Library::Interfaces::C::notify_error (enum ppl_enum_error_code *code*, const char * *description*)

9.3.2.7 mpz_class& Parma_Polyhedra_Library::Interfaces::C::reinterpret_mpz_class (mpz_t *n*) `[inline]`

Reinterpret an mpz_t as mpz_class.

Definition at line 38 of file ppl_c_implementation_common.inlines.hh.

Referenced by ppl_assign_Coefficient_from_mpz_t(), ppl_Coefficient_max(), ppl_Coefficient_min(), ppl_Coefficient_to_mpz_t(), and ppl_new_Coefficient_from_mpz_t().

9.3.2.8 Relation_Symbol Parma_Polyhedra_Library::Interfaces::C::relation_symbol (enum ppl_enum_Constraint_Type *t*) `[inline]`

Definition at line 104 of file ppl_c_implementation_common.inlines.hh.

References PPL_CONSTRAINT_TYPE_EQUAL, PPL_CONSTRAINT_TYPE_GREATER_OR_-EQUAL, PPL_CONSTRAINT_TYPE_GREATER_THAN, PPL_CONSTRAINT_TYPE_LESS_OR_-EQUAL, and PPL_CONSTRAINT_TYPE_LESS_THAN.

9.3.2.9 void Parma_Polyhedra_Library::Interfaces::C::reset_deterministic_timeout ()

Referenced by ppl_reset_deterministic_timeout(), and ppl_set_deterministic_timeout().

9.3.2.10 void Parma_Polyhedra_Library::Interfaces::C::reset_timeout ()

Referenced by ppl_reset_timeout(), and ppl_set_timeout().

9.3.2.11 ppl_const_PIP_Solution_Node_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Solution_Node * *x*) [inline]

Definition at line 101 of file ppl_c_implementation_common.inlines.hh.

9.3.2.12 const PIP_Solution_Node* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Solution_Node_t *x*) [inline]

Definition at line 101 of file ppl_c_implementation_common.inlines.hh.

9.3.2.13 ppl_const_PIP_Decision_Node_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Decision_Node * *x*) [inline]

Definition at line 99 of file ppl_c_implementation_common.inlines.hh.

9.3.2.14 const PIP_Decision_Node* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Decision_Node_t *x*) [inline]

Definition at line 99 of file ppl_c_implementation_common.inlines.hh.

9.3.2.15 ppl_const_PIP_Tree_Node_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Tree_Node * *x*) [inline]

Definition at line 97 of file ppl_c_implementation_common.inlines.hh.

9.3.2.16 const PIP_Tree_Node* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Tree_Node_t *x*) [inline]

Definition at line 97 of file ppl_c_implementation_common.inlines.hh.

9.3.2.17 ppl_const_PIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Problem * *x*) [inline]

Definition at line 95 of file ppl_c_implementation_common.inlines.hh.

9.3.2.18 const PIP_Problem* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Problem_t *x*) [inline]

Definition at line 95 of file ppl_c_implementation_common.inlines.hh.

9.3.2.19 ppl_const_MIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_const (const MIP_Problem * *x*) [inline]

Definition at line 93 of file ppl_c_implementation_common.inlines.hh.

9.3.2.20 const MIP_Problem* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_MIP_Problem_t *x*) [inline]

Definition at line 93 of file ppl_c_implementation_common.inlines.hh.

9.3.2.21 ppl_const_Artificial_Parameter_Sequence_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Artificial_Parameter_Sequence_const_iterator * *x*) [inline]

Definition at line 91 of file ppl_c_implementation_common.inlines.hh.

9.3.2.22 const Artificial_Parameter_Sequence_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Artificial_Parameter_Sequence_const_iterator_t *x*) [inline]

Definition at line 91 of file ppl_c_implementation_common.inlines.hh.

9.3.2.23 ppl_const_Artificial_Parameter_Sequence_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Artificial_Parameter_Sequence * *x*) [inline]

Definition at line 86 of file ppl_c_implementation_common.inlines.hh.

9.3.2.24 const Artificial_Parameter_Sequence* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Artificial_Parameter_Sequence_t *x*) [inline]

Definition at line 86 of file ppl_c_implementation_common.inlines.hh.

9.3.2.25 ppl_const_Artificial_Parameter_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Artificial_Parameter * *x*) [inline]

Definition at line 81 of file ppl_c_implementation_common.inlines.hh.

9.3.2.26 const Artificial_Parameter* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Artificial_Parameter_t *x*) [inline]

Definition at line 81 of file ppl_c_implementation_common.inlines.hh.

9.3.2.27 ppl_const_Grid_Generator_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Grid_Generator_System_const_iterator * *x*) [inline]

Definition at line 77 of file ppl_c_implementation_common.inlines.hh.

9.3.2.28 const Grid_Generator_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Grid_Generator_System_const_iterator_t *x*) [inline]

Definition at line 77 of file ppl_c_implementation_common.inlines.hh.

9.3.2.29 ppl_const_Grid_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Grid_Generator_System * *x*) [inline]

Definition at line 72 of file ppl_c_implementation_common.inlines.hh.

9.3.2.30 const Grid_Generator_System* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Grid_Generator_System_t *x*) [inline]

Definition at line 72 of file ppl_c_implementation_common.inlines.hh.

9.3.2.31 ppl_const_Grid_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Grid_Generator * *x*) [inline]

Definition at line 70 of file ppl_c_implementation_common.inlines.hh.

9.3.2.32 const Grid_Generator* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Grid_Generator_t *x*) [inline]

Definition at line 70 of file ppl_c_implementation_common.inlines.hh.

9.3.2.33 ppl_const_Congruence_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Congruence_System_const_iterator * *x*) [inline]

Definition at line 68 of file ppl_c_implementation_common.inlines.hh.

9.3.2.34 const Congruence_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Congruence_System_const_iterator_t *x*) [inline]

Definition at line 68 of file ppl_c_implementation_common.inlines.hh.

9.3.2.35 ppl_const_Congruence_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Congruence_System * *x*) [inline]

Definition at line 64 of file ppl_c_implementation_common.inlines.hh.

9.3.2.36 const Congruence_System* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Congruence_System_t *x*) [inline]

Definition at line 64 of file ppl_c_implementation_common.inlines.hh.

9.3.2.37 ppl_const_Congruence_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Congruence * *x*) [inline]

Definition at line 62 of file ppl_c_implementation_common.inlines.hh.

9.3.2.38 const Congruence* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Congruence_t *x*) [inline]

Definition at line 62 of file ppl_c_implementation_common.inlines.hh.

9.3.2.39 ppl_const_Generator_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Generator_System_const_iterator * *x*) [inline]

Definition at line 60 of file ppl_c_implementation_common.inlines.hh.

9.3.2.40 const Generator_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Generator_System_const_iterator_t *x*) [inline]

Definition at line 60 of file ppl_c_implementation_common.inlines.hh.

9.3.2.41 ppl_const_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Generator_System * *x*) [inline]

Definition at line 56 of file ppl_c_implementation_common.inlines.hh.

9.3.2.42 const Generator_System* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Generator_System_t *x*) [inline]

Definition at line 56 of file ppl_c_implementation_common.inlines.hh.

9.3.2.43 ppl_const_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Generator * *x*) [inline]

Definition at line 54 of file ppl_c_implementation_common.inlines.hh.

9.3.2.44 const Generator* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Generator_t *x*) [inline]

Definition at line 54 of file ppl_c_implementation_common.inlines.hh.

9.3.2.45 ppl_const_Constraint_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Constraint_System_const_iterator * *x*) [inline]

Definition at line 52 of file ppl_c_implementation_common.inlines.hh.

9.3.2.46 const Constraint_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Constraint_System_const_iterator_t *x*) [inline]

Definition at line 52 of file ppl_c_implementation_common.inlines.hh.

9.3.2.47 ppl_const_Constraint_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Constraint_System * *x*) [inline]

Definition at line 48 of file ppl_c_implementation_common.inlines.hh.

9.3.2.48 const Constraint_System* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Constraint_System_t *x*) [inline]

Definition at line 48 of file ppl_c_implementation_common.inlines.hh.

9.3.2.49 ppl_const_Constraint_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Constraint * *x*) [inline]

Definition at line 46 of file ppl_c_implementation_common.inlines.hh.

9.3.2.50 const Constraint* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Constraint_t *x*) [inline]

Definition at line 46 of file ppl_c_implementation_common.inlines.hh.

9.3.2.51 ppl_const_Linear_Expression_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Linear_Expression * *x*) [inline]

Definition at line 44 of file ppl_c_implementation_common.inlines.hh.

9.3.2.52 const Linear_Expression* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Linear_Expression_t *x*) [inline]

Definition at line 44 of file ppl_c_implementation_common.inlines.hh.

9.3.2.53 ppl_const_Coefficient_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Coefficient * *x*) [inline]

Definition at line 42 of file ppl_c_implementation_common.inlines.hh.

9.3.2.54 const Coefficient* Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Coefficient_t *x*) [inline]

Definition at line 42 of file ppl_c_implementation_common.inlines.hh.

Referenced by ppl_add_Linear_Expression_to_Linear_Expression(), ppl_Artificial_Parameter_-coefficient(), ppl_Artificial_Parameter_denominator(), ppl_Artificial_Parameter_get_Linear_-Expression(), ppl_Artificial_Parameter_inhomogeneous_term(), ppl_Artificial_Parameter_Sequence_-const_iterator_dereference(), ppl_Artificial_Parameter_Sequence_const_iterator_equal_test(), ppl_-assign_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_Sequence_const_-iterator(), ppl_assign_Coefficient_from_Coefficient(), ppl_assign_Congruence_from_Congruence(), ppl_assign_Congruence_System_const_iterator_from_Congruence_System_const_iterator(), ppl_-assign_Congruence_System_from_Congruence_System(), ppl_assign_Constraint_from_Constraint(), ppl_assign_Constraint_System_const_iterator_from_Constraint_System_const_iterator(), ppl_assign_-Constraint_System_from_Constraint_System(), ppl_assign_Generator_from_Generator(), ppl_assign_-Generator_System_const_iterator_from_Generator_System_const_iterator(), ppl_assign_Generator_-System_from_Generator_System(), ppl_assign_Grid_Generator_from_Grid_Generator(), ppl_assign_-Grid_Generator_System_const_iterator_from_Grid_Generator_System_const_iterator(), ppl_assign_-Grid_Generator_System_from_Grid_Generator_System(), ppl_assign_Linear_Expression_from_-Linear_Expression(), ppl_assign_MIP_Problem_from_MIP_Problem(), ppl_assign_PIP_Problem_-from_PIP_Problem(), ppl_Coefficient_to_mpz_t(), ppl_Congruence_coefficient(), ppl_Congruence_-inhomogeneous_term(), ppl_Congruence_modulus(), ppl_Congruence_OK(), ppl_Congruence_-space_dimension(), ppl_Congruence_System_begin(), ppl_Congruence_System_const_iterator_-dereference(), ppl_Congruence_System_const_iterator_equal_test(), ppl_Congruence_System_empty(), ppl_Congruence_System_end(), ppl_Congruence_System_insert_Congruence(), ppl_Congruence_-System_OK(), ppl_Congruence_System_space_dimension(), ppl_Constraint_coefficient(), ppl_-Constraint_inhomogeneous_term(), ppl_Constraint_OK(), ppl_Constraint_space_dimension(), ppl_-Constraint_System_begin(), ppl_Constraint_System_const_iterator_dereference(), ppl_Constraint_-System_const_iterator_equal_test(), ppl_Constraint_System_empty(), ppl_Constraint_System_-end(), ppl_Constraint_System_has_strict_inequalities(), ppl_Constraint_System_insert_Constraint(), ppl_Constraint_System_OK(), ppl_Constraint_System_space_dimension(), ppl_Constraint_type(), ppl_delete_Artificial_Parameter_Sequence_const_iterator(), ppl_delete_Coefficient(), ppl_delete_-Congruence(), ppl_delete_Congruence_System(), ppl_delete_Congruence_System_const_iterator(), ppl_-delete_Constraint(), ppl_delete_Constraint_System(), ppl_delete_Constraint_System_const_iterator(), ppl_delete_Generator(), ppl_delete_Generator_System(), ppl_delete_Generator_System_const_iterator(), ppl_delete_Grid_Generator(), ppl_delete_Grid_Generator_System(), ppl_delete_Grid_Generator_-System_const_iterator(), ppl_delete_Linear_Expression(), ppl_delete_MIP_Problem(), ppl_delete_-PIP_Problem(), ppl_Generator_coefficient(), ppl_Generator_divisor(), ppl_Generator_OK(), ppl_-Generator_space_dimension(), ppl_Generator_System_begin(), ppl_Generator_System_const_iterator_-dereference(), ppl_Generator_System_const_iterator_equal_test(), ppl_Generator_System_empty(), ppl_Generator_System_end(), ppl_Generator_System_insert_Generator(), ppl_Generator_System_OK(), ppl_Generator_System_space_dimension(), ppl_Generator_type(), ppl_Grid_Generator_coefficient(), ppl_Grid_Generator_divisor(), ppl_Grid_Generator_OK(), ppl_Grid_Generator_space_dimension(), ppl_Grid_Generator_System_begin(), ppl_Grid_Generator_System_const_iterator_dereference(), ppl_-Grid_Generator_System_const_iterator_equal_test(), ppl_Grid_Generator_System_empty(), ppl_-Grid_Generator_System_end(), ppl_Grid_Generator_System_insert_Grid_Generator(), ppl_Grid_-Generator_System_OK(), ppl_Grid_Generator_System_space_dimension(), ppl_Grid_Generator_-type(), ppl_Linear_Expression_add_to_coefficient(), ppl_Linear_Expression_add_to_inhomogeneous(), ppl_Linear_Expression_all_homogeneous_terms_are_zero(), ppl_Linear_Expression_coefficient(), ppl_Linear_Expression_inhomogeneous_term(), ppl_Linear_Expression_is_zero(), ppl_Linear_-Expression_OK(), ppl_Linear_Expression_space_dimension(), ppl_MIP_Problem_add_constraint(), ppl_MIP_Problem_add_constraints(), ppl_MIP_Problem_constraint_at_index(), ppl_MIP_Problem_-evaluate_objective_function(), ppl_MIP_Problem_external_memory_in_bytes(), ppl_MIP_Problem_-feasible_point(), ppl_MIP_Problem_get_control_parameter(), ppl_MIP_Problem_integer_space_-dimensions(), ppl_MIP_Problem_is_satisfiable(), ppl_MIP_Problem_number_of_constraints(), ppl_-MIP_Problem_number_of_integer_space_dimensions(), ppl_MIP_Problem_objective_function(), ppl_MIP_Problem_OK(), ppl_MIP_Problem_optimal_value(), ppl_MIP_Problem_optimization_-

mode(), ppl_MIP_Problem_optimizing_point(), ppl_MIP_Problem_set_objective_function(), ppl_MIP_-Problem_solve(), ppl_MIP_Problem_space_dimension(), ppl_MIP_Problem_total_memory_in_bytes(), ppl_multiply_Linear_Expression_by_Coefficient(), ppl_new_Artificial_Parameter_Sequence_const_-iterator_from_Artificial_Parameter_Sequence_const_iterator(), ppl_new_Coefficient_from_Coefficient(), ppl_new_Congruence(), ppl_new_Congruence_from_Congruence(), ppl_new_Congruence_System_-const_iterator_from_Congruence_System_const_iterator(), ppl_new_Congruence_System_from_-Congruence(), ppl_new_Congruence_System_from_Congruence_System(), ppl_new_Constraint(), ppl_new_Constraint_from_Constraint(), ppl_new_Constraint_System_const_iterator_from_Constraint_-System_const_iterator(), ppl_new_Constraint_System_from_Constraint(), ppl_new_Constraint_-System_from_Constraint_System(), ppl_new_Generator(), ppl_new_Generator_from_Generator(), ppl_new_Generator_System_const_iterator_from_Generator_System_const_iterator(), ppl_new_-Generator_System_from_Generator(), ppl_new_Generator_System_from_Generator_System(), ppl_-new_Grid_Generator(), ppl_new_Grid_Generator_from_Grid_Generator(), ppl_new_Grid_Generator_-System_const_iterator_from_Grid_Generator_System_const_iterator(), ppl_new_Grid_Generator_-System_from_Grid_Generator(), ppl_new_Grid_Generator_System_from_Grid_Generator_System(), ppl_new_Linear_Expression_from_Congruence(), ppl_new_Linear_Expression_from_Constraint(), ppl_-new_Linear_Expression_from_Generator(), ppl_new_Linear_Expression_from_Linear_Expression(), ppl_new_MIP_Problem(), ppl_new_MIP_Problem_from_MIP_Problem(), ppl_new_PIP_Problem_-from_constraints(), ppl_new_PIP_Problem_from_PIP_Problem(), ppl_PIP_Decision_Node_get_child_-node(), ppl_PIP_Decision_Node_OK(), ppl_PIP_Problem_add_constraint(), ppl_PIP_Problem_add_-constraints(), ppl_PIP_Problem_constraint_at_index(), ppl_PIP_Problem_external_memory_in_bytes(), ppl_PIP_Problem_get_big_parameter_dimension(), ppl_PIP_Problem_get_control_parameter(), ppl_-PIP_Problem_is_satisfiable(), ppl_PIP_Problem_number_of_constraints(), ppl_PIP_Problem_number_-of_parameter_space_dimensions(), ppl_PIP_Problem_OK(), ppl_PIP_Problem_optimizing_solution(), ppl_PIP_Problem_parameter_space_dimensions(), ppl_PIP_Problem_solution(), ppl_PIP_Problem_-solve(), ppl_PIP_Problem_space_dimension(), ppl_PIP_Problem_total_memory_in_bytes(), ppl_PIP_-Solution_Node_get_parametric_values(), ppl_PIP_Solution_Node_OK(), ppl_PIP_Tree_Node_as_-decision(), ppl_PIP_Tree_Node_as_solution(), ppl_PIP_Tree_Node_begin(), ppl_PIP_Tree_Node_end(), ppl_PIP_Tree_Node_get_constraints(), ppl_PIP_Tree_Node_number_of_artificials(), ppl_PIP_Tree_-Node_OK(), and ppl_subtract_Linear_Expression_from_Linear_Expression().

9.3.2.55 ppl_PIP_Solution_Node_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Solution_Node * *x*) `[inline]`

Definition at line 101 of file ppl_c_implementation_common.inlines.hh.

9.3.2.56 PIP_Solution_Node* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Solution_Node_t *x*) `[inline]`

Definition at line 101 of file ppl_c_implementation_common.inlines.hh.

9.3.2.57 ppl_PIP_Decision_Node_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Decision_Node * *x*) `[inline]`

Definition at line 99 of file ppl_c_implementation_common.inlines.hh.

9.3.2.58 PIP_Decision_Node* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Decision_Node_t *x*) [inline]

Definition at line 99 of file ppl_c_implementation_common.inlines.hh.

9.3.2.59 ppl_PIP_Tree_Node_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Tree_Node * *x*) [inline]

Definition at line 97 of file ppl_c_implementation_common.inlines.hh.

9.3.2.60 PIP_Tree_Node* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Tree_Node_t *x*) [inline]

Definition at line 97 of file ppl_c_implementation_common.inlines.hh.

9.3.2.61 ppl_PIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Problem * *x*) [inline]

Definition at line 95 of file ppl_c_implementation_common.inlines.hh.

9.3.2.62 PIP_Problem* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Problem_t *x*) [inline]

Definition at line 95 of file ppl_c_implementation_common.inlines.hh.

9.3.2.63 ppl_MIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (MIP_Problem * *x*) [inline]

Definition at line 93 of file ppl_c_implementation_common.inlines.hh.

9.3.2.64 MIP_Problem* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_MIP_Problem_t *x*) [inline]

Definition at line 93 of file ppl_c_implementation_common.inlines.hh.

9.3.2.65 ppl_Artificial_Parameter_Sequence_const_iterator_t Parma_Polyhedra_-Library::Interfaces::C::to_nonconst (Artificial_Parameter_Sequence_const_iterator ∗ *x*) [inline]

Definition at line 91 of file ppl_c_implementation_common.inlines.hh.

9.3.2.66 Artificial_Parameter_Sequence_const_iterator∗ Parma_Polyhedra_-Library::Interfaces::C::to_nonconst (ppl_Artificial_Parameter_Sequence_const_-iterator_t *x*) [inline]

Definition at line 91 of file ppl_c_implementation_common.inlines.hh.

9.3.2.67 ppl_Artificial_Parameter_Sequence_t Parma_Polyhedra_Library::Interfaces::C::to_-nonconst (Artificial_Parameter_Sequence ∗ *x*) [inline]

Definition at line 86 of file ppl_c_implementation_common.inlines.hh.

9.3.2.68 Artificial_Parameter_Sequence∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Artificial_Parameter_Sequence_t *x*) [inline]

Definition at line 86 of file ppl_c_implementation_common.inlines.hh.

9.3.2.69 ppl_Artificial_Parameter_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Artificial_Parameter ∗ *x*) [inline]

Definition at line 81 of file ppl_c_implementation_common.inlines.hh.

9.3.2.70 Artificial_Parameter∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Artificial_Parameter_t *x*) [inline]

Definition at line 81 of file ppl_c_implementation_common.inlines.hh.

9.3.2.71 ppl_Grid_Generator_System_const_iterator_t Parma_Polyhedra_-Library::Interfaces::C::to_nonconst (Grid_Generator_System_const_iterator ∗ *x*) [inline]

Definition at line 77 of file ppl_c_implementation_common.inlines.hh.

9.3.2.72 Grid_Generator_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Grid_Generator_System_const_iterator_t *x*) [inline]

Definition at line 77 of file ppl_c_implementation_common.inlines.hh.

9.3.2.73 ppl_Grid_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Grid_Generator_System * *x*) [inline]

Definition at line 72 of file ppl_c_implementation_common.inlines.hh.

9.3.2.74 Grid_Generator_System* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Grid_Generator_System_t *x*) [inline]

Definition at line 72 of file ppl_c_implementation_common.inlines.hh.

9.3.2.75 ppl_Grid_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Grid_Generator * *x*) [inline]

Definition at line 70 of file ppl_c_implementation_common.inlines.hh.

9.3.2.76 Grid_Generator* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Grid_Generator_t *x*) [inline]

Definition at line 70 of file ppl_c_implementation_common.inlines.hh.

9.3.2.77 ppl_Congruence_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Congruence_System_const_iterator * *x*) [inline]

Definition at line 68 of file ppl_c_implementation_common.inlines.hh.

9.3.2.78 Congruence_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Congruence_System_const_iterator_t *x*) [inline]

Definition at line 68 of file ppl_c_implementation_common.inlines.hh.

9.3.2.79 ppl_Congruence_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Congruence_System * *x*) [inline]

Definition at line 64 of file ppl_c_implementation_common.inlines.hh.

9.3.2.80 Congruence_System* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Congruence_System_t *x*) [inline]

Definition at line 64 of file ppl_c_implementation_common.inlines.hh.

9.3.2.81 ppl_Congruence_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Congruence * *x*) [inline]

Definition at line 62 of file ppl_c_implementation_common.inlines.hh.

9.3.2.82 Congruence* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Congruence_t *x*) [inline]

Definition at line 62 of file ppl_c_implementation_common.inlines.hh.

9.3.2.83 ppl_Generator_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_-nonconst (Generator_System_const_iterator * *x*) [inline]

Definition at line 60 of file ppl_c_implementation_common.inlines.hh.

9.3.2.84 Generator_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_-nonconst (ppl_Generator_System_const_iterator_t *x*) [inline]

Definition at line 60 of file ppl_c_implementation_common.inlines.hh.

9.3.2.85 ppl_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Generator_System * *x*) [inline]

Definition at line 56 of file ppl_c_implementation_common.inlines.hh.

9.3.2.86 Generator_System* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Generator_System_t *x*) [inline]

Definition at line 56 of file ppl_c_implementation_common.inlines.hh.

9.3.2.87 ppl_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Generator * *x*) [inline]

Definition at line 54 of file ppl_c_implementation_common.inlines.hh.

9.3.2.88 Generator* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Generator_t *x*) [inline]

Definition at line 54 of file ppl_c_implementation_common.inlines.hh.

9.3.2.89 ppl_Constraint_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Constraint_System_const_iterator * *x*) [inline]

Definition at line 52 of file ppl_c_implementation_common.inlines.hh.

9.3.2.90 Constraint_System_const_iterator* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Constraint_System_const_iterator_t *x*) [inline]

Definition at line 52 of file ppl_c_implementation_common.inlines.hh.

9.3.2.91 ppl_Constraint_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Constraint_System * *x*) [inline]

Definition at line 48 of file ppl_c_implementation_common.inlines.hh.

9.3.2.92 Constraint_System* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Constraint_System_t *x*) [inline]

Definition at line 48 of file ppl_c_implementation_common.inlines.hh.

9.3.2.93 ppl_Constraint_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Constraint * *x*) [inline]

Definition at line 46 of file ppl_c_implementation_common.inlines.hh.

9.3.2.94 Constraint* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Constraint_t *x*) [inline]

Definition at line 46 of file ppl_c_implementation_common.inlines.hh.

9.3.2.95 ppl_Linear_Expression_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Linear_Expression * *x*) [inline]

Definition at line 44 of file ppl_c_implementation_common.inlines.hh.

9.3.2.96 Linear_Expression* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Linear_Expression_t *x*) [inline]

Definition at line 44 of file ppl_c_implementation_common.inlines.hh.

9.3.2.97 ppl_Coefficient_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Coefficient * *x*) [inline]

Definition at line 42 of file ppl_c_implementation_common.inlines.hh.

9.3.2.98 Coefficient* Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Coefficient_t *x*) [inline]

Definition at line 42 of file ppl_c_implementation_common.inlines.hh.

Referenced by ppl_add_Linear_Expression_to_Linear_Expression(), ppl_Artificial_Parameter_coefficient(), ppl_Artificial_Parameter_denominator(), ppl_Artificial_Parameter_get_Linear_Expression(), ppl_Artificial_Parameter_inhomogeneous_term(), ppl_Artificial_Parameter_Sequence_const_iterator_increment(), ppl_assign_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_Sequence_const_iterator(), ppl_assign_Coefficient_from_Coefficient(), ppl_assign_Coefficient_from_mpz_t(), ppl_assign_Congruence_from_Congruence(), ppl_assign_Congruence_System_const_iterator_from_Congruence_System_const_iterator(), ppl_assign_Congruence_System_from_Congruence_System(), ppl_assign_Constraint_from_Constraint(), ppl_assign_Constraint_System_const_iterator_from_Constraint_System_const_iterator(), ppl_assign_Constraint_System_from_Constraint_System(), ppl_assign_Generator_from_Generator(), ppl_assign_Generator_System_const_iterator_from_Generator_System_const_iterator(), ppl_assign_Generator_System_from_Generator_System(), ppl_assign_Grid_Generator_from_Grid_Generator(), ppl_assign_Grid_Generator_System_const_iterator_from_Grid_Generator_System_const_iterator(), ppl_assign_Grid_Generator_System_from_Grid_Generator_System(), ppl_assign_Linear_Expression_from_Linear_Expression(), ppl_assign_MIP_Problem_from_MIP_Problem(), ppl_assign_PIP_Problem_from_PIP_Problem(), ppl_Congruence_coefficient(), ppl_Congruence_inhomogeneous_term(), ppl_Congruence_modulus(), ppl_Congruence_System_begin(), ppl_Congruence_System_clear(), ppl_Congruence_System_const_iterator_increment(), ppl_Congruence_System_end(), ppl_Congruence_System_insert_Congruence(), ppl_Constraint_coefficient(), ppl_Constraint_inhomogeneous_term(), ppl_Constraint_System_begin(),

ppl_Constraint_System_clear(), ppl_Constraint_System_const_iterator_increment(), ppl_Constraint_-System_end(), ppl_Constraint_System_insert_Constraint(), ppl_Generator_coefficient(), ppl_Generator_-divisor(), ppl_Generator_System_begin(), ppl_Generator_System_clear(), ppl_Generator_System_-const_iterator_increment(), ppl_Generator_System_end(), ppl_Generator_System_insert_Generator(), ppl_Grid_Generator_coefficient(), ppl_Grid_Generator_divisor(), ppl_Grid_Generator_System_begin(), ppl_Grid_Generator_System_clear(), ppl_Grid_Generator_System_const_iterator_increment(), ppl_-Grid_Generator_System_end(), ppl_Grid_Generator_System_insert_Grid_Generator(), ppl_Linear_-Expression_add_to_coefficient(), ppl_Linear_Expression_add_to_inhomogeneous(), ppl_Linear_-Expression_coefficient(), ppl_Linear_Expression_inhomogeneous_term(), ppl_MIP_Problem_add_-constraint(), ppl_MIP_Problem_add_constraints(), ppl_MIP_Problem_add_space_dimensions_-and_embed(), ppl_MIP_Problem_add_to_integer_space_dimensions(), ppl_MIP_Problem_clear(), ppl_MIP_Problem_evaluate_objective_function(), ppl_MIP_Problem_optimal_value(), ppl_MIP_-Problem_set_control_parameter(), ppl_MIP_Problem_set_objective_function(), ppl_MIP_Problem_-set_optimization_mode(), ppl_multiply_Linear_Expression_by_Coefficient(), ppl_new_Artificial_-Parameter_Sequence_const_iterator(), ppl_new_Artificial_Parameter_Sequence_const_iterator_from_-Artificial_Parameter_Sequence_const_iterator(), ppl_new_Coefficient(), ppl_new_Coefficient_from_-Coefficient(), ppl_new_Coefficient_from_mpz_t(), ppl_new_Congruence(), ppl_new_Congruence_-from_Congruence(), ppl_new_Congruence_System(), ppl_new_Congruence_System_const_iterator(), ppl_new_Congruence_System_const_iterator_from_Congruence_System_const_iterator(), ppl_new_-Congruence_System_from_Congruence(), ppl_new_Congruence_System_from_Congruence_System(), ppl_new_Congruence_System_zero_dim_empty(), ppl_new_Congruence_zero_dim_false(), ppl_new_-Congruence_zero_dim_integrality(), ppl_new_Constraint(), ppl_new_Constraint_from_Constraint(), ppl_new_Constraint_System(), ppl_new_Constraint_System_const_iterator(), ppl_new_Constraint_-System_const_iterator_from_Constraint_System_const_iterator(), ppl_new_Constraint_System_-from_Constraint(), ppl_new_Constraint_System_from_Constraint_System(), ppl_new_Constraint_-System_zero_dim_empty(), ppl_new_Constraint_zero_dim_false(), ppl_new_Constraint_zero_dim_-positivity(), ppl_new_Generator(), ppl_new_Generator_from_Generator(), ppl_new_Generator_-System(), ppl_new_Generator_System_const_iterator(), ppl_new_Generator_System_const_iterator_-from_Generator_System_const_iterator(), ppl_new_Generator_System_from_Generator(), ppl_new_-Generator_System_from_Generator_System(), ppl_new_Generator_System_zero_dim_univ(), ppl_new_-Generator_zero_dim_closure_point(), ppl_new_Generator_zero_dim_point(), ppl_new_Grid_Generator(), ppl_new_Grid_Generator_from_Grid_Generator(), ppl_new_Grid_Generator_System(), ppl_new_-Grid_Generator_System_const_iterator(), ppl_new_Grid_Generator_System_const_iterator_from_-Grid_Generator_System_const_iterator(), ppl_new_Grid_Generator_System_from_Grid_Generator(), ppl_new_Grid_Generator_System_from_Grid_Generator_System(), ppl_new_Grid_Generator_System_-zero_dim_univ(), ppl_new_Grid_Generator_zero_dim_point(), ppl_new_Linear_Expression(), ppl_-new_Linear_Expression_from_Congruence(), ppl_new_Linear_Expression_from_Constraint(), ppl_-new_Linear_Expression_from_Generator(), ppl_new_Linear_Expression_from_Linear_Expression(), ppl_new_Linear_Expression_with_dimension(), ppl_new_MIP_Problem(), ppl_new_MIP_Problem_-from_MIP_Problem(), ppl_new_MIP_Problem_from_space_dimension(), ppl_new_PIP_Problem_-from_constraints(), ppl_new_PIP_Problem_from_PIP_Problem(), ppl_new_PIP_Problem_from_-space_dimension(), ppl_PIP_Problem_add_constraint(), ppl_PIP_Problem_add_constraints(), ppl_-PIP_Problem_add_space_dimensions_and_embed(), ppl_PIP_Problem_add_to_parameter_space_-dimensions(), ppl_PIP_Problem_clear(), ppl_PIP_Problem_set_big_parameter_dimension(), ppl_-PIP_Problem_set_control_parameter(), ppl_PIP_Tree_Node_begin(), ppl_PIP_Tree_Node_end(), and ppl_subtract_Linear_Expression_from_Linear_Expression().

9.3.3 Variable Documentation

9.3.3.1 ppl_io_variable_output_function_type* Parma_Polyhedra_Library::Interfaces::C::c_-variable_output_function

Definition at line 68 of file ppl_c_implementation_common.cc.

Referenced by cxx_Variable_output_function(), ppl_initialize(), ppl_io_asprint_variable(), ppl_io_fprint_-variable(), ppl_io_get_variable_output_function(), ppl_io_print_variable(), and ppl_io_set_variable_-output_function().

9.3.3.2 Variable::output_function_type* Parma_Polyhedra_Library::Interfaces::C::saved_cxx_-Variable_output_function

Definition at line 84 of file ppl_c_implementation_common.cc.

Referenced by ppl_finalize(), and ppl_initialize().

9.3.3.3 error_handler_type Parma_Polyhedra_Library::Interfaces::C::user_error_handler = 0

Definition at line 29 of file ppl_c_implementation_common.cc.

Referenced by c_variable_default_output_function(), and ppl_set_error_handler().

10 Class Documentation

10.1 Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_-Wrapper Class Reference

A class to wrap an array of fixed length into a partial function interface suitable for the map_space_-dimension() methods.

`#include <ppl_c_implementation_common.defs.hh>`

Public Member Functions

- Array_Partial_Function_Wrapper (dimension_type *v, size_t n)

  Construct a partial function wrapping the first `n` positions of `v`.

- bool has_empty_codomain () const

  Returns `true` if and only if the represented partial function has an empty codomain (i.e., it is always undefined).

- dimension_type max_in_codomain () const

  Returns the maximum value that belongs to the codomain of the partial function.

- bool maps (dimension_type i, dimension_type &j) const

  Assigns to `j` the value associated to `i` by `*this`, if any.

Private Attributes

- dimension_type * vec

  Holds the vector implementing the map.

- size_t vec_size

  Holds the size of `vec`.

- dimension_type max_in_codomain_

  Cache for computing the maximum dimension in the codomain.

- int empty

10.1.1 Detailed Description

A class to wrap an array of fixed length into a partial function interface suitable for the map_space_-dimension() methods.

Definition at line 60 of file ppl_c_implementation_common.defs.hh.

10.1.2 Constructor & Destructor Documentation

10.1.2.1 Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_-Wrapper::Array_Partial_Function_Wrapper (dimension_type * *v*, size_t *n*) `[inline]`

Construct a partial function wrapping the first `n` positions of `v`.

Definition at line 167 of file ppl_c_implementation_common.inlines.hh.

10.1.3 Member Function Documentation

10.1.3.1 bool Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_-Wrapper::has_empty_codomain () const `[inline]`

Returns `true` if and only if the represented partial function has an empty codomain (i.e., it is always undefined).

Definition at line 172 of file ppl_c_implementation_common.inlines.hh.

References empty, vec, and vec_size.

10.1.3.2 bool Parma_Polyhedra_Library::Interfaces::C::Array_Partial_-Function_Wrapper::maps (dimension_type *i*, dimension_type & *j*) const `[inline]`

Assigns to `j` the value associated to `i` by `*this`, if any.

Let f be the function represented by `*this` and k be the value of `i`. If f is defined in k, then $f(k)$ is assigned to `j` and `true` is returned. If f is undefined in k, then `false` is returned.

Definition at line 199 of file ppl_c_implementation_common.inlines.hh.

References vec, and vec_size.

10.1.3.3 dimension_type Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_-Wrapper::max_in_codomain () const [inline]

Returns the maximum value that belongs to the codomain of the partial function.

Definition at line 185 of file ppl_c_implementation_common.inlines.hh.

References max_in_codomain_, vec, and vec_size.

10.1.4 Member Data Documentation

10.1.4.1 int Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_Wrapper::empty [mutable, private]

Cache for computing emptiness: -1 if we still don't know, 0 if not empty, 1 if empty.

Definition at line 103 of file ppl_c_implementation_common.defs.hh.

Referenced by has_empty_codomain().

10.1.4.2 dimension_type Parma_Polyhedra_Library::Interfaces::C::Array_-Partial_Function_Wrapper::max_in_codomain_ [mutable, private]

Cache for computing the maximum dimension in the codomain.

Definition at line 99 of file ppl_c_implementation_common.defs.hh.

Referenced by max_in_codomain().

10.1.4.3 dimension_type* Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_-Wrapper::vec [private]

Holds the vector implementing the map.

Definition at line 93 of file ppl_c_implementation_common.defs.hh.

Referenced by has_empty_codomain(), maps(), and max_in_codomain().

10.1.4.4 size_t Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_-Wrapper::vec_size [private]

Holds the size of `vec`.

Definition at line 96 of file ppl_c_implementation_common.defs.hh.

Referenced by has_empty_codomain(), maps(), and max_in_codomain().

The documentation for this class was generated from the following files:

- ppl_c_implementation_common.defs.hh
- ppl_c_implementation_common.inlines.hh

10.2 Parma_Polyhedra_Library::Interfaces::C::deterministic_timeout_exception Class Reference

```
#include <ppl_c_implementation_common.defs.hh>
```

Public Member Functions

- void throw_me () const
- int priority () const

10.2.1 Detailed Description

Definition at line 118 of file ppl_c_implementation_common.defs.hh.

10.2.2 Member Function Documentation

10.2.2.1 int Parma_Polyhedra_Library::Interfaces::C::deterministic_timeout_exception::priority () const [inline]

Definition at line 124 of file ppl_c_implementation_common.defs.hh.

10.2.2.2 void Parma_Polyhedra_Library::Interfaces::C::deterministic_timeout_-exception::throw_me () const [inline]

Definition at line 121 of file ppl_c_implementation_common.defs.hh.

The documentation for this class was generated from the following file:

- ppl_c_implementation_common.defs.hh

10.3 ppl_Artificial_Parameter_Sequence_const_iterator_tag Interface Reference

Types and functions for iterating on PIP artificial parameters.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t *papit)
  Builds a new 'const iterator' and writes a handle to it at address `papit`.

- int ppl_new_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t *papit, ppl_const_Artificial_Parameter_Sequence_const_iterator_t apit)
  Builds a const iterator that is a copy of `apit`*; writes a handle for the newly created const iterator at address* `papit`.

- int ppl_assign_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t dst, ppl_const_Artificial_Parameter_Sequence_const_iterator_t src)
  Assigns a copy of the const iterator `src` *to* `dst`.

- int ppl_delete_Artificial_Parameter_Sequence_const_iterator (ppl_const_Artificial_Parameter_Sequence_const_iterator_t apit)
  Invalidates the handle `apit`*: this makes sure the corresponding resources will eventually be released.*

Dereferencing, Incrementing and Equality Testing

- int ppl_Artificial_Parameter_Sequence_const_iterator_dereference (ppl_const_Artificial_Parameter_Sequence_const_iterator_t apit, ppl_const_Artificial_Parameter_t *pap)
  Dereference `apit` *writing a const handle to the resulting artificial parameter at address* `pap`.

- int ppl_Artificial_Parameter_Sequence_const_iterator_increment (ppl_Artificial_Parameter_Sequence_const_iterator_t apit)
  Increment `apit` *so that it "points" to the next artificial parameter.*

- int ppl_Artificial_Parameter_Sequence_const_iterator_equal_test (ppl_const_Artificial_Parameter_Sequence_const_iterator_t x, ppl_const_Artificial_Parameter_Sequence_const_iterator_t y)
  Returns a positive integer if the iterators corresponding to `x` *and* `y` *are equal; returns 0 if they are different.*

10.3.1 Detailed Description

Types and functions for iterating on PIP artificial parameters.

10.3.2 Friends And Related Function Documentation

10.3.2.1 int ppl_Artificial_Parameter_Sequence_const_iterator_dereference (ppl_const_Artificial_Parameter_Sequence_const_iterator_t *apit*, ppl_const_Artificial_Parameter_t * *pap*) `[related]`

Dereference `apit` writing a const handle to the resulting artificial parameter at address `pap`.

Definition at line 2561 of file ppl_c_implementation_common.cc.

10.3.2.2 int ppl_Artificial_Parameter_Sequence_const_iterator_equal_test (ppl_const_Artificial_Parameter_Sequence_const_iterator_t *x*, ppl_const_Artificial_Parameter_Sequence_const_iterator_t *y*) `[related]`

Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

Definition at line 2581 of file ppl_c_implementation_common.cc.

10.3.2.3 int ppl_Artificial_Parameter_Sequence_const_iterator_increment (ppl_Artificial_Parameter_Sequence_const_iterator_t *apit*) `[related]`

Increment `apit` so that it "points" to the next artificial parameter.

Definition at line 2572 of file ppl_c_implementation_common.cc.

10.3.2.4 int ppl_assign_Artificial_Parameter_Sequence_const_iterator_from_Artificial_-Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_-iterator_t *dst*, ppl_const_Artificial_Parameter_Sequence_const_iterator_t *src*) `[related]`

Assigns a copy of the const iterator `src` to `dst`.

Definition at line 2550 of file ppl_c_implementation_common.cc.

10.3.2.5 int ppl_delete_Artificial_Parameter_Sequence_const_iterator (ppl_const_Artificial_Parameter_Sequence_const_iterator_t *apit*) `[related]`

Invalidates the handle `apit`: this makes sure the corresponding resources will eventually be released.

Definition at line 2541 of file ppl_c_implementation_common.cc.

10.3.2.6 int ppl_new_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t * *papit*) `[related]`

Builds a new 'const iterator' and writes a handle to it at address `papit`.

Definition at line 2524 of file ppl_c_implementation_common.cc.

10.3.2.7 int ppl_new_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_-Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t * *papit*, ppl_const_Artificial_Parameter_Sequence_const_iterator_t *apit*) `[related]`

Builds a const iterator that is a copy of `apit`; writes a handle for the newly created const iterator at address `papit`.

Definition at line 2532 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.4 ppl_Artificial_Parameter_tag Interface Reference

Types and functions for PIP artificial parameters.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

- int ppl_Artificial_Parameter_get_Linear_Expression (ppl_const_Artificial_Parameter_t ap, ppl_-Linear_Expression_t le)

  Copies into `le` the linear expression in artificial parameter `ap`.

- int ppl_Artificial_Parameter_coefficient (ppl_const_Artificial_Parameter_t ap, ppl_dimension_type var, ppl_Coefficient_t n)

  Copies into `n` the coefficient of variable `var` in the artificial parameter `ap`.

- int ppl_Artificial_Parameter_get_inhomogeneous_term (ppl_const_Artificial_Parameter_t ap, ppl_-Coefficient_t n)

  Copies into `n` the inhomogeneous term of the artificial parameter `ap`.

- int ppl_Artificial_Parameter_denominator (ppl_const_Artificial_Parameter_t ap, ppl_Coefficient_t n)

  Copies into `n` the denominator in artificial parameter `ap`.

10.4.1 Detailed Description

Types and functions for PIP artificial parameters. The types and functions for PIP artificial parameters provide an interface towards *Artificial_Parameter*.

10.4.2 Friends And Related Function Documentation

10.4.2.1 int ppl_Artificial_Parameter_coefficient (ppl_const_Artificial_Parameter_t *ap*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) `[related]`

Copies into `n` the coefficient of variable `var` in the artificial parameter `ap`.

Definition at line 2488 of file ppl_c_implementation_common.cc.

10.4.2.2 int ppl_Artificial_Parameter_denominator (ppl_const_Artificial_Parameter_t *ap*, ppl_Coefficient_t *n*) `[related]`

Copies into `n` the denominator in artificial parameter `ap`.

Definition at line 2510 of file ppl_c_implementation_common.cc.

10.4.2.3 int ppl_Artificial_Parameter_get_inhomogeneous_term (ppl_const_Artificial_Parameter_t *ap*, ppl_Coefficient_t *n*) `[related]`

Copies into `n` the inhomogeneous term of the artificial parameter `ap`.

10.4.2.4 int ppl_Artificial_Parameter_get_Linear_Expression (ppl_const_Artificial_Parameter_t *ap*, ppl_Linear_Expression_t *le*) `[related]`

Copies into `le` the linear expression in artificial parameter `ap`.

Definition at line 2478 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.5 ppl_Coefficient_tag Interface Reference

Types and functions for coefficients.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Coefficient (ppl_Coefficient_t *pc)
  Creates a new coefficient with value 0 and writes a handle for the newly created coefficient at address `pc`.
- int ppl_new_Coefficient_from_mpz_t (ppl_Coefficient_t *pc, mpz_t z)
  Creates a new coefficient with the value given by the GMP integer `z` and writes a handle for the newly created coefficient at address `pc`.
- int ppl_new_Coefficient_from_Coefficient (ppl_Coefficient_t *pc, ppl_const_Coefficient_t c)

Builds a coefficient that is a copy of `c`; writes a handle for the newly created coefficient at address `pc`.

- int ppl_assign_Coefficient_from_mpz_t (ppl_Coefficient_t dst, mpz_t z)
  Assign to `dst` the value given by the GMP integer `z`.
- int ppl_assign_Coefficient_from_Coefficient (ppl_Coefficient_t dst, ppl_const_Coefficient_t src)
  Assigns a copy of the coefficient `src` to `dst`.
- int ppl_delete_Coefficient (ppl_const_Coefficient_t c)
  Invalidates the handle `c`: this makes sure the corresponding resources will eventually be released.

Read-Only Accessor Functions

- int ppl_Coefficient_to_mpz_t (ppl_const_Coefficient_t c, mpz_t z)
  Sets the value of the GMP integer `z` to the value of `c`.
- int ppl_Coefficient_OK (ppl_const_Coefficient_t c)
  Returns a positive integer if `c` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `c` is broken. Useful for debugging purposes.
- int ppl_Coefficient_is_bounded (void)
  Returns a positive integer if coefficients are bounded; returns 0 otherwise.
- int ppl_Coefficient_min (mpz_t min)
  Returns a positive integer if coefficients are bounded, in which case `min` is set to their minimum value; returns 0 otherwise.
- int ppl_Coefficient_max (mpz_t max)
  Returns a positive integer if coefficients are bounded, in which case `max` is set to their maximum value; returns 0 otherwise.

10.5.1 Detailed Description

Types and functions for coefficients. The types and functions for coefficients provide an interface towards *Coefficient*. Depending on configuration, the PPL coefficients may be implemented by the unbounded precision integers provided by GMP (default), or by bounded precision integers (with checks for overflows).

10.5.2 Friends And Related Function Documentation

10.5.2.1 int ppl_assign_Coefficient_from_Coefficient (ppl_Coefficient_t *dst*, ppl_const_Coefficient_t *src*) `[related]`

Assigns a copy of the coefficient `src` to `dst`.

Definition at line 442 of file ppl_c_implementation_common.cc.

10.5.2.2 int ppl_assign_Coefficient_from_mpz_t (ppl_Coefficient_t *dst*, mpz_t *z*) `[related]`

Assign to `dst` the value given by the GMP integer `z`.

Definition at line 434 of file ppl_c_implementation_common.cc.

10.5.2.3 int ppl_Coefficient_is_bounded (void) [related]

Returns a positive integer if coefficients are bounded; returns 0 otherwise.

Definition at line 458 of file ppl_c_implementation_common.cc.

10.5.2.4 int ppl_Coefficient_max (mpz_t *max*) [related]

Returns a positive integer if coefficients are bounded, in which case `max` is set to their maximum value; returns 0 otherwise.

Definition at line 477 of file ppl_c_implementation_common.cc.

10.5.2.5 int ppl_Coefficient_min (mpz_t *min*) [related]

Returns a positive integer if coefficients are bounded, in which case `min` is set to their minimum value; returns 0 otherwise.

Definition at line 464 of file ppl_c_implementation_common.cc.

10.5.2.6 int ppl_Coefficient_OK (ppl_const_Coefficient_t *c*) [related]

Returns a positive integer if `c` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `c` is broken. Useful for debugging purposes.

Definition at line 452 of file ppl_c_implementation_common.cc.

10.5.2.7 int ppl_Coefficient_to_mpz_t (ppl_const_Coefficient_t *c*, mpz_t *z*) [related]

Sets the value of the GMP integer `z` to the value of `c`.

Definition at line 420 of file ppl_c_implementation_common.cc.

10.5.2.8 int ppl_delete_Coefficient (ppl_const_Coefficient_t *c*) [related]

Invalidates the handle `c`: this makes sure the corresponding resources will eventually be released.

Definition at line 427 of file ppl_c_implementation_common.cc.

10.5.2.9 int ppl_new_Coefficient (ppl_Coefficient_t * *pc*) [related]

Creates a new coefficient with value 0 and writes a handle for the newly created coefficient at address `pc`.

Definition at line 397 of file ppl_c_implementation_common.cc.

10.5.2.10 int ppl_new_Coefficient_from_Coefficient (ppl_Coefficient_t * *pc*, ppl_const_Coefficient_t *c*) [related]

Builds a coefficient that is a copy of `c`; writes a handle for the newly created coefficient at address `pc`.

Definition at line 411 of file ppl_c_implementation_common.cc.

10.5.2.11 int ppl_new_Coefficient_from_mpz_t (ppl_Coefficient_t * *pc*, mpz_t *z*) [related]

Creates a new coefficient with the value given by the GMP integer `z` and writes a handle for the newly created coefficient at address `pc`.

Definition at line 404 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.6 ppl_Congruence_System_const_iterator_tag Interface Reference

Types and functions for iterating on congruence systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t *pcit)

  Builds a new 'const iterator' and writes a handle to it at address `pcit`.

- int ppl_new_Congruence_System_const_iterator_from_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t *pcit, ppl_const_Congruence_System_const_-iterator_t cit)

  Builds a const iterator that is a copy of `cit`; writes a handle for the newly created const iterator at address `pcit`.

- int ppl_assign_Congruence_System_const_iterator_from_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t dst, ppl_const_Congruence_System_const_iterator_t src)

Assigns a copy of the const iterator `src` *to* `dst`*.*

- int ppl_delete_Congruence_System_const_iterator (ppl_const_Congruence_System_const_-iterator_t cit)

  Invalidates the handle `cit`*: this makes sure the corresponding resources will eventually be released.*

Dereferencing, Incrementing and Equality Testing

- int ppl_Congruence_System_const_iterator_dereference (ppl_const_Congruence_System_-const_iterator_t cit, ppl_const_Congruence_t *pc)

  Dereference `cit` *writing a const handle to the resulting congruence at address* `pc`*.*

- int ppl_Congruence_System_const_iterator_increment (ppl_Congruence_System_const_-iterator_t cit)

  Increment `cit` *so that it "points" to the next congruence.*

- int ppl_Congruence_System_const_iterator_equal_test (ppl_const_Congruence_System_const_-iterator_t x, ppl_const_Congruence_System_const_iterator_t y)

  Returns a positive integer if the iterators corresponding to `x` *and* `y` *are equal; returns 0 if they are different.*

10.6.1 Detailed Description

Types and functions for iterating on congruence systems. The types and functions for congruence systems iterators provide read-only access to the elements of a congruence system by interfacing *Congruence_-System::const_iterator*.

10.6.2 Friends And Related Function Documentation

10.6.2.1 int ppl_assign_Congruence_System_const_iterator_from_Congruence_-System_const_iterator (ppl_Congruence_System_const_iterator_t *dst*, ppl_const_Congruence_System_const_iterator_t *src*) [related]

Assigns a copy of the const iterator `src` to `dst`.

Definition at line 1496 of file ppl_c_implementation_common.cc.

10.6.2.2 int ppl_Congruence_System_const_iterator_dereference (ppl_const_-Congruence_System_const_iterator_t *cit*, ppl_const_Congruence_t * *pc*) [related]

Dereference `cit` writing a const handle to the resulting congruence at address `pc`.

Definition at line 1527 of file ppl_c_implementation_common.cc.

10.6.2.3 int ppl_Congruence_System_const_iterator_equal_test (ppl_const_Congruence_System_const_iterator_t *x*, ppl_const_Congruence_System_const_iterator_t *y*) [related]

Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

Definition at line 1547 of file ppl_c_implementation_common.cc.

10.6.2.4 int ppl_Congruence_System_const_iterator_increment (ppl_Congruence_System_const_iterator_t *cit*) [related]

Increment `cit` so that it "points" to the next congruence.

Definition at line 1538 of file ppl_c_implementation_common.cc.

10.6.2.5 int ppl_delete_Congruence_System_const_iterator (ppl_const_Congruence_System_const_iterator_t *cit*) [related]

Invalidates the handle `cit`: this makes sure the corresponding resources will eventually be released.

Definition at line 1487 of file ppl_c_implementation_common.cc.

10.6.2.6 int ppl_new_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t * *pcit*) [related]

Builds a new 'const iterator' and writes a handle to it at address `pcit`.

Definition at line 1470 of file ppl_c_implementation_common.cc.

10.6.2.7 int ppl_new_Congruence_System_const_iterator_from_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t * *pcit*, ppl_const_Congruence_System_const_iterator_t *cit*) [related]

Builds a const iterator that is a copy of `cit`; writes a handle for the newly created const iterator at address `pcit`.

Definition at line 1478 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.7 ppl_Congruence_System_tag Interface Reference

Types and functions for congruence systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Congruence_System (ppl_Congruence_System_t *pcs)
  Builds an empty system of congruences and writes a handle to it at address `pcs`.
- int ppl_new_Congruence_System_zero_dim_empty (ppl_Congruence_System_t *pcs)
  Builds a zero-dimensional, unsatisfiable congruence system and writes a handle to it at address `pcs`.
- int ppl_new_Congruence_System_from_Congruence (ppl_Congruence_System_t *pcs, ppl_-const_Congruence_t c)
  Builds the singleton congruence system containing only a copy of congruence `c`*; writes a handle for the newly created system at address* `pcs`.
- int ppl_new_Congruence_System_from_Congruence_System (ppl_Congruence_System_t *pcs, ppl_const_Congruence_System_t cs)
  Builds a congruence system that is a copy of `cs`*; writes a handle for the newly created system at address* `pcs`.
- int ppl_assign_Congruence_System_from_Congruence_System (ppl_Congruence_System_t dst, ppl_const_Congruence_System_t src)
  Assigns a copy of the congruence system `src` *to* `dst`.
- int ppl_delete_Congruence_System (ppl_const_Congruence_System_t cs)
  Invalidates the handle `cs`*: this makes sure the corresponding resources will eventually be released.*

Functions that Do Not Modify the Congruence System

- int ppl_Congruence_System_space_dimension (ppl_const_Congruence_System_t cs, ppl_-dimension_type *m)
  Writes to `m` *the dimension of the vector space enclosing* `cs`.
- int ppl_Congruence_System_empty (ppl_const_Congruence_System_t cs)
  Returns a positive integer if `cs` *contains no (non-trivial) congruence; returns 0 otherwise.*
- int ppl_Congruence_System_begin (ppl_const_Congruence_System_t cs, ppl_Congruence_-System_const_iterator_t cit)
  Assigns to `cit` *a const iterator "pointing" to the beginning of the congruence system* `cs`.
- int ppl_Congruence_System_end (ppl_const_Congruence_System_t cs, ppl_Congruence_-System_const_iterator_t cit)
  Assigns to `cit` *a const iterator "pointing" past the end of the congruence system* `cs`.
- int ppl_Congruence_System_OK (ppl_const_Congruence_System_t cs)
  Returns a positive integer if `cs` *is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if* `cs` *is broken. Useful for debugging purposes.*

Functions that May Modify the Congruence System

- int ppl_Congruence_System_clear (ppl_Congruence_System_t cs)

Removes all the congruences from the congruence system `cs` *and sets its space dimension to 0.*

- int ppl_Congruence_System_insert_Congruence (ppl_Congruence_System_t cs, ppl_const_Congruence_t c)

  Inserts a copy of the congruence `c` *into* `cs`*; the space dimension is increased, if necessary.*

10.7.1 Detailed Description

Types and functions for congruence systems. The types and functions for congruence systems provide an interface towards *Congruence_System*.

10.7.2 Friends And Related Function Documentation

10.7.2.1 int ppl_assign_Congruence_System_from_Congruence_System (ppl_Congruence_System_t *dst*, ppl_const_Congruence_System_t *src*) `[related]`

Assigns a copy of the congruence system `src` to `dst`.

Definition at line 1419 of file ppl_c_implementation_common.cc.

10.7.2.2 int ppl_Congruence_System_begin (ppl_const_Congruence_System_t *cs*, ppl_Congruence_System_const_iterator_t *cit*) `[related]`

Assigns to `cit` a const iterator "pointing" to the beginning of the congruence system `cs`.

Definition at line 1506 of file ppl_c_implementation_common.cc.

10.7.2.3 int ppl_Congruence_System_clear (ppl_Congruence_System_t *cs*) `[related]`

Removes all the congruences from the congruence system `cs` and sets its space dimension to 0.

Definition at line 1444 of file ppl_c_implementation_common.cc.

10.7.2.4 int ppl_Congruence_System_empty (ppl_const_Congruence_System_t *cs*) `[related]`

Returns a positive integer if `cs` contains no (non-trivial) congruence; returns 0 otherwise.

Definition at line 1437 of file ppl_c_implementation_common.cc.

10.7.2.5 int ppl_Congruence_System_end (ppl_const_Congruence_System_t *cs*, ppl_Congruence_System_const_iterator_t *cit*) `[related]`

Assigns to `cit` a const iterator "pointing" past the end of the congruence system `cs`.

Definition at line 1516 of file ppl_c_implementation_common.cc.

10.7.2.6 int ppl_Congruence_System_insert_Congruence (ppl_Congruence_System_t *cs*, ppl_const_Congruence_t *c*) [related]

Inserts a copy of the congruence `c` into `cs`; the space dimension is increased, if necessary.

Definition at line 1451 of file ppl_c_implementation_common.cc.

10.7.2.7 int ppl_Congruence_System_OK (ppl_const_Congruence_System_t *cs*) [related]

Returns a positive integer if `cs` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `cs` is broken. Useful for debugging purposes.

Definition at line 1461 of file ppl_c_implementation_common.cc.

10.7.2.8 int ppl_Congruence_System_space_dimension (ppl_const_Congruence_System_t *cs*, ppl_dimension_type * *m*) [related]

Writes to `m` the dimension of the vector space enclosing `cs`.

Definition at line 1428 of file ppl_c_implementation_common.cc.

10.7.2.9 int ppl_delete_Congruence_System (ppl_const_Congruence_System_t *cs*) [related]

Invalidates the handle `cs`: this makes sure the corresponding resources will eventually be released.

Definition at line 1411 of file ppl_c_implementation_common.cc.

10.7.2.10 int ppl_new_Congruence_System (ppl_Congruence_System_t * *pcs*) [related]

Builds an empty system of congruences and writes a handle to it at address `pcs`.

Definition at line 1377 of file ppl_c_implementation_common.cc.

10.7.2.11 int ppl_new_Congruence_System_from_Congruence (ppl_Congruence_System_t * *pcs*, ppl_const_Congruence_t *c*) [related]

Builds the singleton congruence system containing only a copy of congruence `c`; writes a handle for the newly created system at address `pcs`.

Definition at line 1393 of file ppl_c_implementation_common.cc.

10.7.2.12 int ppl_new_Congruence_System_from_Congruence_System (ppl_Congruence_System_t * *pcs*, ppl_const_Congruence_System_t *cs*) [related]

Builds a congruence system that is a copy of `cs`; writes a handle for the newly created system at address `pcs`.

Definition at line 1403 of file ppl_c_implementation_common.cc.

10.7.2.13 int ppl_new_Congruence_System_zero_dim_empty (ppl_Congruence_System_t * *pcs*) [related]

Builds a zero-dimensional, unsatisfiable congruence system and writes a handle to it at address `pcs`.

Definition at line 1384 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.8 ppl_Congruence_tag Interface Reference

Types and functions for congruences.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Congruence (ppl_Congruence_t *pc, ppl_const_Linear_Expression_t le, ppl_const_Coefficient_t m)

  Creates the new congruence $le = 0 \pmod{m}$ *and writes a handle for it at address* `pc`*. The space dimension of the new congruence is equal to the space dimension of* `le`*.*

- int ppl_new_Congruence_zero_dim_false (ppl_Congruence_t *pc)

  Creates the unsatisfiable (zero-dimension space) congruence $0 = 1 \pmod{0}$ *and writes a handle for it at address* `pc`*.*

- int ppl_new_Congruence_zero_dim_integrality (ppl_Congruence_t *pc)

  Creates the true (zero-dimension space) congruence $0 = 1 \pmod{1}$*, also known as integrality congruence. A handle for the newly created congruence is written at address* `pc`*.*

- int ppl_new_Congruence_from_Congruence (ppl_Congruence_t *pc, ppl_const_Congruence_t c)

  Builds a congruence that is a copy of `c`*; writes a handle for the newly created congruence at address* `pc`*.*

- int ppl_assign_Congruence_from_Congruence (ppl_Congruence_t dst, ppl_const_Congruence_t src)

Assigns a copy of the congruence `src` *to* `dst`.

- int ppl_delete_Congruence (ppl_const_Congruence_t c)

  Invalidates the handle `c`*: this makes sure the corresponding resources will eventually be released.*

Functions that Do Not Modify the Congruence

- int ppl_Congruence_space_dimension (ppl_const_Congruence_t c, ppl_dimension_type *m)

  Writes to `m` *the space dimension of* `c`.

- int ppl_Congruence_coefficient (ppl_const_Congruence_t c, ppl_dimension_type var, ppl_-Coefficient_t n)

  Copies into `n` *the coefficient of variable* `var` *in congruence* `c`.

- int ppl_Congruence_inhomogeneous_term (ppl_const_Congruence_t c, ppl_Coefficient_t n)

  Copies into `n` *the inhomogeneous term of congruence* `c`.

- int ppl_Congruence_modulus (ppl_const_Congruence_t c, ppl_Coefficient_t m)

  Copies into `m` *the modulus of congruence* `c`.

- int ppl_Congruence_OK (ppl_const_Congruence_t c)

  Returns a positive integer if `c` *is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if* `c` *is broken. Useful for debugging purposes.*

10.8.1 Detailed Description

Types and functions for congruences. The types and functions for congruences provide an interface towards *Congruence*.

10.8.2 Friends And Related Function Documentation

10.8.2.1 int ppl_assign_Congruence_from_Congruence (ppl_Congruence_t *dst*, ppl_const_Congruence_t *src*) `[related]`

Assigns a copy of the congruence `src` to `dst`.

Definition at line 1311 of file ppl_c_implementation_common.cc.

10.8.2.2 int ppl_Congruence_coefficient (ppl_const_Congruence_t *c*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) `[related]`

Copies into `n` the coefficient of variable `var` in congruence `c`.

Definition at line 1329 of file ppl_c_implementation_common.cc.

10.8.2.3 int ppl_Congruence_inhomogeneous_term (ppl_const_Congruence_t *c*, ppl_Coefficient_t *n*) [related]

Copies into `n` the inhomogeneous term of congruence `c`.

Definition at line 1340 of file ppl_c_implementation_common.cc.

10.8.2.4 int ppl_Congruence_modulus (ppl_const_Congruence_t *c*, ppl_Coefficient_t *m*) [related]

Copies into `m` the modulus of congruence `c`.

Definition at line 1350 of file ppl_c_implementation_common.cc.

10.8.2.5 int ppl_Congruence_OK (ppl_const_Congruence_t *c*) [related]

Returns a positive integer if `c` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `c` is broken. Useful for debugging purposes.

Definition at line 1360 of file ppl_c_implementation_common.cc.

10.8.2.6 int ppl_Congruence_space_dimension (ppl_const_Congruence_t *c*, ppl_dimension_type * *m*) [related]

Writes to `m` the space dimension of `c`.

Definition at line 1321 of file ppl_c_implementation_common.cc.

10.8.2.7 int ppl_delete_Congruence (ppl_const_Congruence_t *c*) [related]

Invalidates the handle `c`: this makes sure the corresponding resources will eventually be released.

Definition at line 1304 of file ppl_c_implementation_common.cc.

10.8.2.8 int ppl_new_Congruence (ppl_Congruence_t * *pc*, ppl_const_Linear_Expression_t *le*, ppl_const_Coefficient_t *m*) [related]

Creates the new congruence $le = 0 \pmod{m}$ and writes a handle for it at address `pc`. The space dimension of the new congruence is equal to the space dimension of `le`.

Definition at line 1268 of file ppl_c_implementation_common.cc.

10.8.2.9 int ppl_new_Congruence_from_Congruence (ppl_Congruence_t * *pc*, ppl_const_Congruence_t *c*) [related]

Builds a congruence that is a copy of `c`; writes a handle for the newly created congruence at address `pc`.

Definition at line 1295 of file ppl_c_implementation_common.cc.

10.8.2.10 int ppl_new_Congruence_zero_dim_false (ppl_Congruence_t * *pc*) [related]

Creates the unsatisfiable (zero-dimension space) congruence $0 = 1 \pmod 0$ and writes a handle for it at address `pc`.

Definition at line 1281 of file ppl_c_implementation_common.cc.

10.8.2.11 int ppl_new_Congruence_zero_dim_integrality (ppl_Congruence_t * *pc*) [related]

Creates the true (zero-dimension space) congruence $0 = 1 \pmod 1$, also known as *integrality congruence*. A handle for the newly created congruence is written at address `pc`.

Definition at line 1288 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.9 ppl_Constraint_System_const_iterator_tag Interface Reference

Types and functions for iterating on constraint systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t *pcit)
  Builds a new 'const iterator' and writes a handle to it at address `pcit`.
- int ppl_new_Constraint_System_const_iterator_from_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t *pcit, ppl_const_Constraint_System_const_iterator_t cit)
  Builds a const iterator that is a copy of `cit`; writes a handle for the newly created const iterator at address `pcit`.
- int ppl_assign_Constraint_System_const_iterator_from_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t dst, ppl_const_Constraint_System_const_iterator_t src)
  Assigns a copy of the const iterator `src` to `dst`.

- int ppl_delete_Constraint_System_const_iterator (ppl_const_Constraint_System_const_-iterator_t cit)

  Invalidates the handle `cit`: this makes sure the corresponding resources will eventually be released.

Dereferencing, Incrementing and Equality Testing

- int ppl_Constraint_System_const_iterator_dereference (ppl_const_Constraint_System_const_-iterator_t cit, ppl_const_Constraint_t *pc)

  Dereference `cit` writing a const handle to the resulting constraint at address `pc`.

- int ppl_Constraint_System_const_iterator_increment (ppl_Constraint_System_const_iterator_-t cit)

  Increment `cit` so that it "points" to the next constraint.

- int ppl_Constraint_System_const_iterator_equal_test (ppl_const_Constraint_System_const_-iterator_t x, ppl_const_Constraint_System_const_iterator_t y)

  Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

10.9.1 Detailed Description

Types and functions for iterating on constraint systems. The types and functions for constraint systems iterators provide read-only access to the elements of a constraint system by interfacing *Constraint_-System::const_iterator*.

10.9.2 Friends And Related Function Documentation

10.9.2.1 int ppl_assign_Constraint_System_const_iterator_from_Constraint_-System_const_iterator (ppl_Constraint_System_const_iterator_t *dst*, ppl_const_Constraint_System_const_iterator_t *src*) `[related]`

Assigns a copy of the const iterator `src` to `dst`.

Definition at line 895 of file ppl_c_implementation_common.cc.

10.9.2.2 int ppl_Constraint_System_const_iterator_dereference (ppl_const_-Constraint_System_const_iterator_t *cit*, ppl_const_Constraint_t * *pc*) `[related]`

Dereference `cit` writing a const handle to the resulting constraint at address `pc`.

Definition at line 926 of file ppl_c_implementation_common.cc.

10.9.2.3 int ppl_Constraint_System_const_iterator_equal_test (ppl_const_Constraint_-System_const_iterator_t *x*, ppl_const_Constraint_System_const_iterator_t *y*) `[related]`

Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

Definition at line 946 of file ppl_c_implementation_common.cc.

10.9.2.4 int ppl_Constraint_System_const_iterator_increment (ppl_Constraint_System_const_iterator_t *cit*) [related]

Increment `cit` so that it "points" to the next constraint.

Definition at line 937 of file ppl_c_implementation_common.cc.

10.9.2.5 int ppl_delete_Constraint_System_const_iterator (ppl_const_Constraint_System_const_iterator_t *cit*) [related]

Invalidates the handle `cit`: this makes sure the corresponding resources will eventually be released.

Definition at line 886 of file ppl_c_implementation_common.cc.

10.9.2.6 int ppl_new_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t * *pcit*) [related]

Builds a new 'const iterator' and writes a handle to it at address `pcit`.

Definition at line 869 of file ppl_c_implementation_common.cc.

10.9.2.7 int ppl_new_Constraint_System_const_iterator_from_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t * *pcit*, ppl_const_Constraint_System_const_iterator_t *cit*) [related]

Builds a const iterator that is a copy of `cit`; writes a handle for the newly created const iterator at address `pcit`.

Definition at line 877 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.10 ppl_Constraint_System_tag Interface Reference

Types and functions for constraint systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Constraint_System (ppl_Constraint_System_t *pcs)
  Builds an empty system of constraints and writes a handle to it at address `pcs`.
- int ppl_new_Constraint_System_zero_dim_empty (ppl_Constraint_System_t *pcs)
  Builds a zero-dimensional, unsatisfiable constraint system and writes a handle to it at address `pcs`.
- int ppl_new_Constraint_System_from_Constraint (ppl_Constraint_System_t *pcs, ppl_const_Constraint_t c)
  Builds the singleton constraint system containing only a copy of constraint `c`*; writes a handle for the newly created system at address* `pcs`.
- int ppl_new_Constraint_System_from_Constraint_System (ppl_Constraint_System_t *pcs, ppl_const_Constraint_System_t cs)
  Builds a constraint system that is a copy of `cs`*; writes a handle for the newly created system at address* `pcs`.
- int ppl_assign_Constraint_System_from_Constraint_System (ppl_Constraint_System_t dst, ppl_const_Constraint_System_t src)
  Assigns a copy of the constraint system `src` *to* `dst`.
- int ppl_delete_Constraint_System (ppl_const_Constraint_System_t cs)
  Invalidates the handle `cs`*: this makes sure the corresponding resources will eventually be released.*

Functions that Do Not Modify the Constraint System

- int ppl_Constraint_System_space_dimension (ppl_const_Constraint_System_t cs, ppl_dimension_type *m)
  Writes to `m` *the dimension of the vector space enclosing* `cs`.
- int ppl_Constraint_System_empty (ppl_const_Constraint_System_t cs)
  Returns a positive integer if `cs` *contains no (non-trivial) constraint; returns 0 otherwise.*
- int ppl_Constraint_System_has_strict_inequalities (ppl_const_Constraint_System_t cs)
  Returns a positive integer if `cs` *contains any (non-trivial) strict inequality; returns 0 otherwise.*
- int ppl_Constraint_System_begin (ppl_const_Constraint_System_t cs, ppl_Constraint_System_const_iterator_t cit)
  Assigns to `cit` *a const iterator "pointing" to the beginning of the constraint system* `cs`.
- int ppl_Constraint_System_end (ppl_const_Constraint_System_t cs, ppl_Constraint_System_const_iterator_t cit)
  Assigns to `cit` *a const iterator "pointing" past the end of the constraint system* `cs`.
- int ppl_Constraint_System_OK (ppl_const_Constraint_System_t cs)
  Returns a positive integer if `cs` *is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if* `cs` *is broken. Useful for debugging purposes.*

Functions that May Modify the Constraint System

- int ppl_Constraint_System_clear (ppl_Constraint_System_t cs)
  Removes all the constraints from the constraint system `cs` *and sets its space dimension to 0.*

- int ppl_Constraint_System_insert_Constraint (ppl_Constraint_System_t cs, ppl_const_Constraint_t c)

  Inserts a copy of the constraint `c` *into* `cs`*; the space dimension is increased, if necessary.*

10.10.1 Detailed Description

Types and functions for constraint systems. The types and functions for constraint systems provide an interface towards *Constraint_System*.

10.10.2 Friends And Related Function Documentation

10.10.2.1 int ppl_assign_Constraint_System_from_Constraint_System (ppl_Constraint_System_t *dst*, ppl_const_Constraint_System_t *src*) `[related]`

Assigns a copy of the constraint system `src` to `dst`.

Definition at line 810 of file ppl_c_implementation_common.cc.

10.10.2.2 int ppl_Constraint_System_begin (ppl_const_Constraint_System_t *cs*, ppl_Constraint_System_const_iterator_t *cit*) `[related]`

Assigns to `cit` a const iterator "pointing" to the beginning of the constraint system `cs`.

Definition at line 905 of file ppl_c_implementation_common.cc.

10.10.2.3 int ppl_Constraint_System_clear (ppl_Constraint_System_t *cs*) `[related]`

Removes all the constraints from the constraint system `cs` and sets its space dimension to 0.

Definition at line 843 of file ppl_c_implementation_common.cc.

10.10.2.4 int ppl_Constraint_System_empty (ppl_const_Constraint_System_t *cs*) `[related]`

Returns a positive integer if `cs` contains no (non-trivial) constraint; returns 0 otherwise.

Definition at line 828 of file ppl_c_implementation_common.cc.

10.10.2.5 int ppl_Constraint_System_end (ppl_const_Constraint_System_t *cs*, ppl_Constraint_System_const_iterator_t *cit*) `[related]`

Assigns to `cit` a const iterator "pointing" past the end of the constraint system `cs`.

Definition at line 915 of file ppl_c_implementation_common.cc.

10.10.2.6 int ppl_Constraint_System_has_strict_inequalities (ppl_const_Constraint_System_t *cs*) [related]

Returns a positive integer if `cs` contains any (non-trivial) strict inequality; returns 0 otherwise.

Definition at line 836 of file ppl_c_implementation_common.cc.

10.10.2.7 int ppl_Constraint_System_insert_Constraint (ppl_Constraint_System_t *cs*, ppl_const_Constraint_t *c*) [related]

Inserts a copy of the constraint `c` into `cs`; the space dimension is increased, if necessary.

Definition at line 850 of file ppl_c_implementation_common.cc.

10.10.2.8 int ppl_Constraint_System_OK (ppl_const_Constraint_System_t *cs*) [related]

Returns a positive integer if `cs` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `cs` is broken. Useful for debugging purposes.

Definition at line 860 of file ppl_c_implementation_common.cc.

10.10.2.9 int ppl_Constraint_System_space_dimension (ppl_const_Constraint_System_t *cs*, ppl_dimension_type * *m*) [related]

Writes to `m` the dimension of the vector space enclosing `cs`.

Definition at line 819 of file ppl_c_implementation_common.cc.

10.10.2.10 int ppl_delete_Constraint_System (ppl_const_Constraint_System_t *cs*) [related]

Invalidates the handle `cs`: this makes sure the corresponding resources will eventually be released.

Definition at line 802 of file ppl_c_implementation_common.cc.

10.10.2.11 int ppl_new_Constraint_System (ppl_Constraint_System_t * *pcs*) [related]

Builds an empty system of constraints and writes a handle to it at address `pcs`.

Definition at line 768 of file ppl_c_implementation_common.cc.

10.10.2.12 int ppl_new_Constraint_System_from_Constraint (ppl_Constraint_System_t * *pcs*, ppl_const_Constraint_t *c*) [related]

Builds the singleton constraint system containing only a copy of constraint `c`; writes a handle for the newly created system at address `pcs`.

Definition at line 784 of file ppl_c_implementation_common.cc.

10.10.2.13 int ppl_new_Constraint_System_from_Constraint_System (ppl_Constraint_System_t * *pcs*, ppl_const_Constraint_System_t *cs*) [related]

Builds a constraint system that is a copy of `cs`; writes a handle for the newly created system at address `pcs`.

Definition at line 794 of file ppl_c_implementation_common.cc.

10.10.2.14 int ppl_new_Constraint_System_zero_dim_empty (ppl_Constraint_System_t * *pcs*) [related]

Builds a zero-dimensional, unsatisfiable constraint system and writes a handle to it at address `pcs`.

Definition at line 775 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.11 ppl_Constraint_tag Interface Reference

Types and functions for constraints.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Constraint (ppl_Constraint_t *pc, ppl_const_Linear_Expression_t le, enum ppl_enum_Constraint_Type rel)
  Creates the new constraint '`le rel 0`' and writes a handle for it at address `pc`. The space dimension of the new constraint is equal to the space dimension of `le`.

- int ppl_new_Constraint_zero_dim_false (ppl_Constraint_t *pc)
  Creates the unsatisfiable (zero-dimension space) constraint $0 = 1$ *and writes a handle for it at address `pc`.*

- int ppl_new_Constraint_zero_dim_positivity (ppl_Constraint_t *pc)
  Creates the true (zero-dimension space) constraint $0 \leq 1$*, also known as positivity constraint. A handle for the newly created constraint is written at address `pc`.*

- int ppl_new_Constraint_from_Constraint (ppl_Constraint_t *pc, ppl_const_Constraint_t c)
  Builds a constraint that is a copy of `c`; writes a handle for the newly created constraint at address `pc`.

- int ppl_assign_Constraint_from_Constraint (ppl_Constraint_t dst, ppl_const_Constraint_t src)
  Assigns a copy of the constraint `src` *to* `dst`.
- int ppl_delete_Constraint (ppl_const_Constraint_t c)
  Invalidates the handle `c`*: this makes sure the corresponding resources will eventually be released.*

Functions that Do Not Modify the Constraint

- int ppl_Constraint_space_dimension (ppl_const_Constraint_t c, ppl_dimension_type *m)
  Writes to `m` *the space dimension of* `c`.
- int ppl_Constraint_type (ppl_const_Constraint_t c)
  Returns the type of constraint `c`.
- int ppl_Constraint_coefficient (ppl_const_Constraint_t c, ppl_dimension_type var, ppl_-Coefficient_t n)
  Copies into `n` *the coefficient of variable* `var` *in constraint* `c`.
- int ppl_Constraint_inhomogeneous_term (ppl_const_Constraint_t c, ppl_Coefficient_t n)
  Copies into `n` *the inhomogeneous term of constraint* `c`.
- int ppl_Constraint_OK (ppl_const_Constraint_t c)
  Returns a positive integer if `c` *is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if* `c` *is broken. Useful for debugging purposes.*

10.11.1 Detailed Description

Types and functions for constraints. The types and functions for constraints provide an interface towards *Constraint*.

10.11.2 Friends And Related Function Documentation

10.11.2.1 int ppl_assign_Constraint_from_Constraint (ppl_Constraint_t *dst*, ppl_const_Constraint_t *src*) `[related]`

Assigns a copy of the constraint `src` to `dst`.

Definition at line 697 of file ppl_c_implementation_common.cc.

10.11.2.2 int ppl_Constraint_coefficient (ppl_const_Constraint_t *c*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) `[related]`

Copies into `n` the coefficient of variable `var` in constraint `c`.

Definition at line 730 of file ppl_c_implementation_common.cc.

10.11.2.3 int ppl_Constraint_inhomogeneous_term (ppl_const_Constraint_t *c*, ppl_Coefficient_t *n*) [related]

Copies into `n` the inhomogeneous term of constraint `c`.

Definition at line 741 of file ppl_c_implementation_common.cc.

10.11.2.4 int ppl_Constraint_OK (ppl_const_Constraint_t *c*) [related]

Returns a positive integer if `c` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `c` is broken. Useful for debugging purposes.

Definition at line 751 of file ppl_c_implementation_common.cc.

10.11.2.5 int ppl_Constraint_space_dimension (ppl_const_Constraint_t *c*, ppl_dimension_type * *m*) [related]

Writes to `m` the space dimension of `c`.

Definition at line 707 of file ppl_c_implementation_common.cc.

10.11.2.6 int ppl_Constraint_type (ppl_const_Constraint_t *c*) [related]

Returns the type of constraint `c`.

Definition at line 715 of file ppl_c_implementation_common.cc.

10.11.2.7 int ppl_delete_Constraint (ppl_const_Constraint_t *c*) [related]

Invalidates the handle `c`: this makes sure the corresponding resources will eventually be released.

Definition at line 690 of file ppl_c_implementation_common.cc.

10.11.2.8 int ppl_new_Constraint (ppl_Constraint_t * *pc*, ppl_const_Linear_Expression_t *le*, enum ppl_enum_Constraint_Type *rel*) [related]

Creates the new constraint '`le rel` 0' and writes a handle for it at address `pc`. The space dimension of the new constraint is equal to the space dimension of `le`.

Definition at line 636 of file ppl_c_implementation_common.cc.

10.11.2.9 int ppl_new_Constraint_from_Constraint (ppl_Constraint_t * *pc*, ppl_const_Constraint_t *c*) [related]

Builds a constraint that is a copy of `c`; writes a handle for the newly created constraint at address `pc`.

Definition at line 681 of file ppl_c_implementation_common.cc.

10.11.2.10 int ppl_new_Constraint_zero_dim_false (ppl_Constraint_t * *pc*) [related]

Creates the unsatisfiable (zero-dimension space) constraint $0 = 1$ and writes a handle for it at address `pc`.

Definition at line 667 of file ppl_c_implementation_common.cc.

10.11.2.11 int ppl_new_Constraint_zero_dim_positivity (ppl_Constraint_t * *pc*) [related]

Creates the true (zero-dimension space) constraint $0 \leq 1$, also known as *positivity constraint*. A handle for the newly created constraint is written at address `pc`.

Definition at line 674 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.12 ppl_Generator_System_const_iterator_tag Interface Reference

Types and functions for iterating on generator systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t *pgit)

  Builds a new 'const iterator' and writes a handle to it at address `pgit`.

- int ppl_new_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t *pgit, ppl_const_Generator_System_const_iterator_t git)

  Builds a const iterator that is a copy of `git`; writes a handle for the newly created const iterator at address `pgit`.

- int ppl_assign_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t dst, ppl_const_Generator_System_const_iterator_t src)

  Assigns a copy of the const iterator `src` to `dst`.

- int ppl_delete_Generator_System_const_iterator (ppl_const_Generator_System_const_iterator_t git)

  Invalidates the handle `git`: this makes sure the corresponding resources will eventually be released.

Dereferencing, Incrementing and Equality Testing

- int ppl_Generator_System_const_iterator_dereference (ppl_const_Generator_System_const_iterator_t git, ppl_const_Generator_t *pg)

  Dereference `git` writing a const handle to the resulting generator at address `pg`.

- int ppl_Generator_System_const_iterator_increment (ppl_Generator_System_const_iterator_t git)

  Increment `git` so that it "points" to the next generator.

- int ppl_Generator_System_const_iterator_equal_test (ppl_const_Generator_System_const_iterator_t x, ppl_const_Generator_System_const_iterator_t y)

  Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

10.12.1 Detailed Description

Types and functions for iterating on generator systems. The types and functions for generator systems iterators provide read-only access to the elements of a generator system by interfacing *Generator_System::const_iterator*.

10.12.2 Friends And Related Function Documentation

10.12.2.1 int ppl_assign_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t *dst*, ppl_const_Generator_System_const_iterator_t *src*) [related]

Assigns a copy of the const iterator `src` to `dst`.

Definition at line 1206 of file ppl_c_implementation_common.cc.

10.12.2.2 int ppl_delete_Generator_System_const_iterator (ppl_const_Generator_System_const_iterator_t *git*) [related]

Invalidates the handle `git`: this makes sure the corresponding resources will eventually be released.

Definition at line 1198 of file ppl_c_implementation_common.cc.

10.12.2.3 int ppl_Generator_System_const_iterator_dereference (ppl_const_Generator_System_const_iterator_t *git*, ppl_const_Generator_t * *pg*) [related]

Dereference `git` writing a const handle to the resulting generator at address `pg`.

Definition at line 1237 of file ppl_c_implementation_common.cc.

10.12.2.4 int ppl_Generator_System_const_iterator_equal_test (ppl_const_Generator_System_const_iterator_t *x*, ppl_const_Generator_System_const_iterator_t *y*) [related]

Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

Definition at line 1257 of file ppl_c_implementation_common.cc.

10.12.2.5 int ppl_Generator_System_const_iterator_increment (ppl_Generator_System_const_iterator_t *git*) [related]

Increment `git` so that it "points" to the next generator.

Definition at line 1248 of file ppl_c_implementation_common.cc.

10.12.2.6 int ppl_new_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t * *pgit*) [related]

Builds a new 'const iterator' and writes a handle to it at address `pgit`.

Definition at line 1181 of file ppl_c_implementation_common.cc.

10.12.2.7 int ppl_new_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t * *pgit*, ppl_const_Generator_System_const_iterator_t *git*) [related]

Builds a const iterator that is a copy of `git`; writes a handle for the newly created const iterator at address `pgit`.

Definition at line 1189 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.13 ppl_Generator_System_tag Interface Reference

Types and functions for generator systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Generator_System (ppl_Generator_System_t *pgs)
  Builds an empty system of generators and writes a handle to it at address `pgs`.
- int ppl_new_Generator_System_from_Generator (ppl_Generator_System_t *pgs, ppl_const_Generator_t g)
  Builds the singleton generator system containing only a copy of generator `g`*; writes a handle for the newly created system at address* `pgs`.
- int ppl_new_Generator_System_from_Generator_System (ppl_Generator_System_t *pgs, ppl_const_Generator_System_t gs)
  Builds a generator system that is a copy of `gs`*; writes a handle for the newly created system at address* `pgs`.
- int ppl_assign_Generator_System_from_Generator_System (ppl_Generator_System_t dst, ppl_const_Generator_System_t src)
  Assigns a copy of the generator system `src` *to* `dst`.
- int ppl_delete_Generator_System (ppl_const_Generator_System_t gs)
  Invalidates the handle `gs`*: this makes sure the corresponding resources will eventually be released.*

Functions that Do Not Modify the Generator System

- int ppl_Generator_System_space_dimension (ppl_const_Generator_System_t gs, ppl_dimension_type *m)
  Writes to `m` *the dimension of the vector space enclosing* `gs`.
- int ppl_Generator_System_empty (ppl_const_Generator_System_t gs)
  Returns a positive integer if `gs` *contains no generators; returns 0 otherwise.*
- int ppl_Generator_System_begin (ppl_const_Generator_System_t gs, ppl_Generator_System_const_iterator_t git)
  Assigns to `git` *a const iterator "pointing" to the beginning of the generator system* `gs`.
- int ppl_Generator_System_end (ppl_const_Generator_System_t gs, ppl_Generator_System_const_iterator_t git)
  Assigns to `git` *a const iterator "pointing" past the end of the generator system* `gs`.
- int ppl_Generator_System_OK (ppl_const_Generator_System_t gs)
  Returns a positive integer if `gs` *is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if* `gs` *is broken. Useful for debugging purposes.*

Functions that May Modify the Generator System

- int ppl_Generator_System_clear (ppl_Generator_System_t gs)
  Removes all the generators from the generator system `gs` *and sets its space dimension to 0.*
- int ppl_Generator_System_insert_Generator (ppl_Generator_System_t gs, ppl_const_Generator_t g)
  Inserts a copy of the generator `g` *into* `gs`*; the space dimension is increased, if necessary.*

10.13.1 Detailed Description

Types and functions for generator systems. The types and functions for generator systems provide an interface towards *Generator_System*.

10.13.2 Friends And Related Function Documentation

10.13.2.1 int ppl_assign_Generator_System_from_Generator_System (ppl_Generator_System_t *dst*, ppl_const_Generator_System_t *src*) [related]

Assigns a copy of the generator system `src` to `dst`.

Definition at line 1130 of file ppl_c_implementation_common.cc.

10.13.2.2 int ppl_delete_Generator_System (ppl_const_Generator_System_t *gs*) [related]

Invalidates the handle `gs`: this makes sure the corresponding resources will eventually be released.

Definition at line 1122 of file ppl_c_implementation_common.cc.

10.13.2.3 int ppl_Generator_System_begin (ppl_const_Generator_System_t *gs*, ppl_Generator_System_const_iterator_t *git*) [related]

Assigns to `git` a const iterator "pointing" to the beginning of the generator system `gs`.

Definition at line 1216 of file ppl_c_implementation_common.cc.

10.13.2.4 int ppl_Generator_System_clear (ppl_Generator_System_t *gs*) [related]

Removes all the generators from the generator system `gs` and sets its space dimension to 0.

Definition at line 1155 of file ppl_c_implementation_common.cc.

10.13.2.5 int ppl_Generator_System_empty (ppl_const_Generator_System_t *gs*) [related]

Returns a positive integer if `gs` contains no generators; returns 0 otherwise.

Definition at line 1148 of file ppl_c_implementation_common.cc.

10.13.2.6 int ppl_Generator_System_end (ppl_const_Generator_System_t *gs*, ppl_Generator_System_const_iterator_t *git*) [related]

Assigns to `git` a const iterator "pointing" past the end of the generator system `gs`.

Definition at line 1226 of file ppl_c_implementation_common.cc.

10.13.2.7 int ppl_Generator_System_insert_Generator (ppl_Generator_System_t *gs*, ppl_const_Generator_t *g*) [related]

Inserts a copy of the generator `g` into `gs`; the space dimension is increased, if necessary.

Definition at line 1162 of file ppl_c_implementation_common.cc.

10.13.2.8 int ppl_Generator_System_OK (ppl_const_Generator_System_t *gs*) [related]

Returns a positive integer if `gs` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `gs` is broken. Useful for debugging purposes.

Definition at line 1172 of file ppl_c_implementation_common.cc.

10.13.2.9 int ppl_Generator_System_space_dimension (ppl_const_Generator_System_t *gs*, ppl_dimension_type * *m*) [related]

Writes to `m` the dimension of the vector space enclosing `gs`.

Definition at line 1139 of file ppl_c_implementation_common.cc.

10.13.2.10 int ppl_new_Generator_System (ppl_Generator_System_t * *pgs*) [related]

Builds an empty system of generators and writes a handle to it at address `pgs`.

Definition at line 1090 of file ppl_c_implementation_common.cc.

10.13.2.11 int ppl_new_Generator_System_from_Generator (ppl_Generator_System_t * *pgs*, ppl_const_Generator_t *g*) [related]

Builds the singleton generator system containing only a copy of generator `g`; writes a handle for the newly created system at address `pgs`.

Definition at line 1104 of file ppl_c_implementation_common.cc.

10.13.2.12 int ppl_new_Generator_System_from_Generator_System (ppl_Generator_System_t * *pgs*, ppl_const_Generator_System_t *gs*) [related]

Builds a generator system that is a copy of `gs`; writes a handle for the newly created system at address `pgs`.

Definition at line 1114 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.14 ppl_Generator_tag Interface Reference

Types and functions for generators.

`#include <ppl_c_header.h>`

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Generator (ppl_Generator_t *pg, ppl_const_Linear_Expression_t le, enum ppl_enum_Generator_Type t, ppl_const_Coefficient_t d)
  Creates a new generator of direction `le` and type `t`. If the generator to be created is a point or a closure point, the divisor `d` is applied to `le`. For other types of generators `d` is simply disregarded. A handle for the new generator is written at address `pg`. The space dimension of the new generator is equal to the space dimension of `le`.

- int ppl_new_Generator_zero_dim_point (ppl_Generator_t *pg)
  Creates the point that is the origin of the zero-dimensional space $\mathbb{R}^0$. Writes a handle for the new generator at address `pg`.

- int ppl_new_Generator_zero_dim_closure_point (ppl_Generator_t *pg)
  Creates, as a closure point, the point that is the origin of the zero-dimensional space $\mathbb{R}^0$. Writes a handle for the new generator at address `pg`.

- int ppl_new_Generator_from_Generator (ppl_Generator_t *pg, ppl_const_Generator_t g)
  Builds a generator that is a copy of `g`; writes a handle for the newly created generator at address `pg`.

- int ppl_assign_Generator_from_Generator (ppl_Generator_t dst, ppl_const_Generator_t src)
  Assigns a copy of the generator `src` to `dst`.

- int ppl_delete_Generator (ppl_const_Generator_t g)
  Invalidates the handle `g`: this makes sure the corresponding resources will eventually be released.

Functions that Do Not Modify the Generator

- int ppl_Generator_space_dimension (ppl_const_Generator_t g, ppl_dimension_type *m)
  Writes to `m` the space dimension of `g`.

- int ppl_Generator_type (ppl_const_Generator_t g)
  Returns the type of generator `g`.

- int ppl_Generator_coefficient (ppl_const_Generator_t g, ppl_dimension_type var, ppl_Coefficient_t n)
  Copies into `n` the coefficient of variable `var` in generator `g`.

- int ppl_Generator_divisor (ppl_const_Generator_t g, ppl_Coefficient_t n)

If g is a point or a closure point assigns its divisor to n.

- int ppl_Generator_OK (ppl_const_Generator_t g)

  Returns a positive integer if g is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if g is broken. Useful for debugging purposes.

10.14.1 Detailed Description

Types and functions for generators. The types and functions for generators provide an interface towards *Generator*.

10.14.2 Friends And Related Function Documentation

10.14.2.1 int ppl_assign_Generator_from_Generator (ppl_Generator_t *dst*, ppl_const_Generator_t *src*) [related]

Assigns a copy of the generator src to dst.

Definition at line 1017 of file ppl_c_implementation_common.cc.

10.14.2.2 int ppl_delete_Generator (ppl_const_Generator_t *g*) [related]

Invalidates the handle g: this makes sure the corresponding resources will eventually be released.

Definition at line 1010 of file ppl_c_implementation_common.cc.

10.14.2.3 int ppl_Generator_coefficient (ppl_const_Generator_t *g*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Copies into n the coefficient of variable var in generator g.

Definition at line 1052 of file ppl_c_implementation_common.cc.

10.14.2.4 int ppl_Generator_divisor (ppl_const_Generator_t *g*, ppl_Coefficient_t *n*) [related]

If g is a point or a closure point assigns its divisor to n.

Definition at line 1063 of file ppl_c_implementation_common.cc.

10.14.2.5 int ppl_Generator_OK (ppl_const_Generator_t *g*) [related]

Returns a positive integer if `g` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `g` is broken. Useful for debugging purposes.

Definition at line 1073 of file ppl_c_implementation_common.cc.

10.14.2.6 int ppl_Generator_space_dimension (ppl_const_Generator_t *g*, ppl_dimension_type * *m*) [related]

Writes to `m` the space dimension of `g`.

Definition at line 1027 of file ppl_c_implementation_common.cc.

10.14.2.7 int ppl_Generator_type (ppl_const_Generator_t *g*) [related]

Returns the type of generator `g`.

Definition at line 1035 of file ppl_c_implementation_common.cc.

10.14.2.8 int ppl_new_Generator (ppl_Generator_t * *pg*, ppl_const_Linear_Expression_t *le*, enum ppl_enum_Generator_Type *t*, ppl_const_Coefficient_t *d*) [related]

Creates a new generator of direction `le` and type `t`. If the generator to be created is a point or a closure point, the divisor `d` is applied to `le`. For other types of generators `d` is simply disregarded. A handle for the new generator is written at address `pg`. The space dimension of the new generator is equal to the space dimension of `le`.

Definition at line 957 of file ppl_c_implementation_common.cc.

10.14.2.9 int ppl_new_Generator_from_Generator (ppl_Generator_t * *pg*, ppl_const_Generator_t *g*) [related]

Builds a generator that is a copy of `g`; writes a handle for the newly created generator at address `pg`.

Definition at line 1001 of file ppl_c_implementation_common.cc.

10.14.2.10 int ppl_new_Generator_zero_dim_closure_point (ppl_Generator_t * *pg*) [related]

Creates, as a closure point, the point that is the origin of the zero-dimensional space $\mathbb{R}^0$. Writes a handle for the new generator at address `pg`.

Definition at line 994 of file ppl_c_implementation_common.cc.

10.14.2.11 int ppl_new_Generator_zero_dim_point (ppl_Generator_t * *pg*) [related]

Creates the point that is the origin of the zero-dimensional space $\mathbb{R}^0$. Writes a handle for the new generator at address `pg`.

Definition at line 987 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.15 ppl_Grid_Generator_System_const_iterator_tag Interface Reference

Types and functions for iterating on grid generator systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_const_iterator_t *pgit)
  Builds a new 'const iterator' and writes a handle to it at address `pgit`.

- int ppl_new_Grid_Generator_System_const_iterator_from_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_const_iterator_t *pgit, ppl_const_Grid_Generator_System_const_iterator_t git)
  Builds a const iterator that is a copy of `git`; writes a handle for the newly created const iterator at address `pgit`.

- int ppl_assign_Grid_Generator_System_const_iterator_from_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_const_iterator_t dst, ppl_const_Grid_Generator_System_const_iterator_t src)
  Assigns a copy of the const iterator `src` to `dst`.

- int ppl_delete_Grid_Generator_System_const_iterator (ppl_const_Grid_Generator_System_const_iterator_t git)
  Invalidates the handle `git`: this makes sure the corresponding resources will eventually be released.

Dereferencing, Incrementing and Equality Testing

- int ppl_Grid_Generator_System_const_iterator_dereference (ppl_const_Grid_Generator_System_const_iterator_t git, ppl_const_Grid_Generator_t *pg)
  Dereference `git` writing a const handle to the resulting grid generator at address `pg`.

- int ppl_Grid_Generator_System_const_iterator_increment (ppl_Grid_Generator_System_const_iterator_t git)
  Increment `git` so that it "points" to the next grid generator.

- int ppl_Grid_Generator_System_const_iterator_equal_test (ppl_const_Grid_Generator_System_const_iterator_t x, ppl_const_Grid_Generator_System_const_iterator_t y)
  Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

10.15.1 Detailed Description

Types and functions for iterating on grid generator systems. The types and functions for grid generator systems iterators provide read-only access to the elements of a grid generator system by interfacing *Grid_-Generator_System::const_iterator*.

10.15.2 Friends And Related Function Documentation

10.15.2.1 int ppl_assign_Grid_Generator_System_const_iterator_from_Grid_Generator_-System_const_iterator (ppl_Grid_Generator_System_const_iterator_t *dst*, ppl_const_Grid_Generator_System_const_iterator_t *src*) `[related]`

Assigns a copy of the const iterator `src` to `dst`.

Definition at line 1802 of file ppl_c_implementation_common.cc.

10.15.2.2 int ppl_delete_Grid_Generator_System_const_iterator (ppl_const_Grid_Generator_-System_const_iterator_t *git*) `[related]`

Invalidates the handle `git`: this makes sure the corresponding resources will eventually be released.

Definition at line 1794 of file ppl_c_implementation_common.cc.

10.15.2.3 int ppl_Grid_Generator_System_const_iterator_dereference (ppl_const_Grid_-Generator_System_const_iterator_t *git*, ppl_const_Grid_Generator_t * *pg*) `[related]`

Dereference `git` writing a const handle to the resulting grid generator at address `pg`.

Definition at line 1835 of file ppl_c_implementation_common.cc.

10.15.2.4 int ppl_Grid_Generator_System_const_iterator_equal_test (ppl_const_Grid_Generator_System_const_iterator_t *x*, ppl_const_Grid_Generator_-System_const_iterator_t *y*) `[related]`

Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

Definition at line 1855 of file ppl_c_implementation_common.cc.

10.15.2.5 int ppl_Grid_Generator_System_const_iterator_increment (ppl_Grid_Generator_System_const_iterator_t *git*) `[related]`

Increment `git` so that it "points" to the next grid generator.

Definition at line 1846 of file ppl_c_implementation_common.cc.

10.15.2.6 int ppl_new_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_-const_iterator_t * *pgit*) [related]

Builds a new 'const iterator' and writes a handle to it at address `pgit`.

Definition at line 1776 of file ppl_c_implementation_common.cc.

10.15.2.7 int ppl_new_Grid_Generator_System_const_iterator_from_Grid_Generator_-System_const_iterator (ppl_Grid_Generator_System_const_iterator_t * *pgit*, ppl_const_Grid_Generator_System_const_iterator_t *git*) [related]

Builds a const iterator that is a copy of `git`; writes a handle for the newly created const iterator at address `pgit`.

Definition at line 1784 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.16 ppl_Grid_Generator_System_tag Interface Reference

Types and functions for grid generator systems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Grid_Generator_System (ppl_Grid_Generator_System_t *pgs)
  Builds an empty system of grid generators and writes a handle to it at address `pgs`.
- int ppl_new_Grid_Generator_System_from_Grid_Generator (ppl_Grid_Generator_System_t *pgs, ppl_const_Grid_Generator_t g)
  Builds the singleton grid generator system containing only a copy of generator `g`; writes a handle for the newly created system at address `pgs`.
- int ppl_new_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_-System_t *pgs, ppl_const_Grid_Generator_System_t gs)
  Builds a grid generator system that is a copy of `gs`; writes a handle for the newly created system at address `pgs`.
- int ppl_assign_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_-System_t dst, ppl_const_Grid_Generator_System_t src)
  Assigns a copy of the grid generator system `src` to `dst`.
- int ppl_delete_Grid_Generator_System (ppl_const_Grid_Generator_System_t gs)
  Invalidates the handle `gs`: this makes sure the corresponding resources will eventually be released.

Functions that Do Not Modify the Grid Generator System

- int ppl_Grid_Generator_System_space_dimension (ppl_const_Grid_Generator_System_t gs, ppl_dimension_type *m)

  Writes to `m` the dimension of the vector space enclosing `gs`.

- int ppl_Grid_Generator_System_empty (ppl_const_Grid_Generator_System_t gs)

  Returns a positive integer if `gs` contains no generator; returns 0 otherwise.

- int ppl_Grid_Generator_System_begin (ppl_const_Grid_Generator_System_t gs, ppl_Grid_Generator_System_const_iterator_t git)

  Assigns to `git` a const iterator "pointing" to the beginning of the grid generator system `gs`.

- int ppl_Grid_Generator_System_end (ppl_const_Grid_Generator_System_t gs, ppl_Grid_Generator_System_const_iterator_t git)

  Assigns to `git` a const iterator "pointing" past the end of the grid generator system `gs`.

- int ppl_Grid_Generator_System_OK (ppl_const_Grid_Generator_System_t gs)

  Returns a positive integer if `gs` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `gs` is broken. Useful for debugging purposes.

Functions that May Modify the Grid Generator System

- int ppl_Grid_Generator_System_clear (ppl_Grid_Generator_System_t gs)

  Removes all the generators from the grid generator system `gs` and sets its space dimension to 0.

- int ppl_Grid_Generator_System_insert_Grid_Generator (ppl_Grid_Generator_System_t gs, ppl_const_Grid_Generator_t g)

  Inserts a copy of the grid generator `g` into `gs`; the space dimension is increased, if necessary.

10.16.1 Detailed Description

Types and functions for grid generator systems. The types and functions for grid generator systems provide an interface towards *Grid_Generator_System*.

10.16.2 Friends And Related Function Documentation

10.16.2.1 int ppl_assign_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_System_t *dst*, ppl_const_Grid_Generator_System_t *src*) [related]

Assigns a copy of the grid generator system `src` to `dst`.

Definition at line 1724 of file ppl_c_implementation_common.cc.

10.16.2.2 int ppl_delete_Grid_Generator_System (ppl_const_Grid_Generator_System_t *gs*) [related]

Invalidates the handle `gs`: this makes sure the corresponding resources will eventually be released.

Definition at line 1716 of file ppl_c_implementation_common.cc.

10.16.2.3 int ppl_Grid_Generator_System_begin (ppl_const_Grid_Generator_System_t *gs*, ppl_Grid_Generator_System_const_iterator_t *git*) [related]

Assigns to `git` a const iterator "pointing" to the beginning of the grid generator system `gs`.

Definition at line 1813 of file ppl_c_implementation_common.cc.

10.16.2.4 int ppl_Grid_Generator_System_clear (ppl_Grid_Generator_System_t *gs*) [related]

Removes all the generators from the grid generator system `gs` and sets its space dimension to 0.

Definition at line 1749 of file ppl_c_implementation_common.cc.

10.16.2.5 int ppl_Grid_Generator_System_empty (ppl_const_Grid_Generator_System_t *gs*) [related]

Returns a positive integer if `gs` contains no generator; returns 0 otherwise.

Definition at line 1742 of file ppl_c_implementation_common.cc.

10.16.2.6 int ppl_Grid_Generator_System_end (ppl_const_Grid_Generator_System_t *gs*, ppl_Grid_Generator_System_const_iterator_t *git*) [related]

Assigns to `git` a const iterator "pointing" past the end of the grid generator system `gs`.

Definition at line 1824 of file ppl_c_implementation_common.cc.

10.16.2.7 int ppl_Grid_Generator_System_insert_Grid_Generator (ppl_Grid_Generator_System_t *gs*, ppl_const_Grid_Generator_t *g*) [related]

Inserts a copy of the grid generator `g` into `gs`; the space dimension is increased, if necessary.

Definition at line 1757 of file ppl_c_implementation_common.cc.

10.16.2.8 int ppl_Grid_Generator_System_OK (ppl_const_Grid_Generator_System_t *gs*) [related]

Returns a positive integer if `gs` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `gs` is broken. Useful for debugging purposes.

Definition at line 1767 of file ppl_c_implementation_common.cc.

10.16.2.9 int ppl_Grid_Generator_System_space_dimension (ppl_const_Grid_Generator_System_t *gs*, ppl_dimension_type * *m*) [related]

Writes to `m` the dimension of the vector space enclosing `gs`.

Definition at line 1733 of file ppl_c_implementation_common.cc.

10.16.2.10 int ppl_new_Grid_Generator_System (ppl_Grid_Generator_System_t * *pgs*) [related]

Builds an empty system of grid generators and writes a handle to it at address `pgs`.

Definition at line 1682 of file ppl_c_implementation_common.cc.

10.16.2.11 int ppl_new_Grid_Generator_System_from_Grid_Generator (ppl_Grid_Generator_System_t * *pgs*, ppl_const_Grid_Generator_t *g*) [related]

Builds the singleton grid generator system containing only a copy of generator `g`; writes a handle for the newly created system at address `pgs`.

Definition at line 1699 of file ppl_c_implementation_common.cc.

10.16.2.12 int ppl_new_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_System_t * *pgs*, ppl_const_Grid_Generator_System_t *gs*) [related]

Builds a grid generator system that is a copy of `gs`; writes a handle for the newly created system at address `pgs`.

Definition at line 1708 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.17 ppl_Grid_Generator_tag Interface Reference

Types and functions for grid generators.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Grid_Generator (ppl_Grid_Generator_t *pg, ppl_const_Linear_Expression_t le, enum ppl_enum_Grid_Generator_Type t, ppl_const_Coefficient_t d)

  Creates a new grid generator of direction `le` and type `t`. If the grid generator to be created is a point or a parameter, the divisor `d` is applied to `le`. If it is a line, `d` is simply disregarded. A handle for the new grid generator is written at address `pg`. The space dimension of the new grid generator is equal to the space dimension of `le`.

- int ppl_new_Grid_Generator_zero_dim_point (ppl_Grid_Generator_t *pg)

  Creates the point that is the origin of the zero-dimensional space $\mathbb{R}^0$. Writes a handle for the new grid generator at address `pg`.

- int ppl_new_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t *pg, ppl_const_Grid_Generator_t g)

  Builds a grid generator that is a copy of `g`; writes a handle for the newly created grid generator at address `pg`.

- int ppl_assign_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t dst, ppl_const_Grid_Generator_t src)

  Assigns a copy of the grid generator `src` to `dst`.

- int ppl_delete_Grid_Generator (ppl_const_Grid_Generator_t g)

  Invalidates the handle `g`: this makes sure the corresponding resources will eventually be released.

Functions that Do Not Modify the Grid Generator

- int ppl_Grid_Generator_space_dimension (ppl_const_Grid_Generator_t g, ppl_dimension_type *m)

  Writes to `m` the space dimension of `g`.

- int ppl_Grid_Generator_type (ppl_const_Grid_Generator_t g)

  Returns the type of grid generator `g`.

- int ppl_Grid_Generator_coefficient (ppl_const_Grid_Generator_t g, ppl_dimension_type var, ppl_Coefficient_t n)

  Copies into `n` the coefficient of variable `var` in grid generator `g`.

- int ppl_Grid_Generator_divisor (ppl_const_Grid_Generator_t g, ppl_Coefficient_t n)

  If `g` is a point or a parameter assigns its divisor to `n`.

- int ppl_Grid_Generator_OK (ppl_const_Grid_Generator_t g)

  Returns a positive integer if `g` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `g` is broken. Useful for debugging purposes.

10.17.1 Detailed Description

Types and functions for grid generators. The types and functions for grid generators provide an interface towards *Grid_Generator*.

10.17.2 Friends And Related Function Documentation

10.17.2.1 int ppl_assign_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t *dst*, ppl_const_Grid_Generator_t *src*) [related]

Assigns a copy of the grid generator `src` to `dst`.

Definition at line 1609 of file ppl_c_implementation_common.cc.

10.17.2.2 int ppl_delete_Grid_Generator (ppl_const_Grid_Generator_t *g*) [related]

Invalidates the handle `g`: this makes sure the corresponding resources will eventually be released.

Definition at line 1601 of file ppl_c_implementation_common.cc.

10.17.2.3 int ppl_Grid_Generator_coefficient (ppl_const_Grid_Generator_t *g*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Copies into `n` the coefficient of variable `var` in grid generator `g`.

Definition at line 1642 of file ppl_c_implementation_common.cc.

10.17.2.4 int ppl_Grid_Generator_divisor (ppl_const_Grid_Generator_t *g*, ppl_Coefficient_t *n*) [related]

If `g` is a point or a parameter assigns its divisor to `n`.

Definition at line 1653 of file ppl_c_implementation_common.cc.

10.17.2.5 int ppl_Grid_Generator_OK (ppl_const_Grid_Generator_t *g*) [related]

Returns a positive integer if `g` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `g` is broken. Useful for debugging purposes.

Definition at line 1663 of file ppl_c_implementation_common.cc.

10.17.2.6 int ppl_Grid_Generator_space_dimension (ppl_const_Grid_Generator_t *g*, ppl_dimension_type * *m*) [related]

Writes to `m` the space dimension of `g`.

Definition at line 1619 of file ppl_c_implementation_common.cc.

10.17.2.7 int ppl_Grid_Generator_type (ppl_const_Grid_Generator_t *g*) [related]

Returns the type of grid generator `g`.

Definition at line 1627 of file ppl_c_implementation_common.cc.

10.17.2.8 int ppl_new_Grid_Generator (ppl_Grid_Generator_t * *pg*, ppl_const_Linear_Expression_t *le*, enum ppl_enum_Grid_Generator_Type *t*, ppl_const_Coefficient_t *d*) [related]

Creates a new grid generator of direction `le` and type `t`. If the grid generator to be created is a point or a parameter, the divisor `d` is applied to `le`. If it is a line, `d` is simply disregarded. A handle for the new grid generator is written at address `pg`. The space dimension of the new grid generator is equal to the space dimension of `le`.

Definition at line 1558 of file ppl_c_implementation_common.cc.

10.17.2.9 int ppl_new_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t * *pg*, ppl_const_Grid_Generator_t *g*) [related]

Builds a grid generator that is a copy of `g`; writes a handle for the newly created grid generator at address `pg`.

Definition at line 1592 of file ppl_c_implementation_common.cc.

10.17.2.10 int ppl_new_Grid_Generator_zero_dim_point (ppl_Grid_Generator_t * *pg*) [related]

Creates the point that is the origin of the zero-dimensional space $\mathbb{R}^0$. Writes a handle for the new grid generator at address `pg`.

Definition at line 1585 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.18 ppl_Linear_Expression_tag Interface Reference

Types and functions for linear expressions.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Constructors, Assignment and Destructor

- int ppl_new_Linear_Expression (ppl_Linear_Expression_t *ple)

  Creates a new linear expression corresponding to the constant 0 in a zero-dimensional space; writes a handle for the new linear expression at address `ple`.

- int ppl_new_Linear_Expression_with_dimension (ppl_Linear_Expression_t *ple, ppl_dimension_type d)

  Creates a new linear expression corresponding to the constant 0 in a `d`*-dimensional space; writes a handle for the new linear expression at address* `ple`.

- int ppl_new_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t *ple, ppl_const_Linear_Expression_t le)

  Builds a linear expression that is a copy of `le`*; writes a handle for the newly created linear expression at address* `ple`.

- int ppl_new_Linear_Expression_from_Constraint (ppl_Linear_Expression_t *ple, ppl_const_Constraint_t c)

  Builds a linear expression corresponding to constraint `c`*; writes a handle for the newly created linear expression at address* `ple`.

- int ppl_new_Linear_Expression_from_Generator (ppl_Linear_Expression_t *ple, ppl_const_Generator_t g)

  Builds a linear expression corresponding to generator `g`*; writes a handle for the newly created linear expression at address* `ple`.

- int ppl_new_Linear_Expression_from_Congruence (ppl_Linear_Expression_t *ple, ppl_const_Congruence_t c)

  Builds a linear expression corresponding to congruence `c`*; writes a handle for the newly created linear expression at address* `ple`.

- int ppl_new_Linear_Expression_from_Grid_Generator (ppl_Linear_Expression_t *ple, ppl_const_Grid_Generator_t g)

  Builds a linear expression corresponding to grid generator `g`*; writes a handle for the newly created linear expression at address* `ple`.

- int ppl_assign_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t dst, ppl_const_Linear_Expression_t src)

  Assigns a copy of the linear expression `src` *to* `dst`.

- int ppl_delete_Linear_Expression (ppl_const_Linear_Expression_t le)

  Invalidates the handle `le`*: this makes sure the corresponding resources will eventually be released.*

Functions that Do Not Modify the Linear Expression

- int ppl_Linear_Expression_space_dimension (ppl_const_Linear_Expression_t le, ppl_dimension_type *m)

  Writes to `m` *the space dimension of* `le`.

- int ppl_Linear_Expression_coefficient (ppl_const_Linear_Expression_t le, ppl_dimension_type var, ppl_Coefficient_t n)

Copies into `n` *the coefficient of variable* `var` *in the linear expression* `le`.

- int ppl_Linear_Expression_inhomogeneous_term (ppl_const_Linear_Expression_t le, ppl_Coefficient_t n)

  Copies into `n` *the inhomogeneous term of linear expression* `le`.

- int ppl_Linear_Expression_OK (ppl_const_Linear_Expression_t le)

  Returns a positive integer if `le` *is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if* `le` *is broken. Useful for debugging purposes.*

- int ppl_Linear_Expression_is_zero (ppl_const_Linear_Expression_t le)

  Returns `true` *if and only if* `*this` *is* 0.

- int ppl_Linear_Expression_all_homogeneous_terms_are_zero (ppl_const_Linear_Expression_t le)

  Returns `true` *if and only if all the homogeneous terms of* `*this` *are* 0.

Functions that May Modify the Linear Expression

- int ppl_Linear_Expression_add_to_coefficient (ppl_Linear_Expression_t le, ppl_dimension_type var, ppl_const_Coefficient_t n)

  Adds `n` *to the coefficient of variable* `var` *in the linear expression* `le`. *The space dimension is set to be the maximum between* `var` + *1 and the old space dimension.*

- int ppl_Linear_Expression_add_to_inhomogeneous (ppl_Linear_Expression_t le, ppl_const_Coefficient_t n)

  Adds `n` *to the inhomogeneous term of the linear expression* `le`.

- int ppl_add_Linear_Expression_to_Linear_Expression (ppl_Linear_Expression_t dst, ppl_const_Linear_Expression_t src)

  Adds the linear expression `src` *to* `dst`.

- int ppl_subtract_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t dst, ppl_const_Linear_Expression_t src)

  Subtracts the linear expression `src` *from* `dst`.

- int ppl_multiply_Linear_Expression_by_Coefficient (ppl_Linear_Expression_t le, ppl_const_Coefficient_t n)

  Multiply the linear expression `dst` *by* `n`.

10.18.1 Detailed Description

Types and functions for linear expressions. The types and functions for linear expression provide an interface towards *Linear_Expression*.

10.18.2 Friends And Related Function Documentation

10.18.2.1 int ppl_add_Linear_Expression_to_Linear_Expression (ppl_Linear_Expression_t *dst*, ppl_const_Linear_Expression_t *src*) `[related]`

Adds the linear expression `src` to `dst`.

Definition at line 557 of file ppl_c_implementation_common.cc.

10.18.2.2 int ppl_assign_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t *dst*, ppl_const_Linear_Expression_t *src*) [related]

Assigns a copy of the linear expression `src` to `dst`.

Definition at line 526 of file ppl_c_implementation_common.cc.

10.18.2.3 int ppl_delete_Linear_Expression (ppl_const_Linear_Expression_t *le*) [related]

Invalidates the handle `le`: this makes sure the corresponding resources will eventually be released.

Definition at line 518 of file ppl_c_implementation_common.cc.

10.18.2.4 int ppl_Linear_Expression_add_to_coefficient (ppl_Linear_Expression_t *le*, ppl_dimension_type *var*, ppl_const_Coefficient_t *n*) [related]

Adds `n` to the coefficient of variable `var` in the linear expression `le`. The space dimension is set to be the maximum between `var` + 1 and the old space dimension.

Definition at line 535 of file ppl_c_implementation_common.cc.

10.18.2.5 int ppl_Linear_Expression_add_to_inhomogeneous (ppl_Linear_Expression_t *le*, ppl_const_Coefficient_t *n*) [related]

Adds `n` to the inhomogeneous term of the linear expression `le`.

Definition at line 546 of file ppl_c_implementation_common.cc.

10.18.2.6 int ppl_Linear_Expression_all_homogeneous_terms_are_zero (ppl_const_Linear_Expression_t *le*) [related]

Returns `true` if and only if all the homogeneous terms of `*this` are 0.

Definition at line 628 of file ppl_c_implementation_common.cc.

10.18.2.7 int ppl_Linear_Expression_coefficient (ppl_const_Linear_Expression_t *le*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Copies into `n` the coefficient of variable `var` in the linear expression `le`.

Definition at line 594 of file ppl_c_implementation_common.cc.

10.18.2.8 int ppl_Linear_Expression_inhomogeneous_term (ppl_const_Linear_Expression_t *le*, ppl_Coefficient_t *n*) [related]

Copies into `n` the inhomogeneous term of linear expression `le`.

Definition at line 605 of file ppl_c_implementation_common.cc.

10.18.2.9 int ppl_Linear_Expression_is_zero (ppl_const_Linear_Expression_t *le*) [related]

Returns `true` if and only if `*this` is 0.

Definition at line 621 of file ppl_c_implementation_common.cc.

10.18.2.10 int ppl_Linear_Expression_OK (ppl_const_Linear_Expression_t *le*) [related]

Returns a positive integer if `le` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `le` is broken. Useful for debugging purposes.

Definition at line 615 of file ppl_c_implementation_common.cc.

10.18.2.11 int ppl_Linear_Expression_space_dimension (ppl_const_Linear_Expression_t *le*, ppl_dimension_type * *m*) [related]

Writes to `m` the space dimension of `le`.

Definition at line 586 of file ppl_c_implementation_common.cc.

10.18.2.12 int ppl_multiply_Linear_Expression_by_Coefficient (ppl_Linear_Expression_t *le*, ppl_const_Coefficient_t *n*) [related]

Multiply the linear expression `dst` by `n`.

Definition at line 576 of file ppl_c_implementation_common.cc.

10.18.2.13 int ppl_new_Linear_Expression (ppl_Linear_Expression_t * *ple*) [related]

Creates a new linear expression corresponding to the constant 0 in a zero-dimensional space; writes a handle for the new linear expression at address `ple`.

Definition at line 492 of file ppl_c_implementation_common.cc.

10.18.2.14 int ppl_new_Linear_Expression_from_Congruence (ppl_Linear_Expression_t * *ple*, ppl_const_Congruence_t *c*) [related]

Builds a linear expression corresponding to congruence `c`; writes a handle for the newly created linear expression at address `ple`.

Definition at line 1366 of file ppl_c_implementation_common.cc.

10.18.2.15 int ppl_new_Linear_Expression_from_Constraint (ppl_Linear_Expression_t * *ple*, ppl_const_Constraint_t *c*) [related]

Builds a linear expression corresponding to constraint `c`; writes a handle for the newly created linear expression at address `ple`.

Definition at line 757 of file ppl_c_implementation_common.cc.

10.18.2.16 int ppl_new_Linear_Expression_from_Generator (ppl_Linear_Expression_t * *ple*, ppl_const_Generator_t *g*) [related]

Builds a linear expression corresponding to generator `g`; writes a handle for the newly created linear expression at address `ple`.

Definition at line 1079 of file ppl_c_implementation_common.cc.

10.18.2.17 int ppl_new_Linear_Expression_from_Grid_Generator (ppl_Linear_Expression_t * *ple*, ppl_const_Grid_Generator_t *g*) [related]

Builds a linear expression corresponding to grid generator `g`; writes a handle for the newly created linear expression at address `ple`.

10.18.2.18 int ppl_new_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t * *ple*, ppl_const_Linear_Expression_t *le*) [related]

Builds a linear expression that is a copy of `le`; writes a handle for the newly created linear expression at address `ple`.

Definition at line 510 of file ppl_c_implementation_common.cc.

10.18.2.19 int ppl_new_Linear_Expression_with_dimension (ppl_Linear_Expression_t * *ple*, ppl_dimension_type *d*) [related]

Creates a new linear expression corresponding to the constant 0 in a `d`-dimensional space; writes a handle for the new linear expression at address `ple`.

Definition at line 499 of file ppl_c_implementation_common.cc.

10.18.2.20 int ppl_subtract_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t *dst*, ppl_const_Linear_Expression_t *src*) [related]

Subtracts the linear expression `src` from `dst`.

Definition at line 567 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.19 ppl_MIP_Problem_tag Interface Reference

Types and functions for MIP problems.

```
#include <ppl_c_header.h>
```

Related Functions

(Note that these are not member functions.)

Symbolic Constants

- int PPL_OPTIMIZATION_MODE_MAXIMIZATION
  Code of the "maximization" optimization mode.
- int PPL_OPTIMIZATION_MODE_MINIMIZATION
  Code of the "minimization" optimization mode.
- int PPL_MIP_PROBLEM_STATUS_UNFEASIBLE
  Code of the "unfeasible MIP problem" status.
- int PPL_MIP_PROBLEM_STATUS_UNBOUNDED
  Code of the "unbounded MIP problem" status.
- int PPL_MIP_PROBLEM_STATUS_OPTIMIZED
  Code of the "optimized MIP problem" status.
- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_NAME_PRICING
  Code for the MIP problem's "pricing" control parameter name.
- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_TEXTBOOK
  Code of MIP problem's "textbook" pricing method.
- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_EDGE_-EXACT
  Code of MIP problem's "exact steepest-edge" pricing method.
- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_EDGE_-FLOAT

Code of MIP problem's "float steepest-edge" pricing method.

Constructors, Assignment and Destructor

- int ppl_new_MIP_Problem_from_space_dimension (ppl_MIP_Problem_t *pmip, ppl_dimension_type d)

  Builds a trivial MIP problem of dimension `d` *and writes a handle to it at address* `pmip`.

- int ppl_new_MIP_Problem (ppl_MIP_Problem_t *pmip, ppl_dimension_type d, ppl_const_Constraint_System_t cs, ppl_const_Linear_Expression_t le, int m)

  Builds a MIP problem of space dimension `d` *having feasible region* `cs`*, objective function* `le` *and optimization mode* `m`*; writes a handle to it at address* `pmip`.

- int ppl_new_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t *pmip, ppl_const_MIP_Problem_t mip)

  Builds a MIP problem that is a copy of `mip`*; writes a handle for the newly created system at address* `pmip`.

- int ppl_assign_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t dst, ppl_const_MIP_Problem_t src)

  Assigns a copy of the MIP problem `src` *to* `dst`.

- int ppl_delete_MIP_Problem (ppl_const_MIP_Problem_t mip)

  Invalidates the handle `mip`*: this makes sure the corresponding resources will eventually be released.*

Functions that Do Not Modify the MIP_Problem

- int ppl_MIP_Problem_space_dimension (ppl_const_MIP_Problem_t mip, ppl_dimension_type *m)

  Writes to `m` *the dimension of the vector space enclosing* `mip`.

- int ppl_MIP_Problem_number_of_integer_space_dimensions (ppl_const_MIP_Problem_t mip, ppl_dimension_type *m)

  Writes to `m` *the number of integer space dimensions of* `mip`.

- int ppl_MIP_Problem_integer_space_dimensions (ppl_const_MIP_Problem_t mip, ppl_dimension_type ds[ ])

  Writes in the first positions of the array `ds` *all the integer space dimensions of problem* `mip`*. If the array is not big enough to hold all of the integer space dimensions, the behavior is undefined.*

- int ppl_MIP_Problem_number_of_constraints (ppl_const_MIP_Problem_t mip, ppl_dimension_type *m)

  Writes to `m` *the number of constraints defining the feasible region of* `mip`.

- int ppl_MIP_Problem_constraint_at_index (ppl_const_MIP_Problem_t mip, ppl_dimension_type i, ppl_const_Constraint_t *pc)

  Writes at address `pc` *a const handle to the* `i-th` *constraint defining the feasible region of the MIP problem* `mip`.

- int ppl_MIP_Problem_objective_function (ppl_const_MIP_Problem_t mip, ppl_const_Linear_Expression_t *ple)

  Writes a const handle to the linear expression defining the objective function of the MIP problem `mip` *at address* `ple`.

- int ppl_MIP_Problem_optimization_mode (ppl_const_MIP_Problem_t mip)
  Returns the optimization mode of the MIP problem `mip`.

- int ppl_MIP_Problem_OK (ppl_const_MIP_Problem_t mip)
  Returns a positive integer if `mip` *is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if* `mip` *is broken. Useful for debugging purposes.*

Functions that May Modify the MIP_Problem

- int ppl_MIP_Problem_clear (ppl_MIP_Problem_t mip)
  Resets the MIP problem to be a trivial problem of space dimension 0.

- int ppl_MIP_Problem_add_space_dimensions_and_embed (ppl_MIP_Problem_t mip, ppl_-dimension_type d)
  Adds `d` *new dimensions to the space enclosing the MIP problem* `mip` *and to* `mip` *itself.*

- int ppl_MIP_Problem_add_to_integer_space_dimensions (ppl_MIP_Problem_t mip, ppl_-dimension_type ds[ ], size_t n)
  Sets the space dimensions that are specified in first `n` *positions of the array* `ds` *to be integer dimensions of problem* `mip`*. The presence of duplicates in* `ds` *is a waste but an innocuous one.*

- int ppl_MIP_Problem_add_constraint (ppl_MIP_Problem_t mip, ppl_const_Constraint_t c)
  Modifies the feasible region of the MIP problem `mip` *by adding a copy of the constraint* `c`.

- int ppl_MIP_Problem_add_constraints (ppl_MIP_Problem_t mip, ppl_const_Constraint_-System_t cs)
  Modifies the feasible region of the MIP problem `mip` *by adding a copy of the constraints in* `cs`.

- int ppl_MIP_Problem_set_objective_function (ppl_MIP_Problem_t mip, ppl_const_Linear_-Expression_t le)
  Sets the objective function of the MIP problem `mip` *to a copy of* `le`.

- int ppl_MIP_Problem_set_optimization_mode (ppl_MIP_Problem_t mip, int mode)
  Sets the optimization mode of the MIP problem `mip` *to* `mode`.

Computing the Solution of the MIP_Problem

- int ppl_MIP_Problem_is_satisfiable (ppl_const_MIP_Problem_t mip)
  Returns a positive integer if `mip` *is satisfiable; returns 0 otherwise.*

- int ppl_MIP_Problem_solve (ppl_const_MIP_Problem_t mip)
  Solves the MIP problem `mip`*, returning an exit status.*

- int ppl_MIP_Problem_evaluate_objective_function (ppl_const_MIP_Problem_t mip, ppl_const_-Generator_t g, ppl_Coefficient_t num, ppl_Coefficient_t den)
  Evaluates the objective function of `mip` *on point* `g`.

- int ppl_MIP_Problem_feasible_point (ppl_const_MIP_Problem_t mip, ppl_const_Generator_-t *pg)
  Writes a const handle to a feasible point for the MIP problem `mip` *at address* `pg`.

- int ppl_MIP_Problem_optimizing_point (ppl_const_MIP_Problem_t mip, ppl_const_-Generator_t *pg)
  Writes a const handle to an optimizing point for the MIP problem `mip` *at address* `pg`.
- int ppl_MIP_Problem_optimal_value (ppl_const_MIP_Problem_t mip, ppl_Coefficient_t num, ppl_Coefficient_t den)
  Returns the optimal value for `mip`.

Querying/Setting Control Parameters

- int ppl_MIP_Problem_get_control_parameter (ppl_const_MIP_Problem_t mip, int name)
  Returns the value of control parameter `name` *in problem* `mip`.
- int ppl_MIP_Problem_set_control_parameter (ppl_MIP_Problem_t mip, int value)
  Sets control parameter `value` *in problem* `mip`.
- int ppl_MIP_Problem_total_memory_in_bytes (ppl_const_MIP_Problem_t mip, size_t *sz)
  Writes into `*sz` *the size in bytes of the memory occupied by* `mip`.
- int ppl_MIP_Problem_external_memory_in_bytes (ppl_const_MIP_Problem_t mip, size_t *sz)
  Writes into `*sz` *the size in bytes of the memory managed by* `mip`.

10.19.1 Detailed Description

Types and functions for MIP problems. The types and functions for MIP problems provide an interface towards *MIP_Problem*.

10.19.2 Friends And Related Function Documentation

10.19.2.1 int ppl_assign_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t *dst*, ppl_const_MIP_Problem_t *src*) `[related]`

Assigns a copy of the MIP problem `src` to `dst`.

Definition at line 1902 of file ppl_c_implementation_common.cc.

10.19.2.2 int ppl_delete_MIP_Problem (ppl_const_MIP_Problem_t *mip*) `[related]`

Invalidates the handle `mip`: this makes sure the corresponding resources will eventually be released.

Definition at line 1895 of file ppl_c_implementation_common.cc.

10.19.2.3 int ppl_MIP_Problem_add_constraint (ppl_MIP_Problem_t *mip*, ppl_const_Constraint_t *c*) `[related]`

Modifies the feasible region of the MIP problem `mip` by adding a copy of the constraint `c`.

Definition at line 2010 of file ppl_c_implementation_common.cc.

10.19.2.4 int ppl_MIP_Problem_add_constraints (ppl_MIP_Problem_t *mip*, ppl_const_Constraint_System_t *cs*) [related]

Modifies the feasible region of the MIP problem `mip` by adding a copy of the constraints in `cs`.

Definition at line 2020 of file ppl_c_implementation_common.cc.

10.19.2.5 int ppl_MIP_Problem_add_space_dimensions_and_embed (ppl_MIP_Problem_t *mip*, ppl_dimension_type *d*) [related]

Adds `d` new dimensions to the space enclosing the MIP problem `mip` and to `mip` itself.

Definition at line 1988 of file ppl_c_implementation_common.cc.

10.19.2.6 int ppl_MIP_Problem_add_to_integer_space_dimensions (ppl_MIP_Problem_t *mip*, ppl_dimension_type *ds*[ ], size_t *n*) [related]

Sets the space dimensions that are specified in first `n` positions of the array `ds` to be integer dimensions of problem `mip`. The presence of duplicates in `ds` is a waste but an innocuous one.

Definition at line 1997 of file ppl_c_implementation_common.cc.

10.19.2.7 int ppl_MIP_Problem_clear (ppl_MIP_Problem_t *mip*) [related]

Resets the MIP problem to be a trivial problem of space dimension 0.

Definition at line 1981 of file ppl_c_implementation_common.cc.

10.19.2.8 int ppl_MIP_Problem_constraint_at_index (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type *i*, ppl_const_Constraint_t * *pc*) [related]

Writes at address `pc` a const handle to the `i-th` constraint defining the feasible region of the MIP problem `mip`.

Definition at line 1950 of file ppl_c_implementation_common.cc.

10.19.2.9 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_NAME_PRICING [related]

Code for the MIP problem's "pricing" control parameter name.

Definition at line 2428 of file ppl_c_header.h.

10.19.2.10 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_-EDGE_EXACT [related]

Code of MIP problem's "exact steepest-edge" pricing method.

Definition at line 2438 of file ppl_c_header.h.

10.19.2.11 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_-EDGE_FLOAT [related]

Code of MIP problem's "float steepest-edge" pricing method.

Definition at line 2443 of file ppl_c_header.h.

10.19.2.12 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_TEXTBOOK [related]

Code of MIP problem's "textbook" pricing method.

Definition at line 2433 of file ppl_c_header.h.

10.19.2.13 int ppl_MIP_Problem_evaluate_objective_function (ppl_const_MIP_Problem_t *mip*, ppl_const_Generator_t *g*, ppl_Coefficient_t *num*, ppl_Coefficient_t *den*) [related]

Evaluates the objective function of `mip` on point `g`.

Parameters

mip The MIP problem defining the objective function;

g The generator on which the objective function will be evaluated;

num Will be assigned the numerator of the objective function value;

den Will be assigned the denominator of the objective function value;

Definition at line 2062 of file ppl_c_implementation_common.cc.

10.19.2.14 int ppl_MIP_Problem_external_memory_in_bytes (ppl_const_MIP_Problem_t *mip*, size_t * *sz*) [related]

Writes into `*sz` the size in bytes of the memory managed by `mip`.

Definition at line 2138 of file ppl_c_implementation_common.cc.

10.19.2.15 int ppl_MIP_Problem_feasible_point (ppl_const_MIP_Problem_t *mip*, ppl_const_Generator_t * *pg*) [related]

Writes a const handle to a feasible point for the MIP problem `mip` at address `pg`.

Definition at line 2076 of file ppl_c_implementation_common.cc.

10.19.2.16 int ppl_MIP_Problem_get_control_parameter (ppl_const_MIP_Problem_t *mip*, int *name*) [related]

Returns the value of control parameter `name` in problem `mip`.

Definition at line 2105 of file ppl_c_implementation_common.cc.

10.19.2.17 int ppl_MIP_Problem_integer_space_dimensions (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type *ds*[ ]) [related]

Writes in the first positions of the array `ds` all the integer space dimensions of problem `mip`. If the array is not big enough to hold all of the integer space dimensions, the behavior is undefined.

Definition at line 1929 of file ppl_c_implementation_common.cc.

10.19.2.18 int ppl_MIP_Problem_is_satisfiable (ppl_const_MIP_Problem_t *mip*) [related]

Returns a positive integer if `mip` is satisfiable; returns 0 otherwise.

Definition at line 2050 of file ppl_c_implementation_common.cc.

10.19.2.19 int ppl_MIP_Problem_number_of_constraints (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type * *m*) [related]

Writes to `m` the number of constraints defining the feasible region of `mip`.

Definition at line 1941 of file ppl_c_implementation_common.cc.

Referenced by ppl_MIP_Problem_constraint_at_index().

10.19.2.20 int ppl_MIP_Problem_number_of_integer_space_dimensions (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type * *m*) [related]

Writes to `m` the number of integer space dimensions of `mip`.

Definition at line 1920 of file ppl_c_implementation_common.cc.

10.19.2.21 int ppl_MIP_Problem_objective_function (ppl_const_MIP_Problem_t *mip*, ppl_const_Linear_Expression_t * *ple*) [related]

Writes a const handle to the linear expression defining the objective function of the MIP problem `mip` at address `ple`.

Definition at line 1966 of file ppl_c_implementation_common.cc.

10.19.2.22 int ppl_MIP_Problem_OK (ppl_const_MIP_Problem_t *mip*) [related]

Returns a positive integer if `mip` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `mip` is broken. Useful for debugging purposes.

Definition at line 2124 of file ppl_c_implementation_common.cc.

10.19.2.23 int ppl_MIP_Problem_optimal_value (ppl_const_MIP_Problem_t *mip*, ppl_Coefficient_t *num*, ppl_Coefficient_t *den*) [related]

Returns the optimal value for `mip`.

Parameters

mip The MIP problem;

num Will be assigned the numerator of the optimal value;

den Will be assigned the denominator of the optimal value.

Definition at line 2094 of file ppl_c_implementation_common.cc.

10.19.2.24 int ppl_MIP_Problem_optimization_mode (ppl_const_MIP_Problem_t *mip*) [related]

Returns the optimization mode of the MIP problem `mip`.

Definition at line 1975 of file ppl_c_implementation_common.cc.

10.19.2.25 int ppl_MIP_Problem_optimizing_point (ppl_const_MIP_Problem_t *mip*, ppl_const_Generator_t * *pg*) [related]

Writes a const handle to an optimizing point for the MIP problem `mip` at address `pg`.

Definition at line 2085 of file ppl_c_implementation_common.cc.

10.19.2.26 int ppl_MIP_Problem_set_control_parameter (ppl_MIP_Problem_t *mip*, int *value*) [related]

Sets control parameter `value` in problem `mip`.

Definition at line 2114 of file ppl_c_implementation_common.cc.

10.19.2.27 int ppl_MIP_Problem_set_objective_function (ppl_MIP_Problem_t *mip*, ppl_const_Linear_Expression_t *le*) [related]

Sets the objective function of the MIP problem `mip` to a copy of `le`.

Definition at line 2030 of file ppl_c_implementation_common.cc.

10.19.2.28 int ppl_MIP_Problem_set_optimization_mode (ppl_MIP_Problem_t *mip*, int *mode*) [related]

Sets the optimization mode of the MIP problem `mip` to `mode`.

Definition at line 2040 of file ppl_c_implementation_common.cc.

10.19.2.29 int ppl_MIP_Problem_solve (ppl_const_MIP_Problem_t *mip*) [related]

Solves the MIP problem `mip`, returning an exit status.

Returns

`PPL_MIP_PROBLEM_STATUS_UNFEASIBLE` if the MIP problem is not satisfiable; `PPL_MIP_PROBLEM_STATUS_UNBOUNDED` if the MIP problem is satisfiable but there is no finite bound to the value of the objective function; `PPL_MIP_PROBLEM_STATUS_OPTIMIZED` if the MIP problem admits an optimal solution.

Definition at line 2056 of file ppl_c_implementation_common.cc.

10.19.2.30 int ppl_MIP_Problem_space_dimension (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type * *m*) [related]

Writes to `m` the dimension of the vector space enclosing `mip`.

Definition at line 1912 of file ppl_c_implementation_common.cc.

10.19.2.31 int PPL_MIP_PROBLEM_STATUS_OPTIMIZED [related]

Code of the "optimized MIP problem" status.

Definition at line 2423 of file ppl_c_header.h.

10.19.2.32 int PPL_MIP_PROBLEM_STATUS_UNBOUNDED [related]

Code of the "unbounded MIP problem" status.

Definition at line 2418 of file ppl_c_header.h.

10.19.2.33 int PPL_MIP_PROBLEM_STATUS_UNFEASIBLE [related]

Code of the "unfeasible MIP problem" status.

Definition at line 2413 of file ppl_c_header.h.

10.19.2.34 int ppl_MIP_Problem_total_memory_in_bytes (ppl_const_MIP_Problem_t *mip*, size_t * *sz*) [related]

Writes into `*sz` the size in bytes of the memory occupied by `mip`.

Definition at line 2130 of file ppl_c_implementation_common.cc.

10.19.2.35 int ppl_new_MIP_Problem (ppl_MIP_Problem_t * *pmip*, ppl_dimension_type *d*, ppl_const_Constraint_System_t *cs*, ppl_const_Linear_Expression_t *le*, int *m*) [related]

Builds a MIP problem of space dimension `d` having feasible region `cs`, objective function `le` and optimization mode `m`; writes a handle to it at address `pmip`.

Definition at line 1872 of file ppl_c_implementation_common.cc.

10.19.2.36 int ppl_new_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t * *pmip*, ppl_const_MIP_Problem_t *mip*) [related]

Builds a MIP problem that is a copy of `mip`; writes a handle for the newly created system at address `pmip`.

Definition at line 1886 of file ppl_c_implementation_common.cc.

10.19.2.37 int ppl_new_MIP_Problem_from_space_dimension (ppl_MIP_Problem_t * *pmip*, ppl_dimension_type *d*) [related]

Builds a trivial MIP problem of dimension `d` and writes a handle to it at address `pmip`.

Definition at line 1864 of file ppl_c_implementation_common.cc.

10.19.2.38 int PPL_OPTIMIZATION_MODE_MAXIMIZATION [related]

Code of the "maximization" optimization mode.

Definition at line 2403 of file ppl_c_header.h.

10.19.2.39 int PPL_OPTIMIZATION_MODE_MINIMIZATION [related]

Code of the "minimization" optimization mode.

Definition at line 2408 of file ppl_c_header.h.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.20 ppl_PIP_Decision_Node_tag Interface Reference

Types and functions for PIP decision nodes.

`#include <ppl_c_header.h>`

Related Functions

(Note that these are not member functions.)

- int ppl_PIP_Decision_Node_get_child_node (ppl_const_PIP_Decision_Node_t pip_dec, int b, ppl_-const_PIP_Tree_Node_t *pip_tree)

  Writes to `pip_tree` a const pointer to either the true branch (if `b` is not zero) or the false branch (if `b` is zero) of `pip_dec`.

10.20.1 Detailed Description

Types and functions for PIP decision nodes. The types and functions for decision nodes provide an interface towards *PIP_Decision_Node*.

10.20.2 Friends And Related Function Documentation

10.20.2.1 int ppl_PIP_Decision_Node_get_child_node (ppl_const_PIP_Decision_Node_t *pip_dec*, int *b*, ppl_const_PIP_Tree_Node_t * *pip_tree*) [related]

Writes to `pip_tree` a const pointer to either the true branch (if `b` is not zero) or the false branch (if `b` is zero) of `pip_dec`.

Definition at line 2468 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.21 ppl_PIP_Problem_tag Interface Reference

Types and functions for PIP problems.

`#include <ppl_c_header.h>`

Related Functions

(Note that these are not member functions.)

Symbolic Constants

- int PPL_PIP_PROBLEM_STATUS_UNFEASIBLE
  Code of the "unfeasible PIP problem" status.
- int PPL_PIP_PROBLEM_STATUS_OPTIMIZED
  Code of the "optimized PIP problem" status.
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_CUTTING_STRATEGY
  Code for the PIP problem's "cutting strategy" control parameter name.
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_PIVOT_ROW_STRATEGY
  Code for the PIP problem's "pivot row strategy" control parameter name.
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_FIRST
  Code of PIP problem's "first" cutting strategy.
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_DEEPEST
  Code of PIP problem's "deepest" cutting strategy.
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_ALL
  Code of PIP problem's "all" cutting strategy.
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_FIRST
  Code of PIP problem's "first" pivot row strategy.
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_MAX_-COLUMN
  Code of PIP problem's "max column" pivot row strategy.

Constructors, Assignment and Destructor

- int ppl_new_PIP_Problem_from_space_dimension (ppl_PIP_Problem_t *ppip, ppl_dimension_-type d)
  Builds a trivial PIP problem of dimension `d` and writes a handle to it at address `ppip`.
- int ppl_new_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t *ppip, ppl_const_PIP_-Problem_t pip)
  Builds a PIP problem that is a copy of `pip`; writes a handle for the newly created problem at address `ppip`.

- int ppl_assign_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t dst, ppl_const_PIP_Problem_t src)

  Assigns a copy of the PIP problem `src` to `dst`.

- int ppl_new_PIP_Problem_from_constraints (ppl_PIP_Problem_t *ppip, ppl_dimension_type d, ppl_Constraint_System_const_iterator_t first, ppl_Constraint_System_const_iterator_t last, size_t n, ppl_dimension_type ds[ ])

  Builds a PIP problem having space dimension `d` from the sequence of constraints in the range $[\text{first}, \text{last})$*; the `n` dimensions whose indices occur in `ds` are interpreted as parameters.*

- int ppl_delete_PIP_Problem (ppl_const_PIP_Problem_t pip)

  Invalidates the handle `pip`: this makes sure the corresponding resources will eventually be released.

Functions that Do Not Modify the PIP_Problem

- int ppl_PIP_Problem_space_dimension (ppl_const_PIP_Problem_t pip, ppl_dimension_type *m)

  Writes to `m` the dimension of the vector space enclosing `pip`.

- int ppl_PIP_Problem_number_of_parameter_space_dimensions (ppl_const_PIP_Problem_t pip, ppl_dimension_type *m)

  Writes to `m` the number of parameter space dimensions of `pip`.

- int ppl_PIP_Problem_parameter_space_dimensions (ppl_const_PIP_Problem_t pip, ppl_dimension_type ds[ ])

  Writes in the first positions of the array `ds` all the parameter space dimensions of problem `pip`. If the array is not big enough to hold all of the parameter space dimensions, the behavior is undefined.

- int ppl_PIP_Problem_get_big_parameter_dimension (ppl_const_PIP_Problem_t pip, ppl_dimension_type *pd)

  Writes into `*pd` the big parameter dimension of PIP problem `pip`.

- int ppl_PIP_Problem_number_of_constraints (ppl_const_PIP_Problem_t pip, ppl_dimension_type *m)

  Writes to `m` the number of constraints defining the feasible region of `pip`.

- int ppl_PIP_Problem_constraint_at_index (ppl_const_PIP_Problem_t pip, ppl_dimension_type i, ppl_const_Constraint_t *pc)

  Writes at address `pc` a const handle to the `i-th` constraint defining the feasible region of the PIP problem `pip`.

- int ppl_PIP_Problem_total_memory_in_bytes (ppl_const_PIP_Problem_t pip, size_t *sz)

  Writes into `*sz` the size in bytes of the memory occupied by `pip`.

- int ppl_PIP_Problem_external_memory_in_bytes (ppl_const_PIP_Problem_t pip, size_t *sz)

  Writes into `*sz` the size in bytes of the memory managed by `pip`.

- int ppl_PIP_Problem_OK (ppl_const_PIP_Problem_t pip)

  Returns a positive integer if `pip` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `pip` is broken. Useful for debugging purposes.

Functions that May Modify the PIP_Problem

- int ppl_PIP_Problem_clear (ppl_PIP_Problem_t pip)
  Resets the PIP problem to be a trivial problem of space dimension 0.

- int ppl_PIP_Problem_add_space_dimensions_and_embed (ppl_PIP_Problem_t pip, ppl_dimension_type pip_vars, ppl_dimension_type pip_params)
  Adds `pip_vars + pip_params` new space dimensions and embeds the PIP problem `pip` in the new vector space.

- int ppl_PIP_Problem_add_to_parameter_space_dimensions (ppl_PIP_Problem_t pip, ppl_dimension_type ds[ ], size_t n)
  Sets the space dimensions that are specified in first `n` positions of the array `ds` to be parameter dimensions of problem `pip`. The presence of duplicates in `ds` is a waste but an innocuous one.

- int ppl_PIP_Problem_set_big_parameter_dimension (ppl_PIP_Problem_t pip, ppl_dimension_type d)
  Sets the big parameter dimension of PIP problem `pip` to `d`.

- int ppl_PIP_Problem_add_constraint (ppl_PIP_Problem_t pip, ppl_const_Constraint_t c)
  Modifies the feasible region of the PIP problem `pip` by adding a copy of the constraint `c`.

- int ppl_PIP_Problem_add_constraints (ppl_PIP_Problem_t pip, ppl_const_Constraint_System_t cs)
  Modifies the feasible region of the PIP problem `pip` by adding a copy of the constraints in `cs`.

Computing and Printing the Solution of the PIP_Problem

- int ppl_PIP_Problem_is_satisfiable (ppl_const_PIP_Problem_t pip)
  Returns a positive integer if `pip` is satisfiable and an optimal solution can be found; returns 0 otherwise.

- int ppl_PIP_Problem_solve (ppl_const_PIP_Problem_t pip)
  Solves the PIP problem `pip`, returning an exit status.

- int ppl_PIP_Problem_solution (ppl_const_PIP_Problem_t pip, ppl_const_PIP_Tree_Node_t *pip_tree)
  Writes to `pip_tree` a solution for `pip`, if it exists.

- int ppl_PIP_Problem_optimizing_solution (ppl_const_PIP_Problem_t pip, ppl_const_PIP_Tree_Node_t *pip_tree)
  Writes to `pip_tree` an optimizing solution for `pip`, if it exists.

Querying/Setting Control Parameters

- int ppl_PIP_Problem_get_control_parameter (ppl_const_PIP_Problem_t pip, int name)
  Returns the value of control parameter `name` in problem `pip`.

- int ppl_PIP_Problem_set_control_parameter (ppl_PIP_Problem_t pip, int value)
  Sets control parameter `value` in problem `pip`.

10.21.1 Detailed Description

Types and functions for PIP problems. The types and functions for PIP problems provide an interface towards *PIP_Problem*.

10.21.2 Friends And Related Function Documentation

10.21.2.1 int ppl_assign_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t *dst*, ppl_const_PIP_Problem_t *src*) [related]

Assigns a copy of the PIP problem `src` to `dst`.

Definition at line 2180 of file ppl_c_implementation_common.cc.

10.21.2.2 int ppl_delete_PIP_Problem (ppl_const_PIP_Problem_t *pip*) [related]

Invalidates the handle `pip`: this makes sure the corresponding resources will eventually be released.

Definition at line 2190 of file ppl_c_implementation_common.cc.

10.21.2.3 int ppl_new_PIP_Problem_from_constraints (ppl_PIP_Problem_t * *ppip*, ppl_dimension_type *d*, ppl_Constraint_System_const_iterator_t *first*, ppl_Constraint_System_const_iterator_t *last*, size_t *n*, ppl_dimension_type *ds*[ ]) [related]

Builds a PIP problem having space dimension `d` from the sequence of constraints in the range $[\mathrm{first}, \mathrm{last})$; the `n` dimensions whose indices occur in `ds` are interpreted as parameters.

Definition at line 2164 of file ppl_c_implementation_common.cc.

10.21.2.4 int ppl_new_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t * *ppip*, ppl_const_PIP_Problem_t *pip*) [related]

Builds a PIP problem that is a copy of `pip`; writes a handle for the newly created problem at address `ppip`.

Definition at line 2154 of file ppl_c_implementation_common.cc.

10.21.2.5 int ppl_new_PIP_Problem_from_space_dimension (ppl_PIP_Problem_t * *ppip*, ppl_dimension_type *d*) [related]

Builds a trivial PIP problem of dimension `d` and writes a handle to it at address `ppip`.

Definition at line 2146 of file ppl_c_implementation_common.cc.

10.21.2.6 int ppl_PIP_Problem_add_constraint (ppl_PIP_Problem_t *pip*, ppl_const_Constraint_t *c*) [related]

Modifies the feasible region of the PIP problem `pip` by adding a copy of the constraint `c`.

Definition at line 2278 of file ppl_c_implementation_common.cc.

10.21.2.7 int ppl_PIP_Problem_add_constraints (ppl_PIP_Problem_t *pip*, ppl_const_Constraint_System_t *cs*) [related]

Modifies the feasible region of the PIP problem `pip` by adding a copy of the constraints in `cs`.

Definition at line 2288 of file ppl_c_implementation_common.cc.

10.21.2.8 int ppl_PIP_Problem_add_space_dimensions_and_embed (ppl_PIP_Problem_t *pip*, ppl_dimension_type *pip_vars*, ppl_dimension_type *pip_params*) [related]

Adds `pip_vars + pip_params` new space dimensions and embeds the PIP problem `pip` in the new vector space.

Parameters

pip The PIP problem to be embedded in the new vector space.

pip_vars The number of space dimensions to add that are interpreted as PIP problem variables (i.e., non parameters). These are added *before* adding the `pip_params` parameters.

pip_params The number of space dimensions to add that are interpreted as PIP problem parameters. These are added *after* having added the `pip_vars` problem variables.

The new space dimensions will be those having the highest indexes in the new PIP problem; they are initially unconstrained.

Definition at line 2256 of file ppl_c_implementation_common.cc.

10.21.2.9 int ppl_PIP_Problem_add_to_parameter_space_dimensions (ppl_PIP_Problem_t *pip*, ppl_dimension_type *ds*[ ], size_t *n*) [related]

Sets the space dimensions that are specified in first `n` positions of the array `ds` to be parameter dimensions of problem `pip`. The presence of duplicates in `ds` is a waste but an innocuous one.

Definition at line 2266 of file ppl_c_implementation_common.cc.

10.21.2.10 int ppl_PIP_Problem_clear (ppl_PIP_Problem_t *pip*) [related]

Resets the PIP problem to be a trivial problem of space dimension 0.

Definition at line 2250 of file ppl_c_implementation_common.cc.

10.21.2.11 int ppl_PIP_Problem_constraint_at_index (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type *i*, ppl_const_Constraint_t * *pc*) [related]

Writes at address `pc` a const handle to the `i-th` constraint defining the feasible region of the PIP problem `pip`.

Definition at line 2235 of file ppl_c_implementation_common.cc.

10.21.2.12 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_ALL [related]

Code of PIP problem's "all" cutting strategy.

Definition at line 2480 of file ppl_c_header.h.

10.21.2.13 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_-DEEPEST [related]

Code of PIP problem's "deepest" cutting strategy.

Definition at line 2475 of file ppl_c_header.h.

10.21.2.14 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_-FIRST [related]

Code of PIP problem's "first" cutting strategy.

Definition at line 2470 of file ppl_c_header.h.

10.21.2.15 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_CUTTING_-STRATEGY [related]

Code for the PIP problem's "cutting strategy" control parameter name.

Definition at line 2460 of file ppl_c_header.h.

10.21.2.16 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_PIVOT_ROW_-STRATEGY [related]

Code for the PIP problem's "pivot row strategy" control parameter name.

Definition at line 2465 of file ppl_c_header.h.

10.21.2.17 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_-FIRST [related]

Code of PIP problem's "first" pivot row strategy.

Definition at line 2485 of file ppl_c_header.h.

10.21.2.18 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_-MAX_COLUMN [related]

Code of PIP problem's "max column" pivot row strategy.

Definition at line 2490 of file ppl_c_header.h.

10.21.2.19 int ppl_PIP_Problem_external_memory_in_bytes (ppl_const_PIP_Problem_t *pip*, size_t * *sz*) [related]

Writes into `*sz` the size in bytes of the memory managed by `pip`.

Definition at line 2373 of file ppl_c_implementation_common.cc.

10.21.2.20 int ppl_PIP_Problem_get_big_parameter_dimension (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *pd*) [related]

Writes into `*pd` the big parameter dimension of PIP problem `pip`.

Definition at line 2349 of file ppl_c_implementation_common.cc.

10.21.2.21 int ppl_PIP_Problem_get_control_parameter (ppl_const_PIP_Problem_t *pip*, int *name*) [related]

Returns the value of control parameter `name` in problem `pip`.

Definition at line 2330 of file ppl_c_implementation_common.cc.

10.21.2.22 int ppl_PIP_Problem_is_satisfiable (ppl_const_PIP_Problem_t *pip*) [related]

Returns a positive integer if `pip` is satisfiable and an optimal solution can be found; returns 0 otherwise.

Definition at line 2297 of file ppl_c_implementation_common.cc.

10.21.2.23 int ppl_PIP_Problem_number_of_constraints (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *m*) [related]

Writes to `m` the number of constraints defining the feasible region of `pip`.

Definition at line 2226 of file ppl_c_implementation_common.cc.

Referenced by ppl_PIP_Problem_constraint_at_index().

10.21.2.24 int ppl_PIP_Problem_number_of_parameter_space_dimensions (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *m*) [related]

Writes to `m` the number of parameter space dimensions of `pip`.

Definition at line 2206 of file ppl_c_implementation_common.cc.

10.21.2.25 int ppl_PIP_Problem_OK (ppl_const_PIP_Problem_t *pip*) [related]

Returns a positive integer if `pip` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `pip` is broken. Useful for debugging purposes.

Definition at line 2324 of file ppl_c_implementation_common.cc.

10.21.2.26 int ppl_PIP_Problem_optimizing_solution (ppl_const_PIP_Problem_t *pip*, ppl_const_PIP_Tree_Node_t * *pip_tree*) [related]

Writes to `pip_tree` an optimizing solution for `pip`, if it exists.

Definition at line 2316 of file ppl_c_implementation_common.cc.

10.21.2.27 int ppl_PIP_Problem_parameter_space_dimensions (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type *ds*[ ]) [related]

Writes in the first positions of the array `ds` all the parameter space dimensions of problem `pip`. If the array is not big enough to hold all of the parameter space dimensions, the behavior is undefined.

Definition at line 2214 of file ppl_c_implementation_common.cc.

10.21.2.28 int ppl_PIP_Problem_set_big_parameter_dimension (ppl_PIP_Problem_t *pip*, ppl_dimension_type *d*) [related]

Sets the big parameter dimension of PIP problem `pip` to `d`.

Definition at line 2357 of file ppl_c_implementation_common.cc.

10.21.2.29 int ppl_PIP_Problem_set_control_parameter (ppl_PIP_Problem_t *pip*, int *value*) [related]

Sets control parameter `value` in problem `pip`.

Definition at line 2339 of file ppl_c_implementation_common.cc.

10.21.2.30 int ppl_PIP_Problem_solution (ppl_const_PIP_Problem_t *pip*, ppl_const_PIP_Tree_Node_t * *pip_tree*) [related]

Writes to `pip_tree` a solution for `pip`, if it exists.

Definition at line 2308 of file ppl_c_implementation_common.cc.

10.21.2.31 int ppl_PIP_Problem_solve (ppl_const_PIP_Problem_t *pip*) [related]

Solves the PIP problem `pip`, returning an exit status.

Returns

`PPL_PIP_PROBLEM_STATUS_UNFEASIBLE` if the PIP problem is not satisfiable; `PPL_PIP_PROBLEM_STATUS_OPTIMIZED` if the PIP problem admits an optimal solution.

Definition at line 2302 of file ppl_c_implementation_common.cc.

10.21.2.32 int ppl_PIP_Problem_space_dimension (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *m*) [related]

Writes to `m` the dimension of the vector space enclosing `pip`.

The vector space dimensions includes both the problem variables and the problem parameters, but they do not include the artificial parameters.

Definition at line 2197 of file ppl_c_implementation_common.cc.

10.21.2.33 int PPL_PIP_PROBLEM_STATUS_OPTIMIZED [related]

Code of the "optimized PIP problem" status.

Definition at line 2455 of file ppl_c_header.h.

10.21.2.34 int PPL_PIP_PROBLEM_STATUS_UNFEASIBLE [related]

Code of the "unfeasible PIP problem" status.

Definition at line 2450 of file ppl_c_header.h.

10.21.2.35 int ppl_PIP_Problem_total_memory_in_bytes (ppl_const_PIP_Problem_t *pip*, size_t * *sz*) [related]

Writes into `*sz` the size in bytes of the memory occupied by `pip`.

Definition at line 2365 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.22 ppl_PIP_Solution_Node_tag Interface Reference

Types and functions for PIP solution nodes.

`#include <ppl_c_header.h>`

Related Functions

(Note that these are not member functions.)

- int ppl_PIP_Solution_Node_get_parametric_values (ppl_const_PIP_Solution_Node_t pip_sol, ppl_dimension_type var, ppl_const_Linear_Expression_t *le)

  Writes to `le` a const pointer to the parametric expression of the values of variable `var` in solution node `pip_sol`.

10.22.1 Detailed Description

Types and functions for PIP solution nodes. The types and functions for solution nodes provide an interface towards *PIP_Solution_Node*.

10.22.2 Friends And Related Function Documentation

10.22.2.1 int ppl_PIP_Solution_Node_get_parametric_values (ppl_const_PIP_Solution_Node_t *pip_sol*, ppl_dimension_type *var*, ppl_const_Linear_Expression_t * *le*) [related]

Writes to `le` a const pointer to the parametric expression of the values of variable `var` in solution node `pip_sol`.

The linear expression assigned to `le` will only refer to (problem or artificial) parameters.

Parameters

pip_sol The solution tree node.

var The variable which is queried about.

le The returned expression for variable `var`.

Returns

PPL_ERROR_INVALID_ARGUMENT Returned if `var` is dimension-incompatible with `*this` or if `var` is a problem parameter.

Definition at line 2445 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.23 ppl_PIP_Tree_Node_tag Interface Reference

Types and functions for generic PIP tree nodes.

`#include <ppl_c_header.h>`

Related Functions

(Note that these are not member functions.)

- int ppl_PIP_Tree_Node_as_solution (ppl_const_PIP_Tree_Node_t spip_tree, ppl_const_PIP_Solution_Node_t *dpip_tree)

  Writes to `dpip_tree` the solution node if `spip_tree` is a solution node, and 0 otherwise.

- int ppl_PIP_Tree_Node_as_decision (ppl_const_PIP_Tree_Node_t spip_tree, ppl_const_PIP_Decision_Node_t *dpip_tree)

  Writes to `dpip_tree` the decision node if `spip_tree` is a decision node, and 0 otherwise.

- int ppl_PIP_Tree_Node_get_constraints (ppl_const_PIP_Tree_Node_t pip_tree, ppl_const_Constraint_System_t *pcs)

  Writes to `pcs` the local system of parameter constraints at the pip tree node `pip_tree`.

- int ppl_PIP_Tree_Node_OK (ppl_const_PIP_Tree_Node_t pip)

  Returns a positive integer if `pip_tree` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `pip_tree` is broken. Useful for debugging purposes.

- int ppl_PIP_Tree_Node_number_of_artificials (ppl_const_PIP_Tree_Node_t pip_tree, ppl_dimension_type *m)

  Writes to `m` the number of elements in the artificial parameter sequence in the pip tree node `pip_tree`.

- int ppl_PIP_Tree_Node_begin (ppl_const_PIP_Tree_Node_t pip_tree, ppl_Artificial_Parameter_Sequence_const_iterator_t pit)

  Assigns to `pit` a const iterator "pointing" to the beginning of the artificial parameter sequence in the pip tree node `pip_tree`.

- int ppl_PIP_Tree_Node_end (ppl_const_PIP_Tree_Node_t pip_tree, ppl_Artificial_Parameter_Sequence_const_iterator_t pit)

  Assigns to `pit` a const iterator "pointing" to the end of the artificial parameter sequence in the pip tree node `pip_tree`.

10.23.1 Detailed Description

Types and functions for generic PIP tree nodes. The types and functions for tree nodes provide an interface towards *PIP_Tree_Node*.

10.23.2 Friends And Related Function Documentation

10.23.2.1 int ppl_PIP_Tree_Node_as_decision (ppl_const_PIP_Tree_Node_t *spip_tree*, ppl_const_PIP_Decision_Node_t * *dpip_tree*) `[related]`

Writes to `dpip_tree` the decision node if `spip_tree` is a decision node, and 0 otherwise.

Definition at line 2389 of file ppl_c_implementation_common.cc.

10.23.2.2 int ppl_PIP_Tree_Node_as_solution (ppl_const_PIP_Tree_Node_t *spip_tree*, ppl_const_PIP_Solution_Node_t * *dpip_tree*) [related]

Writes to `dpip_tree` the solution node if `spip_tree` is a solution node, and 0 otherwise.

Definition at line 2381 of file ppl_c_implementation_common.cc.

10.23.2.3 int ppl_PIP_Tree_Node_begin (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_Artificial_Parameter_Sequence_const_iterator_t *pit*) [related]

Assigns to `pit` a const iterator "pointing" to the beginning of the artificial parameter sequence in the pip tree node `pip_tree`.

Definition at line 2423 of file ppl_c_implementation_common.cc.

10.23.2.4 int ppl_PIP_Tree_Node_end (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_Artificial_Parameter_Sequence_const_iterator_t *pit*) [related]

Assigns to `pit` a const iterator "pointing" to the end of the artificial parameter sequence in the pip tree node `pip_tree`.

Definition at line 2434 of file ppl_c_implementation_common.cc.

10.23.2.5 int ppl_PIP_Tree_Node_get_constraints (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_const_Constraint_System_t * *pcs*) [related]

Writes to `pcs` the local system of parameter constraints at the pip tree node `pip_tree`.

Definition at line 2397 of file ppl_c_implementation_common.cc.

10.23.2.6 int ppl_PIP_Tree_Node_number_of_artificials (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_dimension_type * *m*) [related]

Writes to `m` the number of elements in the artificial parameter sequence in the pip tree node `pip_tree`.

Definition at line 2413 of file ppl_c_implementation_common.cc.

10.23.2.7 int ppl_PIP_Tree_Node_OK (ppl_const_PIP_Tree_Node_t *pip*) [related]

Returns a positive integer if `pip_tree` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `pip_tree` is broken. Useful for debugging purposes.

Definition at line 2407 of file ppl_c_implementation_common.cc.

The documentation for this interface was generated from the following file:

- ppl_c_header.h

10.24 ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag Interface Reference

Types and functions for iterating on the disjuncts of a const ppl_Pointset_Powerset_C_Polyhedron_tag.

Related Functions

(Note that these are not member functions.)

Construction, Initialization and Destruction

- int ppl_new_Pointset_Powerset_C_Polyhedron_const_iterator (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t *pit)
  Builds a new 'const iterator' and writes a handle to it at address `pit`.

- int ppl_new_Pointset_Powerset_C_Polyhedron_const_iterator_from_const_iterator (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t *pit, ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t y)
  Builds a copy of `y` and writes a handle to it at address `pit`.

- int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_begin (ppl_const_Pointset_Powerset_C_Polyhedron_t ps, ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t psit)
  Assigns to `psit` a const iterator "pointing" to the beginning of the sequence of disjuncts of `ps`.

- int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_end (ppl_const_Pointset_Powerset_C_Polyhedron_t ps, ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t psit)
  Assigns to `psit` a const iterator "pointing" past the end of the sequence of disjuncts of `ps`.

- int ppl_delete_Pointset_Powerset_C_Polyhedron_const_iterator (ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t it)
  Invalidates the handle `it`: this makes sure the corresponding resources will eventually be released.

Dereferencing, Increment, Decrement and Equality Testing

- int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_dereference (ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t it, ppl_const_Polyhedron_t *d)
  Dereferences `it` writing a const handle to the resulting disjunct at address `d`.

- int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_increment (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t it)
  Increments `it` so that it "points" to the next disjunct.

- int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_decrement (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t it)

Decrements `it` so that it "points" to the previous disjunct.

- int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_equal_test (ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t x, ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t y)

  Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

10.24.1 Detailed Description

Types and functions for iterating on the disjuncts of a const ppl_Pointset_Powerset_C_Polyhedron_tag.

10.24.2 Friends And Related Function Documentation

10.24.2.1 int ppl_delete_Pointset_Powerset_C_Polyhedron_const_iterator (ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t *it*) `[related]`

Invalidates the handle `it`: this makes sure the corresponding resources will eventually be released.

10.24.2.2 int ppl_new_Pointset_Powerset_C_Polyhedron_const_iterator (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t * *pit*) `[related]`

Builds a new 'const iterator' and writes a handle to it at address `pit`.

10.24.2.3 int ppl_new_Pointset_Powerset_C_Polyhedron_const_iterator_from_const_iterator (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t * *pit*, ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t *y*) `[related]`

Builds a copy of `y` and writes a handle to it at address `pit`.

10.24.2.4 int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_begin (ppl_const_Pointset_Powerset_C_Polyhedron_t *ps*, ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t *psit*) `[related]`

Assigns to `psit` a const iterator "pointing" to the beginning of the sequence of disjuncts of `ps`.

10.24.2.5 int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_decrement (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t *it*) `[related]`

Decrements `it` so that it "points" to the previous disjunct.

10.24.2.6 int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_dereference (ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t *it*, ppl_const_Polyhedron_t * *d*) [related]

Dereferences `it` writing a const handle to the resulting disjunct at address `d`.

Warning

On exit, the disjunct `d` is still owned by the powerset object: any function call on the owning powerset object may invalidate it. Moreover, `d` should **not** be deleted directly: its resources will be released when deleting the owning powerset.

10.24.2.7 int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_end (ppl_const_Pointset_Powerset_C_Polyhedron_t *ps*, ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t *psit*) [related]

Assigns to `psit` a const iterator "pointing" past the end of the sequence of disjuncts of `ps`.

10.24.2.8 int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_equal_test (ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t *x*, ppl_const_Pointset_Powerset_C_Polyhedron_const_iterator_t *y*) [related]

Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

10.24.2.9 int ppl_Pointset_Powerset_C_Polyhedron_const_iterator_increment (ppl_Pointset_Powerset_C_Polyhedron_const_iterator_t *it*) [related]

Increments `it` so that it "points" to the next disjunct.

The documentation for this interface was generated from the following file:

- C_interface.dox

10.25 ppl_Pointset_Powerset_C_Polyhedron_iterator_tag Interface Reference

Types and functions for iterating on the disjuncts of a ppl_Pointset_Powerset_C_Polyhedron_tag.

Related Functions

(Note that these are not member functions.)

Construction, Initialization and Destruction

- int ppl_new_Pointset_Powerset_C_Polyhedron_iterator (ppl_Pointset_Powerset_C_Polyhedron_iterator_t *pit)

Builds a new 'iterator' and writes a handle to it at address `pit`.

- int ppl_new_Pointset_Powerset_C_Polyhedron_iterator_from_iterator (ppl_Pointset_Powerset_C_Polyhedron_iterator_t *pit, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t y)

  Builds a copy of `y` *and writes a handle to it at address* `pit`.

- int ppl_Pointset_Powerset_C_Polyhedron_iterator_begin (ppl_Pointset_Powerset_C_Polyhedron_t ps, ppl_Pointset_Powerset_C_Polyhedron_iterator_t psit)

  Assigns to `psit` *an iterator "pointing" to the beginning of the sequence of disjuncts of* `ps`.

- int ppl_Pointset_Powerset_C_Polyhedron_iterator_end (ppl_Pointset_Powerset_C_Polyhedron_t ps, ppl_Pointset_Powerset_C_Polyhedron_iterator_t psit)

  Assigns to `psit` *an iterator "pointing" past the end of the sequence of disjuncts of* `ps`.

- int ppl_delete_Pointset_Powerset_C_Polyhedron_iterator (ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t it)

  Invalidates the handle `it`*: this makes sure the corresponding resources will eventually be released.*

Dereferencing, Increment, Decrement and Equality Testing

- int ppl_Pointset_Powerset_C_Polyhedron_iterator_dereference (ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t it, ppl_const_Polyhedron_t *d)

  Dereferences `it` *writing a const handle to the resulting disjunct at address* `d`.

- int ppl_Pointset_Powerset_C_Polyhedron_iterator_increment (ppl_Pointset_Powerset_C_Polyhedron_iterator_t it)

  Increments `it` *so that it "points" to the next disjunct.*

- int ppl_Pointset_Powerset_C_Polyhedron_iterator_decrement (ppl_Pointset_Powerset_C_Polyhedron_iterator_t it)

  Decrements `it` *so that it "points" to the previous disjunct.*

- int ppl_Pointset_Powerset_C_Polyhedron_iterator_equal_test (ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t x, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t y)

  Returns a positive integer if the iterators corresponding to `x` *and* `y` *are equal; returns 0 if they are different.*

10.25.1 Detailed Description

Types and functions for iterating on the disjuncts of a ppl_Pointset_Powerset_C_Polyhedron_tag.

10.25.2 Friends And Related Function Documentation

10.25.2.1 int ppl_delete_Pointset_Powerset_C_Polyhedron_iterator (ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *it*) `[related]`

Invalidates the handle `it`: this makes sure the corresponding resources will eventually be released.

10.25.2.2 int ppl_new_Pointset_Powerset_C_Polyhedron_iterator (ppl_Pointset_Powerset_C_-Polyhedron_iterator_t * *pit*) [related]

Builds a new 'iterator' and writes a handle to it at address `pit`.

10.25.2.3 int ppl_new_Pointset_Powerset_C_Polyhedron_iterator_from_-iterator (ppl_Pointset_Powerset_C_Polyhedron_iterator_t * *pit*, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *y*) [related]

Builds a copy of `y` and writes a handle to it at address `pit`.

10.25.2.4 int ppl_Pointset_Powerset_C_Polyhedron_iterator_begin (ppl_Pointset_Powerset_-C_Polyhedron_t *ps*, ppl_Pointset_Powerset_C_Polyhedron_iterator_t *psit*) [related]

Assigns to `psit` an iterator "pointing" to the beginning of the sequence of disjuncts of `ps`.

10.25.2.5 int ppl_Pointset_Powerset_C_Polyhedron_iterator_decrement (ppl_Pointset_Powerset_C_Polyhedron_iterator_t *it*) [related]

Decrements `it` so that it "points" to the previous disjunct.

10.25.2.6 int ppl_Pointset_Powerset_C_Polyhedron_iterator_dereference (ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *it*, ppl_const_Polyhedron_t * *d*) [related]

Dereferences `it` writing a const handle to the resulting disjunct at address `d`.

Note

Even though `it` is an non-const iterator, dereferencing it results in a handle to a **const** disjunct. This is because mutable iterators are meant to allow for the modification of the sequence of disjuncts (e.g., by dropping elements), while preventing direct modifications of the disjuncts they point to.

Warning

On exit, the disjunct `d` is still owned by the powerset object: any function call on the owning powerset object may invalidate it. Moreover, `d` should **not** be deleted directly: its resources will be released when deleting the owning powerset.

10.25.2.7 int ppl_Pointset_Powerset_C_Polyhedron_iterator_end (ppl_Pointset_Powerset_C_Polyhedron_t *ps*, ppl_Pointset_Powerset_C_Polyhedron_iterator_t *psit*) [related]

Assigns to `psit` an iterator "pointing" past the end of the sequence of disjuncts of `ps`.

10.25.2.8 int ppl_Pointset_Powerset_C_Polyhedron_iterator_equal_test (ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *x*, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *y*) [related]

Returns a positive integer if the iterators corresponding to `x` and `y` are equal; returns 0 if they are different.

10.25.2.9 int ppl_Pointset_Powerset_C_Polyhedron_iterator_increment (ppl_Pointset_Powerset_C_Polyhedron_iterator_t *it*) [related]

Increments `it` so that it "points" to the next disjunct.

The documentation for this interface was generated from the following file:

- C_interface.dox

10.26 ppl_Pointset_Powerset_C_Polyhedron_tag Interface Reference

Types and functions for the Pointset_Powerset of C_Polyhedron objects.

Related Functions

(Note that these are not member functions.)

Ad Hoc Functions for Pointset_Powerset domains

- int ppl_Pointset_Powerset_C_Polyhedron_omega_reduce (ppl_const_Pointset_Powerset_C_Polyhedron_t ps)

  Drops from the sequence of disjuncts in `ps` all the non-maximal elements so that `ps` is non-redundant.

- int ppl_Pointset_Powerset_C_Polyhedron_size (ppl_const_Pointset_Powerset_C_Polyhedron_t ps, size_t *sz)

  Writes to `sz` the number of disjuncts in `ps`.

- int ppl_Pointset_Powerset_C_Polyhedron_geometrically_covers_Pointset_Powerset_C_Polyhedron (ppl_const_Pointset_Powerset_C_Polyhedron_t x, ppl_const_Pointset_Powerset_C_Polyhedron_t y)

  Returns a positive integer if powerset `x` geometrically covers powerset `y`; returns 0 otherwise.

- int ppl_Pointset_Powerset_C_Polyhedron_geometrically_equals_Pointset_Powerset_C_Polyhedron (ppl_const_Pointset_Powerset_C_Polyhedron_t x, ppl_const_Pointset_Powerset_C_Polyhedron_t y)

Returns a positive integer if powerset `x` *is geometrically equal to powerset* `y`*; returns 0 otherwise.*

- int ppl_Pointset_Powerset_C_Polyhedron_add_disjunct (ppl_Pointset_Powerset_C_Polyhedron_t ps, ppl_const_Polyhedron_t d)

  Adds to `ps` *a copy of disjunct* `d`*.*

- int ppl_Pointset_Powerset_C_Polyhedron_drop_disjunct (ppl_Pointset_Powerset_C_Polyhedron_t ps, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t cit, ppl_Pointset_Powerset_C_Polyhedron_iterator_t it)

  Drops from `ps` *the disjunct pointed to by* `cit`*, assigning to* `it` *an iterator to the disjunct following* `cit`*.*

- int ppl_Pointset_Powerset_C_Polyhedron_drop_disjuncts (ppl_Pointset_Powerset_C_Polyhedron_t ps, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t first, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t last)

  Drops from `ps` *all the disjuncts from* `first` *to* `last` *(excluded).*

- int ppl_Pointset_Powerset_C_Polyhedron_pairwise_reduce (ppl_Pointset_Powerset_C_Polyhedron_t ps)

  Modifies `ps` *by (recursively) merging together the pairs of disjuncts whose upper-bound is the same as their set-theoretical union.*

10.26.1 Detailed Description

Types and functions for the Pointset_Powerset of C_Polyhedron objects. The powerset domains can be instantiated by taking as a base domain any fixed semantic geometric description (C and NNC polyhedra, BD and octagonal shapes, boxes and grids). An element of the powerset domain represents a disjunctive collection of base objects (its disjuncts), all having the same space dimension.

Besides the functions that are available in all semantic geometric descriptions (whose documentation is not repeated here), the powerset domain also provides several ad hoc functions. In particular, the iterator types allow for the examination and manipulation of the collection of disjuncts.

10.26.2 Friends And Related Function Documentation

10.26.2.1 int ppl_Pointset_Powerset_C_Polyhedron_add_disjunct (ppl_Pointset_Powerset_C_Polyhedron_t *ps*, ppl_const_Polyhedron_t *d*) `[related]`

Adds to `ps` a copy of disjunct `d`.

10.26.2.2 int ppl_Pointset_Powerset_C_Polyhedron_drop_disjunct (ppl_Pointset_Powerset_C_Polyhedron_t *ps*, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *cit*, ppl_Pointset_Powerset_C_Polyhedron_iterator_t *it*) `[related]`

Drops from `ps` the disjunct pointed to by `cit`, assigning to `it` an iterator to the disjunct following `cit`.

10.26.2.3 int ppl_Pointset_Powerset_C_Polyhedron_drop_disjuncts (ppl_Pointset_Powerset_C_Polyhedron_t *ps*, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *first*, ppl_const_Pointset_Powerset_C_Polyhedron_iterator_t *last*) `[related]`

Drops from `ps` all the disjuncts from `first` to `last` (excluded).

10.26.2.4 int ppl_Pointset_Powerset_C_Polyhedron_geometrically_covers_Pointset_Powerset_C_Polyhedron (ppl_const_Pointset_Powerset_C_Polyhedron_t *x*, ppl_const_Pointset_Powerset_C_Polyhedron_t *y*) `[related]`

Returns a positive integer if powerset `x` geometrically covers powerset `y`; returns 0 otherwise.

10.26.2.5 int ppl_Pointset_Powerset_C_Polyhedron_geometrically_equals_Pointset_Powerset_C_Polyhedron (ppl_const_Pointset_Powerset_C_Polyhedron_t *x*, ppl_const_Pointset_Powerset_C_Polyhedron_t *y*) `[related]`

Returns a positive integer if powerset `x` is geometrically equal to powerset `y`; returns 0 otherwise.

10.26.2.6 int ppl_Pointset_Powerset_C_Polyhedron_omega_reduce (ppl_const_Pointset_Powerset_C_Polyhedron_t *ps*) `[related]`

Drops from the sequence of disjuncts in `ps` all the non-maximal elements so that `ps` is non-redundant.

10.26.2.7 int ppl_Pointset_Powerset_C_Polyhedron_pairwise_reduce (ppl_Pointset_Powerset_C_Polyhedron_t *ps*) `[related]`

Modifies `ps` by (recursively) merging together the pairs of disjuncts whose upper-bound is the same as their set-theoretical union.

10.26.2.8 int ppl_Pointset_Powerset_C_Polyhedron_size (ppl_const_Pointset_Powerset_C_Polyhedron_t *ps*, size_t * *sz*) `[related]`

Writes to `sz` the number of disjuncts in `ps`.

Note

If present, Omega-redundant elements will be counted too.

The documentation for this interface was generated from the following file:

- C_interface.dox

10.27 ppl_Polyhedron_tag Interface Reference

Types and functions for the domains of C and NNC convex polyhedra.

Related Functions

(Note that these are not member functions.)

Constructors and Assignment for C_Polyhedron

- int ppl_new_C_Polyhedron_from_space_dimension (ppl_Polyhedron_t *pph, ppl_dimension_type d, int empty)

  Builds a C polyhedron of dimension `d` *and writes an handle to it at address* `pph`*. If* `empty` *is different from zero, the newly created polyhedron will be empty; otherwise, it will be a universe polyhedron.*

- int ppl_new_C_Polyhedron_from_C_Polyhedron (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph)

  Builds a C polyhedron that is a copy of `ph`*; writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_C_Polyhedron_from_C_Polyhedron_with_complexity (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph, int complexity)

  Builds a C polyhedron that is a copy of `ph`*; writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_C_Polyhedron_from_Constraint_System (ppl_Polyhedron_t *pph, ppl_const_Constraint_System_t cs)

  Builds a new C polyhedron from the system of constraints `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_C_Polyhedron_recycle_Constraint_System (ppl_Polyhedron_t *pph, ppl_Constraint_System_t cs)

  Builds a new C polyhedron recycling the system of constraints `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_C_Polyhedron_from_Congruence_System (ppl_Polyhedron_t *pph, ppl_const_Congruence_System_t cs)

  Builds a new C polyhedron from the system of congruences `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_C_Polyhedron_recycle_Congruence_System (ppl_Polyhedron_t *pph, ppl_Congruence_System_t cs)

  Builds a new C polyhedron recycling the system of congruences `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_assign_C_Polyhedron_from_C_Polyhedron (ppl_Polyhedron_t dst, ppl_const_Polyhedron_t src)

  Assigns a copy of the C polyhedron `src` *to the C polyhedron* `dst`*.*

Constructors and Assignment for NNC_Polyhedron

- int ppl_new_NNC_Polyhedron_from_space_dimension (ppl_Polyhedron_t *pph, ppl_dimension_type d, int empty)

Builds an NNC polyhedron of dimension `d` *and writes an handle to it at address* `pph`*. If* `empty` *is different from zero, the newly created polyhedron will be empty; otherwise, it will be a universe polyhedron.*

- int ppl_new_NNC_Polyhedron_from_NNC_Polyhedron (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph)

  Builds an NNC polyhedron that is a copy of `ph`*; writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_NNC_Polyhedron_from_NNC_Polyhedron_with_complexity (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph, int complexity)

  Builds an NNC polyhedron that is a copy of `ph`*; writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_NNC_Polyhedron_from_Constraint_System (ppl_Polyhedron_t *pph, ppl_const_Constraint_System_t cs)

  Builds a new NNC polyhedron from the system of constraints `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_NNC_Polyhedron_recycle_Constraint_System (ppl_Polyhedron_t *pph, ppl_Constraint_System_t cs)

  Builds a new NNC polyhedron recycling the system of constraints `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_NNC_Polyhedron_from_Congruence_System (ppl_Polyhedron_t *pph, ppl_const_Congruence_System_t cs)

  Builds a new NNC polyhedron from the system of congruences `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_NNC_Polyhedron_recycle_Congruence_System (ppl_Polyhedron_t *pph, ppl_Congruence_System_t cs)

  Builds a new NNC polyhedron recycling the system of congruences `cs` *and writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_assign_NNC_Polyhedron_from_NNC_Polyhedron (ppl_Polyhedron_t dst, ppl_const_Polyhedron_t src)

  Assigns a copy of the NNC polyhedron `src` *to the NNC polyhedron* `dst`*.*

Constructors Behaving as Conversion Operators

Besides the conversions listed here below, the library also provides conversion operators that build a semantic geometric description starting from ***any*** *other semantic geometric description (e.g., ppl_new_Grid_from_C_Polyhedron, ppl_new_C_Polyhedron_from_BD_Shape_mpq_class, etc.). Clearly, the conversion operators are only available if both the source and the target semantic geometric descriptions have been enabled when configuring the library. The conversions also taking as argument a complexity class sometimes provide non-trivial precision/efficiency trade-offs.*

- int ppl_new_C_Polyhedron_from_NNC_Polyhedron (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph)

  Builds a C polyhedron that is a copy of the topological closure of the NNC polyhedron `ph`*; writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_C_Polyhedron_from_NNC_Polyhedron_with_complexity (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph, int complexity)

  Builds a C polyhedron that approximates NNC_Polyhedron `ph`*, using an algorithm whose complexity does not exceed* `complexity`*; writes a handle for the newly created polyhedron at address* `pph`*.*

- int ppl_new_NNC_Polyhedron_from_C_Polyhedron (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph)

  Builds an NNC polyhedron that is a copy of the C polyhedron `ph`; writes a handle for the newly created polyhedron at address `pph`.

- int ppl_new_NNC_Polyhedron_from_C_Polyhedron_with_complexity (ppl_Polyhedron_t *pph, ppl_const_Polyhedron_t ph, int complexity)

  Builds an NNC polyhedron that approximates C_Polyhedron `ph`, using an algorithm whose complexity does not exceed `complexity`; writes a handle for the newly created polyhedron at address `pph`.

Destructor for (C or NNC) Polyhedra

- int ppl_delete_Polyhedron (ppl_const_Polyhedron_t ph)

  Invalidates the handle `ph`: this makes sure the corresponding resources will eventually be released.

Functions that Do Not Modify the Polyhedron

- int ppl_Polyhedron_space_dimension (ppl_const_Polyhedron_t ph, ppl_dimension_type *m)

  Writes to `m` the dimension of the vector space enclosing `ph`.

- int ppl_Polyhedron_affine_dimension (ppl_const_Polyhedron_t ph, ppl_dimension_type *m)

  Writes to `m` the affine dimension of `ph` (not to be confused with the dimension of its enclosing vector space) or 0, if `ph` is empty.

- int ppl_Polyhedron_relation_with_Constraint (ppl_const_Polyhedron_t ph, ppl_const_Constraint_t c)

  Checks the relation between the polyhedron `ph` and the constraint `c`.

- int ppl_Polyhedron_relation_with_Generator (ppl_const_Polyhedron_t ph, ppl_const_Generator_t g)

  Checks the relation between the polyhedron `ph` and the generator `g`.

- int ppl_Polyhedron_get_constraints (ppl_const_Polyhedron_t ph, ppl_const_Constraint_System_t *pcs)

  Writes a const handle to the constraint system defining the polyhedron `ph` at address `pcs`.

- int ppl_Polyhedron_get_congruences (ppl_const_Polyhedron_t ph, ppl_const_Congruence_System_t *pcs)

  Writes at address `pcs` a const handle to a system of congruences approximating the polyhedron `ph`.

- int ppl_Polyhedron_get_minimized_constraints (ppl_const_Polyhedron_t ph, ppl_const_Constraint_System_t *pcs)

  Writes a const handle to the minimized constraint system defining the polyhedron `ph` at address `pcs`.

- int ppl_Polyhedron_get_minimized_congruences (ppl_const_Polyhedron_t ph, ppl_const_Congruence_System_t *pcs)

  Writes at address `pcs` a const handle to a system of minimized congruences approximating the polyhedron `ph`.

- int ppl_Polyhedron_is_empty (ppl_const_Polyhedron_t ph)

  Returns a positive integer if `ph` is empty; returns 0 if `ph` is not empty.

- int ppl_Polyhedron_is_universe (ppl_const_Polyhedron_t ph)
  Returns a positive integer if `ph` is a universe polyhedron; returns 0 if it is not.

- int ppl_Polyhedron_is_bounded (ppl_const_Polyhedron_t ph)
  Returns a positive integer if `ph` is bounded; returns 0 if `ph` is unbounded.

- int ppl_Polyhedron_contains_integer_point (ppl_const_Polyhedron_t ph)
  Returns a positive integer if `ph` contains at least one integer point; returns 0 otherwise.

- int ppl_Polyhedron_is_topologically_closed (ppl_const_Polyhedron_t ph)
  Returns a positive integer if `ph` is topologically closed; returns 0 if `ph` is not topologically closed.

- int ppl_Polyhedron_is_discrete (ppl_const_Polyhedron_t ph)
  Returns a positive integer if `ph` is a discrete set; returns 0 if `ph` is not a discrete set.

- int ppl_Polyhedron_constrains (ppl_Polyhedron_t ph, ppl_dimension_type var)
  Returns a positive integer if `ph` constrains `var`; returns 0 if `ph` does not constrain `var`.

- int ppl_Polyhedron_bounds_from_above (ppl_const_Polyhedron_t ph, ppl_const_Linear_Expression_t le)
  Returns a positive integer if `le` is bounded from above in `ph`; returns 0 otherwise.

- int ppl_Polyhedron_bounds_from_below (ppl_const_Polyhedron_t ph, ppl_const_Linear_Expression_t le)
  Returns a positive integer if `le` is bounded from below in `ph`; returns 0 otherwise.

- int ppl_Polyhedron_maximize_with_point (ppl_const_Polyhedron_t ph, ppl_const_Linear_Expression_t le, ppl_Coefficient_t sup_n, ppl_Coefficient_t sup_d, int *pmaximum, ppl_Generator_t point)
  Returns a positive integer if `ph` is not empty and `le` is bounded from above in `ph`, in which case the supremum value and a point where `le` reaches it are computed.

- int ppl_Polyhedron_maximize (ppl_const_Polyhedron_t ph, ppl_const_Linear_Expression_t le, ppl_Coefficient_t sup_n, ppl_Coefficient_t sup_d, int *pmaximum)
  The same as ppl_Polyhedron_maximize_with_point, but without the output argument for the location where the supremum value is reached.

- int ppl_Polyhedron_minimize_with_point (ppl_const_Polyhedron_t ph, ppl_const_Linear_Expression_t le, ppl_Coefficient_t inf_n, ppl_Coefficient_t inf_d, int *pminimum, ppl_Generator_t point)
  Returns a positive integer if `ph` is not empty and `le` is bounded from below in `ph`, in which case the infimum value and a point where `le` reaches it are computed.

- int ppl_Polyhedron_minimize_with_point (ppl_const_Polyhedron_t ph, ppl_const_Linear_Expression_t le, ppl_Coefficient_t inf_n, ppl_Coefficient_t inf_d, int *pminimum)
  The same as ppl_Polyhedron_minimize_with_point, but without the output argument for the location where the infimum value is reached.

- int ppl_Polyhedron_contains_Polyhedron (ppl_const_Polyhedron_t x, ppl_const_Polyhedron_t y)
  Returns a positive integer if `x` contains or is equal to `y`; returns 0 if it does not.

- int ppl_Polyhedron_strictly_contains_Polyhedron (ppl_const_Polyhedron_t x, ppl_const_Polyhedron_t y)
  Returns a positive integer if `x` strictly contains `y`; returns 0 if it does not.

- int ppl_Polyhedron_is_disjoint_from_Polyhedron (ppl_const_Polyhedron_t x, ppl_const_Polyhedron_t y)
  Returns a positive integer if `x` and `y` are disjoint; returns 0 if they are not.

- int ppl_Polyhedron_equals_Polyhedron (ppl_const_Polyhedron_t x, ppl_const_Polyhedron_t y)
  Returns a positive integer if `x` and `y` are the same polyhedron; returns 0 if they are different.

- int ppl_Polyhedron_OK (ppl_const_Polyhedron_t ph)
  Returns a positive integer if `ph` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `ph` is broken. Useful for debugging purposes.

- int ppl_Polyhedron_external_memory_in_bytes (ppl_const_Polyhedron_t ph, size_t *sz)
  Writes to `sz` a lower bound to the size in bytes of the memory managed by `ph`.

- int ppl_Polyhedron_total_memory_in_bytes (ppl_const_Polyhedron_t ph, size_t *sz)
  Writes to `sz` a lower bound to the size in bytes of the memory managed by `ph`.

Space Dimension Preserving Functions that May Modify the Polyhedron

- int ppl_Polyhedron_add_constraint (ppl_Polyhedron_t ph, ppl_const_Constraint_t c)
  Adds a copy of the constraint `c` to the system of constraints of `ph`.

- int ppl_Polyhedron_add_congruence (ppl_Polyhedron_t ph, ppl_const_Congruence_t c)
  Adds a copy of the congruence `c` to polyhedron of `ph`.

- int ppl_Polyhedron_add_constraints (ppl_Polyhedron_t ph, ppl_const_Constraint_System_t cs)
  Adds a copy of the system of constraints `cs` to the system of constraints of `ph`.

- int ppl_Polyhedron_add_congruences (ppl_Polyhedron_t ph, ppl_const_Congruence_System_t cs)
  Adds a copy of the system of congruences `cs` to the polyhedron `ph`.

- int ppl_Polyhedron_add_recycled_constraints (ppl_Polyhedron_t ph, ppl_Constraint_System_t cs)
  Adds the system of constraints `cs` to the system of constraints of `ph`.

- int ppl_Polyhedron_add_recycled_congruences (ppl_Polyhedron_t ph, ppl_Congruence_System_t cs)
  Adds the system of congruences `cs` to the polyhedron `ph`.

- int ppl_Polyhedron_refine_with_constraint (ppl_Polyhedron_t ph, ppl_const_Constraint_t c)
  Refines `ph` using constraint `c`.

- int ppl_Polyhedron_refine_with_congruence (ppl_Polyhedron_t ph, ppl_const_Congruence_t c)
  Refines `ph` using congruence `c`.

- int ppl_Polyhedron_refine_with_constraints (ppl_Polyhedron_t ph, ppl_const_Constraint_System_t cs)
  Refines `ph` using the constraints in `cs`.

- int ppl_Polyhedron_refine_with_congruences (ppl_Polyhedron_t ph, ppl_const_Congruence_System_t cs)

Refines `ph` *using the congruences in* `cs`.

- int ppl_Polyhedron_intersection_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Intersects `x` *with polyhedron* `y` *and assigns the result to* `x`.

- int ppl_Polyhedron_upper_bound_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Assigns to `x` *an upper bound of* `x` *and* `y`.

- int ppl_Polyhedron_difference_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Same as ppl_Polyhedron_poly_difference_assign(x, y).

- int ppl_Polyhedron_simplify_using_context_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Assigns to `x` *the meet-preserving simplification of* `x` *with respect to context* `y`. *Returns a positive integer if* `x` *and* `y` *have a nonempty intersection; returns* `0` *if they are disjoint.*

- int ppl_Polyhedron_time_elapse_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Assigns to `x` *the time-elapse between the polyhedra* `x` *and* `y`.

- int ppl_Polyhedron_topological_closure_assign (ppl_Polyhedron_t ph)

  Assigns to `ph` *its topological closure.*

- int ppl_Polyhedron_unconstrain_space_dimension (ppl_Polyhedron_t ph, ppl_dimension_type var)

  Modifies `ph` *by unconstraining the space dimension* `var`.

- int ppl_Polyhedron_unconstrain_space_dimensions (ppl_Polyhedron_t ph, ppl_dimension_type ds[ ], size_t n)

  Modifies `ph` *by unconstraining the space dimensions that are specified in the first* `n` *positions of the array* `ds`. *The presence of duplicates in* `ds` *is a waste but an innocuous one.*

- int ppl_Polyhedron_affine_image (ppl_Polyhedron_t ph, ppl_dimension_type var, ppl_const_Linear_Expression_t le, ppl_const_Coefficient_t d)

  Transforms the polyhedron `ph`, *assigning an affine expression to the specified variable.*

- int ppl_Polyhedron_affine_preimage (ppl_Polyhedron_t ph, ppl_dimension_type var, ppl_const_Linear_Expression_t le, ppl_const_Coefficient_t d)

  Transforms the polyhedron `ph`, *substituting an affine expression to the specified variable.*

- int ppl_Polyhedron_bounded_affine_image (ppl_Polyhedron_t ph, ppl_dimension_type var, ppl_const_Linear_Expression_t lb, ppl_const_Linear_Expression_t ub, ppl_const_Coefficient_t d)

  Assigns to `ph` *the image of* `ph` *with respect to the generalized affine transfer relation* $\frac{\mathrm{lb}}{\mathrm{d}} \leq \mathrm{var}' \leq \frac{\mathrm{ub}}{\mathrm{d}}$.

- int ppl_Polyhedron_bounded_affine_preimage (ppl_Polyhedron_t ph, ppl_dimension_type var, ppl_const_Linear_Expression_t lb, ppl_const_Linear_Expression_t ub, ppl_const_Coefficient_t d)

  Assigns to `ph` *the preimage of* `ph` *with respect to the generalized affine transfer relation* $\frac{\mathrm{lb}}{\mathrm{d}} \leq \mathrm{var}' \leq \frac{\mathrm{ub}}{\mathrm{d}}$.

- int ppl_Polyhedron_generalized_affine_image (ppl_Polyhedron_t ph, ppl_dimension_type var, enum ppl_enum_Constraint_Type relsym, ppl_const_Linear_Expression_t le, ppl_const_Coefficient_t d)

  Assigns to `ph` *the image of* `ph` *with respect to the generalized affine transfer relation* $\mathrm{var}' \bowtie \frac{\mathrm{le}}{\mathrm{d}}$, *where* $\bowtie$ *is the relation symbol encoded by* `relsym`.

- int ppl_Polyhedron_generalized_affine_preimage (ppl_Polyhedron_t ph, ppl_dimension_type var, enum ppl_enum_Constraint_Type relsym, ppl_const_Linear_Expression_t le, ppl_const_-Coefficient_t d)

  Assigns to `ph` *the preimage of* `ph` *with respect to the generalized affine transfer relation* $\mathrm{var}' \bowtie \frac{\mathrm{le}}{\mathrm{d}}$, *where* $\bowtie$ *is the relation symbol encoded by* `relsym`.

- int ppl_Polyhedron_generalized_affine_image_lhs_rhs (ppl_Polyhedron_t ph, ppl_const_-Linear_Expression_t lhs, enum ppl_enum_Constraint_Type relsym, ppl_const_Linear_-Expression_t rhs)

  Assigns to `ph` *the image of* `ph` *with respect to the generalized affine transfer relation* $\mathrm{lhs}' \bowtie \mathrm{rhs}$, *where* $\bowtie$ *is the relation symbol encoded by* `relsym`.

- int ppl_Polyhedron_generalized_affine_preimage_lhs_rhs (ppl_Polyhedron_t ph, ppl_const_-Linear_Expression_t lhs, enum ppl_enum_Constraint_Type relsym, ppl_const_Linear_-Expression_t rhs)

  Assigns to `ph` *the preimage of* `ph` *with respect to the generalized affine transfer relation* $\mathrm{lhs}' \bowtie \mathrm{rhs}$, *where* $\bowtie$ *is the relation symbol encoded by* `relsym`.

Functions that May Modify the Dimension of the Vector Space

- int ppl_Polyhedron_concatenate_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Seeing a polyhedron as a set of tuples (its points), assigns to `x` *all the tuples that can be obtained by concatenating, in the order given, a tuple of* `x` *with a tuple of* `y`.

- int ppl_Polyhedron_add_space_dimensions_and_embed (ppl_Polyhedron_t ph, ppl_dimension_-type d)

  Adds `d` *new dimensions to the space enclosing the polyhedron* `ph` *and to* `ph` *itself.*

- int ppl_Polyhedron_add_space_dimensions_and_project (ppl_Polyhedron_t ph, ppl_dimension_-type d)

  Adds `d` *new dimensions to the space enclosing the polyhedron* `ph`.

- int ppl_Polyhedron_remove_space_dimensions (ppl_Polyhedron_t ph, ppl_dimension_type ds[ ], size_t n)

  Removes from the vector space enclosing `ph` *the space dimensions that are specified in first* `n` *positions of the array* `ds`. *The presence of duplicates in* `ds` *is a waste but an innocuous one.*

- int ppl_Polyhedron_remove_higher_space_dimensions (ppl_Polyhedron_t ph, ppl_dimension_-type d)

  Removes the higher dimensions from the vector space enclosing `ph` *so that, upon successful return, the new space dimension is* `d`.

- int ppl_Polyhedron_map_space_dimensions (ppl_Polyhedron_t ph, ppl_dimension_type maps[ ], size_t n)

  Remaps the dimensions of the vector space according to a partial function. This function is specified by means of the `maps` *array, which has* `n` *entries.*

- int ppl_Polyhedron_expand_space_dimension (ppl_Polyhedron_t ph, ppl_dimension_type d, ppl_dimension_type m)

  Expands the d-th dimension of the vector space enclosing `ph` *to* `m` *new space dimensions.*

- int ppl_Polyhedron_fold_space_dimensions (ppl_Polyhedron_t ph, ppl_dimension_type ds[ ], size_t n, ppl_dimension_type d)

  Modifies `ph` *by folding the space dimensions contained in the first* `n` *positions of the array* `ds` *into dimension* `d`. *The presence of duplicates in* `ds` *is a waste but an innocuous one.*

Input/Output Functions

- int ppl_io_print_Polyhedron (ppl_const_Polyhedron_t x)
  Prints x to stdout.
- int ppl_io_fprint_Polyhedron (FILE *stream, ppl_const_Polyhedron_t x)
  Prints x to the given output stream.
- int ppl_io_asprint_Polyhedron (char **strp, ppl_const_Polyhedron_t x)
  Prints x to a malloc-allocated string, a pointer to which is returned via strp.
- int ppl_Polyhedron_ascii_dump (ppl_const_Polyhedron_t x, FILE *stream)
  Dumps an ascii representation of x on stream.
- int ppl_Polyhedron_ascii_load (ppl_Polyhedron_t x, FILE *stream)
  Loads an ascii representation of x from stream.

Ad Hoc Functions for (C or NNC) Polyhedra

The functions listed here below, being specific of the polyhedron domains, do not have a correspondence in other semantic geometric descriptions.

- int ppl_new_C_Polyhedron_from_Generator_System (ppl_Polyhedron_t *pph, ppl_const_Generator_System_t gs)
  Builds a new C polyhedron from the system of generators gs and writes a handle for the newly created polyhedron at address pph.
- int ppl_new_C_Polyhedron_recycle_Generator_System (ppl_Polyhedron_t *pph, ppl_Generator_System_t gs)
  Builds a new C polyhedron recycling the system of generators gs and writes a handle for the newly created polyhedron at address pph.
- int ppl_new_NNC_Polyhedron_from_Generator_System (ppl_Polyhedron_t *pph, ppl_const_Generator_System_t gs)
  Builds a new NNC polyhedron from the system of generators gs and writes a handle for the newly created polyhedron at address pph.
- int ppl_new_NNC_Polyhedron_recycle_Generator_System (ppl_Polyhedron_t *pph, ppl_Generator_System_t gs)
  Builds a new NNC polyhedron recycling the system of generators gs and writes a handle for the newly created polyhedron at address pph.
- int ppl_Polyhedron_get_generators (ppl_const_Polyhedron_t ph, ppl_const_Generator_System_t *pgs)
  Writes a const handle to the generator system defining the polyhedron ph at address pgs.
- int ppl_Polyhedron_get_minimized_generators (ppl_const_Polyhedron_t ph, ppl_const_Generator_System_t *pgs)
  Writes a const handle to the minimized generator system defining the polyhedron ph at address pgs.
- int ppl_Polyhedron_add_generator (ppl_Polyhedron_t ph, ppl_const_Generator_t g)
  Adds a copy of the generator g to the system of generators of ph.

- int ppl_Polyhedron_add_generators (ppl_Polyhedron_t ph, ppl_const_Generator_System_t gs)

  Adds a copy of the system of generators `gs` to the system of generators of `ph`.

- int ppl_Polyhedron_add_recycled_generators (ppl_Polyhedron_t ph, ppl_Generator_System_t gs)

  Adds the system of generators `gs` to the system of generators of `ph`.

- int ppl_Polyhedron_poly_hull_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Assigns to `x` the poly-hull of `x` and `y`.

- int ppl_Polyhedron_poly_difference_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  Assigns to `x` the poly-difference of `x` and `y`.

- int wrap_assign (ppl_Polyhedron_t ph, ppl_dimension_type ds[ ], size_t n, ppl_enum_Bounded_Integer_Type_Width w, ppl_enum_Bounded_Integer_Type_Representation r, ppl_enum_Bounded_Integer_Type_Overflow o, const ppl_const_Constraint_System_t *pcs, unsigned complexity_threshold, int wrap_individually)

  Assigns to `ph` the polyhedron obtained from `ph` by "wrapping" the vector space defined by the first `n` space dimensions in `ds[]`.

- int ppl_Polyhedron_BHRZ03_widening_assign_with_tokens (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, unsigned *tp)

  If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the BHRZ03-widening of `x` and `y`. If `tp` is not the null pointer, the widening with tokens delay technique is applied with `*tp` available tokens.

- int ppl_Polyhedron_H79_widening_assign_with_tokens (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, unsigned *tp)

  If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the H79-widening of `x` and `y`. If `tp` is not the null pointer, the widening with tokens delay technique is applied with `*tp` available tokens.

- int ppl_Polyhedron_BHRZ03_widening_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the BHRZ03-widening of `x` and `y`.

- int ppl_Polyhedron_H79_widening_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y)

  If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the H79-widening of `x` and `y`.

- int ppl_Polyhedron_limited_BHRZ03_extrapolation_assign_with_tokens (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs, unsigned *tp)

  If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the BHRZ03-widening of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`. If `tp` is not the null pointer, the widening with tokens delay technique is applied with `*tp` available tokens.

- int ppl_Polyhedron_limited_H79_extrapolation_assign_with_tokens (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs, unsigned *tp)

  If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the H79-widening of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`. If `tp` is not the null pointer, the widening with tokens delay technique is applied with `*tp` available tokens.

- int ppl_Polyhedron_limited_BHRZ03_extrapolation_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs)

If the polyhedron `y` *is contained in (or equal to) the polyhedron* `x`*, assigns to* `x` *the BHRZ03-widening of* `x` *and* `y` *intersected with the constraints in* `cs` *that are satisfied by all the points of* `x`*.*

- int ppl_Polyhedron_limited_H79_extrapolation_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs)

  If the polyhedron `y` *is contained in (or equal to) the polyhedron* `x`*, assigns to* `x` *the H79-widening of* `x` *and* `y` *intersected with the constraints in* `cs` *that are satisfied by all the points of* `x`*.*

- int ppl_Polyhedron_bounded_BHRZ03_extrapolation_assign_with_tokens (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs, unsigned *tp)

  If the polyhedron `y` *is contained in (or equal to) the polyhedron* `x`*, assigns to* `x` *the BHRZ03-widening of* `x` *and* `y` *intersected with the constraints in* `cs` *that are satisfied by all the points of* `x`*, further intersected with all the constraints of the form* $\pm v \leq r$ *and* $\pm v < r$*, with* $r \in \mathbb{Q}$*, that are satisfied by all the points of* `x`*. If* `tp` *is not the null pointer, the widening with tokens delay technique is applied with* `*tp` *available tokens.*

- int ppl_Polyhedron_bounded_H79_extrapolation_assign_with_tokens (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs, unsigned *tp)

  If the polyhedron `y` *is contained in (or equal to) the polyhedron* `x`*, assigns to* `x` *the H79-widening of* `x` *and* `y` *intersected with the constraints in* `cs` *that are satisfied by all the points of* `x`*, further intersected with all the constraints of the form* $\pm v \leq r$ *and* $\pm v < r$*, with* $r \in \mathbb{Q}$*, that are satisfied by all the points of* `x`*. If* `tp` *is not the null pointer, the widening with tokens delay technique is applied with* `*tp` *available tokens.*

- int ppl_Polyhedron_bounded_BHRZ03_extrapolation_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs)

  If the polyhedron `y` *is contained in (or equal to) the polyhedron* `x`*, assigns to* `x` *the BHRZ03-widening of* `x` *and* `y` *intersected with the constraints in* `cs` *that are satisfied by all the points of* `x`*, further intersected with all the constraints of the form* $\pm v \leq r$ *and* $\pm v < r$*, with* $r \in \mathbb{Q}$*, that are satisfied by all the points of* `x`*.*

- int ppl_Polyhedron_bounded_H79_extrapolation_assign (ppl_Polyhedron_t x, ppl_const_Polyhedron_t y, ppl_const_Constraint_System_t cs)

  If the polyhedron `y` *is contained in (or equal to) the polyhedron* `x`*, assigns to* `x` *the H79-widening of* `x` *and* `y` *intersected with the constraints in* `cs` *that are satisfied by all the points of* `x`*, further intersected with all the constraints of the form* $\pm v \leq r$ *and* $\pm v < r$*, with* $r \in \mathbb{Q}$*, that are satisfied by all the points of* `x`*.*

10.27.1 Detailed Description

Types and functions for the domains of C and NNC convex polyhedra. The types and functions for convex polyhedra provide a single interface for accessing both topologically closed (C) and not necessarily closed (NNC) convex polyhedra. The distinction between C and NNC polyhedra need only be explicitly stated when *creating* or *assigning* a polyhedron object, by means of one of the functions `ppl_new_*` and `ppl_assign_*`.

Having a single datatype does not mean that C and NNC polyhedra can be freely interchanged: as specified in the main manual, most library functions require their arguments to be topologically and/or space-dimension compatible.

10.27.2 Friends And Related Function Documentation

10.27.2.1 int ppl_assign_C_Polyhedron_from_C_Polyhedron (ppl_Polyhedron_t *dst*, ppl_const_Polyhedron_t *src*) [related]

Assigns a copy of the C polyhedron `src` to the C polyhedron `dst`.

10.27.2.2 int ppl_assign_NNC_Polyhedron_from_NNC_Polyhedron (ppl_Polyhedron_t *dst*, ppl_const_Polyhedron_t *src*) [related]

Assigns a copy of the NNC polyhedron `src` to the NNC polyhedron `dst`.

10.27.2.3 int ppl_delete_Polyhedron (ppl_const_Polyhedron_t *ph*) [related]

Invalidates the handle `ph`: this makes sure the corresponding resources will eventually be released.

10.27.2.4 int ppl_io_asprint_Polyhedron (char ** *strp*, ppl_const_Polyhedron_t *x*) [related]

Prints `x` to a malloc-allocated string, a pointer to which is returned via `strp`.

10.27.2.5 int ppl_io_fprint_Polyhedron (FILE * *stream*, ppl_const_Polyhedron_t *x*) [related]

Prints `x` to the given output `stream`.

10.27.2.6 int ppl_io_print_Polyhedron (ppl_const_Polyhedron_t *x*) [related]

Prints `x` to `stdout`.

10.27.2.7 int ppl_new_C_Polyhedron_from_C_Polyhedron (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*) [related]

Builds a C polyhedron that is a copy of `ph`; writes a handle for the newly created polyhedron at address `pph`.

10.27.2.8 int ppl_new_C_Polyhedron_from_C_Polyhedron_with_complexity (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*, int *complexity*) [related]

Builds a C polyhedron that is a copy of `ph`; writes a handle for the newly created polyhedron at address `pph`.

Note

The complexity argument is ignored.

10.27.2.9 int ppl_new_C_Polyhedron_from_Congruence_System (ppl_Polyhedron_t * *pph*, ppl_const_Congruence_System_t *cs*) [related]

Builds a new C polyhedron from the system of congruences `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

10.27.2.10 int ppl_new_C_Polyhedron_from_Constraint_System (ppl_Polyhedron_t * *pph*, ppl_const_Constraint_System_t *cs*) [related]

Builds a new C polyhedron from the system of constraints `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

10.27.2.11 int ppl_new_C_Polyhedron_from_Generator_System (ppl_Polyhedron_t * *pph*, ppl_const_Generator_System_t *gs*) [related]

Builds a new C polyhedron from the system of generators `gs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `gs`.

10.27.2.12 int ppl_new_C_Polyhedron_from_NNC_Polyhedron (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*) [related]

Builds a C polyhedron that is a copy of the topological closure of the NNC polyhedron `ph`; writes a handle for the newly created polyhedron at address `pph`.

10.27.2.13 int ppl_new_C_Polyhedron_from_NNC_Polyhedron_with_complexity (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*, int *complexity*) [related]

Builds a C polyhedron that approximates NNC_Polyhedron `ph`, using an algorithm whose complexity does not exceed `complexity`; writes a handle for the newly created polyhedron at address `pph`.

Note

The complexity argument, which can take values `PPL_COMPLEXITY_CLASS_POLYNOMIAL`, `PPL_COMPLEXITY_CLASS_SIMPLEX` and `PPL_COMPLEXITY_CLASS_ANY`, is ignored since the exact constructor has polynomial complexity.

10.27.2.14 int ppl_new_C_Polyhedron_from_space_dimension (ppl_Polyhedron_t * *pph*, ppl_dimension_type *d*, int *empty*) `[related]`

Builds a C polyhedron of dimension `d` and writes an handle to it at address `pph`. If `empty` is different from zero, the newly created polyhedron will be empty; otherwise, it will be a universe polyhedron.

10.27.2.15 int ppl_new_C_Polyhedron_recycle_Congruence_System (ppl_Polyhedron_t * *pph*, ppl_Congruence_System_t *cs*) `[related]`

Builds a new C polyhedron recycling the system of congruences `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

Warning

This function modifies the congruence system referenced by `cs:` upon return, no assumption can be made on its value.

10.27.2.16 int ppl_new_C_Polyhedron_recycle_Constraint_System (ppl_Polyhedron_t * *pph*, ppl_Constraint_System_t *cs*) `[related]`

Builds a new C polyhedron recycling the system of constraints `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

Warning

This function modifies the constraint system referenced by `cs:` upon return, no assumption can be made on its value.

10.27.2.17 int ppl_new_C_Polyhedron_recycle_Generator_System (ppl_Polyhedron_t * *pph*, ppl_Generator_System_t *gs*) `[related]`

Builds a new C polyhedron recycling the system of generators `gs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `gs`.

Warning

This function modifies the generator system referenced by `gs`: upon return, no assumption can be made on its value.

10.27.2.18 int ppl_new_NNC_Polyhedron_from_C_Polyhedron (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*) `[related]`

Builds an NNC polyhedron that is a copy of the C polyhedron `ph`; writes a handle for the newly created polyhedron at address `pph`.

10.27.2.19 int ppl_new_NNC_Polyhedron_from_C_Polyhedron_with_complexity (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*, int *complexity*) `[related]`

Builds an NNC polyhedron that approximates C_Polyhedron `ph`, using an algorithm whose complexity does not exceed `complexity`; writes a handle for the newly created polyhedron at address `pph`.

Note

The complexity argument, which can take values `PPL_COMPLEXITY_CLASS_POLYNOMIAL`, `PPL_COMPLEXITY_CLASS_SIMPLEX` and `PPL_COMPLEXITY_CLASS_ANY`, is ignored since the exact constructor has polynomial complexity.

10.27.2.20 int ppl_new_NNC_Polyhedron_from_Congruence_System (ppl_Polyhedron_t * *pph*, ppl_const_Congruence_System_t *cs*) `[related]`

Builds a new NNC polyhedron from the system of congruences `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

10.27.2.21 int ppl_new_NNC_Polyhedron_from_Constraint_System (ppl_Polyhedron_t * *pph*, ppl_const_Constraint_System_t *cs*) `[related]`

Builds a new NNC polyhedron from the system of constraints `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

10.27.2.22 int ppl_new_NNC_Polyhedron_from_Generator_System (ppl_Polyhedron_t * *pph*, ppl_const_Generator_System_t *gs*) `[related]`

Builds a new NNC polyhedron from the system of generators `gs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `gs`.

10.27.2.23 int ppl_new_NNC_Polyhedron_from_NNC_Polyhedron (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*) `[related]`

Builds an NNC polyhedron that is a copy of `ph`; writes a handle for the newly created polyhedron at address `pph`.

10.27.2.24 int ppl_new_NNC_Polyhedron_from_NNC_Polyhedron_with_complexity (ppl_Polyhedron_t * *pph*, ppl_const_Polyhedron_t *ph*, int *complexity*) `[related]`

Builds an NNC polyhedron that is a copy of `ph`; writes a handle for the newly created polyhedron at address `pph`.

Note

The complexity argument is ignored.

10.27.2.25 int ppl_new_NNC_Polyhedron_from_space_dimension (ppl_Polyhedron_t * *pph*, ppl_dimension_type *d*, int *empty*) `[related]`

Builds an NNC polyhedron of dimension `d` and writes an handle to it at address `pph`. If `empty` is different from zero, the newly created polyhedron will be empty; otherwise, it will be a universe polyhedron.

10.27.2.26 int ppl_new_NNC_Polyhedron_recycle_Congruence_System (ppl_Polyhedron_t * *pph*, ppl_Congruence_System_t *cs*) `[related]`

Builds a new NNC polyhedron recycling the system of congruences `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

Warning

This function modifies the congruence system referenced by `cs:` upon return, no assumption can be made on its value.

10.27.2.27 int ppl_new_NNC_Polyhedron_recycle_Constraint_System (ppl_Polyhedron_t * *pph*, ppl_Constraint_System_t *cs*) `[related]`

Builds a new NNC polyhedron recycling the system of constraints `cs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `cs`.

Warning

This function modifies the constraint system referenced by `cs`: upon return, no assumption can be made on its value.

10.27.2.28 int ppl_new_NNC_Polyhedron_recycle_Generator_System (ppl_Polyhedron_t * *pph*, ppl_Generator_System_t *gs*) [related]

Builds a new NNC polyhedron recycling the system of generators `gs` and writes a handle for the newly created polyhedron at address `pph`.

The new polyhedron will inherit the space dimension of `gs`.

Warning

This function modifies the generator system referenced by `gs`: upon return, no assumption can be made on its value.

10.27.2.29 int ppl_Polyhedron_add_congruence (ppl_Polyhedron_t *ph*, ppl_const_Congruence_t *c*) [related]

Adds a copy of the congruence `c` to polyhedron of `ph`.

10.27.2.30 int ppl_Polyhedron_add_congruences (ppl_Polyhedron_t *ph*, ppl_const_Congruence_System_t *cs*) [related]

Adds a copy of the system of congruences `cs` to the polyhedron `ph`.

10.27.2.31 int ppl_Polyhedron_add_constraint (ppl_Polyhedron_t *ph*, ppl_const_Constraint_t *c*) [related]

Adds a copy of the constraint `c` to the system of constraints of `ph`.

10.27.2.32 int ppl_Polyhedron_add_constraints (ppl_Polyhedron_t *ph*, ppl_const_Constraint_System_t *cs*) [related]

Adds a copy of the system of constraints `cs` to the system of constraints of `ph`.

10.27.2.33 int ppl_Polyhedron_add_generator (ppl_Polyhedron_t *ph*, ppl_const_Generator_t *g*) [related]

Adds a copy of the generator `g` to the system of generators of `ph`.

10.27.2.34 int ppl_Polyhedron_add_generators (ppl_Polyhedron_t *ph*, ppl_const_Generator_System_t *gs*) [related]

Adds a copy of the system of generators `gs` to the system of generators of `ph`.

10.27.2.35 int ppl_Polyhedron_add_recycled_congruences (ppl_Polyhedron_t *ph*, ppl_Congruence_System_t *cs*) [related]

Adds the system of congruences `cs` to the polyhedron `ph`.

Warning

This function modifies the congruence system referenced by `cs`: upon return, no assumption can be made on its value.

10.27.2.36 int ppl_Polyhedron_add_recycled_constraints (ppl_Polyhedron_t *ph*, ppl_Constraint_System_t *cs*) [related]

Adds the system of constraints `cs` to the system of constraints of `ph`.

Warning

This function modifies the constraint system referenced by `cs`: upon return, no assumption can be made on its value.

10.27.2.37 int ppl_Polyhedron_add_recycled_generators (ppl_Polyhedron_t *ph*, ppl_Generator_System_t *gs*) [related]

Adds the system of generators `gs` to the system of generators of `ph`.

Warning

This function modifies the generator system referenced by `gs`: upon return, no assumption can be made on its value.

10.27.2.38 int ppl_Polyhedron_add_space_dimensions_and_embed (ppl_Polyhedron_t *ph*, ppl_dimension_type *d*) [related]

Adds `d` new dimensions to the space enclosing the polyhedron `ph` and to `ph` itself.

10.27.2.39 int ppl_Polyhedron_add_space_dimensions_and_project (ppl_Polyhedron_t *ph*, ppl_dimension_type *d*) [related]

Adds `d` new dimensions to the space enclosing the polyhedron `ph`.

10.27.2.40 int ppl_Polyhedron_affine_dimension (ppl_const_Polyhedron_t *ph*, ppl_dimension_type * *m*) [related]

Writes to `m` the affine dimension of `ph` (not to be confused with the dimension of its enclosing vector space) or 0, if `ph` is empty.

10.27.2.41 int ppl_Polyhedron_affine_image (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*, ppl_const_Linear_Expression_t *le*, ppl_const_Coefficient_t *d*) [related]

Transforms the polyhedron `ph`, assigning an affine expression to the specified variable.

Parameters

ph The polyhedron that is transformed;

var The variable to which the affine expression is assigned;

le The numerator of the affine expression;

d The denominator of the affine expression.

10.27.2.42 int ppl_Polyhedron_affine_preimage (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*, ppl_const_Linear_Expression_t *le*, ppl_const_Coefficient_t *d*) [related]

Transforms the polyhedron `ph`, substituting an affine expression to the specified variable.

Parameters

ph The polyhedron that is transformed;

var The variable to which the affine expression is substituted;

le The numerator of the affine expression;

d The denominator of the affine expression.

10.27.2.43 int ppl_Polyhedron_ascii_dump (ppl_const_Polyhedron_t *x*, FILE * *stream*) [related]

Dumps an ascii representation of `x` on `stream`.

10.27.2.44 int ppl_Polyhedron_ascii_load (ppl_Polyhedron_t *x*, FILE * *stream*) [related]

Loads an ascii representation of `x` from `stream`.

10.27.2.45 int ppl_Polyhedron_BHRZ03_widening_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) [related]

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *BHRZ03-widening* of `x` and `y`.

10.27.2.46 int ppl_Polyhedron_BHRZ03_widening_assign_with_tokens (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, unsigned * *tp*) [related]

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *BHRZ03-widening* of `x` and `y`. If `tp` is not the null pointer, the *widening with tokens* delay technique is applied with `*tp` available tokens.

10.27.2.47 int ppl_Polyhedron_bounded_affine_image (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*, ppl_const_Linear_Expression_t *lb*, ppl_const_Linear_Expression_t *ub*, ppl_const_Coefficient_t *d*) [related]

Assigns to `ph` the image of `ph` with respect to the *generalized affine transfer relation* $\frac{\mathrm{lb}}{\mathrm{d}} \leq \mathrm{var}' \leq \frac{\mathrm{ub}}{\mathrm{d}}$.

Parameters

ph The polyhedron that is transformed;

var The variable bounded by the generalized affine transfer relation;

lb The numerator of the lower bounding affine expression;

ub The numerator of the upper bounding affine expression;

d The (common) denominator of the lower and upper bounding affine expressions.

10.27.2.48 int ppl_Polyhedron_bounded_affine_preimage (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*, ppl_const_Linear_Expression_t *lb*, ppl_const_Linear_Expression_t *ub*, ppl_const_Coefficient_t *d*) [related]

Assigns to `ph` the preimage of `ph` with respect to the *generalized affine transfer relation* $\frac{\mathrm{lb}}{\mathrm{d}} \leq \mathrm{var}' \leq \frac{\mathrm{ub}}{\mathrm{d}}$.

Parameters

ph The polyhedron that is transformed;

var The variable bounded by the generalized affine transfer relation;

lb The numerator of the lower bounding affine expression;

ub The numerator of the upper bounding affine expression;

d The (common) denominator of the lower and upper bounding affine expressions.

10.27.2.49 int ppl_Polyhedron_bounded_BHRZ03_extrapolation_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*) `[related]`

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *BHRZ03-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`, further intersected with all the constraints of the form $\pm v \leq r$ and $\pm v < r$, with $r \in \mathbb{Q}$, that are satisfied by all the points of `x`.

10.27.2.50 int ppl_Polyhedron_bounded_BHRZ03_extrapolation_assign_with_tokens (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*, unsigned * *tp*) `[related]`

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *BHRZ03-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`, further intersected with all the constraints of the form $\pm v \leq r$ and $\pm v < r$, with $r \in \mathbb{Q}$, that are satisfied by all the points of `x`. If `tp` is not the null pointer, the *widening with tokens* delay technique is applied with `*tp` available tokens.

10.27.2.51 int ppl_Polyhedron_bounded_H79_extrapolation_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*) `[related]`

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *H79-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`, further intersected with all the constraints of the form $\pm v \leq r$ and $\pm v < r$, with $r \in \mathbb{Q}$, that are satisfied by all the points of `x`.

10.27.2.52 int ppl_Polyhedron_bounded_H79_extrapolation_assign_with_tokens (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*, unsigned * *tp*) `[related]`

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *H79-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`, further intersected with all the constraints of the form $\pm v \leq r$ and $\pm v < r$, with $r \in \mathbb{Q}$, that are satisfied by all the points of `x`. If `tp` is not the null pointer, the *widening with tokens* delay technique is applied with `*tp` available tokens.

10.27.2.53 int ppl_Polyhedron_bounds_from_above (ppl_const_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *le*) `[related]`

Returns a positive integer if `le` is bounded from above in `ph`; returns 0 otherwise.

10.27.2.54 int ppl_Polyhedron_bounds_from_below (ppl_const_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *le*) `[related]`

Returns a positive integer if `le` is bounded from below in `ph`; returns 0 otherwise.

10.27.2.55 int ppl_Polyhedron_concatenate_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) `[related]`

Seeing a polyhedron as a set of tuples (its points), assigns to `x` all the tuples that can be obtained by concatenating, in the order given, a tuple of `x` with a tuple of `y`.

10.27.2.56 int ppl_Polyhedron_constrains (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*) `[related]`

Returns a positive integer if `ph` constrains `var`; returns 0 if `ph` does not constrain `var`.

10.27.2.57 int ppl_Polyhedron_contains_integer_point (ppl_const_Polyhedron_t *ph*) `[related]`

Returns a positive integer if `ph` contains at least one integer point; returns 0 otherwise.

10.27.2.58 int ppl_Polyhedron_contains_Polyhedron (ppl_const_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) `[related]`

Returns a positive integer if `x` contains or is equal to `y`; returns 0 if it does not.

10.27.2.59 int ppl_Polyhedron_difference_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) `[related]`

Same as ppl_Polyhedron_poly_difference_assign(x, y).

10.27.2.60 int ppl_Polyhedron_equals_Polyhedron (ppl_const_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) `[related]`

Returns a positive integer if `x` and `y` are the same polyhedron; returns 0 if they are different.

Note that `x` and `y` may be topology- and/or dimension-incompatible polyhedra: in those cases, the value 0 is returned.

10.27.2.61 int ppl_Polyhedron_expand_space_dimension (ppl_Polyhedron_t *ph*, ppl_dimension_type *d*, ppl_dimension_type *m*) `[related]`

Expands the d-th dimension of the vector space enclosing `ph` to `m` new space dimensions.

10.27.2.62 int ppl_Polyhedron_external_memory_in_bytes (ppl_const_Polyhedron_t *ph*, size_t * *sz*) `[related]`

Writes to `sz` a lower bound to the size in bytes of the memory managed by `ph`.

10.27.2.63 int ppl_Polyhedron_fold_space_dimensions (ppl_Polyhedron_t *ph*, ppl_dimension_type *ds*[ ], size_t *n*, ppl_dimension_type *d*) `[related]`

Modifies `ph` by *folding* the space dimensions contained in the first `n` positions of the array `ds` into dimension `d`. The presence of duplicates in `ds` is a waste but an innocuous one.

10.27.2.64 int ppl_Polyhedron_generalized_affine_image (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*, enum ppl_enum_Constraint_Type *relsym*, ppl_const_Linear_Expression_t *le*, ppl_const_Coefficient_t *d*) `[related]`

Assigns to `ph` the image of `ph` with respect to the *generalized affine transfer relation* $\mathrm{var}' \bowtie \frac{\mathrm{le}}{\mathrm{d}}$, where $\bowtie$ is the relation symbol encoded by `relsym`.

Parameters

ph The polyhedron that is transformed;

var The left hand side variable of the generalized affine transfer relation;

relsym The relation symbol;

le The numerator of the right hand side affine expression;

d The denominator of the right hand side affine expression.

10.27.2.65 int ppl_Polyhedron_generalized_affine_image_lhs_rhs (ppl_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *lhs*, enum ppl_enum_Constraint_Type *relsym*, ppl_const_Linear_Expression_t *rhs*) `[related]`

Assigns to `ph` the image of `ph` with respect to the *generalized affine transfer relation* $\mathrm{lhs}' \bowtie \mathrm{rhs}$, where $\bowtie$ is the relation symbol encoded by `relsym`.

Parameters

ph The polyhedron that is transformed;

lhs The left hand side affine expression;

relsym The relation symbol;

rhs The right hand side affine expression.

10.27.2.66 int ppl_Polyhedron_generalized_affine_preimage (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*, enum ppl_enum_Constraint_Type *relsym*, ppl_const_Linear_Expression_t *le*, ppl_const_Coefficient_t *d*) `[related]`

Assigns to `ph` the preimage of `ph` with respect to the *generalized affine transfer relation* $\mathrm{var}' \bowtie \frac{\mathrm{le}}{\mathrm{d}}$, where $\bowtie$ is the relation symbol encoded by `relsym`.

Parameters

ph The polyhedron that is transformed;

var The left hand side variable of the generalized affine transfer relation;

relsym The relation symbol;

le The numerator of the right hand side affine expression;

d The denominator of the right hand side affine expression.

10.27.2.67 int ppl_Polyhedron_generalized_affine_preimage_lhs_rhs (ppl_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *lhs*, enum ppl_enum_Constraint_Type *relsym*, ppl_const_Linear_Expression_t *rhs*) `[related]`

Assigns to `ph` the preimage of `ph` with respect to the *generalized affine transfer relation* $\mathrm{lhs}' \bowtie \mathrm{rhs}$, where $\bowtie$ is the relation symbol encoded by `relsym`.

Parameters

ph The polyhedron that is transformed;

lhs The left hand side affine expression;

relsym The relation symbol;

rhs The right hand side affine expression.

10.27.2.68 int ppl_Polyhedron_get_congruences (ppl_const_Polyhedron_t *ph*, ppl_const_Congruence_System_t * *pcs*) `[related]`

Writes at address `pcs` a const handle to a system of congruences approximating the polyhedron `ph`.

10.27.2.69 int ppl_Polyhedron_get_constraints (ppl_const_Polyhedron_t *ph*, ppl_const_Constraint_System_t * *pcs*) `[related]`

Writes a const handle to the constraint system defining the polyhedron `ph` at address `pcs`.

10.27.2.70 int ppl_Polyhedron_get_generators (ppl_const_Polyhedron_t *ph*, ppl_const_Generator_System_t * *pgs*) [related]

Writes a const handle to the generator system defining the polyhedron `ph` at address `pgs`.

10.27.2.71 int ppl_Polyhedron_get_minimized_congruences (ppl_const_Polyhedron_t *ph*, ppl_const_Congruence_System_t * *pcs*) [related]

Writes at address `pcs` a const handle to a system of minimized congruences approximating the polyhedron `ph`.

10.27.2.72 int ppl_Polyhedron_get_minimized_constraints (ppl_const_Polyhedron_t *ph*, ppl_const_Constraint_System_t * *pcs*) [related]

Writes a const handle to the minimized constraint system defining the polyhedron `ph` at address `pcs`.

10.27.2.73 int ppl_Polyhedron_get_minimized_generators (ppl_const_Polyhedron_t *ph*, ppl_const_Generator_System_t * *pgs*) [related]

Writes a const handle to the minimized generator system defining the polyhedron `ph` at address `pgs`.

10.27.2.74 int ppl_Polyhedron_H79_widening_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) [related]

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *H79-widening* of `x` and `y`.

10.27.2.75 int ppl_Polyhedron_H79_widening_assign_with_tokens (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, unsigned * *tp*) [related]

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *H79-widening* of `x` and `y`. If `tp` is not the null pointer, the *widening with tokens* delay technique is applied with `*tp` available tokens.

10.27.2.76 int ppl_Polyhedron_intersection_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) [related]

Intersects `x` with polyhedron `y` and assigns the result to `x`.

10.27.2.77 int ppl_Polyhedron_is_bounded (ppl_const_Polyhedron_t *ph*) [related]

Returns a positive integer if `ph` is bounded; returns 0 if `ph` is unbounded.

10.27.2.78 int ppl_Polyhedron_is_discrete (ppl_const_Polyhedron_t *ph*) [related]

Returns a positive integer if `ph` is a discrete set; returns 0 if `ph` is not a discrete set.

10.27.2.79 int ppl_Polyhedron_is_disjoint_from_Polyhedron (ppl_const_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) [related]

Returns a positive integer if `x` and `y` are disjoint; returns 0 if they are not.

10.27.2.80 int ppl_Polyhedron_is_empty (ppl_const_Polyhedron_t *ph*) [related]

Returns a positive integer if `ph` is empty; returns 0 if `ph` is not empty.

10.27.2.81 int ppl_Polyhedron_is_topologically_closed (ppl_const_Polyhedron_t *ph*) [related]

Returns a positive integer if `ph` is topologically closed; returns 0 if `ph` is not topologically closed.

10.27.2.82 int ppl_Polyhedron_is_universe (ppl_const_Polyhedron_t *ph*) [related]

Returns a positive integer if `ph` is a universe polyhedron; returns 0 if it is not.

10.27.2.83 int ppl_Polyhedron_limited_BHRZ03_extrapolation_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*) [related]

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *BHRZ03-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`.

10.27.2.84 int ppl_Polyhedron_limited_BHRZ03_extrapolation_assign_with_tokens (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*, unsigned * *tp*) [related]

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *BHRZ03-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`. If `tp` is not the null pointer, the *widening with tokens* delay technique is applied with `*tp` available tokens.

10.27.2.85 int ppl_Polyhedron_limited_H79_extrapolation_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*) `[related]`

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *H79-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`.

10.27.2.86 int ppl_Polyhedron_limited_H79_extrapolation_assign_with_tokens (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*, ppl_const_Constraint_System_t *cs*, unsigned * *tp*) `[related]`

If the polyhedron `y` is contained in (or equal to) the polyhedron `x`, assigns to `x` the *H79-widening* of `x` and `y` intersected with the constraints in `cs` that are satisfied by all the points of `x`. If `tp` is not the null pointer, the *widening with tokens* delay technique is applied with `*tp` available tokens.

10.27.2.87 int ppl_Polyhedron_map_space_dimensions (ppl_Polyhedron_t *ph*, ppl_dimension_type *maps*[ ], size_t *n*) `[related]`

Remaps the dimensions of the vector space according to a *partial function*. This function is specified by means of the `maps` array, which has `n` entries.

The partial function is defined on dimension `i` if `i < n` and `maps[i] != ppl_not_a_dimension`; otherwise it is undefined on dimension `i`. If the function is defined on dimension `i`, then dimension `i` is mapped onto dimension `maps[i]`.

The result is undefined if `maps` does not encode a partial function with the properties described in the *specification of the mapping operator*.

10.27.2.88 int ppl_Polyhedron_maximize (ppl_const_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *le*, ppl_Coefficient_t *sup_n*, ppl_Coefficient_t *sup_d*, int * *pmaximum*) `[related]`

The same as ppl_Polyhedron_maximize_with_point, but without the output argument for the location where the supremum value is reached.

10.27.2.89 int ppl_Polyhedron_maximize_with_point (ppl_const_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *le*, ppl_Coefficient_t *sup_n*, ppl_Coefficient_t *sup_d*, int * *pmaximum*, ppl_Generator_t *point*) `[related]`

Returns a positive integer if `ph` is not empty and `le` is bounded from above in `ph`, in which case the supremum value and a point where `le` reaches it are computed.

Parameters

ph The polyhedron constraining `le`;

le The linear expression to be maximized subject to `ph`;

sup_n Will be assigned the numerator of the supremum value;

sup_d Will be assigned the denominator of the supremum value;

pmaximum Will store 1 in this location if the supremum is also the maximum, will store 0 otherwise;

point Will be assigned the point or closure point where `le` reaches the extremum value.

If `ph` is empty or `le` is not bounded from above, 0 will be returned and `sup_n`, `sup_d`, `*pmaximum` and `point` will be left untouched.

10.27.2.90 int ppl_Polyhedron_minimize_with_point (ppl_const_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *le*, ppl_Coefficient_t *inf_n*, ppl_Coefficient_t *inf_d*, int * *pminimum*) `[related]`

The same as ppl_Polyhedron_minimize_with_point, but without the output argument for the location where the infimum value is reached.

10.27.2.91 int ppl_Polyhedron_minimize_with_point (ppl_const_Polyhedron_t *ph*, ppl_const_Linear_Expression_t *le*, ppl_Coefficient_t *inf_n*, ppl_Coefficient_t *inf_d*, int * *pminimum*, ppl_Generator_t *point*) `[related]`

Returns a positive integer if `ph` is not empty and `le` is bounded from below in `ph`, in which case the infimum value and a point where `le` reaches it are computed.

Parameters

ph The polyhedron constraining `le`;

le The linear expression to be minimized subject to `ph`;

inf_n Will be assigned the numerator of the infimum value;

inf_d Will be assigned the denominator of the infimum value;

pminimum Will store 1 in this location if the infimum is also the minimum, will store 0 otherwise;

point Will be assigned the point or closure point where `le` reaches the extremum value.

If `ph` is empty or `le` is not bounded from below, 0 will be returned and `sup_n`, `sup_d`, `*pmaximum` and `point` will be left untouched.

10.27.2.92 int ppl_Polyhedron_OK (ppl_const_Polyhedron_t *ph*) `[related]`

Returns a positive integer if `ph` is well formed, i.e., if it satisfies all its implementation invariants; returns 0 and perhaps makes some noise if `ph` is broken. Useful for debugging purposes.

10.27.2.93 int ppl_Polyhedron_poly_difference_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) [related]

Assigns to x the *poly-difference* of x and y.

10.27.2.94 int ppl_Polyhedron_poly_hull_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) [related]

Assigns to x the poly-hull of x and y.

10.27.2.95 int ppl_Polyhedron_refine_with_congruence (ppl_Polyhedron_t *ph*, ppl_const_Congruence_t *c*) [related]

Refines ph using congruence c.

10.27.2.96 int ppl_Polyhedron_refine_with_congruences (ppl_Polyhedron_t *ph*, ppl_const_Congruence_System_t *cs*) [related]

Refines ph using the congruences in cs.

10.27.2.97 int ppl_Polyhedron_refine_with_constraint (ppl_Polyhedron_t *ph*, ppl_const_Constraint_t *c*) [related]

Refines ph using constraint c.

10.27.2.98 int ppl_Polyhedron_refine_with_constraints (ppl_Polyhedron_t *ph*, ppl_const_Constraint_System_t *cs*) [related]

Refines ph using the constraints in cs.

10.27.2.99 int ppl_Polyhedron_relation_with_Constraint (ppl_const_Polyhedron_t *ph*, ppl_const_Constraint_t *c*) [related]

Checks the relation between the polyhedron ph and the constraint c.

If successful, returns a non-negative integer that is obtained as the bitwise or of the bits (chosen among PPL_POLY_CON_RELATION_IS_DISJOINT PPL_POLY_CON_RELATION_STRICTLY_-INTERSECTS, PPL_POLY_CON_RELATION_IS_INCLUDED, and PPL_POLY_CON_RELATION_-SATURATES) that describe the relation between ph and c.

10.27.2.100 int ppl_Polyhedron_relation_with_Generator (ppl_const_Polyhedron_t *ph*, ppl_const_Generator_t *g*) `[related]`

Checks the relation between the polyhedron `ph` and the generator `g`.

If successful, returns a non-negative integer that is obtained as the bitwise or of the bits (only PPL_POLY_-GEN_RELATION_SUBSUMES, at present) that describe the relation between `ph` and `g`.

10.27.2.101 int ppl_Polyhedron_remove_higher_space_dimensions (ppl_Polyhedron_t *ph*, ppl_dimension_type *d*) `[related]`

Removes the higher dimensions from the vector space enclosing `ph` so that, upon successful return, the new space dimension is `d`.

10.27.2.102 int ppl_Polyhedron_remove_space_dimensions (ppl_Polyhedron_t *ph*, ppl_dimension_type *ds*[ ], size_t *n*) `[related]`

Removes from the vector space enclosing `ph` the space dimensions that are specified in first `n` positions of the array `ds`. The presence of duplicates in `ds` is a waste but an innocuous one.

10.27.2.103 int ppl_Polyhedron_simplify_using_context_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) `[related]`

Assigns to `x` the *meet-preserving simplification* of `x` with respect to context `y`. Returns a positive integer if `x` and `y` have a nonempty intersection; returns `0` if they are disjoint.

10.27.2.104 int ppl_Polyhedron_space_dimension (ppl_const_Polyhedron_t *ph*, ppl_dimension_type * *m*) `[related]`

Writes to `m` the dimension of the vector space enclosing `ph`.

10.27.2.105 int ppl_Polyhedron_strictly_contains_Polyhedron (ppl_const_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) `[related]`

Returns a positive integer if `x` strictly contains `y`; returns 0 if it does not.

10.27.2.106 int ppl_Polyhedron_time_elapse_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) `[related]`

Assigns to `x` the *time-elapse* between the polyhedra `x` and `y`.

10.27.2.107 int ppl_Polyhedron_topological_closure_assign (ppl_Polyhedron_t *ph*) [related]

Assigns to ph its topological closure.

10.27.2.108 int ppl_Polyhedron_total_memory_in_bytes (ppl_const_Polyhedron_t *ph*, size_t * *sz*) [related]

Writes to sz a lower bound to the size in bytes of the memory managed by ph.

10.27.2.109 int ppl_Polyhedron_unconstrain_space_dimension (ppl_Polyhedron_t *ph*, ppl_dimension_type *var*) [related]

Modifies ph by *unconstraining* the space dimension var.

10.27.2.110 int ppl_Polyhedron_unconstrain_space_dimensions (ppl_Polyhedron_t *ph*, ppl_dimension_type *ds*[ ], size_t *n*) [related]

Modifies ph by *unconstraining* the space dimensions that are specified in the first n positions of the array ds. The presence of duplicates in ds is a waste but an innocuous one.

10.27.2.111 int ppl_Polyhedron_upper_bound_assign (ppl_Polyhedron_t *x*, ppl_const_Polyhedron_t *y*) [related]

Assigns to x an upper bound of x and y.

For the domain of polyhedra, this is the same as ppl_Polyhedron_poly_hull_assign(x, y).

10.27.2.112 int wrap_assign (ppl_Polyhedron_t *ph*, ppl_dimension_type *ds*[ ], size_t *n*, ppl_enum_Bounded_Integer_Type_Width *w*, ppl_enum_Bounded_Integer_-Type_Representation *r*, ppl_enum_Bounded_Integer_Type_Overflow *o*, const ppl_const_Constraint_System_t * *pcs*, unsigned *complexity_threshold*, int *wrap_individually*) [related]

Assigns to ph the polyhedron obtained from ph by "wrapping" the vector space defined by the first n space dimensions in ds[].

Parameters

ph The polyhedron that is transformed;

ds[ ] Specifies the space dimensions to be wrapped.

n The first n space dimensions in the array ds[] will be wrapped.

w The width of the bounded integer type corresponding to all the dimensions to be wrapped.

r The representation of the bounded integer type corresponding to all the dimensions to be wrapped.

o The overflow behavior of the bounded integer type corresponding to all the dimensions to be wrapped.

pcs Possibly null pointer to a constraint system whose space dimensions are the first `n` dimensions in `ds`[]. If `*pcs` depends on variables not in `vars`, the behavior is undefined. When non-null, the constraint system is assumed to represent the conditional or looping construct guard with respect to which wrapping is performed. Since wrapping requires the computation of upper bounds and due to non-distributivity of constraint refinement over upper bounds, passing a constraint system in this way can be more precise than refining the result of the wrapping operation with the constraints in `cs`.

complexity_threshold A precision parameter where higher values result in possibly improved precision.

wrap_individually Non-zero if the dimensions should be wrapped individually (something that results in much greater efficiency to the detriment of precision).

The documentation for this interface was generated from the following file:

- C_interface.dox

10.28 Parma_Polyhedra_Library::Interfaces::C::timeout_exception Class Reference

```
#include <ppl_c_implementation_common.defs.hh>
```

Public Member Functions

- void throw_me () const
- int priority () const

10.28.1 Detailed Description

Definition at line 106 of file ppl_c_implementation_common.defs.hh.

10.28.2 Member Function Documentation

10.28.2.1 int Parma_Polyhedra_Library::Interfaces::C::timeout_exception::priority () const [inline]

Definition at line 111 of file ppl_c_implementation_common.defs.hh.

10.28.2.2 void Parma_Polyhedra_Library::Interfaces::C::timeout_exception::throw_me () const [inline]

Definition at line 108 of file ppl_c_implementation_common.defs.hh.

The documentation for this class was generated from the following file:

- ppl_c_implementation_common.defs.hh

11 File Documentation

11.1 C_interface.dox File Reference

Typedefs

- typedef struct ppl_Polyhedron_tag ∗ ppl_Polyhedron_t

  Opaque pointer.

- typedef struct ppl_Polyhedron_tag const ∗ ppl_const_Polyhedron_t

  Opaque pointer to const object.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_tag ∗ ppl_Pointset_Powerset_C_Polyhedron_-t

  Opaque pointer.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_tag const ∗ ppl_const_Pointset_Powerset_C_-Polyhedron_t

  Opaque pointer to const object.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_iterator_tag ∗ ppl_Pointset_Powerset_C_-Polyhedron_iterator_t

  Opaque pointer.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_iterator_tag const ∗ ppl_const_Pointset_-Powerset_C_Polyhedron_iterator_t

  Opaque pointer to const object.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag ∗ ppl_Pointset_Powerset_-C_Polyhedron_const_iterator_t

  Opaque pointer.

- typedef struct ppl_Pointset_Powerset_C_Polyhedron_const_iterator_tag const ∗ ppl_const_-Pointset_Powerset_C_Polyhedron_const_iterator_t

  Opaque pointer to const object.

Functions

Functions that Do Not Modify the Polyhedron

- int ppl_Polyhedron_relation_with_Congruence (ppl_const_Polyhedron_t ph, ppl_const_-Congruence_t c)

11.1.1 Function Documentation

11.1.1.1 int ppl_Polyhedron_relation_with_Congruence (ppl_const_Polyhedron_t *ph*, ppl_const_Congruence_t *c*)

11.2 fdl.dox File Reference

11.3 gpl.dox File Reference

11.4 ppl_c_header.h File Reference

```
#include <stdio.h>
#include <gmp.h>
#include <stddef.h>
#include "ppl_c_version.h"
#include "ppl_c_domains.h"
```

Include dependency graph for ppl_c_header.h:



Defines

- #define PPL_PROTO(protos) ()
- #define PPL_TYPE_DECLARATION(Type)
- #define PPL_DECLARE_PRINT_FUNCTIONS(Type)
- #define PPL_DECLARE_ASCII_DUMP_LOAD_FUNCTIONS(Type)
- #define PPL_DECLARE_IO_FUNCTIONS(Type)
- #define PPL_DECLARE_AND_DOCUMENT_PRINT_FUNCTIONS(Type)
- #define PPL_DECLARE_AND_DOCUMENT_ASCII_DUMP_LOAD_FUNCTIONS(Type)
- #define PPL_DECLARE_AND_DOCUMENT_IO_FUNCTIONS(Type)

Typedefs

- typedef size_t ppl_dimension_type

  An unsigned integral type for representing space dimensions.

- typedef const char * ppl_io_variable_output_function_type (ppl_dimension_type var)

  The type of output functions used for printing variables.

Enumerations

- enum ppl_enum_error_code {

  PPL_ERROR_OUT_OF_MEMORY, PPL_ERROR_INVALID_ARGUMENT, PPL_ERROR_-DOMAIN_ERROR, PPL_ERROR_LENGTH_ERROR,

  PPL_ARITHMETIC_OVERFLOW, PPL_STDIO_ERROR, PPL_ERROR_INTERNAL_ERROR, PPL_ERROR_UNKNOWN_STANDARD_EXCEPTION,

  PPL_ERROR_UNEXPECTED_ERROR, PPL_TIMEOUT_EXCEPTION, PPL_ERROR_LOGIC_-ERROR }

  Defines the error codes that any function may return.

- enum ppl_enum_Constraint_Type {

  PPL_CONSTRAINT_TYPE_LESS_THAN, PPL_CONSTRAINT_TYPE_LESS_OR_EQUAL, PPL_CONSTRAINT_TYPE_EQUAL, PPL_CONSTRAINT_TYPE_GREATER_OR_EQUAL,

  PPL_CONSTRAINT_TYPE_GREATER_THAN }

  Describes the relations represented by a constraint.

- enum ppl_enum_Generator_Type { PPL_GENERATOR_TYPE_LINE, PPL_GENERATOR_-TYPE_RAY, PPL_GENERATOR_TYPE_POINT, PPL_GENERATOR_TYPE_CLOSURE_-POINT }

  Describes the different kinds of generators.

- enum ppl_enum_Grid_Generator_Type { PPL_GRID_GENERATOR_TYPE_LINE, PPL_GRID_-GENERATOR_TYPE_PARAMETER, PPL_GRID_GENERATOR_TYPE_POINT }

  Describes the different kinds of grid generators.

- enum ppl_enum_Bounded_Integer_Type_Width {

  PPL_BITS_8, PPL_BITS_16, PPL_BITS_32, PPL_BITS_64,

  PPL_BITS_128 }

  Widths of bounded integer types.

- enum ppl_enum_Bounded_Integer_Type_Representation { PPL_UNSIGNED, PPL_SIGNED_2_-COMPLEMENT }

  Representation of bounded integer types.

- enum ppl_enum_Bounded_Integer_Type_Overflow { PPL_OVERFLOW_WRAPS, PPL_-OVERFLOW_UNDEFINED, PPL_OVERFLOW_IMPOSSIBLE }

  Overflow behavior of bounded integer types.

Functions

- int ppl_initialize (void)

  Initializes the Parma Polyhedra Library. This function must be called before any other function.

- int ppl_finalize (void)

  Finalizes the Parma Polyhedra Library. This function must be called after any other function.

- int ppl_set_rounding_for_PPL (void)

Sets the FPU rounding mode so that the PPL abstractions based on floating point numbers work correctly.

- int ppl_restore_pre_PPL_rounding (void)

  Sets the FPU rounding mode as it was before initialization of the PPL.

- int ppl_irrational_precision (unsigned ∗p)

  Writes to `p` *the precision parameter used for irrational calculations.*

- int ppl_set_irrational_precision (unsigned p)

  Sets the precision parameter used for irrational calculations.

- int ppl_version_major (void)

  Returns the major number of the PPL version.

- int ppl_version_minor (void)

  Returns the minor number of the PPL version.

- int ppl_version_revision (void)

  Returns the revision number of the PPL version.

- int ppl_version_beta (void)

  Returns the beta number of the PPL version.

- int ppl_version (const char ∗∗p)

  Writes to `∗p` *a pointer to a character string containing the PPL version.*

- int ppl_banner (const char ∗∗p)

  Writes to `∗p` *a pointer to a character string containing the PPL banner.*

- int ppl_set_error_handler (void(∗h)(enum ppl_enum_error_code code, const char ∗description))

  Installs the user-defined error handler pointed at by `h`.

- int ppl_set_timeout (unsigned time)

  Sets the timeout for computations whose completion could require an exponential amount of time.

- int ppl_reset_timeout (void)

  Resets the timeout time so that the computation is not interrupted.

- int ppl_set_deterministic_timeout (unsigned weight)

  Sets a threshold for computations whose completion could require an exponential amount of time.

- int ppl_reset_deterministic_timeout (void)

  Resets the deterministic timeout so that the computation is not interrupted.

- int ppl_max_space_dimension (ppl_dimension_type ∗m)

  Writes to `m` *the maximum space dimension this library can handle.*

- int ppl_not_a_dimension (ppl_dimension_type ∗m)

  Writes to `m` *a value that does not designate a valid dimension.*

- int ppl_io_print_variable (ppl_dimension_type var)

  Pretty-prints `var` *to* `stdout`.

- int ppl_io_fprint_variable (FILE *stream, ppl_dimension_type var)

  Pretty-prints `var` *to the given output* `stream`.

- int ppl_io_asprint_variable (char **strp, ppl_dimension_type var)

  Pretty-prints `var` *to a malloc-allocated string, a pointer to which is returned via* `strp`.

- int ppl_io_set_variable_output_function (ppl_io_variable_output_function_type *p)

  Sets the output function to be used for printing variables to `p`.

- int ppl_io_get_variable_output_function (ppl_io_variable_output_function_type **pp)

  Writes a pointer to the current variable output function to `pp`.

- char * ppl_io_wrap_string (const char *src, unsigned indent_depth, unsigned preferred_first_line_-length, unsigned preferred_line_length)

  Utility function for the wrapping of lines of text.

Constructors, Assignment and Destructor

- int ppl_new_Generator_System_zero_dim_univ (ppl_Generator_System_t *pgs)
- int ppl_new_Grid_Generator_System_zero_dim_univ (ppl_Grid_Generator_System_t *pgs)

Variables

- unsigned int PPL_COMPLEXITY_CLASS_POLYNOMIAL

  Code of the worst-case polynomial complexity class.

- unsigned int PPL_COMPLEXITY_CLASS_SIMPLEX

  Code of the worst-case exponential but typically polynomial complexity class.

- unsigned int PPL_COMPLEXITY_CLASS_ANY

  Code of the universal complexity class.

- unsigned int PPL_POLY_CON_RELATION_IS_DISJOINT

  Individual bit saying that the polyhedron and the set of points satisfying the constraint are disjoint.

- unsigned int PPL_POLY_CON_RELATION_STRICTLY_INTERSECTS

  Individual bit saying that the polyhedron intersects the set of points satisfying the constraint, but it is not included in it.

- unsigned int PPL_POLY_CON_RELATION_IS_INCLUDED

  Individual bit saying that the polyhedron is included in the set of points satisfying the constraint.

- unsigned int PPL_POLY_CON_RELATION_SATURATES

  Individual bit saying that the polyhedron is included in the set of points saturating the constraint.

- unsigned int PPL_POLY_GEN_RELATION_SUBSUMES

  Individual bit saying that adding the generator would not change the polyhedron.

11.4.1 Define Documentation

11.4.1.1 #define PPL_DECLARE_AND_DOCUMENT_ASCII_DUMP_LOAD_-FUNCTIONS(Type)

Definition at line 794 of file ppl_c_header.h.

11.4.1.2 #define PPL_DECLARE_AND_DOCUMENT_IO_FUNCTIONS(Type)

Value:

```
                \                                                    \
PPL_DECLARE_AND_DOCUMENT_PRINT_FUNCTIONS(Type)           \
PPL_DECLARE_AND_DOCUMENT_ASCII_DUMP_LOAD_FUNCTIONS(Type) \
```

Definition at line 804 of file ppl_c_header.h.

11.4.1.3 #define PPL_DECLARE_AND_DOCUMENT_PRINT_FUNCTIONS(Type)

Definition at line 782 of file ppl_c_header.h.

11.4.1.4 #define PPL_DECLARE_ASCII_DUMP_LOAD_FUNCTIONS(Type)

Definition at line 768 of file ppl_c_header.h.

11.4.1.5 #define PPL_DECLARE_IO_FUNCTIONS(Type)

Value:

```
PPL_DECLARE_PRINT_FUNCTIONS(Type)           \
PPL_DECLARE_ASCII_DUMP_LOAD_FUNCTIONS(Type)
```

Definition at line 778 of file ppl_c_header.h.

11.4.1.6 #define PPL_DECLARE_PRINT_FUNCTIONS(Type)

Definition at line 757 of file ppl_c_header.h.

11.4.1.7 #define PPL_PROTO(protos) ()

Definition at line 162 of file ppl_c_header.h.

11.4.1.8 #define PPL_TYPE_DECLARATION(Type)

Value:

```
                                                                    \
typedef struct ppl_##Type##_tag* ppl_##Type##_t;                    \        \
typedef struct ppl_##Type##_tag const* ppl_const_##Type##_t;
```

Definition at line 539 of file ppl_c_header.h.

11.4.2 Function Documentation

11.4.2.1 int ppl_new_Generator_System_zero_dim_univ (ppl_Generator_System_t * *pgs*)

Definition at line 1097 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.4.2.2 int ppl_new_Grid_Generator_System_zero_dim_univ (ppl_Grid_Generator_System_t * *pgs*)

Definition at line 1690 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5 ppl_c_implementation_common.cc File Reference

```
#include "ppl_c_implementation_common.defs.hh"
#include "ppl.hh"
#include "ppl_c.h"
#include <stdexcept>
```

Include dependency graph for ppl_c_implementation_common.cc:



This graph shows which files directly or indirectly include this file:



Namespaces

- namespace Parma_Polyhedra_Library

- namespace Parma_Polyhedra_Library::Interfaces
- namespace Parma_Polyhedra_Library::Interfaces::C

Defines

- #define FORMAT "%u"
- #define CONVERSION (unsigned)

Typedefs

- typedef const char * Parma_Polyhedra_Library::Interfaces::C::c_variable_output_function_type (ppl_dimension_type var)

Functions

- const char * Parma_Polyhedra_Library::Interfaces::C::c_variable_default_output_function (ppl_-dimension_type var)
- void Parma_Polyhedra_Library::Interfaces::C::cxx_Variable_output_function (std::ostream &s, const Variable &v)
- void Parma_Polyhedra_Library::Interfaces::C::notify_error (enum ppl_enum_error_code code, const char *description)
- void Parma_Polyhedra_Library::Interfaces::C::reset_timeout ()
- void Parma_Polyhedra_Library::Interfaces::C::reset_deterministic_timeout ()
- int ppl_set_error_handler (error_handler_type h)
- int ppl_initialize (void)

  Initializes the Parma Polyhedra Library. This function must be called before any other function.

- catch (const std::invalid_argument &e)
- catch (const std::domain_error &e)
- catch (const std::length_error &e)
- catch (const std::logic_error &e)
- catch (const std::overflow_error &e)
- catch (const std::runtime_error &e)
- catch (const std::exception &e)
- catch (timeout_exception &)
- catch (deterministic_timeout_exception &)
- catch (...)
- int ppl_finalize (void)

  Finalizes the Parma Polyhedra Library. This function must be called after any other function.

- int ppl_set_timeout (unsigned time)

  Sets the timeout for computations whose completion could require an exponential amount of time.

- int ppl_reset_timeout (void)

  Resets the timeout time so that the computation is not interrupted.

- int ppl_set_deterministic_timeout (unsigned weight)

  Sets a threshold for computations whose completion could require an exponential amount of time.

- int ppl_reset_deterministic_timeout (void)

  Resets the deterministic timeout so that the computation is not interrupted.

- int ppl_set_rounding_for_PPL (void)

  Sets the FPU rounding mode so that the PPL abstractions based on floating point numbers work correctly.

- int ppl_restore_pre_PPL_rounding (void)

  Sets the FPU rounding mode as it was before initialization of the PPL.

- int ppl_irrational_precision (unsigned *p)

  Writes to `p` *the precision parameter used for irrational calculations.*

- int ppl_set_irrational_precision (unsigned p)

  Sets the precision parameter used for irrational calculations.

- int ppl_version_major (void)

  Returns the major number of the PPL version.

- int ppl_version_minor (void)

  Returns the minor number of the PPL version.

- int ppl_version_revision (void)

  Returns the revision number of the PPL version.

- int ppl_version_beta (void)

  Returns the beta number of the PPL version.

- int ppl_version (const char **p)

  Writes to `*p` *a pointer to a character string containing the PPL version.*

- int ppl_banner (const char **p)

  Writes to `*p` *a pointer to a character string containing the PPL banner.*

- int ppl_max_space_dimension (ppl_dimension_type *m)

  Writes to `m` *the maximum space dimension this library can handle.*

- int ppl_not_a_dimension (ppl_dimension_type *m)

  Writes to `m` *a value that does not designate a valid dimension.*

- int ppl_new_Coefficient (ppl_Coefficient_t *pc)
- int ppl_new_Coefficient_from_mpz_t (ppl_Coefficient_t *pc, mpz_t z)
- int ppl_new_Coefficient_from_Coefficient (ppl_Coefficient_t *pc, ppl_const_Coefficient_t c)
- int ppl_Coefficient_to_mpz_t (ppl_const_Coefficient_t c, mpz_t z)
- int ppl_delete_Coefficient (ppl_const_Coefficient_t c)
- int ppl_assign_Coefficient_from_mpz_t (ppl_Coefficient_t dst, mpz_t z)
- int ppl_assign_Coefficient_from_Coefficient (ppl_Coefficient_t dst, ppl_const_Coefficient_t src)
- int ppl_Coefficient_OK (ppl_const_Coefficient_t)
- int ppl_Coefficient_is_bounded (void)
- int ppl_Coefficient_min (mpz_t min)
- int ppl_Coefficient_max (mpz_t max)

- int ppl_new_Linear_Expression (ppl_Linear_Expression_t *ple)
- int ppl_new_Linear_Expression_with_dimension (ppl_Linear_Expression_t *ple, ppl_dimension_type d)
- int ppl_new_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t *ple, ppl_const_Linear_Expression_t le)
- int ppl_delete_Linear_Expression (ppl_const_Linear_Expression_t le)
- int ppl_assign_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t dst, ppl_const_Linear_Expression_t src)
- int ppl_Linear_Expression_add_to_coefficient (ppl_Linear_Expression_t le, ppl_dimension_type var, ppl_const_Coefficient_t n)
- int ppl_Linear_Expression_add_to_inhomogeneous (ppl_Linear_Expression_t le, ppl_const_Coefficient_t n)
- int ppl_add_Linear_Expression_to_Linear_Expression (ppl_Linear_Expression_t dst, ppl_const_Linear_Expression_t src)
- int ppl_subtract_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t dst, ppl_const_Linear_Expression_t src)
- int ppl_multiply_Linear_Expression_by_Coefficient (ppl_Linear_Expression_t le, ppl_const_Coefficient_t n)
- int ppl_Linear_Expression_space_dimension (ppl_const_Linear_Expression_t le, ppl_dimension_type *m)
- int ppl_Linear_Expression_coefficient (ppl_const_Linear_Expression_t le, ppl_dimension_type var, ppl_Coefficient_t n)
- int ppl_Linear_Expression_inhomogeneous_term (ppl_const_Linear_Expression_t le, ppl_Coefficient_t n)
- int ppl_Linear_Expression_OK (ppl_const_Linear_Expression_t le)
- int ppl_Linear_Expression_is_zero (ppl_const_Linear_Expression_t le)
- int ppl_Linear_Expression_all_homogeneous_terms_are_zero (ppl_const_Linear_Expression_t le)
- int ppl_new_Constraint (ppl_Constraint_t *pc, ppl_const_Linear_Expression_t le, enum ppl_enum_Constraint_Type t)
- int ppl_new_Constraint_zero_dim_false (ppl_Constraint_t *pc)
- int ppl_new_Constraint_zero_dim_positivity (ppl_Constraint_t *pc)
- int ppl_new_Constraint_from_Constraint (ppl_Constraint_t *pc, ppl_const_Constraint_t c)
- int ppl_delete_Constraint (ppl_const_Constraint_t le)
- int ppl_assign_Constraint_from_Constraint (ppl_Constraint_t dst, ppl_const_Constraint_t src)
- int ppl_Constraint_space_dimension (ppl_const_Constraint_t c, ppl_dimension_type *m)
- int ppl_Constraint_type (ppl_const_Constraint_t c)
- int ppl_Constraint_coefficient (ppl_const_Constraint_t c, ppl_dimension_type var, ppl_Coefficient_t n)
- int ppl_Constraint_inhomogeneous_term (ppl_const_Constraint_t c, ppl_Coefficient_t n)
- int ppl_Constraint_OK (ppl_const_Constraint_t c)
- int ppl_new_Linear_Expression_from_Constraint (ppl_Linear_Expression_t *ple, ppl_const_Constraint_t c)
- int ppl_new_Constraint_System (ppl_Constraint_System_t *pcs)
- int ppl_new_Constraint_System_zero_dim_empty (ppl_Constraint_System_t *pcs)
- int ppl_new_Constraint_System_from_Constraint (ppl_Constraint_System_t *pcs, ppl_const_Constraint_t c)
- int ppl_new_Constraint_System_from_Constraint_System (ppl_Constraint_System_t *pcs, ppl_const_Constraint_System_t cs)
- int ppl_delete_Constraint_System (ppl_const_Constraint_System_t cs)
- int ppl_assign_Constraint_System_from_Constraint_System (ppl_Constraint_System_t dst, ppl_const_Constraint_System_t src)

- int ppl_Constraint_System_space_dimension (ppl_const_Constraint_System_t cs, ppl_dimension_type *m)
- int ppl_Constraint_System_empty (ppl_const_Constraint_System_t cs)
- int ppl_Constraint_System_has_strict_inequalities (ppl_const_Constraint_System_t cs)
- int ppl_Constraint_System_clear (ppl_Constraint_System_t cs)
- int ppl_Constraint_System_insert_Constraint (ppl_Constraint_System_t cs, ppl_const_Constraint_t c)
- int ppl_Constraint_System_OK (ppl_const_Constraint_System_t cs)
- int ppl_new_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t *pcit)
- int ppl_new_Constraint_System_const_iterator_from_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t *pcit, ppl_const_Constraint_System_const_iterator_t cit)
- int ppl_delete_Constraint_System_const_iterator (ppl_const_Constraint_System_const_iterator_t cit)
- int ppl_assign_Constraint_System_const_iterator_from_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t dst, ppl_const_Constraint_System_const_iterator_t src)
- int ppl_Constraint_System_begin (ppl_const_Constraint_System_t cs, ppl_Constraint_System_const_iterator_t cit)
- int ppl_Constraint_System_end (ppl_const_Constraint_System_t cs, ppl_Constraint_System_const_iterator_t cit)
- int ppl_Constraint_System_const_iterator_dereference (ppl_const_Constraint_System_const_iterator_t cit, ppl_const_Constraint_t *pc)
- int ppl_Constraint_System_const_iterator_increment (ppl_Constraint_System_const_iterator_t cit)
- int ppl_Constraint_System_const_iterator_equal_test (ppl_const_Constraint_System_const_iterator_t x, ppl_const_Constraint_System_const_iterator_t y)
- int ppl_new_Generator (ppl_Generator_t *pg, ppl_const_Linear_Expression_t le, enum ppl_enum_Generator_Type t, ppl_const_Coefficient_t d)
- int ppl_new_Generator_zero_dim_point (ppl_Generator_t *pg)
- int ppl_new_Generator_zero_dim_closure_point (ppl_Generator_t *pg)
- int ppl_new_Generator_from_Generator (ppl_Generator_t *pg, ppl_const_Generator_t g)
- int ppl_delete_Generator (ppl_const_Generator_t le)
- int ppl_assign_Generator_from_Generator (ppl_Generator_t dst, ppl_const_Generator_t src)
- int ppl_Generator_space_dimension (ppl_const_Generator_t g, ppl_dimension_type *m)
- int ppl_Generator_type (ppl_const_Generator_t g)
- int ppl_Generator_coefficient (ppl_const_Generator_t g, ppl_dimension_type var, ppl_Coefficient_t n)
- int ppl_Generator_divisor (ppl_const_Generator_t g, ppl_Coefficient_t n)
- int ppl_Generator_OK (ppl_const_Generator_t g)
- int ppl_new_Linear_Expression_from_Generator (ppl_Linear_Expression_t *ple, ppl_const_Generator_t g)
- int ppl_new_Generator_System (ppl_Generator_System_t *pgs)
- int ppl_new_Generator_System_zero_dim_univ (ppl_Generator_System_t *pgs)
- int ppl_new_Generator_System_from_Generator (ppl_Generator_System_t *pgs, ppl_const_Generator_t g)
- int ppl_new_Generator_System_from_Generator_System (ppl_Generator_System_t *pgs, ppl_const_Generator_System_t gs)
- int ppl_delete_Generator_System (ppl_const_Generator_System_t gs)
- int ppl_assign_Generator_System_from_Generator_System (ppl_Generator_System_t dst, ppl_const_Generator_System_t src)
- int ppl_Generator_System_space_dimension (ppl_const_Generator_System_t gs, ppl_dimension_type *m)
- int ppl_Generator_System_empty (ppl_const_Generator_System_t gs)

- int ppl_Generator_System_clear (ppl_Generator_System_t gs)
- int ppl_Generator_System_insert_Generator (ppl_Generator_System_t gs, ppl_const_Generator_t g)
- int ppl_Generator_System_OK (ppl_const_Generator_System_t gs)
- int ppl_new_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t *pgit)
- int ppl_new_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t *pgit, ppl_const_Generator_System_const_iterator_t git)
- int ppl_delete_Generator_System_const_iterator (ppl_const_Generator_System_const_iterator_t git)
- int ppl_assign_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t dst, ppl_const_Generator_System_const_iterator_t src)
- int ppl_Generator_System_begin (ppl_const_Generator_System_t gs, ppl_Generator_System_const_iterator_t git)
- int ppl_Generator_System_end (ppl_const_Generator_System_t gs, ppl_Generator_System_const_iterator_t git)
- int ppl_Generator_System_const_iterator_dereference (ppl_const_Generator_System_const_iterator_t git, ppl_const_Generator_t *pg)
- int ppl_Generator_System_const_iterator_increment (ppl_Generator_System_const_iterator_t git)
- int ppl_Generator_System_const_iterator_equal_test (ppl_const_Generator_System_const_iterator_t x, ppl_const_Generator_System_const_iterator_t y)
- int ppl_new_Congruence (ppl_Congruence_t *pc, ppl_const_Linear_Expression_t le, ppl_const_Coefficient_t m)
- int ppl_new_Congruence_zero_dim_false (ppl_Congruence_t *pc)
- int ppl_new_Congruence_zero_dim_integrality (ppl_Congruence_t *pc)
- int ppl_new_Congruence_from_Congruence (ppl_Congruence_t *pc, ppl_const_Congruence_t c)
- int ppl_delete_Congruence (ppl_const_Congruence_t le)
- int ppl_assign_Congruence_from_Congruence (ppl_Congruence_t dst, ppl_const_Congruence_t src)
- int ppl_Congruence_space_dimension (ppl_const_Congruence_t c, ppl_dimension_type *m)
- int ppl_Congruence_coefficient (ppl_const_Congruence_t c, ppl_dimension_type var, ppl_Coefficient_t n)
- int ppl_Congruence_inhomogeneous_term (ppl_const_Congruence_t c, ppl_Coefficient_t n)
- int ppl_Congruence_modulus (ppl_const_Congruence_t c, ppl_Coefficient_t m)
- int ppl_Congruence_OK (ppl_const_Congruence_t c)
- int ppl_new_Linear_Expression_from_Congruence (ppl_Linear_Expression_t *ple, ppl_const_Congruence_t c)
- int ppl_new_Congruence_System (ppl_Congruence_System_t *pcs)
- int ppl_new_Congruence_System_zero_dim_empty (ppl_Congruence_System_t *pcs)
- int ppl_new_Congruence_System_from_Congruence (ppl_Congruence_System_t *pcs, ppl_const_Congruence_t c)
- int ppl_new_Congruence_System_from_Congruence_System (ppl_Congruence_System_t *pcs, ppl_const_Congruence_System_t cs)
- int ppl_delete_Congruence_System (ppl_const_Congruence_System_t cs)
- int ppl_assign_Congruence_System_from_Congruence_System (ppl_Congruence_System_t dst, ppl_const_Congruence_System_t src)
- int ppl_Congruence_System_space_dimension (ppl_const_Congruence_System_t cs, ppl_dimension_type *m)
- int ppl_Congruence_System_empty (ppl_const_Congruence_System_t cs)
- int ppl_Congruence_System_clear (ppl_Congruence_System_t cs)
- int ppl_Congruence_System_insert_Congruence (ppl_Congruence_System_t cs, ppl_const_Congruence_t c)
- int ppl_Congruence_System_OK (ppl_const_Congruence_System_t cs)

- int ppl_new_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t *pcit)
- int ppl_new_Congruence_System_const_iterator_from_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t *pcit, ppl_const_Congruence_System_const_iterator_t cit)
- int ppl_delete_Congruence_System_const_iterator (ppl_const_Congruence_System_const_iterator_t cit)
- int ppl_assign_Congruence_System_const_iterator_from_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t dst, ppl_const_Congruence_System_const_iterator_t src)
- int ppl_Congruence_System_begin (ppl_const_Congruence_System_t cs, ppl_Congruence_System_const_iterator_t cit)
- int ppl_Congruence_System_end (ppl_const_Congruence_System_t cs, ppl_Congruence_System_const_iterator_t cit)
- int ppl_Congruence_System_const_iterator_dereference (ppl_const_Congruence_System_const_iterator_t cit, ppl_const_Congruence_t *pc)
- int ppl_Congruence_System_const_iterator_increment (ppl_Congruence_System_const_iterator_t cit)
- int ppl_Congruence_System_const_iterator_equal_test (ppl_const_Congruence_System_const_iterator_t x, ppl_const_Congruence_System_const_iterator_t y)
- int ppl_new_Grid_Generator (ppl_Grid_Generator_t *pg, ppl_const_Linear_Expression_t le, enum ppl_enum_Grid_Generator_Type t, ppl_const_Coefficient_t d)
- int ppl_new_Grid_Generator_zero_dim_point (ppl_Grid_Generator_t *pg)
- int ppl_new_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t *pg, ppl_const_Grid_Generator_t g)
- int ppl_delete_Grid_Generator (ppl_const_Grid_Generator_t le)
- int ppl_assign_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t dst, ppl_const_Grid_Generator_t src)
- int ppl_Grid_Generator_space_dimension (ppl_const_Grid_Generator_t g, ppl_dimension_type *m)
- int ppl_Grid_Generator_type (ppl_const_Grid_Generator_t g)
- int ppl_Grid_Generator_coefficient (ppl_const_Grid_Generator_t g, ppl_dimension_type var, ppl_Coefficient_t n)
- int ppl_Grid_Generator_divisor (ppl_const_Grid_Generator_t g, ppl_Coefficient_t n)
- int ppl_Grid_Generator_OK (ppl_const_Grid_Generator_t g)
- int ppl_new_Grid_Generator_System (ppl_Grid_Generator_System_t *pgs)
- int ppl_new_Grid_Generator_System_zero_dim_univ (ppl_Grid_Generator_System_t *pgs)
- int ppl_new_Grid_Generator_System_from_Grid_Generator (ppl_Grid_Generator_System_t *pgs, ppl_const_Grid_Generator_t g)
- int ppl_new_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_System_t *pgs, ppl_const_Grid_Generator_System_t gs)
- int ppl_delete_Grid_Generator_System (ppl_const_Grid_Generator_System_t gs)
- int ppl_assign_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_System_t dst, ppl_const_Grid_Generator_System_t src)
- int ppl_Grid_Generator_System_space_dimension (ppl_const_Grid_Generator_System_t gs, ppl_dimension_type *m)
- int ppl_Grid_Generator_System_empty (ppl_const_Grid_Generator_System_t gs)
- int ppl_Grid_Generator_System_clear (ppl_Grid_Generator_System_t gs)
- int ppl_Grid_Generator_System_insert_Grid_Generator (ppl_Grid_Generator_System_t gs, ppl_const_Grid_Generator_t g)
- int ppl_Grid_Generator_System_OK (ppl_const_Grid_Generator_System_t gs)
- int ppl_new_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_const_iterator_t *pgit)

- int ppl_new_Grid_Generator_System_const_iterator_from_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_const_iterator_t *pgit, ppl_const_Grid_Generator_System_const_iterator_t git)
- int ppl_delete_Grid_Generator_System_const_iterator (ppl_const_Grid_Generator_System_const_iterator_t git)
- int ppl_assign_Grid_Generator_System_const_iterator_from_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_const_iterator_t dst, ppl_const_Grid_Generator_System_const_iterator_t src)
- int ppl_Grid_Generator_System_begin (ppl_const_Grid_Generator_System_t gs, ppl_Grid_Generator_System_const_iterator_t git)
- int ppl_Grid_Generator_System_end (ppl_const_Grid_Generator_System_t gs, ppl_Grid_Generator_System_const_iterator_t git)
- int ppl_Grid_Generator_System_const_iterator_dereference (ppl_const_Grid_Generator_System_const_iterator_t git, ppl_const_Grid_Generator_t *pg)
- int ppl_Grid_Generator_System_const_iterator_increment (ppl_Grid_Generator_System_const_iterator_t git)
- int ppl_Grid_Generator_System_const_iterator_equal_test (ppl_const_Grid_Generator_System_const_iterator_t x, ppl_const_Grid_Generator_System_const_iterator_t y)
- int ppl_new_MIP_Problem_from_space_dimension (ppl_MIP_Problem_t *pmip, ppl_dimension_type d)
- int ppl_new_MIP_Problem (ppl_MIP_Problem_t *pmip, ppl_dimension_type d, ppl_const_Constraint_System_t cs, ppl_const_Linear_Expression_t le, int m)
- int ppl_new_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t *pmip, ppl_const_MIP_Problem_t mip)
- int ppl_delete_MIP_Problem (ppl_const_MIP_Problem_t mip)
- int ppl_assign_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t dst, ppl_const_MIP_Problem_t src)
- int ppl_MIP_Problem_space_dimension (ppl_const_MIP_Problem_t mip, ppl_dimension_type *m)
- int ppl_MIP_Problem_number_of_integer_space_dimensions (ppl_const_MIP_Problem_t mip, ppl_dimension_type *m)
- int ppl_MIP_Problem_integer_space_dimensions (ppl_const_MIP_Problem_t mip, ppl_dimension_type ds[ ])
- int ppl_MIP_Problem_number_of_constraints (ppl_const_MIP_Problem_t mip, ppl_dimension_type *m)
- int ppl_MIP_Problem_constraint_at_index (ppl_const_MIP_Problem_t mip, ppl_dimension_type i, ppl_const_Constraint_t *pc)
- int ppl_MIP_Problem_objective_function (ppl_const_MIP_Problem_t mip, ppl_const_Linear_Expression_t *ple)
- int ppl_MIP_Problem_optimization_mode (ppl_const_MIP_Problem_t mip)
- int ppl_MIP_Problem_clear (ppl_MIP_Problem_t mip)
- int ppl_MIP_Problem_add_space_dimensions_and_embed (ppl_MIP_Problem_t mip, ppl_dimension_type d)
- int ppl_MIP_Problem_add_to_integer_space_dimensions (ppl_MIP_Problem_t mip, ppl_dimension_type ds[ ], size_t n)
- int ppl_MIP_Problem_add_constraint (ppl_MIP_Problem_t mip, ppl_const_Constraint_t c)
- int ppl_MIP_Problem_add_constraints (ppl_MIP_Problem_t mip, ppl_const_Constraint_System_t cs)
- int ppl_MIP_Problem_set_objective_function (ppl_MIP_Problem_t mip, ppl_const_Linear_Expression_t le)
- int ppl_MIP_Problem_set_optimization_mode (ppl_MIP_Problem_t mip, int mode)
- int ppl_MIP_Problem_is_satisfiable (ppl_const_MIP_Problem_t mip)
- int ppl_MIP_Problem_solve (ppl_const_MIP_Problem_t mip)

- int ppl_MIP_Problem_evaluate_objective_function (ppl_const_MIP_Problem_t mip, ppl_const_Generator_t g, ppl_Coefficient_t num, ppl_Coefficient_t den)
- int ppl_MIP_Problem_feasible_point (ppl_const_MIP_Problem_t mip, ppl_const_Generator_t *pg)
- int ppl_MIP_Problem_optimizing_point (ppl_const_MIP_Problem_t mip, ppl_const_Generator_t *pg)
- int ppl_MIP_Problem_optimal_value (ppl_const_MIP_Problem_t mip, ppl_Coefficient_t num, ppl_Coefficient_t den)
- int ppl_MIP_Problem_get_control_parameter (ppl_const_MIP_Problem_t mip, int name)
- int ppl_MIP_Problem_set_control_parameter (ppl_MIP_Problem_t mip, int value)
- int ppl_MIP_Problem_OK (ppl_const_MIP_Problem_t mip)
- int ppl_MIP_Problem_total_memory_in_bytes (ppl_const_MIP_Problem_t mip, size_t *sz)
- int ppl_MIP_Problem_external_memory_in_bytes (ppl_const_MIP_Problem_t mip, size_t *sz)
- int ppl_new_PIP_Problem_from_space_dimension (ppl_PIP_Problem_t *ppip, ppl_dimension_type d)
- int ppl_new_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t *dpip, ppl_const_PIP_Problem_t pip)
- int ppl_new_PIP_Problem_from_constraints (ppl_PIP_Problem_t *ppip, ppl_dimension_type d, ppl_Constraint_System_const_iterator_t first, ppl_Constraint_System_const_iterator_t last, size_t n, ppl_dimension_type ds[ ])
- int ppl_assign_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t dst, ppl_const_PIP_Problem_t src)
- int ppl_delete_PIP_Problem (ppl_const_PIP_Problem_t pip)
- int ppl_PIP_Problem_space_dimension (ppl_const_PIP_Problem_t pip, ppl_dimension_type *m)
- int ppl_PIP_Problem_number_of_parameter_space_dimensions (ppl_const_PIP_Problem_t pip, ppl_dimension_type *m)
- int ppl_PIP_Problem_parameter_space_dimensions (ppl_const_PIP_Problem_t pip, ppl_dimension_type ds[ ])
- int ppl_PIP_Problem_number_of_constraints (ppl_const_PIP_Problem_t pip, ppl_dimension_type *m)
- int ppl_PIP_Problem_constraint_at_index (ppl_const_PIP_Problem_t pip, ppl_dimension_type i, ppl_const_Constraint_t *pc)
- int ppl_PIP_Problem_clear (ppl_PIP_Problem_t pip)
- int ppl_PIP_Problem_add_space_dimensions_and_embed (ppl_PIP_Problem_t pip, ppl_dimension_type pip_vars, ppl_dimension_type pip_params)
- int ppl_PIP_Problem_add_to_parameter_space_dimensions (ppl_PIP_Problem_t pip, ppl_dimension_type ds[ ], size_t n)
- int ppl_PIP_Problem_add_constraint (ppl_PIP_Problem_t pip, ppl_const_Constraint_t c)
- int ppl_PIP_Problem_add_constraints (ppl_PIP_Problem_t pip, ppl_const_Constraint_System_t cs)
- int ppl_PIP_Problem_is_satisfiable (ppl_const_PIP_Problem_t pip)
- int ppl_PIP_Problem_solve (ppl_const_PIP_Problem_t pip)
- int ppl_PIP_Problem_solution (ppl_const_PIP_Problem_t pip, ppl_const_PIP_Tree_Node_t *ppip_tree)
- int ppl_PIP_Problem_optimizing_solution (ppl_const_PIP_Problem_t pip, ppl_const_PIP_Tree_Node_t *ppip_tree)
- int ppl_PIP_Problem_OK (ppl_const_PIP_Problem_t pip)
- int ppl_PIP_Problem_get_control_parameter (ppl_const_PIP_Problem_t pip, int name)
- int ppl_PIP_Problem_set_control_parameter (ppl_PIP_Problem_t pip, int value)
- int ppl_PIP_Problem_get_big_parameter_dimension (ppl_const_PIP_Problem_t pip, ppl_dimension_type *pd)
- int ppl_PIP_Problem_set_big_parameter_dimension (ppl_PIP_Problem_t pip, ppl_dimension_type d)

- int ppl_PIP_Problem_total_memory_in_bytes (ppl_const_PIP_Problem_t pip, size_t *sz)
- int ppl_PIP_Problem_external_memory_in_bytes (ppl_const_PIP_Problem_t pip, size_t *sz)
- int ppl_PIP_Tree_Node_as_solution (ppl_const_PIP_Tree_Node_t spip_tree, ppl_const_PIP_Solution_Node_t *dpip_tree)
- int ppl_PIP_Tree_Node_as_decision (ppl_const_PIP_Tree_Node_t spip_tree, ppl_const_PIP_Decision_Node_t *dpip_tree)
- int ppl_PIP_Tree_Node_get_constraints (ppl_const_PIP_Tree_Node_t pip_tree, ppl_const_Constraint_System_t *pcs)
- int ppl_PIP_Tree_Node_OK (ppl_const_PIP_Tree_Node_t pip_tree)
- int ppl_PIP_Tree_Node_number_of_artificials (ppl_const_PIP_Tree_Node_t pip_tree, ppl_dimension_type *m)
- int ppl_PIP_Tree_Node_begin (ppl_const_PIP_Tree_Node_t pip_tree, ppl_Artificial_Parameter_Sequence_const_iterator_t pit)
- int ppl_PIP_Tree_Node_end (ppl_const_PIP_Tree_Node_t pip_tree, ppl_Artificial_Parameter_Sequence_const_iterator_t pit)
- int ppl_PIP_Solution_Node_get_parametric_values (ppl_const_PIP_Solution_Node_t pip_sol, ppl_dimension_type var, ppl_const_Linear_Expression_t *le)
- int ppl_PIP_Solution_Node_OK (ppl_const_PIP_Solution_Node_t pip_sol)
- int ppl_PIP_Decision_Node_OK (ppl_const_PIP_Decision_Node_t pip_dec)
- int ppl_PIP_Decision_Node_get_child_node (ppl_const_PIP_Decision_Node_t pip_dec, int b, ppl_const_PIP_Tree_Node_t *pip_tree)
- int ppl_Artificial_Parameter_get_Linear_Expression (ppl_const_Artificial_Parameter_t ap, ppl_Linear_Expression_t le)
- int ppl_Artificial_Parameter_coefficient (ppl_const_Artificial_Parameter_t ap, ppl_dimension_type var, ppl_Coefficient_t n)
- int ppl_Artificial_Parameter_inhomogeneous_term (ppl_const_Artificial_Parameter_t ap, ppl_Coefficient_t n)
- int ppl_Artificial_Parameter_denominator (ppl_const_Artificial_Parameter_t ap, ppl_Coefficient_t n)
- int ppl_new_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t *papit)
- int ppl_new_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t *papit, ppl_const_Artificial_Parameter_Sequence_const_iterator_t apit)
- int ppl_delete_Artificial_Parameter_Sequence_const_iterator (ppl_const_Artificial_Parameter_Sequence_const_iterator_t apit)
- int ppl_assign_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t dst, ppl_const_Artificial_Parameter_Sequence_const_iterator_t src)
- int ppl_Artificial_Parameter_Sequence_const_iterator_dereference (ppl_const_Artificial_Parameter_Sequence_const_iterator_t apit, ppl_const_Artificial_Parameter_t *pap)
- int ppl_Artificial_Parameter_Sequence_const_iterator_increment (ppl_Artificial_Parameter_Sequence_const_iterator_t apit)
- int ppl_Artificial_Parameter_Sequence_const_iterator_equal_test (ppl_const_Artificial_Parameter_Sequence_const_iterator_t x, ppl_const_Artificial_Parameter_Sequence_const_iterator_t y)
- int ppl_io_print_variable (ppl_dimension_type var)

  Pretty-prints `var` *to* `stdout`.

- int ppl_io_fprint_variable (FILE *stream, ppl_dimension_type var)

  Pretty-prints `var` *to the given output* `stream`.

- int ppl_io_asprint_variable (char **strp, ppl_dimension_type var)

  Pretty-prints `var` to a malloc-allocated string, a pointer to which is returned via `strp`.

- char * ppl_io_wrap_string (const char *src, unsigned indent_depth, unsigned preferred_first_line_-length, unsigned preferred_line_length)

  Utility function for the wrapping of lines of text.

- int ppl_io_set_variable_output_function (ppl_io_variable_output_function_type *p)

  Sets the output function to be used for printing variables to `p`.

- int ppl_io_get_variable_output_function (ppl_io_variable_output_function_type **pp)

  Writes a pointer to the current variable output function to `pp`.

Variables

- error_handler_type Parma_Polyhedra_Library::Interfaces::C::user_error_handler = 0
- ppl_io_variable_output_function_type * Parma_Polyhedra_Library::Interfaces::C::c_variable_-output_function
- Variable::output_function_type * Parma_Polyhedra_Library::Interfaces::C::saved_cxx_Variable_-output_function
- unsigned int PPL_POLY_CON_RELATION_IS_DISJOINT

  Individual bit saying that the polyhedron and the set of points satisfying the constraint are disjoint.

- unsigned int PPL_POLY_CON_RELATION_STRICTLY_INTERSECTS

  Individual bit saying that the polyhedron intersects the set of points satisfying the constraint, but it is not included in it.

- unsigned int PPL_POLY_CON_RELATION_IS_INCLUDED

  Individual bit saying that the polyhedron is included in the set of points satisfying the constraint.

- unsigned int PPL_POLY_CON_RELATION_SATURATES

  Individual bit saying that the polyhedron is included in the set of points saturating the constraint.

- unsigned int PPL_POLY_GEN_RELATION_SUBSUMES

  Individual bit saying that adding the generator would not change the polyhedron.

- unsigned int PPL_COMPLEXITY_CLASS_POLYNOMIAL

  Code of the worst-case polynomial complexity class.

- unsigned int PPL_COMPLEXITY_CLASS_SIMPLEX

  Code of the worst-case exponential but typically polynomial complexity class.

- unsigned int PPL_COMPLEXITY_CLASS_ANY

  Code of the universal complexity class.

- int PPL_MIP_PROBLEM_STATUS_UNFEASIBLE
- int PPL_MIP_PROBLEM_STATUS_UNBOUNDED
- int PPL_MIP_PROBLEM_STATUS_OPTIMIZED
- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_NAME_PRICING

- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_EDGE_FLOAT
- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_EDGE_EXACT
- int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_TEXTBOOK
- int PPL_PIP_PROBLEM_STATUS_UNFEASIBLE
- int PPL_PIP_PROBLEM_STATUS_OPTIMIZED
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_CUTTING_STRATEGY
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_FIRST
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_DEEPEST
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_ALL
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_PIVOT_ROW_STRATEGY
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_FIRST
- int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_MAX_-COLUMN
- int PPL_OPTIMIZATION_MODE_MINIMIZATION
- int PPL_OPTIMIZATION_MODE_MAXIMIZATION

11.5.1 Define Documentation

11.5.1.1 #define CONVERSION (unsigned)

Referenced by Parma_Polyhedra_Library::Interfaces::C::c_variable_default_output_function().

11.5.1.2 #define FORMAT "%u"

Referenced by Parma_Polyhedra_Library::Interfaces::C::c_variable_default_output_function().

11.5.2 Function Documentation

11.5.2.1 catch (...)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.2 catch (deterministic_timeout_exception &)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.3 catch (timeout_exception &)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.4 catch (const std::exception & *e*)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.5 catch (const std::runtime_error & *e*)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.6 catch (const std::overflow_error & *e*)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.7 catch (const std::logic_error & *e*)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.8 catch (const std::length_error & *e*)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.9 catch (const std::domain_error & *e*)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.10 catch (const std::invalid_argument & *e*)

Definition at line 2677 of file ppl_c_implementation_common.cc.

11.5.2.11 int ppl_add_Linear_Expression_to_Linear_Expression (ppl_Linear_Expression_t *dst*, ppl_const_Linear_Expression_t *src*) `[related]`

Definition at line 557 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.12 int ppl_Artificial_Parameter_coefficient (ppl_const_Artificial_Parameter_t *ap*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) `[related]`

Definition at line 2488 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.13 int ppl_Artificial_Parameter_denominator (ppl_const_Artificial_Parameter_t *ap*, ppl_Coefficient_t *n*) `[related]`

Definition at line 2510 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.14 int ppl_Artificial_Parameter_get_Linear_Expression (ppl_const_Artificial_Parameter_t *ap*, ppl_Linear_Expression_t *le*) `[related]`

Definition at line 2478 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.15 int ppl_Artificial_Parameter_inhomogeneous_term (ppl_const_Artificial_Parameter_t *ap*, ppl_Coefficient_t *n*)

Definition at line 2500 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.16 int ppl_Artificial_Parameter_Sequence_const_iterator_dereference (ppl_const_-Artificial_Parameter_Sequence_const_iterator_t *apit*, ppl_const_Artificial_Parameter_t ∗ *pap*) `[related]`

Definition at line 2561 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.17 int ppl_Artificial_Parameter_Sequence_const_iterator_equal_test (ppl_const_Artificial_Parameter_Sequence_const_iterator_t *x*, ppl_const_Artificial_Parameter_Sequence_const_iterator_t *y*) `[related]`

Definition at line 2581 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.18 int ppl_Artificial_Parameter_Sequence_const_iterator_increment (ppl_Artificial_Parameter_Sequence_const_iterator_t *apit*) [related]

Definition at line 2572 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.19 int ppl_assign_Artificial_Parameter_Sequence_const_iterator_from_Artificial_-Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_-iterator_t *dst*, ppl_const_Artificial_Parameter_Sequence_const_iterator_t *src*) [related]

Definition at line 2550 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.20 int ppl_assign_Coefficient_from_Coefficient (ppl_Coefficient_t *dst*, ppl_const_Coefficient_t *src*) [related]

Definition at line 442 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.21 int ppl_assign_Coefficient_from_mpz_t (ppl_Coefficient_t *dst*, mpz_t *z*) [related]

Definition at line 434 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reinterpret_mpz_class(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.22 int ppl_assign_Congruence_from_Congruence (ppl_Congruence_t *dst*, ppl_const_Congruence_t *src*) [related]

Definition at line 1311 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.23 int ppl_assign_Congruence_System_const_iterator_from_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t *dst*, ppl_const_Congruence_System_const_iterator_t *src*) [related]

Definition at line 1496 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.24 int ppl_assign_Congruence_System_from_Congruence_System (ppl_Congruence_System_t *dst*, ppl_const_Congruence_System_t *src*) [related]

Definition at line 1419 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.25 int ppl_assign_Constraint_from_Constraint (ppl_Constraint_t *dst*, ppl_const_Constraint_t *src*) [related]

Definition at line 697 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.26 int ppl_assign_Constraint_System_const_iterator_from_Constraint_System_const_iterator (ppl_Constraint_System_const_iterator_t *dst*, ppl_const_Constraint_System_const_iterator_t *src*) [related]

Definition at line 895 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.27 int ppl_assign_Constraint_System_from_Constraint_System (ppl_Constraint_System_t *dst*, ppl_const_Constraint_System_t *src*) [related]

Definition at line 810 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.28 int ppl_assign_Generator_from_Generator (ppl_Generator_t *dst*, ppl_const_Generator_t *src*) [related]

Definition at line 1017 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.29 int ppl_assign_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t *dst*, ppl_const_Generator_System_const_iterator_t *src*) [related]

Definition at line 1206 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.30 int ppl_assign_Generator_System_from_Generator_System (ppl_Generator_System_t *dst*, ppl_const_Generator_System_t *src*) [related]

Definition at line 1130 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.31 int ppl_assign_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t *dst*, ppl_const_Grid_Generator_t *src*) [related]

Definition at line 1609 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.32 int ppl_assign_Grid_Generator_System_const_iterator_from_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_const_iterator_t *dst*, ppl_const_Grid_Generator_System_const_iterator_t *src*) [related]

Definition at line 1802 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.33 int ppl_assign_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_System_t *dst*, ppl_const_Grid_Generator_System_t *src*) [related]

Definition at line 1724 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.34 int ppl_assign_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t *dst*, ppl_const_Linear_Expression_t *src*) [related]

Definition at line 526 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.35 int ppl_assign_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t *dst*, ppl_const_MIP_Problem_t *src*) [related]

Definition at line 1902 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.36 int ppl_assign_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t *dst*, ppl_const_PIP_Problem_t *src*) [related]

Definition at line 2180 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.37 int ppl_Coefficient_is_bounded (void) [related]

Definition at line 458 of file ppl_c_implementation_common.cc.

11.5.2.38 int ppl_Coefficient_max (mpz_t *max*) [related]

Definition at line 477 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reinterpret_mpz_class().

11.5.2.39 int ppl_Coefficient_min (mpz_t *min*) [related]

Definition at line 464 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reinterpret_mpz_class().

11.5.2.40 int ppl_Coefficient_OK (ppl_const_Coefficient_t) [related]

Definition at line 452 of file ppl_c_implementation_common.cc.

11.5.2.41 int ppl_Coefficient_to_mpz_t (ppl_const_Coefficient_t *c*, mpz_t *z*) [related]

Definition at line 420 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reinterpret_mpz_class(), and Parma_Polyhedra_-Library::Interfaces::C::to_const().

11.5.2.42 int ppl_Congruence_coefficient (ppl_const_Congruence_t *c*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Definition at line 1329 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.43 int ppl_Congruence_inhomogeneous_term (ppl_const_Congruence_t *c*, ppl_Coefficient_t *n*) [related]

Definition at line 1340 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.44 int ppl_Congruence_modulus (ppl_const_Congruence_t *c*, ppl_Coefficient_t *m*) [related]

Definition at line 1350 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.45 int ppl_Congruence_OK (ppl_const_Congruence_t *c*) [related]

Definition at line 1360 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.46 int ppl_Congruence_space_dimension (ppl_const_Congruence_t *c*, ppl_dimension_type * *m*) [related]

Definition at line 1321 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.47 int ppl_Congruence_System_begin (ppl_const_Congruence_System_t *cs*, ppl_Congruence_System_const_iterator_t *cit*) [related]

Definition at line 1506 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.48 int ppl_Congruence_System_clear (ppl_Congruence_System_t *cs*) [related]

Definition at line 1444 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.49 int ppl_Congruence_System_const_iterator_dereference (ppl_const_-Congruence_System_const_iterator_t *cit*, ppl_const_Congruence_t * *pc*) [related]

Definition at line 1527 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.50 int ppl_Congruence_System_const_iterator_equal_test (ppl_const_Congruence_-System_const_iterator_t *x*, ppl_const_Congruence_System_const_iterator_t *y*) [related]

Definition at line 1547 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.51 int ppl_Congruence_System_const_iterator_increment (ppl_Congruence_System_-const_iterator_t *cit*) [related]

Definition at line 1538 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.52 int ppl_Congruence_System_empty (ppl_const_Congruence_System_t *cs*) [related]

Definition at line 1437 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.53 int ppl_Congruence_System_end (ppl_const_Congruence_System_t *cs*, ppl_Congruence_System_const_iterator_t *cit*) [related]

Definition at line 1516 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.54 int ppl_Congruence_System_insert_Congruence (ppl_Congruence_System_t *cs*, ppl_const_Congruence_t *c*) [related]

Definition at line 1451 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.55 int ppl_Congruence_System_OK (ppl_const_Congruence_System_t *cs*) [related]

Definition at line 1461 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.56 int ppl_Congruence_System_space_dimension (ppl_const_Congruence_System_t *cs*, ppl_dimension_type * *m*) [related]

Definition at line 1428 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.57 int ppl_Constraint_coefficient (ppl_const_Constraint_t *c*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Definition at line 730 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.58 int ppl_Constraint_inhomogeneous_term (ppl_const_Constraint_t *c*, ppl_Coefficient_t *n*) [related]

Definition at line 741 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.59 int ppl_Constraint_OK (ppl_const_Constraint_t *c*) [related]

Definition at line 751 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.60 int ppl_Constraint_space_dimension (ppl_const_Constraint_t *c*, ppl_dimension_type * *m*) [related]

Definition at line 707 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.61 int ppl_Constraint_System_begin (ppl_const_Constraint_System_t *cs*, ppl_Constraint_System_const_iterator_t *cit*) [related]

Definition at line 905 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.62 int ppl_Constraint_System_clear (ppl_Constraint_System_t *cs*) [related]

Definition at line 843 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.63 int ppl_Constraint_System_const_iterator_dereference (ppl_const_Constraint_System_const_iterator_t *cit*, ppl_const_Constraint_t * *pc*) [related]

Definition at line 926 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.64 int ppl_Constraint_System_const_iterator_equal_test (ppl_const_Constraint_System_const_iterator_t *x*, ppl_const_Constraint_System_const_iterator_t *y*) [related]

Definition at line 946 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.65 int ppl_Constraint_System_const_iterator_increment (ppl_Constraint_System_const_iterator_t *cit*) [related]

Definition at line 937 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.66 int ppl_Constraint_System_empty (ppl_const_Constraint_System_t *cs*) [related]

Definition at line 828 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.67 int ppl_Constraint_System_end (ppl_const_Constraint_System_t *cs*, ppl_Constraint_System_const_iterator_t *cit*) [related]

Definition at line 915 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.68 int ppl_Constraint_System_has_strict_inequalities (ppl_const_Constraint_System_t *cs*) [related]

Definition at line 836 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.69 int ppl_Constraint_System_insert_Constraint (ppl_Constraint_System_t *cs*, ppl_const_Constraint_t *c*) [related]

Definition at line 850 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.70 int ppl_Constraint_System_OK (ppl_const_Constraint_System_t *cs*) [related]

Definition at line 860 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.71 int ppl_Constraint_System_space_dimension (ppl_const_Constraint_System_t *cs*, ppl_dimension_type * *m*) [related]

Definition at line 819 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.72 int ppl_Constraint_type (ppl_const_Constraint_t *c*) [related]

Definition at line 715 of file ppl_c_implementation_common.cc.

References PPL_CONSTRAINT_TYPE_EQUAL, PPL_CONSTRAINT_TYPE_GREATER_OR_EQUAL, PPL_CONSTRAINT_TYPE_GREATER_THAN, and Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.73 int ppl_delete_Artificial_Parameter_Sequence_const_iterator (ppl_const_Artificial_Parameter_Sequence_const_iterator_t *apit*) [related]

Definition at line 2541 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.74 int ppl_delete_Coefficient (ppl_const_Coefficient_t *c*) [related]

Definition at line 427 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.75 int ppl_delete_Congruence (ppl_const_Congruence_t *le*) [related]

Definition at line 1304 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.76 int ppl_delete_Congruence_System (ppl_const_Congruence_System_t *cs*) [related]

Definition at line 1411 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.77 int ppl_delete_Congruence_System_const_iterator (ppl_const_Congruence_System_-const_iterator_t *cit*) [related]

Definition at line 1487 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.78 int ppl_delete_Constraint (ppl_const_Constraint_t *le*) [related]

Definition at line 690 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.79 int ppl_delete_Constraint_System (ppl_const_Constraint_System_t *cs*) [related]

Definition at line 802 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.80 int ppl_delete_Constraint_System_const_iterator (ppl_const_Constraint_System_-const_iterator_t *cit*) [related]

Definition at line 886 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.81 int ppl_delete_Generator (ppl_const_Generator_t *le*) [related]

Definition at line 1010 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.82 int ppl_delete_Generator_System (ppl_const_Generator_System_t *gs*) [related]

Definition at line 1122 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.83 int ppl_delete_Generator_System_const_iterator (ppl_const_Generator_System_const_-iterator_t *git*) [related]

Definition at line 1198 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.84 int ppl_delete_Grid_Generator (ppl_const_Grid_Generator_t *le*) [related]

Definition at line 1601 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.85 int ppl_delete_Grid_Generator_System (ppl_const_Grid_Generator_System_t *gs*) [related]

Definition at line 1716 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.86 int ppl_delete_Grid_Generator_System_const_iterator (ppl_const_Grid_Generator_-System_const_iterator_t *git*) [related]

Definition at line 1794 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.87 int ppl_delete_Linear_Expression (ppl_const_Linear_Expression_t *le*) [related]

Definition at line 518 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.88 int ppl_delete_MIP_Problem (ppl_const_MIP_Problem_t *mip*) [related]

Definition at line 1895 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.89 int ppl_delete_PIP_Problem (ppl_const_PIP_Problem_t *pip*) [related]

Definition at line 2190 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.90 int ppl_Generator_coefficient (ppl_const_Generator_t *g*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Definition at line 1052 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.91 int ppl_Generator_divisor (ppl_const_Generator_t *g*, ppl_Coefficient_t *n*) [related]

Definition at line 1063 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.92 int ppl_Generator_OK (ppl_const_Generator_t *g*) [related]

Definition at line 1073 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.93 int ppl_Generator_space_dimension (ppl_const_Generator_t *g*, ppl_dimension_type * *m*) [related]

Definition at line 1027 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.94 int ppl_Generator_System_begin (ppl_const_Generator_System_t *gs*, ppl_Generator_System_const_iterator_t *git*) [related]

Definition at line 1216 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.95 int ppl_Generator_System_clear (ppl_Generator_System_t *gs*) [related]

Definition at line 1155 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.96 int ppl_Generator_System_const_iterator_dereference (ppl_const_-Generator_System_const_iterator_t *git*, ppl_const_Generator_t * *pg*) [related]

Definition at line 1237 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.97 int ppl_Generator_System_const_iterator_equal_test (ppl_const_Generator_-System_const_iterator_t *x*, ppl_const_Generator_System_const_iterator_t *y*) [related]

Definition at line 1257 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.98 int ppl_Generator_System_const_iterator_increment (ppl_Generator_System_const_-iterator_t *git*) [related]

Definition at line 1248 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.99 int ppl_Generator_System_empty (ppl_const_Generator_System_t *gs*) [related]

Definition at line 1148 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.100 int ppl_Generator_System_end (ppl_const_Generator_System_t *gs*, ppl_Generator_System_const_iterator_t *git*) [related]

Definition at line 1226 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.101 int ppl_Generator_System_insert_Generator (ppl_Generator_System_t *gs*, ppl_const_Generator_t *g*) [related]

Definition at line 1162 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.102 int ppl_Generator_System_OK (ppl_const_Generator_System_t *gs*) [related]

Definition at line 1172 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.103 int ppl_Generator_System_space_dimension (ppl_const_Generator_System_t *gs*, ppl_dimension_type * *m*) [related]

Definition at line 1139 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.104 int ppl_Generator_type (ppl_const_Generator_t *g*) [related]

Definition at line 1035 of file ppl_c_implementation_common.cc.

References PPL_GENERATOR_TYPE_CLOSURE_POINT, PPL_GENERATOR_TYPE_LINE, PPL_GENERATOR_TYPE_POINT, PPL_GENERATOR_TYPE_RAY, and Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.105 int ppl_Grid_Generator_coefficient (ppl_const_Grid_Generator_t *g*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Definition at line 1642 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.106 int ppl_Grid_Generator_divisor (ppl_const_Grid_Generator_t *g*, ppl_Coefficient_t *n*) [related]

Definition at line 1653 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.107 int ppl_Grid_Generator_OK (ppl_const_Grid_Generator_t *g*) [related]

Definition at line 1663 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.108 int ppl_Grid_Generator_space_dimension (ppl_const_Grid_Generator_t *g*, ppl_dimension_type * *m*) [related]

Definition at line 1619 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.109 int ppl_Grid_Generator_System_begin (ppl_const_Grid_Generator_System_t *gs*, ppl_Grid_Generator_System_const_iterator_t *git*) [related]

Definition at line 1813 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.110 int ppl_Grid_Generator_System_clear (ppl_Grid_Generator_System_t *gs*) [related]

Definition at line 1749 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.111 int ppl_Grid_Generator_System_const_iterator_dereference (ppl_const_Grid_-Generator_System_const_iterator_t *git*, ppl_const_Grid_Generator_t * *pg*) [related]

Definition at line 1835 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.112 int ppl_Grid_Generator_System_const_iterator_equal_test (ppl_const_Grid_Generator_System_const_iterator_t *x*, ppl_const_Grid_Generator_-System_const_iterator_t *y*) [related]

Definition at line 1855 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.113 int ppl_Grid_Generator_System_const_iterator_increment (ppl_Grid_Generator_System_const_iterator_t *git*) [related]

Definition at line 1846 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.114 int ppl_Grid_Generator_System_empty (ppl_const_Grid_Generator_System_t *gs*) [related]

Definition at line 1742 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.115 int ppl_Grid_Generator_System_end (ppl_const_Grid_Generator_System_t *gs*, ppl_Grid_Generator_System_const_iterator_t *git*) [related]

Definition at line 1824 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.116 int ppl_Grid_Generator_System_insert_Grid_Generator (ppl_Grid_Generator_System_t *gs*, ppl_const_Grid_Generator_t *g*) [related]

Definition at line 1757 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.117 int ppl_Grid_Generator_System_OK (ppl_const_Grid_Generator_System_t *gs*) [related]

Definition at line 1767 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.118 int ppl_Grid_Generator_System_space_dimension (ppl_const_Grid_Generator_System_t *gs*, ppl_dimension_type * *m*) [related]

Definition at line 1733 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.119 int ppl_Grid_Generator_type (ppl_const_Grid_Generator_t *g*) [related]

Definition at line 1627 of file ppl_c_implementation_common.cc.

References PPL_GRID_GENERATOR_TYPE_LINE, PPL_GRID_GENERATOR_TYPE_-PARAMETER, PPL_GRID_GENERATOR_TYPE_POINT, and Parma_Polyhedra_-Library::Interfaces::C::to_const().

11.5.2.120 int ppl_Linear_Expression_add_to_coefficient (ppl_Linear_Expression_t *le*, ppl_dimension_type *var*, ppl_const_Coefficient_t *n*) [related]

Definition at line 535 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.121 int ppl_Linear_Expression_add_to_inhomogeneous (ppl_Linear_Expression_t *le*, ppl_const_Coefficient_t *n*) [related]

Definition at line 546 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.122 int ppl_Linear_Expression_all_homogeneous_terms_are_zero (ppl_const_Linear_Expression_t *le*) [related]

Definition at line 628 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.123 int ppl_Linear_Expression_coefficient (ppl_const_Linear_Expression_t *le*, ppl_dimension_type *var*, ppl_Coefficient_t *n*) [related]

Definition at line 594 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.124 int ppl_Linear_Expression_inhomogeneous_term (ppl_const_Linear_Expression_t *le*, ppl_Coefficient_t *n*) [related]

Definition at line 605 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.125 int ppl_Linear_Expression_is_zero (ppl_const_Linear_Expression_t *le*) [related]

Definition at line 621 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.126 int ppl_Linear_Expression_OK (ppl_const_Linear_Expression_t *le*) [related]

Definition at line 615 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.127 int ppl_Linear_Expression_space_dimension (ppl_const_Linear_Expression_t *le*, ppl_dimension_type * *m*) [related]

Definition at line 586 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.128 int ppl_MIP_Problem_add_constraint (ppl_MIP_Problem_t *mip*, ppl_const_Constraint_t *c*) [related]

Definition at line 2010 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.129 int ppl_MIP_Problem_add_constraints (ppl_MIP_Problem_t *mip*, ppl_const_Constraint_System_t *cs*) [related]

Definition at line 2020 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.130 int ppl_MIP_Problem_add_space_dimensions_and_embed (ppl_MIP_Problem_t *mip*, ppl_dimension_type *d*) [related]

Definition at line 1988 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.131 int ppl_MIP_Problem_add_to_integer_space_dimensions (ppl_MIP_Problem_t *mip*, ppl_dimension_type *ds*[ ], size_t *n*) [related]

Definition at line 1997 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.132 int ppl_MIP_Problem_clear (ppl_MIP_Problem_t *mip*) [related]

Definition at line 1981 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.133 int ppl_MIP_Problem_constraint_at_index (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type *i*, ppl_const_Constraint_t * *pc*) [related]

Definition at line 1950 of file ppl_c_implementation_common.cc.

References ppl_MIP_Problem_tag::ppl_MIP_Problem_number_of_constraints(), and Parma_Polyhedra_-Library::Interfaces::C::to_const().

11.5.2.134 int ppl_MIP_Problem_evaluate_objective_function (ppl_const_MIP_Problem_t *mip*, ppl_const_Generator_t *g*, ppl_Coefficient_t *num*, ppl_Coefficient_t *den*) [related]

Definition at line 2062 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.135 int ppl_MIP_Problem_external_memory_in_bytes (ppl_const_MIP_Problem_t *mip*, size_t * *sz*) [related]

Definition at line 2138 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.136 int ppl_MIP_Problem_feasible_point (ppl_const_MIP_Problem_t *mip*, ppl_const_Generator_t * *pg*) [related]

Definition at line 2076 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.137 int ppl_MIP_Problem_get_control_parameter (ppl_const_MIP_Problem_t *mip*, int *name*) [related]

Definition at line 2105 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.138 int ppl_MIP_Problem_integer_space_dimensions (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type *ds*[ ]) [related]

Definition at line 1929 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.139 int ppl_MIP_Problem_is_satisfiable (ppl_const_MIP_Problem_t *mip*) [related]

Definition at line 2050 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.140 int ppl_MIP_Problem_number_of_constraints (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type * *m*) [related]

Definition at line 1941 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.141 int ppl_MIP_Problem_number_of_integer_space_dimensions (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type * *m*) [related]

Definition at line 1920 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.142 int ppl_MIP_Problem_objective_function (ppl_const_MIP_Problem_t *mip*, ppl_const_Linear_Expression_t * *ple*) [related]

Definition at line 1966 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.143 int ppl_MIP_Problem_OK (ppl_const_MIP_Problem_t *mip*) [related]

Definition at line 2124 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.144 int ppl_MIP_Problem_optimal_value (ppl_const_MIP_Problem_t *mip*, ppl_Coefficient_t *num*, ppl_Coefficient_t *den*) [related]

Definition at line 2094 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.145 int ppl_MIP_Problem_optimization_mode (ppl_const_MIP_Problem_t *mip*) [related]

Definition at line 1975 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.146 int ppl_MIP_Problem_optimizing_point (ppl_const_MIP_Problem_t *mip*, ppl_const_Generator_t * *pg*) [related]

Definition at line 2085 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.147 int ppl_MIP_Problem_set_control_parameter (ppl_MIP_Problem_t *mip*, int *value*) [related]

Definition at line 2114 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.148 int ppl_MIP_Problem_set_objective_function (ppl_MIP_Problem_t *mip*, ppl_const_Linear_Expression_t *le*) [related]

Definition at line 2030 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.149 int ppl_MIP_Problem_set_optimization_mode (ppl_MIP_Problem_t *mip*, int *mode*) [related]

Definition at line 2040 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.150 int ppl_MIP_Problem_solve (ppl_const_MIP_Problem_t *mip*) [related]

Definition at line 2056 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.151 int ppl_MIP_Problem_space_dimension (ppl_const_MIP_Problem_t *mip*, ppl_dimension_type * *m*) [related]

Definition at line 1912 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.152 int ppl_MIP_Problem_total_memory_in_bytes (ppl_const_MIP_Problem_t *mip*, size_t * *sz*) [related]

Definition at line 2130 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.153 int ppl_multiply_Linear_Expression_by_Coefficient (ppl_Linear_Expression_t *le*, ppl_const_Coefficient_t *n*) [related]

Definition at line 576 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.154 int ppl_new_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t * *papit*) [related]

Definition at line 2524 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.155 int ppl_new_Artificial_Parameter_Sequence_const_iterator_from_Artificial_Parameter_Sequence_const_iterator (ppl_Artificial_Parameter_Sequence_const_iterator_t * *papit*, ppl_const_Artificial_Parameter_Sequence_const_iterator_t *apit*) [related]

Definition at line 2532 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.156 int ppl_new_Coefficient (ppl_Coefficient_t * *pc*) [related]

Definition at line 397 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.157 int ppl_new_Coefficient_from_Coefficient (ppl_Coefficient_t * *pc*, ppl_const_Coefficient_t *c*) [related]

Definition at line 411 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.158 int ppl_new_Coefficient_from_mpz_t (ppl_Coefficient_t * *pc*, mpz_t *z*) [related]

Definition at line 404 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::reinterpret_mpz_class(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.159 int ppl_new_Congruence (ppl_Congruence_t * *pc*, ppl_const_Linear_Expression_t *le*, ppl_const_Coefficient_t *m*) [related]

Definition at line 1268 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.160 int ppl_new_Congruence_from_Congruence (ppl_Congruence_t * *pc*, ppl_const_Congruence_t *c*) [related]

Definition at line 1295 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.161 int ppl_new_Congruence_System (ppl_Congruence_System_t * *pcs*) [related]

Definition at line 1377 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.162 int ppl_new_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t * *pcit*) [related]

Definition at line 1470 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.163 int ppl_new_Congruence_System_const_iterator_from_Congruence_System_const_iterator (ppl_Congruence_System_const_iterator_t * *pcit*, ppl_const_Congruence_System_const_iterator_t *cit*) [related]

Definition at line 1478 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.164 int ppl_new_Congruence_System_from_Congruence (ppl_Congruence_System_t * *pcs*, ppl_const_Congruence_t *c*) [related]

Definition at line 1393 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.165 int ppl_new_Congruence_System_from_Congruence_System (ppl_Congruence_System_t * *pcs*, ppl_const_Congruence_System_t *cs*) [related]

Definition at line 1403 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.166 int ppl_new_Congruence_System_zero_dim_empty (ppl_Congruence_System_t * *pcs*) [related]

Definition at line 1384 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.167 int ppl_new_Congruence_zero_dim_false (ppl_Congruence_t * *pc*) [related]

Definition at line 1281 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.168 int ppl_new_Congruence_zero_dim_integrality (ppl_Congruence_t * *pc*) [related]

Definition at line 1288 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.169 int ppl_new_Constraint (ppl_Constraint_t * *pc*, ppl_const_Linear_Expression_t *le*, enum ppl_enum_Constraint_Type *t*) [related]

Definition at line 636 of file ppl_c_implementation_common.cc.

References PPL_CONSTRAINT_TYPE_EQUAL, PPL_CONSTRAINT_TYPE_GREATER_OR_-EQUAL, PPL_CONSTRAINT_TYPE_GREATER_THAN, PPL_CONSTRAINT_TYPE_LESS_OR_-EQUAL, PPL_CONSTRAINT_TYPE_LESS_THAN, Parma_Polyhedra_Library::Interfaces::C::to_-const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.170 int ppl_new_Constraint_from_Constraint (ppl_Constraint_t * *pc*, ppl_const_Constraint_t *c*) [related]

Definition at line 681 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.171 int ppl_new_Constraint_System (ppl_Constraint_System_t * *pcs*) [related]

Definition at line 768 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.172 int ppl_new_Constraint_System_const_iterator (ppl_Constraint_System_const_-iterator_t * *pcit*) [related]

Definition at line 869 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.173 int ppl_new_Constraint_System_const_iterator_from_Constraint_-System_const_iterator (ppl_Constraint_System_const_iterator_t * *pcit*, ppl_const_Constraint_System_const_iterator_t *cit*) [related]

Definition at line 877 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.174 int ppl_new_Constraint_System_from_Constraint (ppl_Constraint_System_t * *pcs*, ppl_const_Constraint_t *c*) [related]

Definition at line 784 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.175 int ppl_new_Constraint_System_from_Constraint_System (ppl_Constraint_System_t * *pcs*, ppl_const_Constraint_System_t *cs*) [related]

Definition at line 794 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.176 int ppl_new_Constraint_System_zero_dim_empty (ppl_Constraint_System_t * *pcs*) [related]

Definition at line 775 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.177 int ppl_new_Constraint_zero_dim_false (ppl_Constraint_t * *pc*) [related]

Definition at line 667 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.178 int ppl_new_Constraint_zero_dim_positivity (ppl_Constraint_t * *pc*) [related]

Definition at line 674 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.179 int ppl_new_Generator (ppl_Generator_t * *pg*, ppl_const_Linear_Expression_t *le*, enum ppl_enum_Generator_Type *t*, ppl_const_Coefficient_t *d*) [related]

Definition at line 957 of file ppl_c_implementation_common.cc.

References PPL_GENERATOR_TYPE_CLOSURE_POINT, PPL_GENERATOR_TYPE_LINE, PPL_GENERATOR_TYPE_POINT, PPL_GENERATOR_TYPE_RAY, Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.180 int ppl_new_Generator_from_Generator (ppl_Generator_t * *pg*, ppl_const_Generator_t *g*) [related]

Definition at line 1001 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.181 int ppl_new_Generator_System (ppl_Generator_System_t * *pgs*) [related]

Definition at line 1090 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.182 int ppl_new_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t * *pgit*) [related]

Definition at line 1181 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.183 int ppl_new_Generator_System_const_iterator_from_Generator_System_const_iterator (ppl_Generator_System_const_iterator_t * *pgit*, ppl_const_Generator_System_const_iterator_t *git*) [related]

Definition at line 1189 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.184 int ppl_new_Generator_System_from_Generator (ppl_Generator_System_t * *pgs*, ppl_const_Generator_t *g*) [related]

Definition at line 1104 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.185 int ppl_new_Generator_System_from_Generator_System (ppl_Generator_System_t * *pgs*, ppl_const_Generator_System_t *gs*) [related]

Definition at line 1114 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.186 int ppl_new_Generator_System_zero_dim_univ (ppl_Generator_System_t * *pgs*)

Definition at line 1097 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.187 int ppl_new_Generator_zero_dim_closure_point (ppl_Generator_t * *pg*) [related]

Definition at line 994 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.188 int ppl_new_Generator_zero_dim_point (ppl_Generator_t * *pg*) [related]

Definition at line 987 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.189 int ppl_new_Grid_Generator (ppl_Grid_Generator_t * *pg*, ppl_const_Linear_-Expression_t *le*, enum ppl_enum_Grid_Generator_Type *t*, ppl_const_Coefficient_t *d*) [related]

Definition at line 1558 of file ppl_c_implementation_common.cc.

References PPL_GRID_GENERATOR_TYPE_LINE, PPL_GRID_GENERATOR_-TYPE_PARAMETER, PPL_GRID_GENERATOR_TYPE_POINT, Parma_Polyhedra_-Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.190 int ppl_new_Grid_Generator_from_Grid_Generator (ppl_Grid_Generator_t * *pg*, ppl_const_Grid_Generator_t *g*) [related]

Definition at line 1592 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.191 int ppl_new_Grid_Generator_System (ppl_Grid_Generator_System_t * *pgs*) [related]

Definition at line 1682 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.192 int ppl_new_Grid_Generator_System_const_iterator (ppl_Grid_Generator_System_-const_iterator_t * *pgit*) [related]

Definition at line 1776 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.193 int ppl_new_Grid_Generator_System_const_iterator_from_Grid_Generator_-System_const_iterator (ppl_Grid_Generator_System_const_iterator_t * *pgit*, ppl_const_Grid_Generator_System_const_iterator_t *git*) [related]

Definition at line 1784 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.194 int ppl_new_Grid_Generator_System_from_Grid_Generator (ppl_Grid_Generator_System_t * *pgs*, ppl_const_Grid_Generator_t *g*) [related]

Definition at line 1699 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.195 int ppl_new_Grid_Generator_System_from_Grid_Generator_System (ppl_Grid_Generator_System_t * *pgs*, ppl_const_Grid_Generator_System_t *gs*) [related]

Definition at line 1708 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.196 int ppl_new_Grid_Generator_System_zero_dim_univ (ppl_Grid_Generator_System_t * *pgs*)

Definition at line 1690 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.197 int ppl_new_Grid_Generator_zero_dim_point (ppl_Grid_Generator_t * *pg*) `[related]`

Definition at line 1585 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.198 int ppl_new_Linear_Expression (ppl_Linear_Expression_t * *ple*) `[related]`

Definition at line 492 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.199 int ppl_new_Linear_Expression_from_Congruence (ppl_Linear_Expression_t * *ple*, ppl_const_Congruence_t *c*) `[related]`

Definition at line 1366 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.200 int ppl_new_Linear_Expression_from_Constraint (ppl_Linear_Expression_t * *ple*, ppl_const_Constraint_t *c*) `[related]`

Definition at line 757 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.201 int ppl_new_Linear_Expression_from_Generator (ppl_Linear_Expression_t * *ple*, ppl_const_Generator_t *g*) `[related]`

Definition at line 1079 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.202 int ppl_new_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t * *ple*, ppl_const_Linear_Expression_t *le*) [related]

Definition at line 510 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.203 int ppl_new_Linear_Expression_with_dimension (ppl_Linear_Expression_t * *ple*, ppl_dimension_type *d*) [related]

Definition at line 499 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.204 int ppl_new_MIP_Problem (ppl_MIP_Problem_t * *pmip*, ppl_dimension_type *d*, ppl_const_Constraint_System_t *cs*, ppl_const_Linear_Expression_t *le*, int *m*) [related]

Definition at line 1872 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.205 int ppl_new_MIP_Problem_from_MIP_Problem (ppl_MIP_Problem_t * *pmip*, ppl_const_MIP_Problem_t *mip*) [related]

Definition at line 1886 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.206 int ppl_new_MIP_Problem_from_space_dimension (ppl_MIP_Problem_t * *pmip*, ppl_dimension_type *d*) [related]

Definition at line 1864 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.207 int ppl_new_PIP_Problem_from_constraints (ppl_PIP_Problem_t * *ppip*, ppl_dimension_type *d*, ppl_Constraint_System_const_iterator_t *first*, ppl_Constraint_System_const_iterator_t *last*, size_t *n*, ppl_dimension_type *ds*[ ]) [related]

Definition at line 2164 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.208 int ppl_new_PIP_Problem_from_PIP_Problem (ppl_PIP_Problem_t * *dpip*, ppl_const_PIP_Problem_t *pip*) [related]

Definition at line 2154 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.209 int ppl_new_PIP_Problem_from_space_dimension (ppl_PIP_Problem_t * *ppip*, ppl_dimension_type *d*) [related]

Definition at line 2146 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.210 int ppl_PIP_Decision_Node_get_child_node (ppl_const_PIP_Decision_Node_t *pip_dec*, int *b*, ppl_const_PIP_Tree_Node_t * *pip_tree*) [related]

Definition at line 2468 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.211 int ppl_PIP_Decision_Node_OK (ppl_const_PIP_Decision_Node_t *pip_dec*)

Definition at line 2462 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.212 int ppl_PIP_Problem_add_constraint (ppl_PIP_Problem_t *pip*, ppl_const_Constraint_t *c*) [related]

Definition at line 2278 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.213 int ppl_PIP_Problem_add_constraints (ppl_PIP_Problem_t *pip*, ppl_const_Constraint_System_t *cs*) [related]

Definition at line 2288 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.214 int ppl_PIP_Problem_add_space_dimensions_and_embed (ppl_PIP_Problem_t *pip*, ppl_dimension_type *pip_vars*, ppl_dimension_type *pip_params*) [related]

Definition at line 2256 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.215 int ppl_PIP_Problem_add_to_parameter_space_dimensions (ppl_PIP_Problem_t *pip*, ppl_dimension_type *ds*[ ], size_t *n*) [related]

Definition at line 2266 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.216 int ppl_PIP_Problem_clear (ppl_PIP_Problem_t *pip*) [related]

Definition at line 2250 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.217 int ppl_PIP_Problem_constraint_at_index (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type *i*, ppl_const_Constraint_t * *pc*) [related]

Definition at line 2235 of file ppl_c_implementation_common.cc.

References ppl_PIP_Problem_tag::ppl_PIP_Problem_number_of_constraints(), and Parma_Polyhedra_-Library::Interfaces::C::to_const().

11.5.2.218 int ppl_PIP_Problem_external_memory_in_bytes (ppl_const_PIP_Problem_t *pip*, size_t * *sz*) [related]

Definition at line 2373 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.219 int ppl_PIP_Problem_get_big_parameter_dimension (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *pd*) [related]

Definition at line 2349 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.220 int ppl_PIP_Problem_get_control_parameter (ppl_const_PIP_Problem_t *pip*, int *name*) [related]

Definition at line 2330 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.221 int ppl_PIP_Problem_is_satisfiable (ppl_const_PIP_Problem_t *pip*) [related]

Definition at line 2297 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.222 int ppl_PIP_Problem_number_of_constraints (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *m*) [related]

Definition at line 2226 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.223 int ppl_PIP_Problem_number_of_parameter_space_dimensions (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *m*) [related]

Definition at line 2206 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.224 int ppl_PIP_Problem_OK (ppl_const_PIP_Problem_t *pip*) [related]

Definition at line 2324 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.225 int ppl_PIP_Problem_optimizing_solution (ppl_const_PIP_Problem_t *pip*, ppl_const_PIP_Tree_Node_t * *ppip_tree*) [related]

Definition at line 2316 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.226 int ppl_PIP_Problem_parameter_space_dimensions (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type *ds*[ ]) `[related]`

Definition at line 2214 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.227 int ppl_PIP_Problem_set_big_parameter_dimension (ppl_PIP_Problem_t *pip*, ppl_dimension_type *d*) `[related]`

Definition at line 2357 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.228 int ppl_PIP_Problem_set_control_parameter (ppl_PIP_Problem_t *pip*, int *value*) `[related]`

Definition at line 2339 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_nonconst().

11.5.2.229 int ppl_PIP_Problem_solution (ppl_const_PIP_Problem_t *pip*, ppl_const_PIP_Tree_Node_t * *ppip_tree*) `[related]`

Definition at line 2308 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.230 int ppl_PIP_Problem_solve (ppl_const_PIP_Problem_t *pip*) `[related]`

Definition at line 2302 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.231 int ppl_PIP_Problem_space_dimension (ppl_const_PIP_Problem_t *pip*, ppl_dimension_type * *m*) `[related]`

Definition at line 2197 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.232 int ppl_PIP_Problem_total_memory_in_bytes (ppl_const_PIP_Problem_t *pip*, size_t * *sz*) [related]

Definition at line 2365 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.233 int ppl_PIP_Solution_Node_get_parametric_values (ppl_const_PIP_Solution_Node_t *pip_sol*, ppl_dimension_type *var*, ppl_const_Linear_Expression_t * *le*) [related]

Definition at line 2445 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.234 int ppl_PIP_Solution_Node_OK (ppl_const_PIP_Solution_Node_t *pip_sol*)

Definition at line 2456 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.235 int ppl_PIP_Tree_Node_as_decision (ppl_const_PIP_Tree_Node_t *spip_tree*, ppl_const_PIP_Decision_Node_t * *dpip_tree*) [related]

Definition at line 2389 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.236 int ppl_PIP_Tree_Node_as_solution (ppl_const_PIP_Tree_Node_t *spip_tree*, ppl_const_PIP_Solution_Node_t * *dpip_tree*) [related]

Definition at line 2381 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.237 int ppl_PIP_Tree_Node_begin (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_Artificial_Parameter_Sequence_const_iterator_t *pit*) [related]

Definition at line 2423 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.238 int ppl_PIP_Tree_Node_end (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_Artificial_Parameter_Sequence_const_iterator_t *pit*) [related]

Definition at line 2434 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.2.239 int ppl_PIP_Tree_Node_get_constraints (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_const_Constraint_System_t * *pcs*) [related]

Definition at line 2397 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.240 int ppl_PIP_Tree_Node_number_of_artificials (ppl_const_PIP_Tree_Node_t *pip_tree*, ppl_dimension_type * *m*) [related]

Definition at line 2413 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.241 int ppl_PIP_Tree_Node_OK (ppl_const_PIP_Tree_Node_t *pip_tree*) [related]

Definition at line 2407 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const().

11.5.2.242 int ppl_set_error_handler (error_handler_type *h*)

Definition at line 175 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::user_error_handler.

11.5.2.243 int ppl_subtract_Linear_Expression_from_Linear_Expression (ppl_Linear_Expression_t *dst*, ppl_const_Linear_Expression_t *src*) [related]

Definition at line 567 of file ppl_c_implementation_common.cc.

References Parma_Polyhedra_Library::Interfaces::C::to_const(), and Parma_Polyhedra_-Library::Interfaces::C::to_nonconst().

11.5.3 Variable Documentation

11.5.3.1 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_NAME_PRICING [related]

Definition at line 155 of file ppl_c_implementation_common.cc.

11.5.3.2 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_-EDGE_EXACT [related]

Definition at line 157 of file ppl_c_implementation_common.cc.

11.5.3.3 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_STEEPEST_-EDGE_FLOAT [related]

Definition at line 156 of file ppl_c_implementation_common.cc.

11.5.3.4 int PPL_MIP_PROBLEM_CONTROL_PARAMETER_PRICING_TEXTBOOK [related]

Definition at line 158 of file ppl_c_implementation_common.cc.

11.5.3.5 int PPL_MIP_PROBLEM_STATUS_OPTIMIZED [related]

Definition at line 153 of file ppl_c_implementation_common.cc.

11.5.3.6 int PPL_MIP_PROBLEM_STATUS_UNBOUNDED [related]

Definition at line 152 of file ppl_c_implementation_common.cc.

11.5.3.7 int PPL_MIP_PROBLEM_STATUS_UNFEASIBLE [related]

Definition at line 151 of file ppl_c_implementation_common.cc.

11.5.3.8 int PPL_OPTIMIZATION_MODE_MAXIMIZATION [related]

Definition at line 172 of file ppl_c_implementation_common.cc.

11.5.3.9 int PPL_OPTIMIZATION_MODE_MINIMIZATION [related]

Definition at line 171 of file ppl_c_implementation_common.cc.

11.5.3.10 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_ALL [related]

Definition at line 166 of file ppl_c_implementation_common.cc.

11.5.3.11 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_-DEEPEST [related]

Definition at line 165 of file ppl_c_implementation_common.cc.

11.5.3.12 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_CUTTING_STRATEGY_-FIRST [related]

Definition at line 164 of file ppl_c_implementation_common.cc.

11.5.3.13 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_CUTTING_-STRATEGY [related]

Definition at line 163 of file ppl_c_implementation_common.cc.

11.5.3.14 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_NAME_PIVOT_ROW_-STRATEGY [related]

Definition at line 167 of file ppl_c_implementation_common.cc.

11.5.3.15 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_-FIRST [related]

Definition at line 168 of file ppl_c_implementation_common.cc.

11.5.3.16 int PPL_PIP_PROBLEM_CONTROL_PARAMETER_PIVOT_ROW_STRATEGY_-MAX_COLUMN [related]

Definition at line 169 of file ppl_c_implementation_common.cc.

11.5.3.17 int PPL_PIP_PROBLEM_STATUS_OPTIMIZED [related]

Definition at line 161 of file ppl_c_implementation_common.cc.

11.5.3.18 int PPL_PIP_PROBLEM_STATUS_UNFEASIBLE [related]

Definition at line 160 of file ppl_c_implementation_common.cc.

11.6 ppl_c_implementation_common.defs.hh File Reference

```
#include "ppl.hh"
#include "ppl_c.h"
#include <stdexcept>
#include "ppl_c_implementation_common.inlines.hh"
```

Include dependency graph for ppl_c_implementation_common.defs.hh:



Classes

- class Parma_Polyhedra_Library::Interfaces::C::Array_Partial_Function_Wrapper

  A class to wrap an array of fixed length into a partial function interface suitable for the map_space_-dimension() methods.

- class Parma_Polyhedra_Library::Interfaces::C::timeout_exception
- class Parma_Polyhedra_Library::Interfaces::C::deterministic_timeout_exception

Namespaces

- namespace Parma_Polyhedra_Library
- namespace Parma_Polyhedra_Library::Interfaces
- namespace Parma_Polyhedra_Library::Interfaces::C

Defines

- #define PPL_NO_AUTOMATIC_INITIALIZATION
- #define CATCH_STD_EXCEPTION(exception, code)
- #define CATCH_ALL

- #define DECLARE_CONVERSIONS(Type, CPP_Type)
- #define DEFINE_PRINT_FUNCTIONS(Type)
- #define DEFINE_ASCII_DUMP_FUNCTIONS(Type)
- #define DEFINE_ASCII_LOAD_FUNCTIONS(Type)
- #define DEFINE_ASCII_DUMP_LOAD_FUNCTIONS(Type)
- #define DEFINE_OUTPUT_FUNCTIONS(Type)

Typedefs

- typedef void(∗ Parma_Polyhedra_Library::Interfaces::C::error_handler_type)(enum ppl_enum_error_code code, const char ∗description)

Functions

- void Parma_Polyhedra_Library::Interfaces::C::notify_error (enum ppl_enum_error_code code, const char ∗description)
- Relation_Symbol Parma_Polyhedra_Library::Interfaces::C::relation_symbol (enum ppl_enum_Constraint_Type t)
- Bounded_Integer_Type_Width Parma_Polyhedra_Library::Interfaces::C::bounded_integer_type_width (enum ppl_enum_Bounded_Integer_Type_Width w)
- Bounded_Integer_Type_Representation Parma_Polyhedra_Library::Interfaces::C::bounded_integer_type_representation (enum ppl_enum_Bounded_Integer_Type_Representation r)
- void Parma_Polyhedra_Library::Interfaces::C::reset_timeout ()
- void Parma_Polyhedra_Library::Interfaces::C::reset_deterministic_timeout ()

11.6.1 Define Documentation

11.6.1.1 #define CATCH_ALL

Definition at line 144 of file ppl_c_implementation_common.defs.hh.

11.6.1.2 #define CATCH_STD_EXCEPTION(exception, code)

Value:

```
catch (const std::exception& e) {            \
  notify_error(code, e.what()); \
  return code; \
}
```

Definition at line 138 of file ppl_c_implementation_common.defs.hh.

11.6.1.3 #define DECLARE_CONVERSIONS(Type, CPP_Type)

Definition at line 169 of file ppl_c_implementation_common.defs.hh.

11.6.1.4 #define DEFINE_ASCII_DUMP_FUNCTIONS(Type)

Definition at line 229 of file ppl_c_implementation_common.defs.hh.

11.6.1.5 #define DEFINE_ASCII_DUMP_LOAD_FUNCTIONS(Type)

Value:

```
DEFINE_ASCII_DUMP_FUNCTIONS(Type)             \
  DEFINE_ASCII_LOAD_FUNCTIONS(Type)
```

Definition at line 252 of file ppl_c_implementation_common.defs.hh.

11.6.1.6 #define DEFINE_ASCII_LOAD_FUNCTIONS(Type)

Definition at line 241 of file ppl_c_implementation_common.defs.hh.

11.6.1.7 #define DEFINE_OUTPUT_FUNCTIONS(Type)

Value:

```
DEFINE_PRINT_FUNCTIONS(Type)                  \
  DEFINE_ASCII_DUMP_LOAD_FUNCTIONS(Type)
```

Definition at line 256 of file ppl_c_implementation_common.defs.hh.

11.6.1.8 #define DEFINE_PRINT_FUNCTIONS(Type)

Definition at line 190 of file ppl_c_implementation_common.defs.hh.

11.6.1.9 #define PPL_NO_AUTOMATIC_INITIALIZATION

Definition at line 27 of file ppl_c_implementation_common.defs.hh.

11.7 ppl_c_implementation_common.inlines.hh File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- namespace Parma_Polyhedra_Library
- namespace Parma_Polyhedra_Library::Interfaces
- namespace Parma_Polyhedra_Library::Interfaces::C

Typedefs

- typedef Constraint_System::const_iterator Parma_Polyhedra_Library::Interfaces::C::Constraint_System_const_iterator
- typedef Generator_System::const_iterator Parma_Polyhedra_Library::Interfaces::C::Generator_System_const_iterator
- typedef Congruence_System::const_iterator Parma_Polyhedra_Library::Interfaces::C::Congruence_System_const_iterator
- typedef Grid_Generator_System::const_iterator Parma_Polyhedra_Library::Interfaces::C::Grid_Generator_System_const_iterator
- typedef PIP_Tree_Node::Artificial_Parameter Parma_Polyhedra_Library::Interfaces::C::Artificial_Parameter
- typedef PIP_Tree_Node::Artificial_Parameter_Sequence Parma_Polyhedra_Library::Interfaces::C::Artificial_Parameter_Sequence
- typedef PIP_Tree_Node::Artificial_Parameter_Sequence::const_iterator Parma_Polyhedra_Library::Interfaces::C::Artificial_Parameter_Sequence_const_iterator

Functions

- mpz_class & Parma_Polyhedra_Library::Interfaces::C::reinterpret_mpz_class (mpz_t n)

  Reinterpret an mpz_t as mpz_class.

- const Coefficient * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Coefficient_t x)
- Coefficient * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Coefficient_t x)
- ppl_const_Coefficient_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Coefficient *x)
- ppl_Coefficient_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Coefficient *x)
- const Linear_Expression * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Linear_Expression_t x)
- Linear_Expression * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Linear_Expression_t x)
- ppl_const_Linear_Expression_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Linear_Expression *x)
- ppl_Linear_Expression_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Linear_Expression *x)
- const Constraint * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Constraint_t x)
- Constraint * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Constraint_t x)
- ppl_const_Constraint_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Constraint *x)
- ppl_Constraint_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Constraint *x)
- const Constraint_System * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Constraint_System_t x)
- Constraint_System * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Constraint_System_t x)
- ppl_const_Constraint_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Constraint_System *x)

- ppl_Constraint_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Constraint_System ∗x)
- const Constraint_System_const_iterator ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Constraint_System_const_iterator_t x)
- Constraint_System_const_iterator ∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Constraint_System_const_iterator_t x)
- ppl_const_Constraint_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Constraint_System_const_iterator ∗x)
- ppl_Constraint_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Constraint_System_const_iterator ∗x)
- const Generator ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Generator_t x)
- Generator ∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Generator_t x)
- ppl_const_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Generator ∗x)
- ppl_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Generator ∗x)
- const Generator_System ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Generator_System_t x)
- Generator_System ∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Generator_System_t x)
- ppl_const_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Generator_System ∗x)
- ppl_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Generator_System ∗x)
- const Generator_System_const_iterator ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Generator_System_const_iterator_t x)
- Generator_System_const_iterator ∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Generator_System_const_iterator_t x)
- ppl_const_Generator_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Generator_System_const_iterator ∗x)
- ppl_Generator_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Generator_System_const_iterator ∗x)
- const Congruence ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Congruence_t x)
- Congruence ∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Congruence_t x)
- ppl_const_Congruence_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Congruence ∗x)
- ppl_Congruence_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Congruence ∗x)
- const Congruence_System ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Congruence_System_t x)
- Congruence_System ∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Congruence_System_t x)
- ppl_const_Congruence_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Congruence_System ∗x)
- ppl_Congruence_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Congruence_System ∗x)
- const Congruence_System_const_iterator ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Congruence_System_const_iterator_t x)
- Congruence_System_const_iterator ∗ Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Congruence_System_const_iterator_t x)
- ppl_const_Congruence_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Congruence_System_const_iterator ∗x)
- ppl_Congruence_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Congruence_System_const_iterator ∗x)
- const Grid_Generator ∗ Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Grid_Generator_t x)

- Grid_Generator * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Grid_Generator_t x)
- ppl_const_Grid_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Grid_Generator *x)
- ppl_Grid_Generator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Grid_Generator *x)
- const Grid_Generator_System * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Grid_Generator_System_t x)
- Grid_Generator_System * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Grid_Generator_System_t x)
- ppl_const_Grid_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Grid_Generator_System *x)
- ppl_Grid_Generator_System_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Grid_Generator_System *x)
- const Grid_Generator_System_const_iterator * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Grid_Generator_System_const_iterator_t x)
- Grid_Generator_System_const_iterator * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Grid_Generator_System_const_iterator_t x)
- ppl_const_Grid_Generator_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Grid_Generator_System_const_iterator *x)
- ppl_Grid_Generator_System_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Grid_Generator_System_const_iterator *x)
- const Artificial_Parameter * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Artificial_Parameter_t x)
- Artificial_Parameter * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Artificial_Parameter_t x)
- ppl_const_Artificial_Parameter_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Artificial_Parameter *x)
- ppl_Artificial_Parameter_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Artificial_Parameter *x)
- const Artificial_Parameter_Sequence * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Artificial_Parameter_Sequence_t x)
- Artificial_Parameter_Sequence * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Artificial_Parameter_Sequence_t x)
- ppl_const_Artificial_Parameter_Sequence_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Artificial_Parameter_Sequence *x)
- ppl_Artificial_Parameter_Sequence_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Artificial_Parameter_Sequence *x)
- const Artificial_Parameter_Sequence_const_iterator * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_Artificial_Parameter_Sequence_const_iterator_t x)
- Artificial_Parameter_Sequence_const_iterator * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_Artificial_Parameter_Sequence_const_iterator_t x)
- ppl_const_Artificial_Parameter_Sequence_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_const (const Artificial_Parameter_Sequence_const_iterator *x)
- ppl_Artificial_Parameter_Sequence_const_iterator_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (Artificial_Parameter_Sequence_const_iterator *x)
- const MIP_Problem * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_MIP_Problem_t x)
- MIP_Problem * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_MIP_Problem_t x)
- ppl_const_MIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_const (const MIP_Problem *x)
- ppl_MIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (MIP_Problem *x)

- const PIP_Problem * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Problem_t x)
- PIP_Problem * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Problem_t x)
- ppl_const_PIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Problem *x)
- ppl_PIP_Problem_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Problem *x)
- const PIP_Tree_Node * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Tree_Node_t x)
- PIP_Tree_Node * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Tree_Node_t x)
- ppl_const_PIP_Tree_Node_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Tree_Node *x)
- ppl_PIP_Tree_Node_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Tree_Node *x)
- const PIP_Decision_Node * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Decision_Node_t x)
- PIP_Decision_Node * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Decision_Node_t x)
- ppl_const_PIP_Decision_Node_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Decision_Node *x)
- ppl_PIP_Decision_Node_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Decision_Node *x)
- const PIP_Solution_Node * Parma_Polyhedra_Library::Interfaces::C::to_const (ppl_const_PIP_Solution_Node_t x)
- PIP_Solution_Node * Parma_Polyhedra_Library::Interfaces::C::to_nonconst (ppl_PIP_Solution_Node_t x)
- ppl_const_PIP_Solution_Node_t Parma_Polyhedra_Library::Interfaces::C::to_const (const PIP_Solution_Node *x)
- ppl_PIP_Solution_Node_t Parma_Polyhedra_Library::Interfaces::C::to_nonconst (PIP_Solution_Node *x)
- Relation_Symbol Parma_Polyhedra_Library::Interfaces::C::relation_symbol (enum ppl_enum_Constraint_Type t)
- Bounded_Integer_Type_Width Parma_Polyhedra_Library::Interfaces::C::bounded_integer_type_width (enum ppl_enum_Bounded_Integer_Type_Width w)
- Bounded_Integer_Type_Representation Parma_Polyhedra_Library::Interfaces::C::bounded_integer_type_representation (enum ppl_enum_Bounded_Integer_Type_Representation r)
- Bounded_Integer_Type_Overflow Parma_Polyhedra_Library::Interfaces::C::bounded_integer_type_overflow (enum ppl_enum_Bounded_Integer_Type_Overflow o)

11.8 ppl_c_version.h File Reference

This graph shows which files directly or indirectly include this file:



Defines

- #define PPL_VERSION "0.11.2"

  A string containing the PPL version.

- #define PPL_VERSION_MAJOR 0

  The major number of the PPL version.

- #define PPL_VERSION_MINOR 11

  The minor number of the PPL version.

- #define PPL_VERSION_REVISION 2

  The revision number of the PPL version.

- #define PPL_VERSION_BETA 0

  The beta number of the PPL version. This is zero for official releases and nonzero for development snapshots.

Index

Array_Partial_Function_Wrapper
Parma_Polyhedra_-
Library::Interfaces::C::Array_Partial_-
Function_Wrapper, 59
Artificial_Parameter
Parma_Polyhedra_Library::Interfaces::C, 40
Artificial_Parameter_Sequence
Parma_Polyhedra_Library::Interfaces::C, 40
Artificial_Parameter_Sequence_const_iterator
Parma_Polyhedra_Library::Interfaces::C, 40

bounded_integer_type_overflow
Parma_Polyhedra_Library::Interfaces::C, 41
bounded_integer_type_representation
Parma_Polyhedra_Library::Interfaces::C, 41
bounded_integer_type_width
Parma_Polyhedra_Library::Interfaces::C, 41

C Language Interface, 19
C_interface.dox, 171
ppl_Polyhedron_relation_with_Congruence,
172
c_variable_default_output_function
Parma_Polyhedra_Library::Interfaces::C, 41
c_variable_output_function
Parma_Polyhedra_Library::Interfaces::C, 57
c_variable_output_function_type
Parma_Polyhedra_Library::Interfaces::C, 40
catch
ppl_c_implementation_common.cc, 188, 189
CATCH_ALL
ppl_c_implementation_common.defs.hh, 232
CATCH_STD_EXCEPTION
ppl_c_implementation_common.defs.hh, 232
Congruence_System_const_iterator
Parma_Polyhedra_Library::Interfaces::C, 40
Constraint_System_const_iterator
Parma_Polyhedra_Library::Interfaces::C, 40
CONVERSION
ppl_c_implementation_common.cc, 188
cxx_Variable_output_function
Parma_Polyhedra_Library::Interfaces::C, 42

Datatypes
PPL_BITS_128, 32
PPL_BITS_16, 32
PPL_BITS_32, 32
PPL_BITS_64, 32
PPL_BITS_8, 32
PPL_CONSTRAINT_TYPE_EQUAL, 33
PPL_CONSTRAINT_TYPE_GREATER_-
OR_EQUAL, 33
PPL_CONSTRAINT_TYPE_GREATER_-
THAN, 33
PPL_CONSTRAINT_TYPE_LESS_OR_-
EQUAL, 33
PPL_CONSTRAINT_TYPE_LESS_THAN,
33
PPL_GENERATOR_TYPE_CLOSURE_-
POINT, 33
PPL_GENERATOR_TYPE_LINE, 33
PPL_GENERATOR_TYPE_POINT, 33
PPL_GENERATOR_TYPE_RAY, 33
PPL_GRID_GENERATOR_TYPE_LINE, 33
PPL_GRID_GENERATOR_TYPE_-
PARAMETER, 33
PPL_GRID_GENERATOR_TYPE_POINT,
33
PPL_OVERFLOW_IMPOSSIBLE, 32
PPL_OVERFLOW_UNDEFINED, 32
PPL_OVERFLOW_WRAPS, 32
PPL_SIGNED_2_COMPLEMENT, 32
PPL_UNSIGNED, 32
PPL_COMPLEXITY_CLASS_ANY, 35
PPL_COMPLEXITY_CLASS_-
POLYNOMIAL, 35
PPL_COMPLEXITY_CLASS_SIMPLEX, 35
ppl_const_Pointset_Powerset_C_-
Polyhedron_const_iterator_t, 30
ppl_const_Pointset_Powerset_C_-
Polyhedron_iterator_t, 30
ppl_const_Pointset_Powerset_C_-
Polyhedron_t, 30
ppl_const_Polyhedron_t, 30
ppl_dimension_type, 30
ppl_enum_Bounded_Integer_Type_Overflow,
32
ppl_enum_Bounded_Integer_Type_-
Representation, 32
ppl_enum_Bounded_Integer_Type_Width, 32
ppl_enum_Constraint_Type, 32
ppl_enum_Generator_Type, 33
ppl_enum_Grid_Generator_Type, 33
ppl_io_asprint_variable, 33
ppl_io_fprint_variable, 34
ppl_io_get_variable_output_function, 34
ppl_io_print_variable, 34
ppl_io_set_variable_output_function, 34
ppl_io_variable_output_function_type, 31
ppl_io_wrap_string, 34

ppl_max_space_dimension, 35
ppl_not_a_dimension, 35
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_t, 31
ppl_Pointset_Powerset_C_Polyhedron_-iterator_t, 31
ppl_Pointset_Powerset_C_Polyhedron_t, 31
PPL_POLY_CON_RELATION_IS_-DISJOINT, 35
PPL_POLY_CON_RELATION_IS_-INCLUDED, 36
PPL_POLY_CON_RELATION_-SATURATES, 36
PPL_POLY_CON_RELATION_-STRICTLY_INTERSECTS, 36
PPL_POLY_GEN_RELATION_SUBSUMES, 36
ppl_Polyhedron_t, 31
DECLARE_CONVERSIONS
ppl_c_implementation_common.defs.hh, 232
DEFINE_ASCII_DUMP_FUNCTIONS
ppl_c_implementation_common.defs.hh, 232
DEFINE_ASCII_DUMP_LOAD_FUNCTIONS
ppl_c_implementation_common.defs.hh, 233
DEFINE_ASCII_LOAD_FUNCTIONS
ppl_c_implementation_common.defs.hh, 233
DEFINE_OUTPUT_FUNCTIONS
ppl_c_implementation_common.defs.hh, 233
DEFINE_PRINT_FUNCTIONS
ppl_c_implementation_common.defs.hh, 233

empty
Parma_Polyhedra_-Library::Interfaces::C::Array_Partial_-Function_Wrapper, 60
Error
PPL_ARITHMETIC_OVERFLOW, 25
PPL_ERROR_DOMAIN_ERROR, 25
PPL_ERROR_INTERNAL_ERROR, 25
PPL_ERROR_INVALID_ARGUMENT, 25
PPL_ERROR_LENGTH_ERROR, 25
PPL_ERROR_LOGIC_ERROR, 25
PPL_ERROR_OUT_OF_MEMORY, 25
PPL_ERROR_UNEXPECTED_ERROR, 25
PPL_ERROR_UNKNOWN_STANDARD_-EXCEPTION, 25
PPL_STDIO_ERROR, 25
PPL_TIMEOUT_EXCEPTION, 25
ppl_enum_error_code, 24
ppl_set_error_handler, 25
Error Handling, 24
error_handler_type
Parma_Polyhedra_Library::Interfaces::C, 40

fdl.dox, 172
FORMAT
ppl_c_implementation_common.cc, 188

Generator_System_const_iterator
Parma_Polyhedra_Library::Interfaces::C, 40
gpl.dox, 172
Grid_Generator_System_const_iterator
Parma_Polyhedra_Library::Interfaces::C, 41

Handling, 25
has_empty_codomain
Parma_Polyhedra_-Library::Interfaces::C::Array_Partial_-Function_Wrapper, 59

Init
ppl_finalize, 20
ppl_initialize, 20
ppl_irrational_precision, 20
ppl_restore_pre_PPL_rounding, 20
ppl_set_irrational_precision, 21
ppl_set_rounding_for_PPL, 21

Library Datatypes, 27
Library Initialization and Finalization, 19

maps
Parma_Polyhedra_-Library::Interfaces::C::Array_Partial_-Function_Wrapper, 59
max_in_codomain
Parma_Polyhedra_-Library::Interfaces::C::Array_Partial_-Function_Wrapper, 60
max_in_codomain_
Parma_Polyhedra_-Library::Interfaces::C::Array_Partial_-Function_Wrapper, 60

notify_error
Parma_Polyhedra_Library::Interfaces::C, 42

Parma_Polyhedra_Library, 36
Parma_Polyhedra_Library::Interfaces, 36
Parma_Polyhedra_Library::Interfaces::C, 37
Artificial_Parameter, 40
Artificial_Parameter_Sequence, 40
Artificial_Parameter_Sequence_const_-iterator, 40
bounded_integer_type_overflow, 41
bounded_integer_type_representation, 41
bounded_integer_type_width, 41
c_variable_default_output_function, 41
c_variable_output_function, 57

c_variable_output_function_type, 40
Congruence_System_const_iterator, 40
Constraint_System_const_iterator, 40
cxx_Variable_output_function, 42
error_handler_type, 40
Generator_System_const_iterator, 40
Grid_Generator_System_const_iterator, 41
notify_error, 42
reinterpret_mpz_class, 42
relation_symbol, 42
reset_deterministic_timeout, 42
reset_timeout, 42
saved_cxx_Variable_output_function, 58
to_const, 42–48
to_nonconst, 50–56
user_error_handler, 58
Parma_Polyhedra_Library::Interfaces::C::Array_-Partial_Function_Wrapper, 58
Array_Partial_Function_Wrapper, 59
empty, 60
has_empty_codomain, 59
maps, 59
max_in_codomain, 60
max_in_codomain_, 60
vec, 60
vec_size, 60
Parma_Polyhedra_-Library::Interfaces::C::deterministic_-timeout_exception, 61
priority, 61
throw_me, 61
Parma_Polyhedra_-Library::Interfaces::C::timeout_-exception, 170
priority, 170
throw_me, 170
PPL_ARITHMETIC_OVERFLOW
Error, 25
PPL_BITS_128
Datatypes, 32
PPL_BITS_16
Datatypes, 32
PPL_BITS_32
Datatypes, 32
PPL_BITS_64
Datatypes, 32
PPL_BITS_8
Datatypes, 32
PPL_CONSTRAINT_TYPE_EQUAL
Datatypes, 33
PPL_CONSTRAINT_TYPE_GREATER_OR_-EQUAL
Datatypes, 33
PPL_CONSTRAINT_TYPE_GREATER_THAN
Datatypes, 33
PPL_CONSTRAINT_TYPE_LESS_OR_EQUAL
Datatypes, 33
PPL_CONSTRAINT_TYPE_LESS_THAN
Datatypes, 33
PPL_ERROR_DOMAIN_ERROR
Error, 25
PPL_ERROR_INTERNAL_ERROR
Error, 25
PPL_ERROR_INVALID_ARGUMENT
Error, 25
PPL_ERROR_LENGTH_ERROR
Error, 25
PPL_ERROR_LOGIC_ERROR
Error, 25
PPL_ERROR_OUT_OF_MEMORY
Error, 25
PPL_ERROR_UNEXPECTED_ERROR
Error, 25
PPL_ERROR_UNKNOWN_STANDARD_-EXCEPTION
Error, 25
PPL_GENERATOR_TYPE_CLOSURE_POINT
Datatypes, 33
PPL_GENERATOR_TYPE_LINE
Datatypes, 33
PPL_GENERATOR_TYPE_POINT
Datatypes, 33
PPL_GENERATOR_TYPE_RAY
Datatypes, 33
PPL_GRID_GENERATOR_TYPE_LINE
Datatypes, 33
PPL_GRID_GENERATOR_TYPE_PARAMETER
Datatypes, 33
PPL_GRID_GENERATOR_TYPE_POINT
Datatypes, 33
PPL_OVERFLOW_IMPOSSIBLE
Datatypes, 32
PPL_OVERFLOW_UNDEFINED
Datatypes, 32
PPL_OVERFLOW_WRAPS
Datatypes, 32
PPL_SIGNED_2_COMPLEMENT
Datatypes, 32
PPL_STDIO_ERROR
Error, 25
PPL_TIMEOUT_EXCEPTION
Error, 25
PPL_UNSIGNED
Datatypes, 32
ppl_add_Linear_Expression_to_Linear_Expression
ppl_c_implementation_common.cc, 189
ppl_Linear_Expression_tag, 105
ppl_Artificial_Parameter_coefficient

ppl_Artificial_Parameter_tag, 64
ppl_c_implementation_common.cc, 189
ppl_Artificial_Parameter_denominator
ppl_Artificial_Parameter_tag, 65
ppl_c_implementation_common.cc, 190
ppl_Artificial_Parameter_get_inhomogeneous_-term
ppl_Artificial_Parameter_tag, 65
ppl_Artificial_Parameter_get_Linear_Expression
ppl_Artificial_Parameter_tag, 65
ppl_c_implementation_common.cc, 190
ppl_Artificial_Parameter_inhomogeneous_term
ppl_c_implementation_common.cc, 190
ppl_Artificial_Parameter_Sequence_const_-iterator_dereference
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 62
ppl_c_implementation_common.cc, 190
ppl_Artificial_Parameter_Sequence_const_-iterator_equal_test
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 63
ppl_c_implementation_common.cc, 190
ppl_Artificial_Parameter_Sequence_const_-iterator_increment
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 63
ppl_c_implementation_common.cc, 191
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 61
ppl_Artificial_Parameter_Sequence_const_-iterator_dereference, 62
ppl_Artificial_Parameter_Sequence_const_-iterator_equal_test, 63
ppl_Artificial_Parameter_Sequence_const_-iterator_increment, 63
ppl_delete_Artificial_Parameter_Sequence_-const_iterator, 63
ppl_new_Artificial_Parameter_Sequence_-const_iterator, 63
ppl_Artificial_Parameter_tag, 64
ppl_Artificial_Parameter_coefficient, 64
ppl_Artificial_Parameter_denominator, 65
ppl_Artificial_Parameter_get_-inhomogeneous_term, 65
ppl_Artificial_Parameter_get_Linear_-Expression, 65
ppl_assign_Artificial_Parameter_Sequence_const_-iterator_from_Artificial_Parameter_-Sequence_const_iterator
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 63
ppl_c_implementation_common.cc, 191
ppl_assign_C_Polyhedron_from_C_Polyhedron
ppl_Polyhedron_tag, 150
ppl_assign_Coefficient_from_Coefficient
ppl_c_implementation_common.cc, 191
ppl_Coefficient_tag, 66
ppl_assign_Coefficient_from_mpz_t
ppl_c_implementation_common.cc, 191
ppl_Coefficient_tag, 66
ppl_assign_Congruence_from_Congruence
ppl_c_implementation_common.cc, 191
ppl_Congruence_tag, 75
ppl_assign_Congruence_System_const_iterator_-from_Congruence_System_const_iterator
ppl_c_implementation_common.cc, 191
ppl_Congruence_System_const_iterator_tag, 69
ppl_assign_Congruence_System_from_-Congruence_System
ppl_c_implementation_common.cc, 192
ppl_Congruence_System_tag, 72
ppl_assign_Constraint_from_Constraint
ppl_c_implementation_common.cc, 192
ppl_Constraint_tag, 84
ppl_assign_Constraint_System_const_iterator_-from_Constraint_System_const_iterator
ppl_c_implementation_common.cc, 192
ppl_Constraint_System_const_iterator_tag, 78
ppl_assign_Constraint_System_from_Constraint_-System
ppl_c_implementation_common.cc, 192
ppl_Constraint_System_tag, 81
ppl_assign_Generator_from_Generator
ppl_c_implementation_common.cc, 192
ppl_Generator_tag, 93
ppl_assign_Generator_System_const_iterator_-from_Generator_System_const_iterator
ppl_c_implementation_common.cc, 193
ppl_Generator_System_const_iterator_tag, 87
ppl_assign_Generator_System_from_Generator_-System
ppl_c_implementation_common.cc, 193
ppl_Generator_System_tag, 90
ppl_assign_Grid_Generator_from_Grid_Generator
ppl_c_implementation_common.cc, 193
ppl_Grid_Generator_tag, 102
ppl_assign_Grid_Generator_System_const_-iterator_from_Grid_Generator_System_-const_iterator
ppl_c_implementation_common.cc, 193
ppl_Grid_Generator_System_const_iterator_-tag, 96
ppl_assign_Grid_Generator_System_from_Grid_-Generator_System
ppl_c_implementation_common.cc, 193
ppl_Grid_Generator_System_tag, 98

ppl_assign_Linear_Expression_from_Linear_-Expression
ppl_c_implementation_common.cc, 194
ppl_Linear_Expression_tag, 106
ppl_assign_MIP_Problem_from_MIP_Problem
ppl_c_implementation_common.cc, 194
ppl_MIP_Problem_tag, 112
ppl_assign_NNC_Polyhedron_from_NNC_-Polyhedron
ppl_Polyhedron_tag, 150
ppl_assign_PIP_Problem_from_PIP_Problem
ppl_c_implementation_common.cc, 194
ppl_PIP_Problem_tag, 123
ppl_banner
Version, 23
ppl_c_header.h, 172
PPL_DECLARE_AND_DOCUMENT_-ASCII_DUMP_LOAD_FUNCTIONS, 176
PPL_DECLARE_AND_DOCUMENT_IO_-FUNCTIONS, 176
PPL_DECLARE_AND_DOCUMENT_-PRINT_FUNCTIONS, 176
PPL_DECLARE_ASCII_DUMP_LOAD_-FUNCTIONS, 176
PPL_DECLARE_IO_FUNCTIONS, 176
PPL_DECLARE_PRINT_FUNCTIONS, 176
ppl_new_Generator_System_zero_dim_univ, 177
ppl_new_Grid_Generator_System_zero_-dim_univ, 177
PPL_PROTO, 176
PPL_TYPE_DECLARATION, 176
ppl_c_implementation_common.cc, 177
catch, 188, 189
CONVERSION, 188
FORMAT, 188
ppl_add_Linear_Expression_to_Linear_-Expression, 189
ppl_Artificial_Parameter_coefficient, 189
ppl_Artificial_Parameter_denominator, 190
ppl_Artificial_Parameter_get_Linear_-Expression, 190
ppl_Artificial_Parameter_inhomogeneous_-term, 190
ppl_Artificial_Parameter_Sequence_const_-iterator_dereference, 190
ppl_Artificial_Parameter_Sequence_const_-iterator_equal_test, 190
ppl_Artificial_Parameter_Sequence_const_-iterator_increment, 191
ppl_assign_Artificial_Parameter_Sequence_-const_iterator_from_Artificial_-Parameter_Sequence_const_iterator, 191
ppl_assign_Coefficient_from_Coefficient, 191
ppl_assign_Coefficient_from_mpz_t, 191
ppl_assign_Congruence_from_Congruence, 191
ppl_assign_Congruence_System_const_-iterator_from_Congruence_System_-const_iterator, 191
ppl_assign_Congruence_System_from_-Congruence_System, 192
ppl_assign_Constraint_from_Constraint, 192
ppl_assign_Constraint_System_const_-iterator_from_Constraint_System_-const_iterator, 192
ppl_assign_Constraint_System_from_-Constraint_System, 192
ppl_assign_Generator_from_Generator, 192
ppl_assign_Generator_System_const_-iterator_from_Generator_System_-const_iterator, 193
ppl_assign_Generator_System_from_-Generator_System, 193
ppl_assign_Grid_Generator_from_Grid_-Generator, 193
ppl_assign_Grid_Generator_System_const_-iterator_from_Grid_Generator_System_-const_iterator, 193
ppl_assign_Grid_Generator_System_from_-Grid_Generator_System, 193
ppl_assign_Linear_Expression_from_Linear_-Expression, 194
ppl_assign_MIP_Problem_from_MIP_-Problem, 194
ppl_assign_PIP_Problem_from_PIP_Problem, 194
ppl_Coefficient_is_bounded, 194
ppl_Coefficient_max, 194
ppl_Coefficient_min, 194
ppl_Coefficient_OK, 195
ppl_Coefficient_to_mpz_t, 195
ppl_Congruence_coefficient, 195
ppl_Congruence_inhomogeneous_term, 195
ppl_Congruence_modulus, 195
ppl_Congruence_OK, 195
ppl_Congruence_space_dimension, 196
ppl_Congruence_System_begin, 196
ppl_Congruence_System_clear, 196
ppl_Congruence_System_const_iterator_-dereference, 196
ppl_Congruence_System_const_iterator_-equal_test, 196
ppl_Congruence_System_const_iterator_-increment, 196
ppl_Congruence_System_empty, 197

ppl_Congruence_System_end, 197
ppl_Congruence_System_insert_Congruence, 197
ppl_Congruence_System_OK, 197
ppl_Congruence_System_space_dimension, 197
ppl_Constraint_coefficient, 197
ppl_Constraint_inhomogeneous_term, 198
ppl_Constraint_OK, 198
ppl_Constraint_space_dimension, 198
ppl_Constraint_System_begin, 198
ppl_Constraint_System_clear, 198
ppl_Constraint_System_const_iterator_-dereference, 198
ppl_Constraint_System_const_iterator_-equal_test, 199
ppl_Constraint_System_const_iterator_-increment, 199
ppl_Constraint_System_empty, 199
ppl_Constraint_System_end, 199
ppl_Constraint_System_has_strict_-inequalities, 199
ppl_Constraint_System_insert_Constraint, 199
ppl_Constraint_System_OK, 200
ppl_Constraint_System_space_dimension, 200
ppl_Constraint_type, 200
ppl_delete_Artificial_Parameter_Sequence_-const_iterator, 200
ppl_delete_Coefficient, 200
ppl_delete_Congruence, 200
ppl_delete_Congruence_System, 201
ppl_delete_Congruence_System_const_-iterator, 201
ppl_delete_Constraint, 201
ppl_delete_Constraint_System, 201
ppl_delete_Constraint_System_const_iterator, 201
ppl_delete_Generator, 201
ppl_delete_Generator_System, 201
ppl_delete_Generator_System_const_iterator, 202
ppl_delete_Grid_Generator, 202
ppl_delete_Grid_Generator_System, 202
ppl_delete_Grid_Generator_System_const_-iterator, 202
ppl_delete_Linear_Expression, 202
ppl_delete_MIP_Problem, 202
ppl_delete_PIP_Problem, 203
ppl_Generator_coefficient, 203
ppl_Generator_divisor, 203
ppl_Generator_OK, 203
ppl_Generator_space_dimension, 203
ppl_Generator_System_begin, 203
ppl_Generator_System_clear, 203
ppl_Generator_System_const_iterator_-dereference, 204
ppl_Generator_System_const_iterator_equal_-test, 204
ppl_Generator_System_const_iterator_-increment, 204
ppl_Generator_System_empty, 204
ppl_Generator_System_end, 204
ppl_Generator_System_insert_Generator, 204
ppl_Generator_System_OK, 205
ppl_Generator_System_space_dimension, 205
ppl_Generator_type, 205
ppl_Grid_Generator_coefficient, 205
ppl_Grid_Generator_divisor, 205
ppl_Grid_Generator_OK, 205
ppl_Grid_Generator_space_dimension, 206
ppl_Grid_Generator_System_begin, 206
ppl_Grid_Generator_System_clear, 206
ppl_Grid_Generator_System_const_iterator_-dereference, 206
ppl_Grid_Generator_System_const_iterator_-equal_test, 206
ppl_Grid_Generator_System_const_iterator_-increment, 206
ppl_Grid_Generator_System_empty, 207
ppl_Grid_Generator_System_end, 207
ppl_Grid_Generator_System_insert_Grid_-Generator, 207
ppl_Grid_Generator_System_OK, 207
ppl_Grid_Generator_System_space_-dimension, 207
ppl_Grid_Generator_type, 207
ppl_Linear_Expression_add_to_coefficient, 208
ppl_Linear_Expression_add_to_-inhomogeneous, 208
ppl_Linear_Expression_all_homogeneous_-terms_are_zero, 208
ppl_Linear_Expression_coefficient, 208
ppl_Linear_Expression_inhomogeneous_-term, 208
ppl_Linear_Expression_is_zero, 209
ppl_Linear_Expression_OK, 209
ppl_Linear_Expression_space_dimension, 209
ppl_MIP_Problem_add_constraint, 209
ppl_MIP_Problem_add_constraints, 209
ppl_MIP_Problem_add_space_dimensions_-and_embed, 209
ppl_MIP_Problem_add_to_integer_space_-dimensions, 209
ppl_MIP_Problem_clear, 210
ppl_MIP_Problem_constraint_at_index, 210

PPL_MIP_PROBLEM_CONTROL_-PARAMETER_NAME_PRICING, 229
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_STEEPEST_-EDGE_EXACT, 229
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_STEEPEST_-EDGE_FLOAT, 229
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_TEXTBOOK, 229
ppl_MIP_Problem_evaluate_objective_-function, 210
ppl_MIP_Problem_external_memory_in_-bytes, 210
ppl_MIP_Problem_feasible_point, 210
ppl_MIP_Problem_get_control_parameter, 210
ppl_MIP_Problem_integer_space_-dimensions, 211
ppl_MIP_Problem_is_satisfiable, 211
ppl_MIP_Problem_number_of_constraints, 211
ppl_MIP_Problem_number_of_integer_-space_dimensions, 211
ppl_MIP_Problem_objective_function, 211
ppl_MIP_Problem_OK, 211
ppl_MIP_Problem_optimal_value, 212
ppl_MIP_Problem_optimization_mode, 212
ppl_MIP_Problem_optimizing_point, 212
ppl_MIP_Problem_set_control_parameter, 212
ppl_MIP_Problem_set_objective_function, 212
ppl_MIP_Problem_set_optimization_mode, 212
ppl_MIP_Problem_solve, 213
ppl_MIP_Problem_space_dimension, 213
PPL_MIP_PROBLEM_STATUS_-OPTIMIZED, 229
PPL_MIP_PROBLEM_STATUS_-UNBOUNDED, 229
PPL_MIP_PROBLEM_STATUS_-UNFEASIBLE, 229
ppl_MIP_Problem_total_memory_in_bytes, 213
ppl_multiply_Linear_Expression_by_-Coefficient, 213
ppl_new_Artificial_Parameter_Sequence_-const_iterator, 213
ppl_new_Artificial_Parameter_Sequence_-const_iterator_from_Artificial_-Parameter_Sequence_const_iterator, 213
ppl_new_Coefficient, 214
ppl_new_Coefficient_from_Coefficient, 214
ppl_new_Coefficient_from_mpz_t, 214
ppl_new_Congruence, 214
ppl_new_Congruence_from_Congruence, 214
ppl_new_Congruence_System, 214
ppl_new_Congruence_System_const_iterator, 215
ppl_new_Congruence_System_const_-iterator_from_Congruence_System_-const_iterator, 215
ppl_new_Congruence_System_from_-Congruence, 215
ppl_new_Congruence_System_from_-Congruence_System, 215
ppl_new_Congruence_System_zero_dim_-empty, 215
ppl_new_Congruence_zero_dim_false, 215
ppl_new_Congruence_zero_dim_integrality, 216
ppl_new_Constraint, 216
ppl_new_Constraint_from_Constraint, 216
ppl_new_Constraint_System, 216
ppl_new_Constraint_System_const_iterator, 216
ppl_new_Constraint_System_const_iterator_-from_Constraint_System_const_iterator, 216
ppl_new_Constraint_System_from_-Constraint, 217
ppl_new_Constraint_System_from_-Constraint_System, 217
ppl_new_Constraint_System_zero_dim_-empty, 217
ppl_new_Constraint_zero_dim_false, 217
ppl_new_Constraint_zero_dim_positivity, 217
ppl_new_Generator, 217
ppl_new_Generator_from_Generator, 218
ppl_new_Generator_System, 218
ppl_new_Generator_System_const_iterator, 218
ppl_new_Generator_System_const_iterator_-from_Generator_System_const_iterator, 218
ppl_new_Generator_System_from_Generator, 218
ppl_new_Generator_System_from_-Generator_System, 219
ppl_new_Generator_System_zero_dim_univ, 219
ppl_new_Generator_zero_dim_closure_point, 219
ppl_new_Generator_zero_dim_point, 219

ppl_new_Grid_Generator, 219
ppl_new_Grid_Generator_from_Grid_-Generator, 219
ppl_new_Grid_Generator_System, 220
ppl_new_Grid_Generator_System_const_-iterator, 220
ppl_new_Grid_Generator_System_const_-iterator_from_Grid_Generator_System_-const_iterator, 220
ppl_new_Grid_Generator_System_from_-Grid_Generator, 220
ppl_new_Grid_Generator_System_from_-Grid_Generator_System, 220
ppl_new_Grid_Generator_System_zero_-dim_univ, 220
ppl_new_Grid_Generator_zero_dim_point, 221
ppl_new_Linear_Expression, 221
ppl_new_Linear_Expression_from_-Congruence, 221
ppl_new_Linear_Expression_from_-Constraint, 221
ppl_new_Linear_Expression_from_Generator, 221
ppl_new_Linear_Expression_from_Linear_-Expression, 221
ppl_new_Linear_Expression_with_dimension, 222
ppl_new_MIP_Problem, 222
ppl_new_MIP_Problem_from_MIP_Problem, 222
ppl_new_MIP_Problem_from_space_-dimension, 222
ppl_new_PIP_Problem_from_constraints, 222
ppl_new_PIP_Problem_from_PIP_Problem, 223
ppl_new_PIP_Problem_from_space_-dimension, 223
PPL_OPTIMIZATION_MODE_-MAXIMIZATION, 229
PPL_OPTIMIZATION_MODE_-MINIMIZATION, 229
ppl_PIP_Decision_Node_get_child_node, 223
ppl_PIP_Decision_Node_OK, 223
ppl_PIP_Problem_add_constraint, 223
ppl_PIP_Problem_add_constraints, 223
ppl_PIP_Problem_add_space_dimensions_-and_embed, 224
ppl_PIP_Problem_add_to_parameter_space_-dimensions, 224
ppl_PIP_Problem_clear, 224
ppl_PIP_Problem_constraint_at_index, 224
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_ALL, 230
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_DEEPEST, 230
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_FIRST, 230
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_NAME_CUTTING_-STRATEGY, 230
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_NAME_PIVOT_ROW_-STRATEGY, 230
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_PIVOT_ROW_-STRATEGY_FIRST, 230
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_PIVOT_ROW_-STRATEGY_MAX_COLUMN, 230
ppl_PIP_Problem_external_memory_in_-bytes, 224
ppl_PIP_Problem_get_big_parameter_-dimension, 224
ppl_PIP_Problem_get_control_parameter, 225
ppl_PIP_Problem_is_satisfiable, 225
ppl_PIP_Problem_number_of_constraints, 225
ppl_PIP_Problem_number_of_parameter_-space_dimensions, 225
ppl_PIP_Problem_OK, 225
ppl_PIP_Problem_optimizing_solution, 225
ppl_PIP_Problem_parameter_space_-dimensions, 225
ppl_PIP_Problem_set_big_parameter_-dimension, 226
ppl_PIP_Problem_set_control_parameter, 226
ppl_PIP_Problem_solution, 226
ppl_PIP_Problem_solve, 226
ppl_PIP_Problem_space_dimension, 226
PPL_PIP_PROBLEM_STATUS_-OPTIMIZED, 231
PPL_PIP_PROBLEM_STATUS_-UNFEASIBLE, 231
ppl_PIP_Problem_total_memory_in_bytes, 226
ppl_PIP_Solution_Node_get_parametric_-values, 227
ppl_PIP_Solution_Node_OK, 227
ppl_PIP_Tree_Node_as_decision, 227
ppl_PIP_Tree_Node_as_solution, 227
ppl_PIP_Tree_Node_begin, 227
ppl_PIP_Tree_Node_end, 227
ppl_PIP_Tree_Node_get_constraints, 228

ppl_PIP_Tree_Node_number_of_artificials, 228
ppl_PIP_Tree_Node_OK, 228
ppl_set_error_handler, 228
ppl_subtract_Linear_Expression_from_-Linear_Expression, 228
ppl_c_implementation_common.defs.hh, 231
CATCH_ALL, 232
CATCH_STD_EXCEPTION, 232
DECLARE_CONVERSIONS, 232
DEFINE_ASCII_DUMP_FUNCTIONS, 232
DEFINE_ASCII_DUMP_LOAD_-FUNCTIONS, 233
DEFINE_ASCII_LOAD_FUNCTIONS, 233
DEFINE_OUTPUT_FUNCTIONS, 233
DEFINE_PRINT_FUNCTIONS, 233
PPL_NO_AUTOMATIC_INITIALIZATION, 233
ppl_c_implementation_common.inlines.hh, 233
ppl_c_version.h, 237
ppl_Coefficient_is_bounded
ppl_c_implementation_common.cc, 194
ppl_Coefficient_tag, 67
ppl_Coefficient_max
ppl_c_implementation_common.cc, 194
ppl_Coefficient_tag, 67
ppl_Coefficient_min
ppl_c_implementation_common.cc, 194
ppl_Coefficient_tag, 67
ppl_Coefficient_OK
ppl_c_implementation_common.cc, 195
ppl_Coefficient_tag, 67
ppl_Coefficient_tag, 65
ppl_assign_Coefficient_from_Coefficient, 66
ppl_assign_Coefficient_from_mpz_t, 66
ppl_Coefficient_is_bounded, 67
ppl_Coefficient_max, 67
ppl_Coefficient_min, 67
ppl_Coefficient_OK, 67
ppl_Coefficient_to_mpz_t, 67
ppl_delete_Coefficient, 67
ppl_new_Coefficient, 67
ppl_new_Coefficient_from_Coefficient, 68
ppl_new_Coefficient_from_mpz_t, 68
ppl_Coefficient_to_mpz_t
ppl_c_implementation_common.cc, 195
ppl_Coefficient_tag, 67
PPL_COMPLEXITY_CLASS_ANY
Datatypes, 35
PPL_COMPLEXITY_CLASS_POLYNOMIAL
Datatypes, 35
PPL_COMPLEXITY_CLASS_SIMPLEX
Datatypes, 35
ppl_Congruence_coefficient
ppl_c_implementation_common.cc, 195
ppl_Congruence_tag, 75
ppl_Congruence_inhomogeneous_term
ppl_c_implementation_common.cc, 195
ppl_Congruence_tag, 75
ppl_Congruence_modulus
ppl_c_implementation_common.cc, 195
ppl_Congruence_tag, 76
ppl_Congruence_OK
ppl_c_implementation_common.cc, 195
ppl_Congruence_tag, 76
ppl_Congruence_space_dimension
ppl_c_implementation_common.cc, 196
ppl_Congruence_tag, 76
ppl_Congruence_System_begin
ppl_c_implementation_common.cc, 196
ppl_Congruence_System_tag, 72
ppl_Congruence_System_clear
ppl_c_implementation_common.cc, 196
ppl_Congruence_System_tag, 72
ppl_Congruence_System_const_iterator_-dereference
ppl_c_implementation_common.cc, 196
ppl_Congruence_System_const_iterator_tag, 69
ppl_Congruence_System_const_iterator_equal_test
ppl_c_implementation_common.cc, 196
ppl_Congruence_System_const_iterator_tag, 69
ppl_Congruence_System_const_iterator_increment
ppl_c_implementation_common.cc, 196
ppl_Congruence_System_const_iterator_tag, 70
ppl_Congruence_System_const_iterator_tag, 68
ppl_assign_Congruence_System_const_-iterator_from_Congruence_System_-const_iterator, 69
ppl_Congruence_System_const_iterator_-dereference, 69
ppl_Congruence_System_const_iterator_-equal_test, 69
ppl_Congruence_System_const_iterator_-increment, 70
ppl_delete_Congruence_System_const_-iterator, 70
ppl_new_Congruence_System_const_iterator, 70
ppl_new_Congruence_System_const_-iterator_from_Congruence_System_-const_iterator, 70
ppl_Congruence_System_empty
ppl_c_implementation_common.cc, 197
ppl_Congruence_System_tag, 72
ppl_Congruence_System_end

ppl_c_implementation_common.cc, 197
ppl_Congruence_System_tag, 72
ppl_Congruence_System_insert_Congruence
ppl_c_implementation_common.cc, 197
ppl_Congruence_System_tag, 73
ppl_Congruence_System_OK
ppl_c_implementation_common.cc, 197
ppl_Congruence_System_tag, 73
ppl_Congruence_System_space_dimension
ppl_c_implementation_common.cc, 197
ppl_Congruence_System_tag, 73
ppl_Congruence_System_tag, 70
ppl_assign_Congruence_System_from_-Congruence_System, 72
ppl_Congruence_System_begin, 72
ppl_Congruence_System_clear, 72
ppl_Congruence_System_empty, 72
ppl_Congruence_System_end, 72
ppl_Congruence_System_insert_Congruence, 73
ppl_Congruence_System_OK, 73
ppl_Congruence_System_space_dimension, 73
ppl_delete_Congruence_System, 73
ppl_new_Congruence_System, 73
ppl_new_Congruence_System_from_-Congruence, 73
ppl_new_Congruence_System_from_-Congruence_System, 73
ppl_new_Congruence_System_zero_dim_-empty, 74
ppl_Congruence_tag, 74
ppl_assign_Congruence_from_Congruence, 75
ppl_Congruence_coefficient, 75
ppl_Congruence_inhomogeneous_term, 75
ppl_Congruence_modulus, 76
ppl_Congruence_OK, 76
ppl_Congruence_space_dimension, 76
ppl_delete_Congruence, 76
ppl_new_Congruence, 76
ppl_new_Congruence_from_Congruence, 76
ppl_new_Congruence_zero_dim_false, 77
ppl_new_Congruence_zero_dim_integrality, 77
ppl_const_Pointset_Powerset_C_Polyhedron_-const_iterator_t
Datatypes, 30
ppl_const_Pointset_Powerset_C_Polyhedron_-iterator_t
Datatypes, 30
ppl_const_Pointset_Powerset_C_Polyhedron_t
Datatypes, 30
ppl_const_Polyhedron_t
Datatypes, 30
ppl_Constraint_coefficient
ppl_c_implementation_common.cc, 197
ppl_Constraint_tag, 84
ppl_Constraint_inhomogeneous_term
ppl_c_implementation_common.cc, 198
ppl_Constraint_tag, 84
ppl_Constraint_OK
ppl_c_implementation_common.cc, 198
ppl_Constraint_tag, 85
ppl_Constraint_space_dimension
ppl_c_implementation_common.cc, 198
ppl_Constraint_tag, 85
ppl_Constraint_System_begin
ppl_c_implementation_common.cc, 198
ppl_Constraint_System_tag, 81
ppl_Constraint_System_clear
ppl_c_implementation_common.cc, 198
ppl_Constraint_System_tag, 81
ppl_Constraint_System_const_iterator_dereference
ppl_c_implementation_common.cc, 198
ppl_Constraint_System_const_iterator_tag, 78
ppl_Constraint_System_const_iterator_equal_test
ppl_c_implementation_common.cc, 199
ppl_Constraint_System_const_iterator_tag, 78
ppl_Constraint_System_const_iterator_increment
ppl_c_implementation_common.cc, 199
ppl_Constraint_System_const_iterator_tag, 79
ppl_Constraint_System_const_iterator_tag, 77
ppl_assign_Constraint_System_const_-iterator_from_Constraint_System_-const_iterator, 78
ppl_Constraint_System_const_iterator_-dereference, 78
ppl_Constraint_System_const_iterator_-equal_test, 78
ppl_Constraint_System_const_iterator_-increment, 79
ppl_delete_Constraint_System_const_iterator, 79
ppl_new_Constraint_System_const_iterator, 79
ppl_new_Constraint_System_const_iterator_-from_Constraint_System_const_iterator, 79
ppl_Constraint_System_empty
ppl_c_implementation_common.cc, 199
ppl_Constraint_System_tag, 81
ppl_Constraint_System_end
ppl_c_implementation_common.cc, 199
ppl_Constraint_System_tag, 81
ppl_Constraint_System_has_strict_inequalities
ppl_c_implementation_common.cc, 199
ppl_Constraint_System_tag, 81

ppl_Constraint_System_insert_Constraint
ppl_c_implementation_common.cc, 199
ppl_Constraint_System_tag, 82
ppl_Constraint_System_OK
ppl_c_implementation_common.cc, 200
ppl_Constraint_System_tag, 82
ppl_Constraint_System_space_dimension
ppl_c_implementation_common.cc, 200
ppl_Constraint_System_tag, 82
ppl_Constraint_System_tag, 79
ppl_assign_Constraint_System_from_-Constraint_System, 81
ppl_Constraint_System_begin, 81
ppl_Constraint_System_clear, 81
ppl_Constraint_System_empty, 81
ppl_Constraint_System_end, 81
ppl_Constraint_System_has_strict_-inequalities, 81
ppl_Constraint_System_insert_Constraint, 82
ppl_Constraint_System_OK, 82
ppl_Constraint_System_space_dimension, 82
ppl_delete_Constraint_System, 82
ppl_new_Constraint_System, 82
ppl_new_Constraint_System_from_-Constraint, 82
ppl_new_Constraint_System_from_-Constraint_System, 83
ppl_new_Constraint_System_zero_dim_-empty, 83
ppl_Constraint_tag, 83
ppl_assign_Constraint_from_Constraint, 84
ppl_Constraint_coefficient, 84
ppl_Constraint_inhomogeneous_term, 84
ppl_Constraint_OK, 85
ppl_Constraint_space_dimension, 85
ppl_Constraint_type, 85
ppl_delete_Constraint, 85
ppl_new_Constraint, 85
ppl_new_Constraint_from_Constraint, 85
ppl_new_Constraint_zero_dim_false, 86
ppl_new_Constraint_zero_dim_positivity, 86
ppl_Constraint_type
ppl_c_implementation_common.cc, 200
ppl_Constraint_tag, 85
PPL_DECLARE_AND_DOCUMENT_ASCII_-DUMP_LOAD_FUNCTIONS
ppl_c_header.h, 176
PPL_DECLARE_AND_DOCUMENT_IO_-FUNCTIONS
ppl_c_header.h, 176
PPL_DECLARE_AND_DOCUMENT_PRINT_-FUNCTIONS
ppl_c_header.h, 176
PPL_DECLARE_ASCII_DUMP_LOAD_-FUNCTIONS
ppl_c_header.h, 176
PPL_DECLARE_IO_FUNCTIONS
ppl_c_header.h, 176
PPL_DECLARE_PRINT_FUNCTIONS
ppl_c_header.h, 176
ppl_delete_Artificial_Parameter_Sequence_const_-iterator
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 63
ppl_c_implementation_common.cc, 200
ppl_delete_Coefficient
ppl_c_implementation_common.cc, 200
ppl_Coefficient_tag, 67
ppl_delete_Congruence
ppl_c_implementation_common.cc, 200
ppl_Congruence_tag, 76
ppl_delete_Congruence_System
ppl_c_implementation_common.cc, 201
ppl_Congruence_System_tag, 73
ppl_delete_Congruence_System_const_iterator
ppl_c_implementation_common.cc, 201
ppl_Congruence_System_const_iterator_tag, 70
ppl_delete_Constraint
ppl_c_implementation_common.cc, 201
ppl_Constraint_tag, 85
ppl_delete_Constraint_System
ppl_c_implementation_common.cc, 201
ppl_Constraint_System_tag, 82
ppl_delete_Constraint_System_const_iterator
ppl_c_implementation_common.cc, 201
ppl_Constraint_System_const_iterator_tag, 79
ppl_delete_Generator
ppl_c_implementation_common.cc, 201
ppl_Generator_tag, 93
ppl_delete_Generator_System
ppl_c_implementation_common.cc, 201
ppl_Generator_System_tag, 90
ppl_delete_Generator_System_const_iterator
ppl_c_implementation_common.cc, 202
ppl_Generator_System_const_iterator_tag, 87
ppl_delete_Grid_Generator
ppl_c_implementation_common.cc, 202
ppl_Grid_Generator_tag, 102
ppl_delete_Grid_Generator_System
ppl_c_implementation_common.cc, 202
ppl_Grid_Generator_System_tag, 98
ppl_delete_Grid_Generator_System_const_iterator
ppl_c_implementation_common.cc, 202
ppl_Grid_Generator_System_const_iterator_-tag, 96
ppl_delete_Linear_Expression

ppl_c_implementation_common.cc, 202
ppl_Linear_Expression_tag, 106
ppl_delete_MIP_Problem
ppl_c_implementation_common.cc, 202
ppl_MIP_Problem_tag, 112
ppl_delete_PIP_Problem
ppl_c_implementation_common.cc, 203
ppl_PIP_Problem_tag, 123
ppl_delete_Pointset_Powerset_C_Polyhedron_-const_iterator
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 133
ppl_delete_Pointset_Powerset_C_Polyhedron_-iterator
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 135
ppl_delete_Polyhedron
ppl_Polyhedron_tag, 150
ppl_dimension_type
Datatypes, 30
ppl_enum_Bounded_Integer_Type_Overflow
Datatypes, 32
ppl_enum_Bounded_Integer_Type_Representation
Datatypes, 32
ppl_enum_Bounded_Integer_Type_Width
Datatypes, 32
ppl_enum_Constraint_Type
Datatypes, 32
ppl_enum_error_code
Error, 24
ppl_enum_Generator_Type
Datatypes, 33
ppl_enum_Grid_Generator_Type
Datatypes, 33
ppl_finalize
Init, 20
ppl_Generator_coefficient
ppl_c_implementation_common.cc, 203
ppl_Generator_tag, 93
ppl_Generator_divisor
ppl_c_implementation_common.cc, 203
ppl_Generator_tag, 93
ppl_Generator_OK
ppl_c_implementation_common.cc, 203
ppl_Generator_tag, 93
ppl_Generator_space_dimension
ppl_c_implementation_common.cc, 203
ppl_Generator_tag, 94
ppl_Generator_System_begin
ppl_c_implementation_common.cc, 203
ppl_Generator_System_tag, 90
ppl_Generator_System_clear
ppl_c_implementation_common.cc, 203
ppl_Generator_System_tag, 90
ppl_Generator_System_const_iterator_dereference
ppl_c_implementation_common.cc, 204
ppl_Generator_System_const_iterator_tag, 87
ppl_Generator_System_const_iterator_equal_test
ppl_c_implementation_common.cc, 204
ppl_Generator_System_const_iterator_tag, 88
ppl_Generator_System_const_iterator_increment
ppl_c_implementation_common.cc, 204
ppl_Generator_System_const_iterator_tag, 88
ppl_Generator_System_const_iterator_tag, 86
ppl_assign_Generator_System_const_-iterator_from_Generator_System_-const_iterator, 87
ppl_delete_Generator_System_const_iterator, 87
ppl_Generator_System_const_iterator_-dereference, 87
ppl_Generator_System_const_iterator_equal_-test, 88
ppl_Generator_System_const_iterator_-increment, 88
ppl_new_Generator_System_const_iterator, 88
ppl_new_Generator_System_const_iterator_-from_Generator_System_const_iterator, 88
ppl_Generator_System_empty
ppl_c_implementation_common.cc, 204
ppl_Generator_System_tag, 90
ppl_Generator_System_end
ppl_c_implementation_common.cc, 204
ppl_Generator_System_tag, 90
ppl_Generator_System_insert_Generator
ppl_c_implementation_common.cc, 204
ppl_Generator_System_tag, 91
ppl_Generator_System_OK
ppl_c_implementation_common.cc, 205
ppl_Generator_System_tag, 91
ppl_Generator_System_space_dimension
ppl_c_implementation_common.cc, 205
ppl_Generator_System_tag, 91
ppl_Generator_System_tag, 88
ppl_assign_Generator_System_from_-Generator_System, 90
ppl_delete_Generator_System, 90
ppl_Generator_System_begin, 90
ppl_Generator_System_clear, 90
ppl_Generator_System_empty, 90
ppl_Generator_System_end, 90
ppl_Generator_System_insert_Generator, 91
ppl_Generator_System_OK, 91
ppl_Generator_System_space_dimension, 91
ppl_new_Generator_System, 91

ppl_new_Generator_System_from_Generator, 91
ppl_new_Generator_System_from_-Generator_System, 91
ppl_Generator_tag, 92
ppl_assign_Generator_from_Generator, 93
ppl_delete_Generator, 93
ppl_Generator_coefficient, 93
ppl_Generator_divisor, 93
ppl_Generator_OK, 93
ppl_Generator_space_dimension, 94
ppl_Generator_type, 94
ppl_new_Generator, 94
ppl_new_Generator_from_Generator, 94
ppl_new_Generator_zero_dim_closure_point, 94
ppl_new_Generator_zero_dim_point, 94
ppl_Generator_type
ppl_c_implementation_common.cc, 205
ppl_Generator_tag, 94
ppl_Grid_Generator_coefficient
ppl_c_implementation_common.cc, 205
ppl_Grid_Generator_tag, 102
ppl_Grid_Generator_divisor
ppl_c_implementation_common.cc, 205
ppl_Grid_Generator_tag, 102
ppl_Grid_Generator_OK
ppl_c_implementation_common.cc, 205
ppl_Grid_Generator_tag, 102
ppl_Grid_Generator_space_dimension
ppl_c_implementation_common.cc, 206
ppl_Grid_Generator_tag, 102
ppl_Grid_Generator_System_begin
ppl_c_implementation_common.cc, 206
ppl_Grid_Generator_System_tag, 99
ppl_Grid_Generator_System_clear
ppl_c_implementation_common.cc, 206
ppl_Grid_Generator_System_tag, 99
ppl_Grid_Generator_System_const_iterator_-dereference
ppl_c_implementation_common.cc, 206
ppl_Grid_Generator_System_const_iterator_-tag, 96
ppl_Grid_Generator_System_const_iterator_-equal_test
ppl_c_implementation_common.cc, 206
ppl_Grid_Generator_System_const_iterator_-tag, 96
ppl_Grid_Generator_System_const_iterator_-increment
ppl_c_implementation_common.cc, 206
ppl_Grid_Generator_System_const_iterator_-tag, 96
ppl_Grid_Generator_System_const_iterator_tag, 95
ppl_delete_Grid_Generator_System_const_-iterator, 96
ppl_Grid_Generator_System_const_iterator_-dereference, 96
ppl_Grid_Generator_System_const_iterator_-equal_test, 96
ppl_Grid_Generator_System_const_iterator_-increment, 96
ppl_new_Grid_Generator_System_const_-iterator, 96
ppl_Grid_Generator_System_empty
ppl_c_implementation_common.cc, 207
ppl_Grid_Generator_System_tag, 99
ppl_Grid_Generator_System_end
ppl_c_implementation_common.cc, 207
ppl_Grid_Generator_System_tag, 99
ppl_Grid_Generator_System_insert_Grid_-Generator
ppl_c_implementation_common.cc, 207
ppl_Grid_Generator_System_tag, 99
ppl_Grid_Generator_System_OK
ppl_c_implementation_common.cc, 207
ppl_Grid_Generator_System_tag, 99
ppl_Grid_Generator_System_space_dimension
ppl_c_implementation_common.cc, 207
ppl_Grid_Generator_System_tag, 100
ppl_Grid_Generator_System_tag, 97
ppl_assign_Grid_Generator_System_from_-Grid_Generator_System, 98
ppl_delete_Grid_Generator_System, 98
ppl_Grid_Generator_System_begin, 99
ppl_Grid_Generator_System_clear, 99
ppl_Grid_Generator_System_empty, 99
ppl_Grid_Generator_System_end, 99
ppl_Grid_Generator_System_insert_Grid_-Generator, 99
ppl_Grid_Generator_System_OK, 99
ppl_Grid_Generator_System_space_-dimension, 100
ppl_new_Grid_Generator_System, 100
ppl_new_Grid_Generator_System_from_-Grid_Generator, 100
ppl_new_Grid_Generator_System_from_-Grid_Generator_System, 100
ppl_Grid_Generator_tag, 100
ppl_assign_Grid_Generator_from_Grid_-Generator, 102
ppl_delete_Grid_Generator, 102
ppl_Grid_Generator_coefficient, 102
ppl_Grid_Generator_divisor, 102
ppl_Grid_Generator_OK, 102
ppl_Grid_Generator_space_dimension, 102
ppl_Grid_Generator_type, 103
ppl_new_Grid_Generator, 103

ppl_new_Grid_Generator_from_Grid_-Generator, 103
ppl_new_Grid_Generator_zero_dim_point, 103
ppl_Grid_Generator_type
ppl_c_implementation_common.cc, 207
ppl_Grid_Generator_tag, 103
ppl_initialize
Init, 20
ppl_io_asprint_Polyhedron
ppl_Polyhedron_tag, 150
ppl_io_asprint_variable
Datatypes, 33
ppl_io_fprint_Polyhedron
ppl_Polyhedron_tag, 150
ppl_io_fprint_variable
Datatypes, 34
ppl_io_get_variable_output_function
Datatypes, 34
ppl_io_print_Polyhedron
ppl_Polyhedron_tag, 150
ppl_io_print_variable
Datatypes, 34
ppl_io_set_variable_output_function
Datatypes, 34
ppl_io_variable_output_function_type
Datatypes, 31
ppl_io_wrap_string
Datatypes, 34
ppl_irrational_precision
Init, 20
ppl_Linear_Expression_add_to_coefficient
ppl_c_implementation_common.cc, 208
ppl_Linear_Expression_tag, 106
ppl_Linear_Expression_add_to_inhomogeneous
ppl_c_implementation_common.cc, 208
ppl_Linear_Expression_tag, 106
ppl_Linear_Expression_all_homogeneous_terms_-are_zero
ppl_c_implementation_common.cc, 208
ppl_Linear_Expression_tag, 106
ppl_Linear_Expression_coefficient
ppl_c_implementation_common.cc, 208
ppl_Linear_Expression_tag, 106
ppl_Linear_Expression_inhomogeneous_term
ppl_c_implementation_common.cc, 208
ppl_Linear_Expression_tag, 107
ppl_Linear_Expression_is_zero
ppl_c_implementation_common.cc, 209
ppl_Linear_Expression_tag, 107
ppl_Linear_Expression_OK
ppl_c_implementation_common.cc, 209
ppl_Linear_Expression_tag, 107
ppl_Linear_Expression_space_dimension
ppl_c_implementation_common.cc, 209
ppl_Linear_Expression_tag, 107
ppl_Linear_Expression_tag, 103
ppl_add_Linear_Expression_to_Linear_-Expression, 105
ppl_assign_Linear_Expression_from_Linear_-Expression, 106
ppl_delete_Linear_Expression, 106
ppl_Linear_Expression_add_to_coefficient, 106
ppl_Linear_Expression_add_to_-inhomogeneous, 106
ppl_Linear_Expression_all_homogeneous_-terms_are_zero, 106
ppl_Linear_Expression_coefficient, 106
ppl_Linear_Expression_inhomogeneous_-term, 107
ppl_Linear_Expression_is_zero, 107
ppl_Linear_Expression_OK, 107
ppl_Linear_Expression_space_dimension, 107
ppl_multiply_Linear_Expression_by_-Coefficient, 107
ppl_new_Linear_Expression, 107
ppl_new_Linear_Expression_from_-Congruence, 107
ppl_new_Linear_Expression_from_-Constraint, 108
ppl_new_Linear_Expression_from_Generator, 108
ppl_new_Linear_Expression_from_Grid_-Generator, 108
ppl_new_Linear_Expression_from_Linear_-Expression, 108
ppl_new_Linear_Expression_with_dimension, 108
ppl_subtract_Linear_Expression_from_-Linear_Expression, 109
ppl_max_space_dimension
Datatypes, 35
ppl_MIP_Problem_add_constraint
ppl_c_implementation_common.cc, 209
ppl_MIP_Problem_tag, 112
ppl_MIP_Problem_add_constraints
ppl_c_implementation_common.cc, 209
ppl_MIP_Problem_tag, 112
ppl_MIP_Problem_add_space_dimensions_and_-embed
ppl_c_implementation_common.cc, 209
ppl_MIP_Problem_tag, 113
ppl_MIP_Problem_add_to_integer_space_-dimensions
ppl_c_implementation_common.cc, 209
ppl_MIP_Problem_tag, 113
ppl_MIP_Problem_clear

ppl_c_implementation_common.cc, 210
ppl_MIP_Problem_tag, 113
ppl_MIP_Problem_constraint_at_index
ppl_c_implementation_common.cc, 210
ppl_MIP_Problem_tag, 113
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_NAME_PRICING
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 113
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_STEEPEST_-EDGE_EXACT
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 113
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_STEEPEST_-EDGE_FLOAT
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 114
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_TEXTBOOK
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 114
ppl_MIP_Problem_evaluate_objective_function
ppl_c_implementation_common.cc, 210
ppl_MIP_Problem_tag, 114
ppl_MIP_Problem_external_memory_in_bytes
ppl_c_implementation_common.cc, 210
ppl_MIP_Problem_tag, 114
ppl_MIP_Problem_feasible_point
ppl_c_implementation_common.cc, 210
ppl_MIP_Problem_tag, 114
ppl_MIP_Problem_get_control_parameter
ppl_c_implementation_common.cc, 210
ppl_MIP_Problem_tag, 115
ppl_MIP_Problem_integer_space_dimensions
ppl_c_implementation_common.cc, 211
ppl_MIP_Problem_tag, 115
ppl_MIP_Problem_is_satisfiable
ppl_c_implementation_common.cc, 211
ppl_MIP_Problem_tag, 115
ppl_MIP_Problem_number_of_constraints
ppl_c_implementation_common.cc, 211
ppl_MIP_Problem_tag, 115
ppl_MIP_Problem_number_of_integer_space_-dimensions
ppl_c_implementation_common.cc, 211
ppl_MIP_Problem_tag, 115
ppl_MIP_Problem_objective_function
ppl_c_implementation_common.cc, 211
ppl_MIP_Problem_tag, 115
ppl_MIP_Problem_OK
ppl_c_implementation_common.cc, 211
ppl_MIP_Problem_tag, 116
ppl_MIP_Problem_optimal_value
ppl_c_implementation_common.cc, 212
ppl_MIP_Problem_tag, 116
ppl_MIP_Problem_optimization_mode
ppl_c_implementation_common.cc, 212
ppl_MIP_Problem_tag, 116
ppl_MIP_Problem_optimizing_point
ppl_c_implementation_common.cc, 212
ppl_MIP_Problem_tag, 116
ppl_MIP_Problem_set_control_parameter
ppl_c_implementation_common.cc, 212
ppl_MIP_Problem_tag, 116
ppl_MIP_Problem_set_objective_function
ppl_c_implementation_common.cc, 212
ppl_MIP_Problem_tag, 117
ppl_MIP_Problem_set_optimization_mode
ppl_c_implementation_common.cc, 212
ppl_MIP_Problem_tag, 117
ppl_MIP_Problem_solve
ppl_c_implementation_common.cc, 213
ppl_MIP_Problem_tag, 117
ppl_MIP_Problem_space_dimension
ppl_c_implementation_common.cc, 213
ppl_MIP_Problem_tag, 117
PPL_MIP_PROBLEM_STATUS_OPTIMIZED
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 117
PPL_MIP_PROBLEM_STATUS_UNBOUNDED
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 118
PPL_MIP_PROBLEM_STATUS_UNFEASIBLE
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 118
ppl_MIP_Problem_tag, 109
ppl_assign_MIP_Problem_from_MIP_-Problem, 112
ppl_delete_MIP_Problem, 112
ppl_MIP_Problem_add_constraint, 112
ppl_MIP_Problem_add_constraints, 112
ppl_MIP_Problem_add_space_dimensions_-and_embed, 113
ppl_MIP_Problem_add_to_integer_space_-dimensions, 113
ppl_MIP_Problem_clear, 113
ppl_MIP_Problem_constraint_at_index, 113
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_NAME_PRICING, 113
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_STEEPEST_-EDGE_EXACT, 113
PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_STEEPEST_-EDGE_FLOAT, 114

PPL_MIP_PROBLEM_CONTROL_-PARAMETER_PRICING_TEXTBOOK, 114
ppl_MIP_Problem_evaluate_objective_-function, 114
ppl_MIP_Problem_external_memory_in_-bytes, 114
ppl_MIP_Problem_feasible_point, 114
ppl_MIP_Problem_get_control_parameter, 115
ppl_MIP_Problem_integer_space_-dimensions, 115
ppl_MIP_Problem_is_satisfiable, 115
ppl_MIP_Problem_number_of_constraints, 115
ppl_MIP_Problem_number_of_integer_-space_dimensions, 115
ppl_MIP_Problem_objective_function, 115
ppl_MIP_Problem_OK, 116
ppl_MIP_Problem_optimal_value, 116
ppl_MIP_Problem_optimization_mode, 116
ppl_MIP_Problem_optimizing_point, 116
ppl_MIP_Problem_set_control_parameter, 116
ppl_MIP_Problem_set_objective_function, 117
ppl_MIP_Problem_set_optimization_mode, 117
ppl_MIP_Problem_solve, 117
ppl_MIP_Problem_space_dimension, 117
PPL_MIP_PROBLEM_STATUS_-OPTIMIZED, 117
PPL_MIP_PROBLEM_STATUS_-UNBOUNDED, 118
PPL_MIP_PROBLEM_STATUS_-UNFEASIBLE, 118
ppl_MIP_Problem_total_memory_in_bytes, 118
ppl_new_MIP_Problem, 118
ppl_new_MIP_Problem_from_MIP_Problem, 118
ppl_new_MIP_Problem_from_space_-dimension, 118
PPL_OPTIMIZATION_MODE_-MAXIMIZATION, 118
PPL_OPTIMIZATION_MODE_-MINIMIZATION, 119
ppl_MIP_Problem_total_memory_in_bytes
ppl_c_implementation_common.cc, 213
ppl_MIP_Problem_tag, 118
ppl_multiply_Linear_Expression_by_Coefficient
ppl_c_implementation_common.cc, 213
ppl_Linear_Expression_tag, 107
ppl_new_Artificial_Parameter_Sequence_const_-iterator
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 63
ppl_c_implementation_common.cc, 213
ppl_new_Artificial_Parameter_Sequence_const_-iterator_from_Artificial_Parameter_-Sequence_const_iterator
ppl_Artificial_Parameter_Sequence_const_-iterator_tag, 63
ppl_c_implementation_common.cc, 213
ppl_new_C_Polyhedron_from_C_Polyhedron
ppl_Polyhedron_tag, 150
ppl_new_C_Polyhedron_from_C_Polyhedron_-with_complexity
ppl_Polyhedron_tag, 150
ppl_new_C_Polyhedron_from_Congruence_-System
ppl_Polyhedron_tag, 151
ppl_new_C_Polyhedron_from_Constraint_System
ppl_Polyhedron_tag, 151
ppl_new_C_Polyhedron_from_Generator_System
ppl_Polyhedron_tag, 151
ppl_new_C_Polyhedron_from_NNC_Polyhedron
ppl_Polyhedron_tag, 151
ppl_new_C_Polyhedron_from_NNC_Polyhedron_-with_complexity
ppl_Polyhedron_tag, 151
ppl_new_C_Polyhedron_from_space_dimension
ppl_Polyhedron_tag, 152
ppl_new_C_Polyhedron_recycle_Congruence_-System
ppl_Polyhedron_tag, 152
ppl_new_C_Polyhedron_recycle_Constraint_-System
ppl_Polyhedron_tag, 152
ppl_new_C_Polyhedron_recycle_Generator_-System
ppl_Polyhedron_tag, 152
ppl_new_Coefficient
ppl_c_implementation_common.cc, 214
ppl_Coefficient_tag, 67
ppl_new_Coefficient_from_Coefficient
ppl_c_implementation_common.cc, 214
ppl_Coefficient_tag, 68
ppl_new_Coefficient_from_mpz_t
ppl_c_implementation_common.cc, 214
ppl_Coefficient_tag, 68
ppl_new_Congruence
ppl_c_implementation_common.cc, 214
ppl_Congruence_tag, 76
ppl_new_Congruence_from_Congruence
ppl_c_implementation_common.cc, 214
ppl_Congruence_tag, 76

ppl_new_Congruence_System
ppl_c_implementation_common.cc, 214
ppl_Congruence_System_tag, 73
ppl_new_Congruence_System_const_iterator
ppl_c_implementation_common.cc, 215
ppl_Congruence_System_const_iterator_tag, 70
ppl_new_Congruence_System_const_iterator_-from_Congruence_System_const_iterator
ppl_c_implementation_common.cc, 215
ppl_Congruence_System_const_iterator_tag, 70
ppl_new_Congruence_System_from_Congruence
ppl_c_implementation_common.cc, 215
ppl_Congruence_System_tag, 73
ppl_new_Congruence_System_from_-Congruence_System
ppl_c_implementation_common.cc, 215
ppl_Congruence_System_tag, 73
ppl_new_Congruence_System_zero_dim_empty
ppl_c_implementation_common.cc, 215
ppl_Congruence_System_tag, 74
ppl_new_Congruence_zero_dim_false
ppl_c_implementation_common.cc, 215
ppl_Congruence_tag, 77
ppl_new_Congruence_zero_dim_integrality
ppl_c_implementation_common.cc, 216
ppl_Congruence_tag, 77
ppl_new_Constraint
ppl_c_implementation_common.cc, 216
ppl_Constraint_tag, 85
ppl_new_Constraint_from_Constraint
ppl_c_implementation_common.cc, 216
ppl_Constraint_tag, 85
ppl_new_Constraint_System
ppl_c_implementation_common.cc, 216
ppl_Constraint_System_tag, 82
ppl_new_Constraint_System_const_iterator
ppl_c_implementation_common.cc, 216
ppl_Constraint_System_const_iterator_tag, 79
ppl_new_Constraint_System_const_iterator_-from_Constraint_System_const_iterator
ppl_c_implementation_common.cc, 216
ppl_Constraint_System_const_iterator_tag, 79
ppl_new_Constraint_System_from_Constraint
ppl_c_implementation_common.cc, 217
ppl_Constraint_System_tag, 82
ppl_new_Constraint_System_from_Constraint_-System
ppl_c_implementation_common.cc, 217
ppl_Constraint_System_tag, 83
ppl_new_Constraint_System_zero_dim_empty
ppl_c_implementation_common.cc, 217
ppl_Constraint_System_tag, 83
ppl_new_Constraint_zero_dim_false
ppl_c_implementation_common.cc, 217
ppl_Constraint_tag, 86
ppl_new_Constraint_zero_dim_positivity
ppl_c_implementation_common.cc, 217
ppl_Constraint_tag, 86
ppl_new_Generator
ppl_c_implementation_common.cc, 217
ppl_Generator_tag, 94
ppl_new_Generator_from_Generator
ppl_c_implementation_common.cc, 218
ppl_Generator_tag, 94
ppl_new_Generator_System
ppl_c_implementation_common.cc, 218
ppl_Generator_System_tag, 91
ppl_new_Generator_System_const_iterator
ppl_c_implementation_common.cc, 218
ppl_Generator_System_const_iterator_tag, 88
ppl_new_Generator_System_const_iterator_from_-Generator_System_const_iterator
ppl_c_implementation_common.cc, 218
ppl_Generator_System_const_iterator_tag, 88
ppl_new_Generator_System_from_Generator
ppl_c_implementation_common.cc, 218
ppl_Generator_System_tag, 91
ppl_new_Generator_System_from_Generator_-System
ppl_c_implementation_common.cc, 219
ppl_Generator_System_tag, 91
ppl_new_Generator_System_zero_dim_univ
ppl_c_header.h, 177
ppl_c_implementation_common.cc, 219
ppl_new_Generator_zero_dim_closure_point
ppl_c_implementation_common.cc, 219
ppl_Generator_tag, 94
ppl_new_Generator_zero_dim_point
ppl_c_implementation_common.cc, 219
ppl_Generator_tag, 94
ppl_new_Grid_Generator
ppl_c_implementation_common.cc, 219
ppl_Grid_Generator_tag, 103
ppl_new_Grid_Generator_from_Grid_Generator
ppl_c_implementation_common.cc, 219
ppl_Grid_Generator_tag, 103
ppl_new_Grid_Generator_System
ppl_c_implementation_common.cc, 220
ppl_Grid_Generator_System_tag, 100
ppl_new_Grid_Generator_System_const_iterator
ppl_c_implementation_common.cc, 220
ppl_Grid_Generator_System_const_iterator_-tag, 96
ppl_new_Grid_Generator_System_const_iterator_-from_Grid_Generator_System_const_-iterator

ppl_c_implementation_common.cc, 220
ppl_Grid_Generator_System_const_iterator_-tag, 97
ppl_new_Grid_Generator_System_from_Grid_-Generator
ppl_c_implementation_common.cc, 220
ppl_Grid_Generator_System_tag, 100
ppl_new_Grid_Generator_System_from_Grid_-Generator_System
ppl_c_implementation_common.cc, 220
ppl_Grid_Generator_System_tag, 100
ppl_new_Grid_Generator_System_zero_dim_univ
ppl_c_header.h, 177
ppl_c_implementation_common.cc, 220
ppl_new_Grid_Generator_zero_dim_point
ppl_c_implementation_common.cc, 221
ppl_Grid_Generator_tag, 103
ppl_new_Linear_Expression
ppl_c_implementation_common.cc, 221
ppl_Linear_Expression_tag, 107
ppl_new_Linear_Expression_from_Congruence
ppl_c_implementation_common.cc, 221
ppl_Linear_Expression_tag, 107
ppl_new_Linear_Expression_from_Constraint
ppl_c_implementation_common.cc, 221
ppl_Linear_Expression_tag, 108
ppl_new_Linear_Expression_from_Generator
ppl_c_implementation_common.cc, 221
ppl_Linear_Expression_tag, 108
ppl_new_Linear_Expression_from_Grid_-Generator
ppl_Linear_Expression_tag, 108
ppl_new_Linear_Expression_from_Linear_-Expression
ppl_c_implementation_common.cc, 221
ppl_Linear_Expression_tag, 108
ppl_new_Linear_Expression_with_dimension
ppl_c_implementation_common.cc, 222
ppl_Linear_Expression_tag, 108
ppl_new_MIP_Problem
ppl_c_implementation_common.cc, 222
ppl_MIP_Problem_tag, 118
ppl_new_MIP_Problem_from_MIP_Problem
ppl_c_implementation_common.cc, 222
ppl_MIP_Problem_tag, 118
ppl_new_MIP_Problem_from_space_dimension
ppl_c_implementation_common.cc, 222
ppl_MIP_Problem_tag, 118
ppl_new_NNC_Polyhedron_from_C_Polyhedron
ppl_Polyhedron_tag, 153
ppl_new_NNC_Polyhedron_from_C_Polyhedron_-with_complexity
ppl_Polyhedron_tag, 153
ppl_new_NNC_Polyhedron_from_Congruence_-System
ppl_Polyhedron_tag, 153
ppl_new_NNC_Polyhedron_from_Constraint_-System
ppl_Polyhedron_tag, 153
ppl_new_NNC_Polyhedron_from_Generator_-System
ppl_Polyhedron_tag, 153
ppl_new_NNC_Polyhedron_from_NNC_-Polyhedron
ppl_Polyhedron_tag, 154
ppl_new_NNC_Polyhedron_from_NNC_-Polyhedron_with_complexity
ppl_Polyhedron_tag, 154
ppl_new_NNC_Polyhedron_from_space_-dimension
ppl_Polyhedron_tag, 154
ppl_new_NNC_Polyhedron_recycle_Congruence_-System
ppl_Polyhedron_tag, 154
ppl_new_NNC_Polyhedron_recycle_Constraint_-System
ppl_Polyhedron_tag, 154
ppl_new_NNC_Polyhedron_recycle_Generator_-System
ppl_Polyhedron_tag, 155
ppl_new_PIP_Problem_from_constraints
ppl_c_implementation_common.cc, 222
ppl_PIP_Problem_tag, 123
ppl_new_PIP_Problem_from_PIP_Problem
ppl_c_implementation_common.cc, 223
ppl_PIP_Problem_tag, 123
ppl_new_PIP_Problem_from_space_dimension
ppl_c_implementation_common.cc, 223
ppl_PIP_Problem_tag, 123
ppl_new_Pointset_Powerset_C_Polyhedron_-const_iterator
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 133
ppl_new_Pointset_Powerset_C_Polyhedron_-const_iterator_from_const_iterator
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 133
ppl_new_Pointset_Powerset_C_Polyhedron_-iterator
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 135
ppl_new_Pointset_Powerset_C_Polyhedron_-iterator_from_iterator
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 136
PPL_NO_AUTOMATIC_INITIALIZATION
ppl_c_implementation_common.defs.hh, 233

ppl_not_a_dimension
Datatypes, 35
PPL_OPTIMIZATION_MODE_MAXIMIZATION
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 118
PPL_OPTIMIZATION_MODE_MINIMIZATION
ppl_c_implementation_common.cc, 229
ppl_MIP_Problem_tag, 119
ppl_PIP_Decision_Node_get_child_node
ppl_c_implementation_common.cc, 223
ppl_PIP_Decision_Node_tag, 119
ppl_PIP_Decision_Node_OK
ppl_c_implementation_common.cc, 223
ppl_PIP_Decision_Node_tag, 119
ppl_PIP_Decision_Node_get_child_node, 119
ppl_PIP_Problem_add_constraint
ppl_c_implementation_common.cc, 223
ppl_PIP_Problem_tag, 123
ppl_PIP_Problem_add_constraints
ppl_c_implementation_common.cc, 223
ppl_PIP_Problem_tag, 124
ppl_PIP_Problem_add_space_dimensions_and_-embed
ppl_c_implementation_common.cc, 224
ppl_PIP_Problem_tag, 124
ppl_PIP_Problem_add_to_parameter_space_-dimensions
ppl_c_implementation_common.cc, 224
ppl_PIP_Problem_tag, 124
ppl_PIP_Problem_clear
ppl_c_implementation_common.cc, 224
ppl_PIP_Problem_tag, 124
ppl_PIP_Problem_constraint_at_index
ppl_c_implementation_common.cc, 224
ppl_PIP_Problem_tag, 124
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_ALL
ppl_c_implementation_common.cc, 230
ppl_PIP_Problem_tag, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_DEEPEST
ppl_c_implementation_common.cc, 230
ppl_PIP_Problem_tag, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_FIRST
ppl_c_implementation_common.cc, 230
ppl_PIP_Problem_tag, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_NAME_CUTTING_-STRATEGY
ppl_c_implementation_common.cc, 230
ppl_PIP_Problem_tag, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_NAME_PIVOT_ROW_-STRATEGY
ppl_c_implementation_common.cc, 230
ppl_PIP_Problem_tag, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_PIVOT_ROW_-STRATEGY_FIRST
ppl_c_implementation_common.cc, 230
ppl_PIP_Problem_tag, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_PIVOT_ROW_-STRATEGY_MAX_COLUMN
ppl_c_implementation_common.cc, 230
ppl_PIP_Problem_tag, 126
ppl_PIP_Problem_external_memory_in_bytes
ppl_c_implementation_common.cc, 224
ppl_PIP_Problem_tag, 126
ppl_PIP_Problem_get_big_parameter_dimension
ppl_c_implementation_common.cc, 224
ppl_PIP_Problem_tag, 126
ppl_PIP_Problem_get_control_parameter
ppl_c_implementation_common.cc, 225
ppl_PIP_Problem_tag, 126
ppl_PIP_Problem_is_satisfiable
ppl_c_implementation_common.cc, 225
ppl_PIP_Problem_tag, 126
ppl_PIP_Problem_number_of_constraints
ppl_c_implementation_common.cc, 225
ppl_PIP_Problem_tag, 126
ppl_PIP_Problem_number_of_parameter_space_-dimensions
ppl_c_implementation_common.cc, 225
ppl_PIP_Problem_tag, 126
ppl_PIP_Problem_OK
ppl_c_implementation_common.cc, 225
ppl_PIP_Problem_tag, 127
ppl_PIP_Problem_optimizing_solution
ppl_c_implementation_common.cc, 225
ppl_PIP_Problem_tag, 127
ppl_PIP_Problem_parameter_space_dimensions
ppl_c_implementation_common.cc, 225
ppl_PIP_Problem_tag, 127
ppl_PIP_Problem_set_big_parameter_dimension
ppl_c_implementation_common.cc, 226
ppl_PIP_Problem_tag, 127
ppl_PIP_Problem_set_control_parameter
ppl_c_implementation_common.cc, 226
ppl_PIP_Problem_tag, 127
ppl_PIP_Problem_solution
ppl_c_implementation_common.cc, 226
ppl_PIP_Problem_tag, 127
ppl_PIP_Problem_solve

ppl_c_implementation_common.cc, 226
ppl_PIP_Problem_tag, 128
ppl_PIP_Problem_space_dimension
ppl_c_implementation_common.cc, 226
ppl_PIP_Problem_tag, 128
PPL_PIP_PROBLEM_STATUS_OPTIMIZED
ppl_c_implementation_common.cc, 231
ppl_PIP_Problem_tag, 128
PPL_PIP_PROBLEM_STATUS_UNFEASIBLE
ppl_c_implementation_common.cc, 231
ppl_PIP_Problem_tag, 128
ppl_PIP_Problem_tag, 120
ppl_assign_PIP_Problem_from_PIP_Problem, 123
ppl_delete_PIP_Problem, 123
ppl_new_PIP_Problem_from_constraints, 123
ppl_new_PIP_Problem_from_PIP_Problem, 123
ppl_new_PIP_Problem_from_space_-dimension, 123
ppl_PIP_Problem_add_constraint, 123
ppl_PIP_Problem_add_constraints, 124
ppl_PIP_Problem_add_space_dimensions_-and_embed, 124
ppl_PIP_Problem_add_to_parameter_space_-dimensions, 124
ppl_PIP_Problem_clear, 124
ppl_PIP_Problem_constraint_at_index, 124
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_ALL, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_DEEPEST, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_CUTTING_-STRATEGY_FIRST, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_NAME_CUTTING_-STRATEGY, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_NAME_PIVOT_ROW_-STRATEGY, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_PIVOT_ROW_-STRATEGY_FIRST, 125
PPL_PIP_PROBLEM_CONTROL_-PARAMETER_PIVOT_ROW_-STRATEGY_MAX_COLUMN, 126
ppl_PIP_Problem_external_memory_in_-bytes, 126
ppl_PIP_Problem_get_big_parameter_-dimension, 126
ppl_PIP_Problem_get_control_parameter, 126
ppl_PIP_Problem_is_satisfiable, 126
ppl_PIP_Problem_number_of_constraints, 126
ppl_PIP_Problem_number_of_parameter_-space_dimensions, 126
ppl_PIP_Problem_OK, 127
ppl_PIP_Problem_optimizing_solution, 127
ppl_PIP_Problem_parameter_space_-dimensions, 127
ppl_PIP_Problem_set_big_parameter_-dimension, 127
ppl_PIP_Problem_set_control_parameter, 127
ppl_PIP_Problem_solution, 127
ppl_PIP_Problem_solve, 128
ppl_PIP_Problem_space_dimension, 128
PPL_PIP_PROBLEM_STATUS_-OPTIMIZED, 128
PPL_PIP_PROBLEM_STATUS_-UNFEASIBLE, 128
ppl_PIP_Problem_total_memory_in_bytes, 128
ppl_PIP_Problem_total_memory_in_bytes
ppl_c_implementation_common.cc, 226
ppl_PIP_Problem_tag, 128
ppl_PIP_Solution_Node_get_parametric_values
ppl_c_implementation_common.cc, 227
ppl_PIP_Solution_Node_tag, 129
ppl_PIP_Solution_Node_OK
ppl_c_implementation_common.cc, 227
ppl_PIP_Solution_Node_tag, 129
ppl_PIP_Solution_Node_get_parametric_-values, 129
ppl_PIP_Tree_Node_as_decision
ppl_c_implementation_common.cc, 227
ppl_PIP_Tree_Node_tag, 130
ppl_PIP_Tree_Node_as_solution
ppl_c_implementation_common.cc, 227
ppl_PIP_Tree_Node_tag, 131
ppl_PIP_Tree_Node_begin
ppl_c_implementation_common.cc, 227
ppl_PIP_Tree_Node_tag, 131
ppl_PIP_Tree_Node_end
ppl_c_implementation_common.cc, 227
ppl_PIP_Tree_Node_tag, 131
ppl_PIP_Tree_Node_get_constraints
ppl_c_implementation_common.cc, 228
ppl_PIP_Tree_Node_tag, 131
ppl_PIP_Tree_Node_number_of_artificials
ppl_c_implementation_common.cc, 228
ppl_PIP_Tree_Node_tag, 131
ppl_PIP_Tree_Node_OK
ppl_c_implementation_common.cc, 228
ppl_PIP_Tree_Node_tag, 131
ppl_PIP_Tree_Node_tag, 130

ppl_PIP_Tree_Node_as_decision, 130
ppl_PIP_Tree_Node_as_solution, 131
ppl_PIP_Tree_Node_begin, 131
ppl_PIP_Tree_Node_end, 131
ppl_PIP_Tree_Node_get_constraints, 131
ppl_PIP_Tree_Node_number_of_artificials, 131
ppl_PIP_Tree_Node_OK, 131
ppl_Pointset_Powerset_C_Polyhedron_add_-disjunct
ppl_Pointset_Powerset_C_Polyhedron_tag, 138
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_begin
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 133
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_decrement
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 133
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_dereference
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 133
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_end
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 134
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_equal_test
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 134
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_increment
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_tag, 134
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_t
Datatypes, 31
ppl_Pointset_Powerset_C_Polyhedron_const_-iterator_tag, 132
ppl_delete_Pointset_Powerset_C_-Polyhedron_const_iterator, 133
ppl_new_Pointset_Powerset_C_Polyhedron_-const_iterator, 133
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_begin, 133
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_decrement, 133
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_dereference, 133
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_end, 134
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_equal_test, 134
ppl_Pointset_Powerset_C_Polyhedron_-const_iterator_increment, 134
ppl_Pointset_Powerset_C_Polyhedron_drop_-disjunct
ppl_Pointset_Powerset_C_Polyhedron_tag, 138
ppl_Pointset_Powerset_C_Polyhedron_drop_-disjuncts
ppl_Pointset_Powerset_C_Polyhedron_tag, 138
ppl_Pointset_Powerset_C_Polyhedron_-geometrically_covers_Pointset_-Powerset_C_Polyhedron
ppl_Pointset_Powerset_C_Polyhedron_tag, 139
ppl_Pointset_Powerset_C_Polyhedron_-geometrically_equals_Pointset_-Powerset_C_Polyhedron
ppl_Pointset_Powerset_C_Polyhedron_tag, 139
ppl_Pointset_Powerset_C_Polyhedron_iterator_-begin
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 136
ppl_Pointset_Powerset_C_Polyhedron_iterator_-decrement
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 136
ppl_Pointset_Powerset_C_Polyhedron_iterator_-dereference
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 136
ppl_Pointset_Powerset_C_Polyhedron_iterator_-end
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 136
ppl_Pointset_Powerset_C_Polyhedron_iterator_-equal_test
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 137
ppl_Pointset_Powerset_C_Polyhedron_iterator_-increment
ppl_Pointset_Powerset_C_Polyhedron_-iterator_tag, 137
ppl_Pointset_Powerset_C_Polyhedron_iterator_t
Datatypes, 31
ppl_Pointset_Powerset_C_Polyhedron_iterator_-tag, 134
ppl_delete_Pointset_Powerset_C_-Polyhedron_iterator, 135
ppl_new_Pointset_Powerset_C_Polyhedron_-iterator, 135

ppl_new_Pointset_Powerset_C_Polyhedron_-iterator_from_iterator, 136
ppl_Pointset_Powerset_C_Polyhedron_-iterator_begin, 136
ppl_Pointset_Powerset_C_Polyhedron_-iterator_decrement, 136
ppl_Pointset_Powerset_C_Polyhedron_-iterator_dereference, 136
ppl_Pointset_Powerset_C_Polyhedron_-iterator_end, 136
ppl_Pointset_Powerset_C_Polyhedron_-iterator_equal_test, 137
ppl_Pointset_Powerset_C_Polyhedron_-iterator_increment, 137
ppl_Pointset_Powerset_C_Polyhedron_omega_-reduce
ppl_Pointset_Powerset_C_Polyhedron_tag, 139
ppl_Pointset_Powerset_C_Polyhedron_pairwise_-reduce
ppl_Pointset_Powerset_C_Polyhedron_tag, 139
ppl_Pointset_Powerset_C_Polyhedron_size
ppl_Pointset_Powerset_C_Polyhedron_tag, 139
ppl_Pointset_Powerset_C_Polyhedron_t
Datatypes, 31
ppl_Pointset_Powerset_C_Polyhedron_tag, 137
ppl_Pointset_Powerset_C_Polyhedron_add_-disjunct, 138
ppl_Pointset_Powerset_C_Polyhedron_drop_-disjunct, 138
ppl_Pointset_Powerset_C_Polyhedron_drop_-disjuncts, 138
ppl_Pointset_Powerset_C_Polyhedron_-geometrically_covers_Pointset_-Powerset_C_Polyhedron, 139
ppl_Pointset_Powerset_C_Polyhedron_-geometrically_equals_Pointset_-Powerset_C_Polyhedron, 139
ppl_Pointset_Powerset_C_Polyhedron_-omega_reduce, 139
ppl_Pointset_Powerset_C_Polyhedron_-pairwise_reduce, 139
ppl_Pointset_Powerset_C_Polyhedron_size, 139
PPL_POLY_CON_RELATION_IS_DISJOINT
Datatypes, 35
PPL_POLY_CON_RELATION_IS_INCLUDED
Datatypes, 36
PPL_POLY_CON_RELATION_SATURATES
Datatypes, 36
PPL_POLY_CON_RELATION_STRICTLY_-INTERSECTS
Datatypes, 36
PPL_POLY_GEN_RELATION_SUBSUMES
Datatypes, 36
ppl_Polyhedron_add_congruence
ppl_Polyhedron_tag, 155
ppl_Polyhedron_add_congruences
ppl_Polyhedron_tag, 155
ppl_Polyhedron_add_constraint
ppl_Polyhedron_tag, 155
ppl_Polyhedron_add_constraints
ppl_Polyhedron_tag, 155
ppl_Polyhedron_add_generator
ppl_Polyhedron_tag, 155
ppl_Polyhedron_add_generators
ppl_Polyhedron_tag, 155
ppl_Polyhedron_add_recycled_congruences
ppl_Polyhedron_tag, 156
ppl_Polyhedron_add_recycled_constraints
ppl_Polyhedron_tag, 156
ppl_Polyhedron_add_recycled_generators
ppl_Polyhedron_tag, 156
ppl_Polyhedron_add_space_dimensions_and_-embed
ppl_Polyhedron_tag, 156
ppl_Polyhedron_add_space_dimensions_and_-project
ppl_Polyhedron_tag, 156
ppl_Polyhedron_affine_dimension
ppl_Polyhedron_tag, 157
ppl_Polyhedron_affine_image
ppl_Polyhedron_tag, 157
ppl_Polyhedron_affine_preimage
ppl_Polyhedron_tag, 157
ppl_Polyhedron_ascii_dump
ppl_Polyhedron_tag, 157
ppl_Polyhedron_ascii_load
ppl_Polyhedron_tag, 157
ppl_Polyhedron_BHRZ03_widening_assign
ppl_Polyhedron_tag, 158
ppl_Polyhedron_BHRZ03_widening_assign_-with_tokens
ppl_Polyhedron_tag, 158
ppl_Polyhedron_bounded_affine_image
ppl_Polyhedron_tag, 158
ppl_Polyhedron_bounded_affine_preimage
ppl_Polyhedron_tag, 158
ppl_Polyhedron_bounded_BHRZ03_-extrapolation_assign
ppl_Polyhedron_tag, 159
ppl_Polyhedron_bounded_BHRZ03_-extrapolation_assign_with_tokens
ppl_Polyhedron_tag, 159
ppl_Polyhedron_bounded_H79_extrapolation_-assign

ppl_Polyhedron_tag, 159
ppl_Polyhedron_bounded_H79_extrapolation_-assign_with_tokens
ppl_Polyhedron_tag, 159
ppl_Polyhedron_bounds_from_above
ppl_Polyhedron_tag, 159
ppl_Polyhedron_bounds_from_below
ppl_Polyhedron_tag, 159
ppl_Polyhedron_concatenate_assign
ppl_Polyhedron_tag, 160
ppl_Polyhedron_constrains
ppl_Polyhedron_tag, 160
ppl_Polyhedron_contains_integer_point
ppl_Polyhedron_tag, 160
ppl_Polyhedron_contains_Polyhedron
ppl_Polyhedron_tag, 160
ppl_Polyhedron_difference_assign
ppl_Polyhedron_tag, 160
ppl_Polyhedron_equals_Polyhedron
ppl_Polyhedron_tag, 160
ppl_Polyhedron_expand_space_dimension
ppl_Polyhedron_tag, 160
ppl_Polyhedron_external_memory_in_bytes
ppl_Polyhedron_tag, 161
ppl_Polyhedron_fold_space_dimensions
ppl_Polyhedron_tag, 161
ppl_Polyhedron_generalized_affine_image
ppl_Polyhedron_tag, 161
ppl_Polyhedron_generalized_affine_image_lhs_rhs
ppl_Polyhedron_tag, 161
ppl_Polyhedron_generalized_affine_preimage
ppl_Polyhedron_tag, 162
ppl_Polyhedron_generalized_affine_preimage_-lhs_rhs
ppl_Polyhedron_tag, 162
ppl_Polyhedron_get_congruences
ppl_Polyhedron_tag, 162
ppl_Polyhedron_get_constraints
ppl_Polyhedron_tag, 162
ppl_Polyhedron_get_generators
ppl_Polyhedron_tag, 162
ppl_Polyhedron_get_minimized_congruences
ppl_Polyhedron_tag, 163
ppl_Polyhedron_get_minimized_constraints
ppl_Polyhedron_tag, 163
ppl_Polyhedron_get_minimized_generators
ppl_Polyhedron_tag, 163
ppl_Polyhedron_H79_widening_assign
ppl_Polyhedron_tag, 163
ppl_Polyhedron_H79_widening_assign_with_-tokens
ppl_Polyhedron_tag, 163
ppl_Polyhedron_intersection_assign
ppl_Polyhedron_tag, 163
ppl_Polyhedron_is_bounded
ppl_Polyhedron_tag, 163
ppl_Polyhedron_is_discrete
ppl_Polyhedron_tag, 164
ppl_Polyhedron_is_disjoint_from_Polyhedron
ppl_Polyhedron_tag, 164
ppl_Polyhedron_is_empty
ppl_Polyhedron_tag, 164
ppl_Polyhedron_is_topologically_closed
ppl_Polyhedron_tag, 164
ppl_Polyhedron_is_universe
ppl_Polyhedron_tag, 164
ppl_Polyhedron_limited_BHRZ03_extrapolation_-assign
ppl_Polyhedron_tag, 164
ppl_Polyhedron_limited_BHRZ03_extrapolation_-assign_with_tokens
ppl_Polyhedron_tag, 164
ppl_Polyhedron_limited_H79_extrapolation_assign
ppl_Polyhedron_tag, 165
ppl_Polyhedron_limited_H79_extrapolation_-assign_with_tokens
ppl_Polyhedron_tag, 165
ppl_Polyhedron_map_space_dimensions
ppl_Polyhedron_tag, 165
ppl_Polyhedron_maximize
ppl_Polyhedron_tag, 165
ppl_Polyhedron_maximize_with_point
ppl_Polyhedron_tag, 165
ppl_Polyhedron_minimize_with_point
ppl_Polyhedron_tag, 166
ppl_Polyhedron_OK
ppl_Polyhedron_tag, 166
ppl_Polyhedron_poly_difference_assign
ppl_Polyhedron_tag, 166
ppl_Polyhedron_poly_hull_assign
ppl_Polyhedron_tag, 167
ppl_Polyhedron_refine_with_congruence
ppl_Polyhedron_tag, 167
ppl_Polyhedron_refine_with_congruences
ppl_Polyhedron_tag, 167
ppl_Polyhedron_refine_with_constraint
ppl_Polyhedron_tag, 167
ppl_Polyhedron_refine_with_constraints
ppl_Polyhedron_tag, 167
ppl_Polyhedron_relation_with_Congruence
C_interface.dox, 172
ppl_Polyhedron_relation_with_Constraint
ppl_Polyhedron_tag, 167
ppl_Polyhedron_relation_with_Generator
ppl_Polyhedron_tag, 167
ppl_Polyhedron_remove_higher_space_dimensions
ppl_Polyhedron_tag, 168
ppl_Polyhedron_remove_space_dimensions

ppl_Polyhedron_tag, 168
ppl_Polyhedron_simplify_using_context_assign
ppl_Polyhedron_tag, 168
ppl_Polyhedron_space_dimension
ppl_Polyhedron_tag, 168
ppl_Polyhedron_strictly_contains_Polyhedron
ppl_Polyhedron_tag, 168
ppl_Polyhedron_t
Datatypes, 31
ppl_Polyhedron_tag, 140
ppl_assign_C_Polyhedron_from_C_-Polyhedron, 150
ppl_assign_NNC_Polyhedron_from_NNC_-Polyhedron, 150
ppl_delete_Polyhedron, 150
ppl_io_asprint_Polyhedron, 150
ppl_io_fprint_Polyhedron, 150
ppl_io_print_Polyhedron, 150
ppl_new_C_Polyhedron_from_C_Polyhedron, 150
ppl_new_C_Polyhedron_from_C_-Polyhedron_with_complexity, 150
ppl_new_C_Polyhedron_from_Congruence_-System, 151
ppl_new_C_Polyhedron_from_Constraint_-System, 151
ppl_new_C_Polyhedron_from_Generator_-System, 151
ppl_new_C_Polyhedron_from_NNC_-Polyhedron, 151
ppl_new_C_Polyhedron_from_NNC_-Polyhedron_with_complexity, 151
ppl_new_C_Polyhedron_from_space_-dimension, 152
ppl_new_C_Polyhedron_recycle_-Congruence_System, 152
ppl_new_C_Polyhedron_recycle_Constraint_-System, 152
ppl_new_C_Polyhedron_recycle_Generator_-System, 152
ppl_new_NNC_Polyhedron_from_C_-Polyhedron, 153
ppl_new_NNC_Polyhedron_from_C_-Polyhedron_with_complexity, 153
ppl_new_NNC_Polyhedron_from_-Congruence_System, 153
ppl_new_NNC_Polyhedron_from_-Constraint_System, 153
ppl_new_NNC_Polyhedron_from_-Generator_System, 153
ppl_new_NNC_Polyhedron_from_NNC_-Polyhedron, 154
ppl_new_NNC_Polyhedron_from_NNC_-Polyhedron_with_complexity, 154
ppl_new_NNC_Polyhedron_from_space_-dimension, 154
ppl_new_NNC_Polyhedron_recycle_-Congruence_System, 154
ppl_new_NNC_Polyhedron_recycle_-Constraint_System, 154
ppl_new_NNC_Polyhedron_recycle_-Generator_System, 155
ppl_Polyhedron_add_congruence, 155
ppl_Polyhedron_add_congruences, 155
ppl_Polyhedron_add_constraint, 155
ppl_Polyhedron_add_constraints, 155
ppl_Polyhedron_add_generator, 155
ppl_Polyhedron_add_generators, 155
ppl_Polyhedron_add_recycled_congruences, 156
ppl_Polyhedron_add_recycled_constraints, 156
ppl_Polyhedron_add_recycled_generators, 156
ppl_Polyhedron_add_space_dimensions_-and_embed, 156
ppl_Polyhedron_add_space_dimensions_-and_project, 156
ppl_Polyhedron_affine_dimension, 157
ppl_Polyhedron_affine_image, 157
ppl_Polyhedron_affine_preimage, 157
ppl_Polyhedron_ascii_dump, 157
ppl_Polyhedron_ascii_load, 157
ppl_Polyhedron_BHRZ03_widening_assign, 158
ppl_Polyhedron_BHRZ03_widening_assign_-with_tokens, 158
ppl_Polyhedron_bounded_affine_image, 158
ppl_Polyhedron_bounded_affine_preimage, 158
ppl_Polyhedron_bounded_BHRZ03_-extrapolation_assign, 159
ppl_Polyhedron_bounded_BHRZ03_-extrapolation_assign_with_tokens, 159
ppl_Polyhedron_bounded_H79_-extrapolation_assign, 159
ppl_Polyhedron_bounded_H79_-extrapolation_assign_with_tokens, 159
ppl_Polyhedron_bounds_from_above, 159
ppl_Polyhedron_bounds_from_below, 159
ppl_Polyhedron_concatenate_assign, 160
ppl_Polyhedron_constrains, 160
ppl_Polyhedron_contains_integer_point, 160
ppl_Polyhedron_contains_Polyhedron, 160
ppl_Polyhedron_difference_assign, 160
ppl_Polyhedron_equals_Polyhedron, 160

ppl_Polyhedron_expand_space_dimension, 160
ppl_Polyhedron_external_memory_in_bytes, 161
ppl_Polyhedron_fold_space_dimensions, 161
ppl_Polyhedron_generalized_affine_image, 161
ppl_Polyhedron_generalized_affine_image_-lhs_rhs, 161
ppl_Polyhedron_generalized_affine_preimage, 162
ppl_Polyhedron_generalized_affine_-preimage_lhs_rhs, 162
ppl_Polyhedron_get_congruences, 162
ppl_Polyhedron_get_constraints, 162
ppl_Polyhedron_get_generators, 162
ppl_Polyhedron_get_minimized_congruences, 163
ppl_Polyhedron_get_minimized_constraints, 163
ppl_Polyhedron_get_minimized_generators, 163
ppl_Polyhedron_H79_widening_assign, 163
ppl_Polyhedron_H79_widening_assign_-with_tokens, 163
ppl_Polyhedron_intersection_assign, 163
ppl_Polyhedron_is_bounded, 163
ppl_Polyhedron_is_discrete, 164
ppl_Polyhedron_is_disjoint_from_-Polyhedron, 164
ppl_Polyhedron_is_empty, 164
ppl_Polyhedron_is_topologically_closed, 164
ppl_Polyhedron_is_universe, 164
ppl_Polyhedron_limited_BHRZ03_-extrapolation_assign, 164
ppl_Polyhedron_limited_BHRZ03_-extrapolation_assign_with_tokens, 164
ppl_Polyhedron_limited_H79_extrapolation_-assign, 165
ppl_Polyhedron_limited_H79_extrapolation_-assign_with_tokens, 165
ppl_Polyhedron_map_space_dimensions, 165
ppl_Polyhedron_maximize, 165
ppl_Polyhedron_maximize_with_point, 165
ppl_Polyhedron_minimize_with_point, 166
ppl_Polyhedron_OK, 166
ppl_Polyhedron_poly_difference_assign, 166
ppl_Polyhedron_poly_hull_assign, 167
ppl_Polyhedron_refine_with_congruence, 167
ppl_Polyhedron_refine_with_congruences, 167
ppl_Polyhedron_refine_with_constraint, 167
ppl_Polyhedron_refine_with_constraints, 167
ppl_Polyhedron_relation_with_Constraint, 167
ppl_Polyhedron_relation_with_Generator, 167
ppl_Polyhedron_remove_higher_space_-dimensions, 168
ppl_Polyhedron_remove_space_dimensions, 168
ppl_Polyhedron_simplify_using_context_-assign, 168
ppl_Polyhedron_space_dimension, 168
ppl_Polyhedron_strictly_contains_-Polyhedron, 168
ppl_Polyhedron_time_elapse_assign, 168
ppl_Polyhedron_topological_closure_assign, 168
ppl_Polyhedron_total_memory_in_bytes, 169
ppl_Polyhedron_unconstrain_space_-dimension, 169
ppl_Polyhedron_unconstrain_space_-dimensions, 169
ppl_Polyhedron_upper_bound_assign, 169
wrap_assign, 169
ppl_Polyhedron_time_elapse_assign
ppl_Polyhedron_tag, 168
ppl_Polyhedron_topological_closure_assign
ppl_Polyhedron_tag, 168
ppl_Polyhedron_total_memory_in_bytes
ppl_Polyhedron_tag, 169
ppl_Polyhedron_unconstrain_space_dimension
ppl_Polyhedron_tag, 169
ppl_Polyhedron_unconstrain_space_dimensions
ppl_Polyhedron_tag, 169
ppl_Polyhedron_upper_bound_assign
ppl_Polyhedron_tag, 169
PPL_PROTO
ppl_c_header.h, 176
ppl_reset_deterministic_timeout
Timeout, 26
ppl_reset_timeout
Timeout, 26
ppl_restore_pre_PPL_rounding
Init, 20
ppl_set_deterministic_timeout
Timeout, 26
ppl_set_error_handler
Error, 25
ppl_c_implementation_common.cc, 228
ppl_set_irrational_precision
Init, 21
ppl_set_rounding_for_PPL
Init, 21
ppl_set_timeout
Timeout, 27

ppl_subtract_Linear_Expression_from_Linear_-
Expression
ppl_c_implementation_common.cc, 228
ppl_Linear_Expression_tag, 109
PPL_TYPE_DECLARATION
ppl_c_header.h, 176
PPL_VERSION
Version, 22
ppl_version
Version, 23
PPL_VERSION_BETA
Version, 22
ppl_version_beta
Version, 23
PPL_VERSION_MAJOR
Version, 22
ppl_version_major
Version, 23
PPL_VERSION_MINOR
Version, 23
ppl_version_minor
Version, 24
PPL_VERSION_REVISION
Version, 23
ppl_version_revision
Version, 24
priority
Parma_Polyhedra_-
Library::Interfaces::C::deterministic_-
timeout_exception, 61
Parma_Polyhedra_-
Library::Interfaces::C::timeout_-
exception, 170

reinterpret_mpz_class
Parma_Polyhedra_Library::Interfaces::C, 42
relation_symbol
Parma_Polyhedra_Library::Interfaces::C, 42
reset_deterministic_timeout
Parma_Polyhedra_Library::Interfaces::C, 42
reset_timeout
Parma_Polyhedra_Library::Interfaces::C, 42

saved_cxx_Variable_output_function
Parma_Polyhedra_Library::Interfaces::C, 58

throw_me
Parma_Polyhedra_-
Library::Interfaces::C::deterministic_-
timeout_exception, 61
Parma_Polyhedra_-
Library::Interfaces::C::timeout_-
exception, 170
Timeout
ppl_reset_deterministic_timeout, 26
ppl_reset_timeout, 26
ppl_set_deterministic_timeout, 26
ppl_set_timeout, 27
to_const
Parma_Polyhedra_Library::Interfaces::C, 42–
48
to_nonconst
Parma_Polyhedra_Library::Interfaces::C, 50–
56

user_error_handler
Parma_Polyhedra_Library::Interfaces::C, 58

vec
Parma_Polyhedra_-
Library::Interfaces::C::Array_Partial_-
Function_Wrapper, 60
vec_size
Parma_Polyhedra_-
Library::Interfaces::C::Array_Partial_-
Function_Wrapper, 60
Version
ppl_banner, 23
PPL_VERSION, 22
ppl_version, 23
PPL_VERSION_BETA, 22
ppl_version_beta, 23
PPL_VERSION_MAJOR, 22
ppl_version_major, 23
PPL_VERSION_MINOR, 23
ppl_version_minor, 24
PPL_VERSION_REVISION, 23
ppl_version_revision, 24
Version Checking, 21

wrap_assign
ppl_Polyhedron_tag, 169